

# REMS Amigo 2

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site.

Pipe threads  $\frac{1}{8}$ –2", 16–50 mm  
Bolt threads 6–30 mm,  $\frac{1}{4}$ –1"

Thread types see page 28, 29.

## REMS Amigo 2 – extremely strong up to 2".

### System advantage

Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

### Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

### Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 6.5 kg, without die head.

### Drive

Solid, maintenance-free gear. Robust 1700 W universal motor with 30% power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Fast threading time 30–18 rpm. Safety tip switch.

### Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

### Dies

The proven, inducturable REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

### Thread-cutting oil

REMS Sanitol and REMS Spezial (page 47). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

### Nipple-threading

Efficient with REMS Nippelspanner  $\frac{3}{8}$ –1" (2") (page 46).



German Quality Product



Info



Tested by electrosuisse >>>

## Supply format

**REMS Amigo 2 Set.** Electric die stock with quick-change die heads. For pipe threads  $\frac{1}{8}$ –2", 16–50 mm, bolt threads 6–30 mm,  $\frac{1}{4}$ –1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50–60 Hz, 1700 W, safety tip switch, power increase thanks to automatic carbon brush adjustment, right and left-hand rotation. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7–1, EN 10226 (DIN 2999, BSPT) R right-hand respectively for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.
Set R $\frac{1}{2}$ – $\frac{3}{4}$ –1–1 $\frac{1}{4}$ –1 $\frac{1}{2}$ –2	540020
Set M 20–25–32–40–50 (M × 1.5)	540022

REMS Amigo 2 Set for NPT threads available.  
Other voltages on request.



## Accessories

Description	Art.-No.
<b>Quick-change die heads, dies, attachment heads for button dies, see page 28–29.</b>	
<b>REMS Amigo 2 drive unit</b>	540000
<b>Support bracket Amigo 2</b>	543000
<b>REMS REG St <math>\frac{1}{4}</math>–2"</b> , pipe deburrer, see page 85.	731700
<b>Dual purpose holder</b> for threading and sawing with REMS Amigo E, Amigo, Amigo 2 and REMS Tiger ANC	543100
<b>Ratchet lever</b> see page 22.	522000
<b>Thread-cutting oil</b> see page 47.	
<b>REMS Nippelspanner <math>\frac{3}{8}</math>–2"</b> see page 46.	
<b>Steel case with inlay</b>	546000

