

REMS Ax-Press 25 / 25 L ACC

Cordless axial press with automatic return

Compact, handy electric tool for producing compression sleeve joints and for expanding tubes. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression Ø 12–40 mm

REMS Ax-Press 25 ACC – universal up to Ø 40 mm. Super light, super handy. Fast. With automatic return. Optimum weight distribution for single-hand operation. Swivelling compression device.

System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 and REMS Ax-Press 25 L. Thus easy, economic stocking.

Compression heads for all common systems

Full range of REMS compression heads for all common compression sleeve systems (page 179–180). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (**Patent DE pending**) (page 179). No need to change compression heads. Extremely simple, saves time.

Design

Compact, handy, light. REMS Ax-Press 25 drive machine with battery weighs only 2.9 kg, only 29 cm long REMS Ax-Press 25 L drive machine with battery weighs only 3.1 kg, only 32 cm long REMS Ax-Press 25 and REMS Ax-Press 25 L with 40 mm stroke respectively REMS Ax-Press 25 with preset compression head position for pressing compression sleeve connectors with a clamping distance ≤ 82 mm in one action REMS Ax-Press 25 L with selectable compression head position for pressing compression sleeve connectors with a clamping distance ≤ 116 mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. Integrated LED work light for illuminating the work place. Swivelling compression device for working in confined area. Extension for enlarging the clamping distance on the pressing sleeve connector, also for double pressings, as an accessory. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads. For battery and corded operation. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED.

Drive

Enormous pressing force for fast and perfect jointing. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 420 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 1.5 or 3.0 Ah capacity for long service life. Powerful and light. Total discharge and overload protection with single cell monitoring. Temperature monitoring during the charging process. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger for short charging times. Li-Ion 230 V/14.4 V voltage supply for mains operation 230 V instead of Li-Ion 14.4 V battery, as accessory.

Expanding

Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems



←ACC→
Automatic Circuit Control

with automatic circuit control and charging status check

e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
ROTEX,
Seppelfricke,
TECE,
TIEMME,
Würth



←ACC→
Automatic Circuit Control


with automatic circuit control and charging status check

e.g.
AC-FIX,
BARBI,
BRASELI,
Brass & Fittings,
EUROP FLUIDES,
Fittings Estándar,
ISOLTUBEX,
PLÁSTICOS FERRO,
Velta



Tested by electro:uisse >>

German Quality Product



Supply format

REMS Ax-Press 25 ACC Basic-Pack. Cordless axial press for producing compression sleeve joints Ø 12–40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance ≤ 82 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 14,4 V, 420 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. Integrated LED work light. Battery Li-Ion 14.4 V, 1.5 Ah, rapid charger Li-Ion/Ni-Cd 230 V or 110 V, 50–60 Hz, 50 W. Without compression heads. In sturdy steel case.

	Art.-No.	
	573033	

Other voltages on request.



Supply format

REMS Ax-Press 25 L ACC Basic-Pack. Cordless axial press for producing compression sleeve joints Ø 12–40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance ≤ 116 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 14,4 V, 420 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. Integrated LED work light. Battery Li-Ion 14.4 V, 1.5 Ah, rapid charger Li-Ion/Ni-Cd 230 V or 110 V, 50–60 Hz, 50 W. Without compression heads. In sturdy steel case.

	Art.-No.	
	573034	

Other voltages on request.



Accessories

Description	Art.-No.
REMS compression heads see page 179–180.	

Expander heads P see page 189.

REMS Ax-Press 25 ACC drive unit, without battery	573003
REMS Ax-Press 25 L ACC drive unit, without battery	573004
REMS Akku-Ex-Press P ACC drive unit, without battery	575008
Battery Li-Ion 14,4 V, 1.5 Ah	571545
Battery Li-Ion 14.4 V, 3.0 Ah	571555
Rapid charger Li-Ion/Ni-Cd 230 V, 50–60 Hz, 65 W	571560
Voltage supply Li-Ion 230 V/14.4 V for mains operation 230 V instead of battery Li-Ion 14.4 V.	571565
Steel case with insert	578290
REMS cordless LED lamp see page 95	175200

