

# REMS Ax-Press 30 22V

Cordless axial press 30 kN

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Axial compression  $\varnothing$  12–32 mm

**REMS Ax-Press 30 22V – up to  $\varnothing$  32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfcI ALUPEX-EXPRESS  $\varnothing$  16 mm with one battery charge\*.**

## Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

## Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

## Drive

High pressing force for perfect pressing in seconds, e.g.  $\varnothing$  26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

## Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings, 4.4 Ah for approx. 380 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfcI ALUPEX-EXPRESS  $\varnothing$  16 mm with one battery charge\*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

## Supply format

**REMS Ax-Press 30 22V Basic-Pack.** Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve  $\varnothing$  12–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V, 50–60Hz, 70W. In sturdy steel case.

	Art.-No.	лв.
	573018R220	4 150,00

## Accessories

Description	Art.-No.	лв.
<b>REMS Ax-Press 30 22V drive unit, without battery</b>	573008R22	3 090,00
<b>Battery Li-Ion 21.6V, 2.5 Ah</b>	571571R22	510,00
<b>Battery Li-Ion 21.6V, 4.4 Ah</b>	571574R22	730,00
<b>Battery Li-Ion 21.6V, 5.0 Ah</b>	571581R22	610,00
<b>Battery Li-Ion 21.6V, 9.0 Ah</b>	571583R22	820,00
<b>Rapid charger 100–240V, 50–60Hz, 90W</b>	571585R220	344,00
<b>Rapid charger 100–240V, 50–60Hz, 290W</b>	571587R220	820,00
<b>Voltage supply 220–240V/21.6V, 50–60Hz, 15A, for mains operation instead of battery Li-Ion 21.6 V.</b>	571567R220	820,00
<b>Steel case with insert</b>	573282R	216,00
<b>REMS Lumen 2800 22V, cordless LED flood light, see page 111</b>		

## REMS compression heads

Compression sleeve system	Compression head	Art.-No.	лв.
<b>Brasstech Raptor/ Metalpex/ Raptor 2/ MULTitermoSAN</b>	ME 14 (pack of 2)	573100	212,00
	ME 16 (pack of 2)	573102	212,00
	ME 20 (pack of 2)	573106	212,00
	ME 26 (pack of 2)	573108	212,00
	ME 32 (pack of 2)	573110	232,00
<b>General Fittings Serie 5400</b>	ME 14 (pack of 2)	573100	212,00
	ME 16 (pack of 2)	573102	212,00
	ME 20 (pack of 2)	573106	212,00
	ME 26 (pack of 2)	573108	212,00
	ME 32 (pack of 2)	573110	232,00



e.g.  
Brasstech,  
General Fittings,  
Georg Fischer pfcI

German Quality Product



## REMS compression heads

Compression sleeve system	Compression head	Art.-No.	лв.
<b>Georg Fischer pfcI ALUPEX-EXPRESS/ Alupex Gas System</b>	ME 16 (pack of 2)	573102	212,00
	ME 20 (pack of 2)	573106	212,00
	ME 26 (pack of 2)	573108	212,00
<b>Logstor</b>	ME 16 (pack of 2)	573102	212,00
	LR 20 (pack of 2)	573430	212,00
	LR 22 (pack of 2)	573432	212,00
	LR 25 (pack of 2)	573434	212,00
	LR 28 (pack of 2)	573436	212,00
	LR 32 (pack of 2)	573438	232,00