Accessories

| Description | ArtNo. | лв. |
|--|-------------------|------------------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| REMS Simplex 2. Robust, handy drilling stand for core | 183700R | 2040.00 |
| drilling up to Ø 202 mm. Description see page 328. | 103700K | 2 060,00 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| REMS Titan. Robust, highly stable drilling stand for core | | |
| drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Description see | | |
| page 328. | 183600 R | 3 120,00 |
| Titan drilling template for easy setting of the fastening | 102/050 | 117.00 |
| holes. For REMS Titan drilling stand. Carbide masonry drills Ø 15 mm SDS-plus | 183605R | 117,00 |
| for hammer anchors M12 | 079018 | 57,20 |
| Hammer anchor M12 (pack of 50), for concrete | 079005R50 | 223,00 |
| Setting iron for hammer anchor M12 Carbide masonry drill Ø 20 mm SDS-plus | 182050R | 32,70 |
| for splaying anchors M12 | 079019 | 129,00 |
| Splaying anchor M12 (pack of 10), for masonry, reusable | 079006R10 | 210,00 |
| Quick clamping set 160 for fastening the drilling stand | 077000110 | 210,00 |
| with anchors, consisting of cord threaded bar 160 mm | | |
| with M12 × 52 thread, quick clamping nut, washer. Quick clamping set 500 for fastening the drilling stand | 079010 | 148,00 |
| without anchor, consisting of cord threaded bar 500 mm, | | |
| 2 quick clamping nuts, 2 washers | 183607R | 110,00 |
| Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring | | |
| for base plate. | 183603R | 202,00 |
| Vacuum pump, for vacuum ≤ - 900 mbar (90%), | | |
| consisting of dry running rotary slide pump, oil-free, | | |
| performance 6 m3/h, condenser motor 230 V, | | |
| 50 – 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC | | |
| fabric hose with bayonet coupling. | 183670 R220 | 3 880,00 |
| Laser drilling centre pointer | 183604R | 265,00 |
| Drilling start aid G ½ TDKB , with bores for extracting the drilling dust from the bore hole, with carbide | | |
| masonry drill Ø 8 mm | 180145R | 187,00 |
| Carbide masonry drill Ø 8 mm for drilling aid | 079013 | 38,40 |
| Single open ended wrench size 41 for loosening the universal diamond core drilling crowns | 079003 | 77,70 |
| Light loosening ring, for light loosening | | , , , , |
| of the diamond core crown | 180015 | 41,90 |
| Sharpening stone for diamond core drilling crowns | 180155R 079012 | 124,00 132,00 |
| Circular spirit level, magnetic, | 0/7012 | 132,00 |
| for aligning the drill stand | 182010R | 153,00 |
| Detect B. Electronic bore hole centre tracking device, for | exact deter | mination |

Detect B. Electronic bore hole centre tracking device, for exact determination of the in and out centres of through-bores, see page 340.

Dust protection doors, see page 120.

REMS Pull 2 M, dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 344

