

Accessories

For REMS Picus S1, REMS Picus S3, REMS Picus SR,
REMS Picus S2/3,5 and other makes

Description	Art.-No.	лв.
Water pressure tank for 10 ltr of water, for wet drilling without water connection	182006R	402,00
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	113,00
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	55,10
Hammer anchor M12 (pack of 50) , for concrete	079005R50	215,00
Setting iron for hammer anchor M12	182050R	31,50
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	125,00
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	201,00
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	143,00
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	106,00
Titan vacuum fastening , consisting of cover plate with nipple for 3/8" screw connection and sealing ring for base plate.	183603R	195,00
Vacuum pump , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	3 740,00
Laser drilling centre pointer	183604R	254,00
Drilling start aid G ½ UDKB , with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 180160 R), with carbide masonry drill Ø 8 mm	180140R	180,00
Carbide masonry drill Ø 8 mm for drilling aid	079013	37,00
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	75,10
Light loosening ring , for light loosening of the diamond core crown	180015	40,50
Drilling crown extension 200 mm	180155R	120,00
Sharpening stone for diamond core drilling crowns	079012	127,00
Circular spirit level , magnetic, for aligning the drill stand	182010R	148,00
Suction rotor for dust extraction with G ½ male connecting thread, UNC 1¼ male connecting thread and with connection for REMS Pull 2 and other suitable extractors.	180160R	340,00
Water suction device , for wet drilling up to Ø 170 mm, consisting of water collection ring with pressure ring, rubber washer Ø 200 mm and universal pressure pad for all REMS drilling stands.	183606R	770,00
Rubber washer Ø 200 mm (pack of 10) , for water suction device	183675R10	146,00
REMS Pull 2 L / M , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		

