# **REMS Turbo Cu-INOX**

Compact, portable circular pipe sawing machinefor burr-reduced, right angle and rapid sawing.For stainless steel pipes, carbon steel pipes and copperpipes of the press fitting systems etc. Also for cuttingthin-walled sections for front-wall installation.For job site and workshop.Stainless steel pipes, carbon steel pipes,copper pipes and other materials≤ Ø 76 mmREMS saw bladeØ 225 mm

# REMS Turbo Cu-INOX – burr-reduced, right angle, rapid. Burr-reduced sawing through double clamping vice. Powerful, e.g. Ø 22 mm in only 4 s. Easy to transport.

## Ideal for pressfitting systems

In accordance with requirements: **Dry sawing**, so no damage to 0-rings from lubricants. **<u>Burr-reduced</u>** through double clamping vice. **<u>Optimum cutting</u>** speed prevents degradation of pipe material through overheating.

### Design

Compact, robust, job site-proven. Small in size, handy, portable, only 17 kg. Easy sawing through favourable leverage effect. Fast saw blade change. Precise sawing. Mark on the saw blade protection cover showing the saw blade cutting line. Connection for driving outer/inner pipe deburrer REMS REG 10–54 E. For workbench, stand or wheel stand as an accessory, for easy transport, optimum working height and stable positioning.

### Universal double clamping vice

Robust, easy-running universal double clamping vice for burr-reduced sawing. Both pipe ends remain securely clamped during sawing. Easy, secure clamping also of thin-walled pipes through inclined jaw. Only one strong clamping spindle for both clamping sides ensures even, effortless and secure clamping of the material.

#### Drive

Robust gear, precisely mounted in roller and needle bearings, maintenance-free. Proven universal motor, 500 W. Powerful, e.g. stainless steel pipe Ø 22 mm in only 4 s. Ideal speed 60 rpm for optimum cutting speed and smooth sawing.

#### **REMS** saw blades

Top German quality. REMS circular saw blade HSS 225 × 2 × 32 mm, 220 teeth, for metal, adjusted to the efficiency of REMS Turbo Cu-INOX for sawing stainless steel tubes. Specially fine-toothed, hardened and ground. For easy and exact sawing. Prolonged durability. REMS circular saw blade HSS-E (cobalt alloyed)  $225 \times 2 \times 32$  mm, 220 teeth, for metal, for even better durability. Specially fine-toothed, hardened and ground.

#### Outer/inner pipe deburrer

Outer/inner pipe deburrer REMS REG 10-54 E for pipes Ø 10-54 mm, Ø  $\frac{1}{2}$  - 21%", for electric drive with the REMS Turbo Cu-INOX pipe circular sawing machine and others, see page 99.

#### Supply format

**REMS Turbo Cu-INOX Basic.** Circular pipe saw with universal double clamping vice for burr-reduced, right angle, rapid sawing. For stainless steel pipes, carbon steel pipes and copper pipes of the press fitting systems etc. Also for cutting thin-walled sections for front-wall installation. For REMS saw blade Ø 225 mm. With maintenance-free gear, proven universal motor 230 V or 110 V, 50–60 Hz, 500 W. Safety tip switch, saw blade protection cover. Speed 60 rpm. Ring spanner. Hexagon key. Without saw blade. For workbench, stand or wheel stand. In a carton.

	ArtNo.	лв.
	849006 R220	2 520,00
Other voltages on request.		

#### Accessories

Description	ArtNo.	лв.
<b>REMS circular saw blade HSS</b> for metal, specially for stainless steel pipes, fine-toothing, 225 × 2 × 32 mm, 220 teeth.	849703R	435,00
REMS circular saw blade HSS-E (cobalt alloyed) circular saw blade HSS-E (cobalt alloyed) toothing, 225 × 2 × 32 mm, 220 teeth. Very long service life.	849706R	610,00
REMS REG 10-54 E outer/inner pipe deburrer, see pag	ge 99	
Stand	849315R	425,00
Wheel stand	849310R	690,00
REMS Jumbo, folding workbenches, see page 106.		
<b>REMS Herkules</b> , material supports, see page 107.		







German Quality Product



