

REMS Amigo 2 Compact

Electric die stock with quick-change die heads

Powerful, easy-to-operate electric tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site.

Pipe threads $\frac{1}{8}$ – 2", 16 – 50 mm
Bolt threads 6 – 30 mm, $\frac{1}{4}$ – 1"

Thread types see page 36, 37.

REMS Amigo 2 Compact – The smallest and lightest up to 2".

System advantage

Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Drive unit only 4.9 kg, without die head. Perfect seating of quick-change die heads.

Drive

Solid, maintenance-free gear. Robust 1200 W universal motor with 30 % power increase thanks to automatic carbon brush adjustment while changing the direction of rotation. Peak power input up to 1800 W. Fast threading time 30 – 18 rpm. Safety tip switch.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 53). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner $\frac{3}{8}$ – 1" (2") (page 52).



German Quality Product



Info



Supply format

REMS Amigo 2 Compact Set. Electric die stock with quick-change die heads. For pipe threads $\frac{1}{8}$ – 2", 16 – 50 mm, bolt threads 6 – 30 mm, $\frac{1}{4}$ – 1". For right and left-hand threads. Drive unit with maintenance-free gear, powerful universal motor 230 V or 110 V, 50 – 60 Hz, 1200 W, safety tip switch, power increase thanks to automatic carbon brush adjustment. Peak power input up to 1800 W. Right and left-hand rotation. Overload protection. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, for pipe thread taper Pipe Thread ASME B1.20.1 NPT right-hand or for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	Art.-No.	KM
Set R $\frac{1}{2}$ + $\frac{3}{4}$ + 1 + 1 $\frac{1}{4}$	540023R220	3.330,00
Set R $\frac{1}{2}$ + $\frac{3}{4}$ + 1 + 1 $\frac{1}{4}$ + 1 $\frac{1}{2}$ + 2	540024R220	3.630,00
Set NPT $\frac{1}{2}$ + $\frac{3}{4}$ + 1 + 1 $\frac{1}{4}$	540026R220	3.330,00
Set NPT $\frac{1}{2}$ + $\frac{3}{4}$ + 1 + 1 $\frac{1}{4}$ + 1 $\frac{1}{2}$ + 2	540027R220	3.630,00
Set M 20 + 25 + 32 + 40 + 50 (M x 1.5)	540025R220	3.970,00

Other voltages on request.



Accessories

Description	Art.-No.	KM
Quick-change die heads, dies, attachment heads for button dies, see page 36 – 37.		
Amigo 2 Compact drive unit	540001R220	2.310,00
Support bracket Amigo 2 Compact	543010	478,00
REG St $\frac{1}{2}$ – 2", pipe deburrer, see page 105.	731700	316,00
Ratchet lever eva see page 28.	522000	354,00
Thread-cutting oil see page 53.		
REMS Nippelspanner $\frac{3}{8}$ – 2" see page 52.		
Steel case with inlay	546000	271,00

