REMS Blitz

Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.

Copper tubes	≤ Ø 35 mm
Heating, annealing, burning, melting, thaw	ing, shrinking
and similar thermal procedures.	

Flame temperature 1950°C (3500°F)

REMS Blitz – extremely fast soft soldering.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 200 g/h!

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame

Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.



German Quality Product



REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes ≤ Ø 35 mm. Piezo-electric self-lighting. Hose connector BSPP %" LH. Hollow cap nut and socket BSPP %" LH. In blister pack.

ArtNo.	KM
160010R	494,00

Accessories

Description	ArtNo.	KM
REMS soldering material see page 267.		
High pressure hose 3 m, BSPP ¾ LH	152106	183,00
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109	236,00



REMS Macho

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.		
Copper tubes and others	≤ Ø 64 mm	
Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.		
Flame temperature	2500°C	

REMS Macho – super fast brazing.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 360 g/h!

Acetylene only

Injection torch burns atmospheric oxygen. Hence only acetylene necessary. **Design**

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame

Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others ≤ Ø 64 mm. Piezo-electric self-lighting. Hose connector BSPP %" LH. Hollow cap nut and socket %" LH. In blister pack.

ArtNo.	KM
161010R	544,00

Turbo soldering torch acetylene



German Quality Product



Accessories

REMS soldering material see page 267.