

REMS Lumen 2800 22V

Cordless LED flood light

Powerful, mobile cordless LED flood light with high light intensity. Li-Ion 22V Technology. For battery and corded operation.

Light flux brightness stage 1	1100 lm
Light flux brightness stage 2	2000 lm
Light flux brightness stage 3	2800 lm

REMS Lumen 2800 22V – lights everywhere. With high light intensity. Mobile, handy, light. For battery and corded operation. Continuous swivel.

Universal use

Powerful, mobile, cordless LED flood light with high light intensity for universal use on the building site or in the workshop. 3 selectable brightness stages, ideal for any application purpose.

Design

Handy, lightweight, cordless LED flood light, only 1.7 kg, with battery only 2.1 kg. Impact-resistant plastic housing. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by wing nuts, for optimum alignment of the light. On/Off switch. Tubular steel frame with plastic plate and pluggable hook, for fastening or hanging the flood light. Practical, non-slip handle. 220–240V, 50–60 Hz, 138 W power supply, for mains operation included. Holder for REMS Li-Ion 22V integrated into the housing for cordless instead of mains operation. In cordless operation with Li-Ion 22V, 2.5 Ah, 54 Wh (output). Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. LED brightness selectable in 3 stages. 120° radiation angle for high illumination. Colour temperature 6,500 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks prevents overheating. For continuous operation.

Battery or mains operation

REMS Li-Ion 22V Technology, see page 20–25. Highly resistant Li-Ion 22V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240 V, 90 W. Rapid charger 100–240 V, 90 W, 22 V or 290 W, 22 V, for shorter charging times, as accessory.

Description	Operating hours h*		
	Stage 1	Stage 2	Stage 3
Battery Li-Ion 22V, 2.5 Ah, 54 Wh	5.4	2.4	1.6
Battery Li-Ion 22V, 4.4 Ah, 95 Wh	9.6	4.2	2.8
Battery Li-Ion 22V, 5.0 Ah, 108 Wh	10.9	4.8	3.2
Battery Li-Ion 22V, 9.0 Ah, 194 Wh	19.6	8.6	5.7

Supply format

REMS Lumen 2800 22V Set Power-Edition. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Voltage supply 220–240 V, 50–60 Hz, 138 W, 24 V, 1.5 A. Without battery, without rapid charger. In a carton.

	Art.-No.	KM
	175210R220	302,00

Other voltages on request.

Supply format

REMS Lumen 2800 22V Set. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Battery Li-Ion 22V, 2.5 Ah, 54 Wh, rapid charger 220–240 V or 110 V, 50–60 Hz, 70 W, 22 V. Voltage supply 220–240 V, 50–60 Hz, 138 W, 24 V, 1.5 A. In a carton.

	Art.-No.	KM
	175211R220	888,00

Other voltages on request.

Accessories

Description	Art.-No.	KM
Power-Pack 22V 2.5 Ah + 2.5 Ah + 90 W, 108 Wh, consisting of 2 batteries Li-Ion 22V, 2.5 Ah, 54 Wh, rapid charger 100–240 V, 50–60 Hz, 90 W, 22 V	571590R220	1.330,00
Battery Li-Ion 22V, 2.5 Ah, 54 Wh	571571R22	464,00
For other batteries Li-Ion 22V/Power-Packs 22V see page 20–25.		
Rapid charger 100–240 V, 50–60 Hz, 90 W, 22 V	571585R220	403,00
Rapid charger 100–240 V, 50–60 Hz, 290 W, 22 V	571587R220	868,00
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230R	65,20



Info

