Accessories

Description	ArtNo.	KM
REMS Simplex 2. Robust, handy drilling stand for core	1027000	2 120 00
drilling up to Ø 202 mm. Description see page 328.	183700 R	2.130,00
$\textbf{REMS Titan.} \ \textbf{Robust, highly stable drilling stand for core}$		
drilling in steel-reinforced concrete and other materials up to \emptyset 300 mm. For high demands. Description see		
page 328.	183600R	3.230,00
Titan drilling template for easy setting of the fastening	10240ED	121.00
holes. For REMS Titan drilling stand. Carbide masonry drills Ø 15 mm SDS-plus	183605 R	121,00
for hammer anchors M12	079018	59,10
Hammer anchor M12 (pack of 50), for concrete	079005R50	231,00
Setting iron for hammer anchor M12 Carbide masonry drill Ø 20 mm SDS-plus	182050R	33,80
for splaying anchors M12	079019	133,00
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	217,00
Quick clamping set 160 for fastening the drilling stand	077000110	217,00
with anchors, consisting of cord threaded bar 160 mm		
with M12 × 52 thread, quick clamping nut, washer.	079010	153,00
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm,		
2 quick clamping nuts, 2 washers	183607R	114,00
Titan vacuum fastening, consisting of cover plate with nipple for 3/8" screw connection and sealing ring		
for base plate.	183603R	209,00
No		
Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free,		
performance 6 m3/h, condenser motor 230 V,		
50 – 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC		
fabric hose with bayonet coupling.	183670R220	4.010,00
Laser drilling centre pointer	183604R	273,00
Drilling start aid G ½ TDKB , with bores for extracting the drilling dust from the bore hole, with carbide		
masonry drill Ø 8 mm	180145R	193,00
Carbide masonry drill Ø 8 mm for drilling aid	079013	39,70
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	80,30
Light loosening ring, for light loosening		
of the diamond core crown	180015	43,30
Drilling crown extension 200 mm Sharpening stone for diamond core drilling crowns	180155R 079012	129,00 136,00
Circular spirit level, magnetic,	0/7012	130,00
for aligning the drill stand	182010R	158,00
Detect B. Electronic bore hole centre tracking device, for of the in and out centres of through-hores, see page 3/0	exact deter	mination

Detect B. Electronic bore hole centre tracking device, for exact determination of the in and out centres of through-bores, see page 340.

Dust protection doors, see page 120.

REMS Pull 2 M, dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 344

