## **REMS Power-Ex-Press P-CEF ACC**

Electro-hydraulic pipe expander 34 kN with automatic return

Compact, handy power tool for fast, easy expanding of pipes/rings. For trade and industry. For the building site and the workshop.

Cold Expansion Fittings made of plastic (P-CEF)  $\emptyset$  16-63 mm  $\emptyset$   $\frac{1}{2}-2"$  s  $\leq$  6.3 mm

# REMS Power-Ex-Press P-CEF ACC – Fast, easy electric expanding up to Ø 63 mm. With automatic return. For Uponor Quick & Easy and Giacomini GX System.

#### **Expander heads**

Large expanding capacity up to Ø 63 mm. Automatic, gradual expansion until reaching the given end position which is determined by the expander head. Use of the REMS P-CEF expander heads and suitable expander heads of other makes for: Expander 50-63 mm, 2", for holding the REMS P-CEF expander heads 50-63 mm, 2" and suitable expander heads of other makes. Expander 16-40 mm,  $\frac{1}{2}-1\frac{1}{2}$ ", for holding the REMS P-CEF expander heads of other makes itable expander heads of other makes the expander heads of other makes and suitable expander heads of -40 mm,  $\frac{1}{2}-1\frac{1}{2}$ " and suitable expander heads of other makes, as an accessory.

#### Execution

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.6 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip.

#### Drive

High pressing force for fast, perfect expanding. Thrust force 34 kN. Powerful electro-mechanical drive with automatic return (ACC), with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Safety tip switch.



German Quality Product



### Supply format

**REMS Power-Ex-Press P-CEF ACC Basic-Pack.** Electro-hydraulic pipe expander 34 kN for expanding tubes/coils of the Uponor Quick & Easy system Ø 16-63 mm, Ø  $\frac{1}{2} - 2^{\circ}$ , s  $\leq 6.3$  mm. Electro-hydraulic drive with automatic retraction, ith proven universal motor 230 V or 110 V, 50-60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Expanding device 50-63 mm, 2°. Without expander heads. In sturdy steel case.

ArtNo.	KM
575017R220	2.960,00

Note assembly instructions of system supplier. Battery tube expander for other systems on request. Other voltages on request.

#### Accessories

Description	ArtNo.	KM
<b>Expander 16 – 40 mm, <math>\frac{1}{2}</math> – <math>\frac{1}{2}</math>", for holding the P-CEF expander heads <math>16-40</math> mm, <math>\frac{1}{2}</math> – <math>\frac{1}{2}</math>"</b>	575100R	248,00
Expander heads P-CEF see page 257.		
Steel case with insert	575278R	223,00





rman Quality Draduat

