

REMS Power-Press XL ACC

Electro-hydraulic radial press XL 32 kN
with automatic retraction

Universal, powerful power tool with automatic circuit control for making press joints of all common press fitting systems.

Pipe pressing joints \varnothing 10 – 108 (110) mm
 \varnothing 3/8 – 4"

Complete range of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems, see page 212 – 258.

REMS Power-Press XL ACC – universal up to \varnothing 110 mm.
Pressing of \varnothing 10 – 108 mm in just one action.
Ultra-fast, e.g. Geberit Mapress stainless steel \varnothing 108 mm in only 15 seconds. With automatic circuit control.
Automatic locking of pressing tongs.

System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with * have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

Pressing tongs/pressing rings for all common systems
Complete assortment of REMS pressing tongs/pressing rings/pressing rings XL for all common pressfitting systems (page 212 – 258). Highly durable pressing tongs/XL pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings/pressing rings XL are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs are required, as an accessory, for driving the REMS (PR) pressing rings.

Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.5 kg. Long working stroke for pressings in a single action, ideal for large dimensions. Ultra-fast, e.g. Geberit Mapress stainless steel \varnothing 108 mm in only 15 seconds. Ergonomically designed housing with soft grip and recessed handle. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings. Adjustable hand guard.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Supply format

REMS Power-Press XL ACC Basic-Pack. Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints \varnothing 10 – 108 (110) mm, \varnothing 3/8 – 4". For driving REMS pressing tongs/pressing rings/pressing rings XL and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. In XL-Boxx system case.

	Art.-No.	KM
	579012R220	4.920,00

Other voltages on request.

Accessories

Description	Art.-No.	KM
Power-Press XL ACC drive Unit	579000R220	4.410,00
Adapter tongs Z6 XL for driving REMS pressing rings 64.0 – 108.0 XL (PR-3S), 2 1/2 – 4" XL (PR-3S) with REMS Power-Press XL ACC	579120R	779,00
Adapter tongs for other REMS pressing rings see page 258.		
Pressing tongs/pressing rings/pressing rings XL see page 212 – 258.		
Cropping tongs for threaded rods see page 261.		
Cable shear for electric cable see page 261.		
XL-Boxx system case with inserts	579601R	504,00



German Quality Product



Info

