Handy quality tools for simple and fast external chamfering  $(15^{\circ})$  of pipes.

Plastic pipes  $\emptyset$  16 – 250 mm,  $\emptyset$  3⁄4 – 10" Wall thickness  $\leq$  PN 16

## REMS RAG - chamfering at 15°.

Chamfering at 15° on commonly used plastic pipes.

Also suited for deburring plastic pipes. Ensures easy joining of sleeves to be welded.

Easily adjusted for pipe diameter and wall thickness.

Very fast and easy chamfering due to a particularly favourable cutting geometry of the chamfering blades.

Two adjacent, identical chamfering blades, one of which cuts the chamfer and the other one serves as a support for the pipe during chamfering. If the cutting chamfering blade is worn, it can be exchanged with the support part, for double the service life.

Easy-to-slide V-block with two different bevel angles for good guidance of small pipe sizes. In high-grade, glass-fibre reinforced polyamide.



German Quality Product



Supply format			
REMS RAG. Pipe chamfering tool f	or plastic pipes. With bla	ades. In a ca	rton.
Description	Pipes ≤ Ø mm/inch	ArtNo.	KM
P 16-110	16-110 / 3/4-4"	292110R	449,00
P 32-250	32-250 / 11/4-10"	292210R	524,00





## Accessories

Description	ArtNo.	KM
Chamfering blades (pack of 2) for REMS RAG P 16-250	292011	180,00