

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	425,00
	R 1/4	521010	371,00
	R 3/8	521020	251,00
	R 1/2	521030	261,00
	R 3/4	521040	273,00
	R 1	521050	284,00
	R 1 1/4	521060	296,00
	R 1 1/2	521070	348,00
	R 2	521080	371,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	510,00
	R 1/4 LH	521110	445,00
	R 3/8 LH	521120	302,00
	R 1/2 LH	521130	314,00
	R 3/4 LH	521140	328,00
	R 1 LH	521150	340,00
	R 1 1/4 LH	521160	356,00
	R 1 1/2 LH	521170	419,00
	R 2 LH	521180	445,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	425,00
	NPT 1/4	521210	371,00
	NPT 3/8	521220	251,00
	NPT 1/2	521230	261,00
	NPT 3/4	521240	273,00
	NPT 1	521250	284,00
	NPT 1 1/4	521260	296,00
	NPT 1 1/2	521270	348,00
	NPT 2	521280	371,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	328,00
	M 20 x 1.5	521310	328,00
	M 25 x 1.5	521320	340,00
	M 32 x 1.5	521330	356,00
	M 40 x 1.5	521340	419,00
	M 50 x 1.5	521350	445,00



Right-hand pipe thread



Left-hand pipe thread

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	KM
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	194,00
	R 1/4	521012RWS	183,00
	R 3/8	521022RWS	183,00
	R 1/2	521032RWS	183,00
	R 3/4	521042RWS	200,00
	R 1	521052RWS	200,00
	R 1 1/4	521062RWS	200,00
	R 1 1/2	521072RWS	200,00
	R 2	521082RWS	200,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	233,00
	R 1/4 LH	521112RWS	221,00
	R 3/8 LH	521122RWS	221,00
	R 1/2 LH	521132RWS	221,00
	R 3/4 LH	521142RWS	241,00
	R 1 LH	521152RWS	241,00
	R 1 1/4 LH	521162RWS	241,00
	R 1 1/2 LH	521172RWS	241,00
	R 2 LH	521182RWS	241,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	194,00
	NPT 1/4	521212RWS	183,00
	NPT 3/8	521222RWS	183,00
	NPT 1/2	521232RWS	183,00
	NPT 3/4	521242RWS	200,00
	NPT 1	521252RWS	200,00
	NPT 1 1/4	521262RWS	200,00
	NPT 1 1/2	521272RWS	200,00
	NPT 2	521282RWS	200,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	241,00
	M 20 x 1.5	521312RWS	241,00
	M 25 x 1.5	521322RWS	241,00
	M 32 x 1.5	521332RWS	241,00
	M 40 x 1.5	521342RWS	241,00
	M 50 x 1.5	521352RWS	240,00



German Quality Product