

REMS Tiger pneumatic

Pneumatic reciprocating pipe saw

Powerful, robust, handy compressed air tool with force-transmitting guide holder for effortless, fast, right-angled sawing everywhere on site, without a vice. Also for universal free-hand sawing. Ideal for use in dangerous, e.g. in wet environment.

Ideal for steel pipes and others.

Many materials, e.g. wood, wood with nails, pallets, metal, even stainless steel, cast iron, breeze blocks, plaster boards, pumice stone, brick

For materials that are difficult to cut, e.g. stainless steel pipes, hard cast iron, use the REMS Tiger SR with electronic stroke speed control.

REMS Tiger pneumatic – for sawing in dangerous environment.

Saws effortless, fast, right-angle. Force transmitting guide support for 400 % more sawing power.

Sturdy, square lift rod. Oscillating drive with ANC.

Aggressive orbital action for fast feed forward sawing and long service life of saw blades. Universal saw blade clamp.

Design

Robust, job site-proven. Slender, handy design. Super light, only 3.8 kg. Can be used anywhere. Ergonomically shaped front housing grip with slip resistant, heat insulating protection cover with soft grip, for forceful feed forward during free-hand sawing. Swivel support shoe for safe guiding of the saw on the material to be sawn. High sliding silicone gasket protects gear against water and dust. Powerful pneumatic motor with ample reserve capacity, 1000 W. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Operating pressure 6 bar, air consumption $\leq 1.6 \text{ m}^3/\text{min}$. Safety switch with lock.

Additional description see REMS Tiger, page 70 – 71.



German Quality Product



Info



Supply format

REMS Tiger pneumatic Set. Pneumatic reciprocating pipe saw for effortless, fast, right angle sawing with guide support and for free-hand sawing. Drive unit with straight machine handle, maintenance-free, water and dust resistant oscillating drive with allround needle bearing mounted crank drive (ANC), aggressive orbital action, powerful pneumatic 1000 W, operating pressure 6 bar, safety switch with lock. Stroke speed control (accelerator switch) 0 to 1,700 rpm. Air inlet hose, air outlet hose. Universal saw blade clamp. Hexagon key. Guide support 2". 2 pcs. REMS special saw blades 2"/140-3.2. In sturdy steel case.

	Art.-No.	KM
	560022	4.520,00

Accessories

Description	Art.-No.	KM
Saw blades see page 76 – 77.		
Tiger pneumatic drive unit	560002R	3.890,00
Guide support 2" , for pipes $\varnothing \frac{1}{2}$ – 2"	563000R	346,00
Guide support 4" , for pipes $\varnothing 2\frac{1}{2}$ – 4"	563100R	478,00
Guide support 6" , for pipes $\varnothing 5$ – 6"	563200R	542,00
Chain guide support 6" , for $\varnothing \frac{1}{2}$ – 6" pipes and other profiles	563203R	431,00
Dual purpose holder for sawing and threading, with REMS Tiger and REMS Amigo, REMS Amigo 2	543100	555,00
Protective cap for guide support 2", 4" and 6" , for clamping of thin-walled material	563008R	42,30
Steel case	566051R	174,00

