

Powerful, highly efficient electric construction ventilator for supporting dehumidifiers/construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

### REMS Orkan 1360

Air volume	1360 m <sup>3</sup> /h
Power	145 W

### REMS Orkan 2050

Air volume stage I	1740 m <sup>3</sup> /h
Power stage I	355 W
Air volume stage II	2050 m <sup>3</sup> /h
Power stage II	450 W

### REMS Orkan – for aeration.

#### Universal use

Powerful, highly efficient construction ventilator for supporting dehumidifiers/construction driers after floods and water mains damage. Ideal for aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms and for speeding up the drying of concrete, masonry, plaster and screed, for example. For commercial use in trade and industry.

#### Design Orkan 1360

Axial fan in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 6.8 kg, with low-noise, single-phase capacitor motor 230 V, 145 W, with practical handle for carrying. Generated air volume 1,360 m<sup>3</sup>/h.

Large-diameter exhaust air and suction hose, Ø 200 mm, 10 m long, e.g. for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example, as an accessory. An exhaust and suction hose can be fitted to the aeration or deaeration side of the construction ventilator as the situation requires. Dust sack, Ø 200 mm, 2,980 mm long, washable, for collecting coarse and fine dusts up to dust class M, as an accessory.

#### Design Orkan 2050

Turbo radial fan with 2 air volume stages, in sturdy plastic housing of rotation-moulded polyethylene for a long life. Compact, handy design, weighing only 10 kg, with low-noise, single-phase capacitor motor 230 V, 355/450 W, with practical handle for carrying. Horizontal air outlet, adjustable to below 45° or vertical by appropriate resting surfaces on the plastic housing. Generated air volume in 2 selectable stages 1,740/2,050 m<sup>3</sup>/h. Especially suitable for speeding up drying of concrete, masonry, plaster and screed, for example.



### Supply format

**REMS Orkan 1360.** Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms, for supporting the drying of, e.g., concrete, masonry, plaster and screed and for inflating bouncy castles, hot air balloons, for example. Capacitor motor 230V, 50 Hz, 145W, for continuous operation. Very quiet running. Air volume 1,360 m<sup>3</sup>/h. In a sturdy plastic housing. In a carton.

	Art.-No.	€
	132300R220	<b>410,01</b>

Other voltages on request.



Info

### Supply format

**REMS Orkan 2050.** Electric construction ventilator for commercial use. For aeration and deaeration of rooms, spaces, shafts and cavities as well as aeration and wind cooling of machines, marquees, event halls. For supporting the exchange of air in damp, musty cellar rooms. Especially also for drying of, e.g., concrete, masonry, plaster and screed. Capacitor motor 230V, 50 Hz, 355/450 W, for continuous operation. Very quiet running. Air volume 1,740/2,050 m<sup>3</sup>/h. In a sturdy plastic housing. In a carton.

	Art.-No.	€
	132301R220	<b>432,85</b>

Other voltages on request.



Info

### Accessories

Description	Art.-No.	€
<b>Exhaust air and suction hose, Ø 200 mm, 10 m long,</b> for extracting air from rooms, spaces, shafts and cavities, for discharging sucked-in air or dusts to the outside and for inflating bouncy castles, hot-air balloons, for example. For REMS Orkan 1360.	132307R	<b>158,71</b>
<b>Dust sack, Ø 200 mm, 2,980 mm long, washable,</b> for collecting coarse and fine dusts up to dust class M. For REMS Orkan 1360.	132308R	<b>146,67</b>
<b>Operating hours counter and electricity meter,</b> e.g. for reporting to the damage regulator/customer. For REMS Orkan and others.	132132R220	<b>54,81</b>
<b>REMS Detect W,</b> dielectric moisture measuring device for non-destructive moisture measurement in building materials, e.g. concrete, masonry, plaster, wood. In a case.	132115R	<b>233,55</b>
<b>REMS Secco,</b> electric air dehumidifiers/building driers, see page 328.		

