Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.

Copper tubes $\leq \emptyset$ 35 mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 1950°C (3500°F)

REMS Blitz - extremely fast soft soldering.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 200 g/h!

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame

Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.



REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes $\leq \emptyset$ 35 mm. Piezo-electric self-lighting. Hose connector BSPP %" LH. Hollow cap nut and socket BSPP %" LH. In blister pack.

 ArtNo.	€
160010R	259,00









Accessories

Description	ArtNo.	€				
REMS soldering material see page 267.						
High pressure hose 3 m, BSPP 3/8 LH	152106	95,90				
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109	124,00				





REMS Macho

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.

Copper tubes and others $\leq \emptyset$ 64 mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 2500°C

REMS Macho – super fast brazing.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 360 g/h!

Acetylene only

Injection torch burns atmospheric oxygen. Hence only acetylene necessary.

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame

Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others ≤ Ø 64 mm. Piezo-electric self-lighting. Hose connector RSPP %" | H Hollow can put and socket %" | H In blister pack

DO: 1	11 70 Entrodew cap hat and socket 70 Ent in buster pack.				
			ArtNo.	€	
			161010R	285,00	

Turbo soldering torch acetylene



German Quality Product





Accessories

REMS soldering material see page 267.