Proven, reliable testing pump for pressure and tightness tests of piping systems and receptacles.

Testing and pressure range	≤ 6 MPa/60 bar/870 psi		
Water, oil, glycol			
pH-value of liquids	7 – 12		
Temperature of liquids	≤ 60°C		
Viscosity of liquids	≤ 1.5 mPa s		

## REMS Push - reliable pressure hold.

### Universal use

For plumbing, heating, solar system and sprinkler installations, for compressed air, steam and cooling systems, oil installations, for boiler and pressure vessel building.

# Design

Robust, job-site proven metal design for tough use. REMS Push with corrosion-resistant, powder-coated 12 ltr steel tank. Distortion resistant lever with ergonomic handle, doubles as carrying handle when locked. Wear resistant pressure piston in brass, Ø 30 mm. High-pressure hose with  $\frac{1}{2}$ -connection. Fine scale pressure gauge (accessory), p  $\leq$  1.6 MPa/16 bar/232 psi, for reading a pressure change of 0.01 MPa/0.1 bar/1.45 psi for tightness testing according to DIN 1988, as accessory.

### Stainless steel tank

REMS Push INOX with 12 ltr stainless steel tank. For extremely long life.

#### Functioning

Pressure and tightness test with water or oil. Double valve system for reliable pressure built-up, with rust-proof steel balls. High pumping capacity with long stroke, fine pressure adjustment at short pushes. High pressure hose with fabric ply prevents measurement errors.





### Supply format

**REMS Push.** Hand pressure testing pump with pressure gauge,  $p \le 6$  MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi, Corrosion-resistant, powder-coated 12 ltr steel tank. 1.5 m high-pressure hose with  $\frac{1}{2}$ "-connection. In a carton.

€	ArtNo.
295.00	115000R



## Supply format

**REMS Push INOX.** Hand pressure testing pump with pressure gauge,  $p \le 6$  MPa/60 bar/870 psi, for pressure and tightness testing of piping systems and receptacles up to 6 MPa/60 bar/870 psi. 12 ltr stainless steel tank. 1.5 m high-pressure hose with ½"-connection. In a carton.

Art	No. €
1150	1R <b>380,00</b>



## Accessories

Description	Pressure p ≤ MPa/bar/psi	ArtNo.	€
Connecting piece with pressure			
gauge and shut off valve	6/60/870	115110R	131,00
Fine scale pressure gauge	1.6/16/232	115045	84,40



