REMS RAS Cu

Pipe cutters

REMS RAS Cu – quality pipe cutter. With quick adjustment.

Solid, handy, U-shaped design.


Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut. Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for the complete working capacity Ø 3-120 mm.





quick adjustment



German Quality Products

International Design Award

Supply format

REMS RAS Cu. Pipe cutter for copper tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.	€
Cu 8–42 with quick adjustment	8-42 ³ / ₈ -1 ⁵ / ₈ "	3	113370R	164,00
Cu 8–64 with quick adjustment	8-64 ³ / ₈ -2 ¹ / ₂ "	3	113410R	197,00

Accessories

Description	Wall thick- ness s ≤ mm	ArtNo.	€
REMS cutter wheel Cu 3–120, s 3	3	113225 R	12,80
Universal deburring blade, ground		113360	8,40

REMS RAS P

REMS RAS P – the compact version with telescopic spindle.

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life. Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.









Supply format

REMS RAS P. Pipe cutter for plasic pipes and multi-layer composite tubess, with integrated pipe deburring device. With cutter wheel. In blister pack.

with integrated pipe de	eburring device. V	with cutter wheel.	in blister p	ack.
Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.	€
P 10-32 T	10-32 ½-1¾"	4,5	290001 R	61,60
P 10–40 T	10−40 ½−15⁄8″	4,5	290002R	73,90



REMS RAS P

Pipe cutters

High performance quality tools for cutting pipes. With quick adjustment.

Plastic pipes, multi-layer composite tubes

Ø 10-315 mm Ø ½-12"

REMS RAS P – quality pipe cutter. With quick adjustment.

Solid, handy, U-shaped design.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe, easy in-feed, easy cutting and precise, right angle cut. Ergonomic, handy operating knob in metal for easy work and long service life.

Ratchet for quick adjustment in both directions.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers

by in-feed limitation.

Cutter wheels for different wall thicknesses (s).

REMS RAS P 50–125 with integrated pipe deburrer, on rotating bearing, adapts to the workpiece edge to be deburred. Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life. Fast, simple blade change. Additional guide roller, adjustable, for cutting Ø 110 mm or Ø 125 mm pipes Fast cutting wheel change without tools by cutting wheel axle with ball catch.

Supply format

REMS RAS P. Pipe cutter for plasic pipes and multi-layer composite tubes. With cutter wheel. In blister pack/in box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.	€
P 10-40* with quick adjustment	10−40 ½−15⁄8"	7	290050R	164,00
P 10-63* with quick adjustment	10-63 ½-2"	7	290000R	208,00
P 50–110 *, s11 with quick adjustment	50–110 2–4"	11	290100R	249,00
P 50–110 *, s16 with quick adjustment	50–110 2–4"	16	290100R	249,00
P 50–110 *, s19 with quick adjustment	50-90 2-3"	19	290100R	249,00
P 50–125 , s16 with quick adjustment	50–125 2–5"	16	290500 R-S16	257,00
P 110-160* with quick adjustment	110–160 4–6"	16	290200R	307,00

REMS RAS P – cutting up to Ø 315 mm, s \leq 19 mm.

Fast and inexpensive cutting of large pipes. Quick adjustment. Separate pipe centering for right angle cutting. Solid design, double-T-shaped body.

Cutter wheels for different wall thicknesses (s).

Supply format

REMS RAS P. Pipe cutter With cutter wheel and s				e tubes.
Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.	€
P 180–315 with quick adjustment	180–315 7–12"	16	290300	1 830,00

Accessories

Description	s ≤ mm	ArtNo.	€
REMS cutter wheel P 10–40, s 4,5			
for REMS RAS P 10-32 T, 10-40 T	4,5	290023R	20,70
REMS cutter wheel P 10–63, s 7			
for REMS RAS P 10-40, 10-63	7	290016 R	20,70
REMS cutter wheel P 50 – 315, s 11 for REMS RAS P 50 – 110, 50 – 125, 110 – 160, 180 – 315	11	290116R	25,10
REMS cutter wheel P 50 – 315, s 16 for REMS RAS P 50 – 110, 50 – 125, 110 – 160, 180 – 315	16	290216 R	30,00
REMS cutter wheel P 50 – 315, s 19 for REMS RAS P 50 – 110, 110 – 160, 180 – 315	19	290316R	48,40





*German Quality Products







P 50–110, s11 P 50–110, s16 P 50–110, s19





