

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	231,00
	R 1/4	521010	201,00
	R 3/8	521020	136,00
	R 1/2	521030	141,00
	R 3/4	521040	148,00
	R 1	521050	154,00
	R 1 1/4	521060	161,00
	R 1 1/2	521070	188,00
	R 2	521080	201,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	277,00
	R 1/4 LH	521110	241,00
	R 3/8 LH	521120	164,00
	R 1/2 LH	521130	170,00
	R 3/4 LH	521140	178,00
	R 1 LH	521150	185,00
	R 1 1/4 LH	521160	193,00
	R 1 1/2 LH	521170	226,00
	R 2 LH	521180	241,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	231,00
	NPT 1/4	521210	201,00
	NPT 3/8	521220	136,00
	NPT 1/2	521230	141,00
	NPT 3/4	521240	148,00
	NPT 1	521250	154,00
	NPT 1 1/4	521260	161,00
	NPT 1 1/2	521270	188,00
	NPT 2	521280	201,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	178,00
	M 20 x 1.5	521310	178,00
	M 25 x 1.5	521320	185,00
	M 32 x 1.5	521330	193,00
	M 40 x 1.5	521340	226,00
	M 50 x 1.5	521350	241,00



Right-hand
pipe thread



Left-hand
pipe thread



Info

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	105,00
	R 1/4	521012RWS	98,60
	R 3/8	521022RWS	98,60
	R 1/2	521032RWS	98,60
	R 3/4	521042RWS	108,00
	R 1	521052RWS	108,00
	R 1 1/4	521062RWS	108,00
	R 1 1/2	521072RWS	108,00
	R 2	521082RWS	108,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	127,00
	R 1/4 LH	521112RWS	119,00
	R 3/8 LH	521122RWS	119,00
	R 1/2 LH	521132RWS	119,00
	R 3/4 LH	521142RWS	131,00
	R 1 LH	521152RWS	131,00
	R 1 1/4 LH	521162RWS	131,00
	R 1 1/2 LH	521172RWS	131,00
	R 2 LH	521182RWS	130,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	105,00
	NPT 1/4	521212RWS	98,60
	NPT 3/8	521222RWS	98,60
	NPT 1/2	521232RWS	98,60
	NPT 3/4	521242RWS	108,00
	NPT 1	521252RWS	108,00
	NPT 1 1/4	521262RWS	108,00
	NPT 1 1/2	521272RWS	108,00
	NPT 2	521282RWS	108,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	131,00
	M 20 x 1.5	521312RWS	131,00
	M 25 x 1.5	521322RWS	131,00
	M 32 x 1.5	521332RWS	131,00
	M 40 x 1.5	521342RWS	131,00
	M 50 x 1.5	521352RWS	131,00



German Quality Product



Info