

# Accessories

For REMS Picus S1, REMS Picus S3, REMS Picus SR,  
REMS Picus S2/3,5 and other makes

Description	Art.-No.	£
<b>Water pressure tank</b> for 10 ltr of water, for wet drilling without water connection	182006R	<b>212.00</b>
<b>Titan drilling template</b> for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	<b>59.40</b>
<b>Carbide masonry drills Ø 15 mm SDS-plus</b> for hammer anchors M12	079018	<b>29.00</b>
<b>Hammer anchor M12 (pack of 50)</b> , for concrete	079005R50	<b>114.00</b>
<b>Setting iron for hammer anchor M12</b>	182050R	<b>16.60</b>
<b>Carbide masonry drill Ø 20 mm SDS-plus</b> for splaying anchors M12	079019	<b>65.40</b>
<b>Splaying anchor M12 (pack of 10)</b> , for masonry, reusable	079006R10	<b>106.00</b>
<b>Quick clamping set 160</b> for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.	079010	<b>75.00</b>
<b>Quick clamping set 500</b> for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	<b>55.80</b>
<b>Titan vacuum fastening</b> , consisting of cover plate with nipple for 3/8" screw connection and sealing ring for base plate.	183603R	<b>103.00</b>
<b>Vacuum pump</b> , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	<b>1,970.00</b>
<b>Laser drilling centre pointer</b>	183604R	<b>134.00</b>
<b>Drilling start aid G ½ UDKB</b> , with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 180160 R), with carbide masonry drill Ø 8 mm	180140R	<b>94.80</b>
<b>Carbide masonry drill Ø 8 mm</b> for drilling aid	079013	<b>19.50</b>
<b>Single open ended wrench size 41</b> for loosening the universal diamond core drilling crowns	079003	<b>39.60</b>
<b>Light loosening ring</b> , for light loosening of the diamond core crown	180015	<b>21.30</b>
<b>Drilling crown extension 200 mm</b>	180155R	<b>63.10</b>
<b>Sharpening stone</b> for diamond core drilling crowns	079012	<b>66.70</b>
<b>Circular spirit level</b> , magnetic, for aligning the drill stand	182010R	<b>77.60</b>
<b>Suction rotor for dust extraction</b> with G ½ male connecting thread, UNC 1¼ male connecting thread and with connection for REMS Pull 2 and other suitable extractors.	180160R	<b>179.00</b>
<b>Water suction device</b> , for wet drilling up to Ø 170 mm, consisting of water collection ring with pressure ring, rubber washer Ø 200 mm and universal pressure pad for all REMS drilling stands.	183606R	<b>406.00</b>
<b>Rubber washer Ø 200 mm (pack of 10)</b> , for water suction device	183675R10	<b>76.80</b>
<b>REMS Pull 2 L / M</b> , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		

