

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	£
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	224.00
	R 1/4	521010	195.00
	R 3/8	521020	132.00
	R 1/2	521030	137.00
	R 3/4	521040	144.00
	R 1	521050	150.00
	R 1 1/4	521060	156.00
	R 1 1/2	521070	183.00
	R 2	521080	195.00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	269.00
	R 1/4 LH	521110	234.00
	R 3/8 LH	521120	159.00
	R 1/2 LH	521130	165.00
	R 3/4 LH	521140	173.00
	R 1 LH	521150	180.00
	R 1 1/4 LH	521160	188.00
	R 1 1/2 LH	521170	220.00
	R 2 LH	521180	234.00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	224.00
	NPT 1/4	521210	195.00
	NPT 3/8	521220	132.00
	NPT 1/2	521230	137.00
	NPT 3/4	521240	144.00
	NPT 1	521250	150.00
	NPT 1 1/4	521260	156.00
	NPT 1 1/2	521270	183.00
	NPT 2	521280	195.00
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	173.00
	M 20 x 1.5	521310	173.00
	M 25 x 1.5	521320	180.00
	M 32 x 1.5	521330	188.00
	M 40 x 1.5	521340	220.00
	M 50 x 1.5	521350	234.00



Right-hand pipe thread



Left-hand pipe thread



Info

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	£
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	102.00
	R 1/4	521012RWS	95.80
	R 3/8	521022RWS	95.80
	R 1/2	521032RWS	95.80
	R 3/4	521042RWS	105.00
	R 1	521052RWS	105.00
	R 1 1/4	521062RWS	105.00
	R 1 1/2	521072RWS	105.00
	R 2	521082RWS	105.00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	123.00
	R 1/4 LH	521112RWS	116.00
	R 3/8 LH	521122RWS	116.00
	R 1/2 LH	521132RWS	116.00
	R 3/4 LH	521142RWS	127.00
	R 1 LH	521152RWS	127.00
	R 1 1/4 LH	521162RWS	127.00
	R 1 1/2 LH	521172RWS	127.00
	R 2 LH	521182RWS	126.00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	102.00
	NPT 1/4	521212RWS	95.80
	NPT 3/8	521222RWS	95.80
	NPT 1/2	521232RWS	95.80
	NPT 3/4	521242RWS	105.00
	NPT 1	521252RWS	105.00
	NPT 1 1/4	521262RWS	105.00
	NPT 1 1/2	521272RWS	105.00
	NPT 2	521282RWS	105.00
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	127.00
	M 20 x 1.5	521312RWS	127.00
	M 25 x 1.5	521322RWS	127.00
	M 32 x 1.5	521332RWS	127.00
	M 40 x 1.5	521342RWS	127.00
	M 50 x 1.5	521352RWS	127.00



German Quality Product



Info