

## REMS Ax-Press 25 22V ACC REMS Ax-Press 25 L 22V ACC

Cordless axial press 20 kN with automatic return  
Cordless axial press 13 kN with automatic return

Compact, handy power tool with automatic return for manufacturing compression sleeve joints. Li-Ion 22V Technology. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression  $\varnothing$  12 – 40 mm

**REMS Ax-Press 25 22V ACC – universal up to  $\varnothing$  40 mm. Super light, super handy. Fast. With automatic return. Optimum weight distribution for single-hand operation. Swivelling compression device. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings REHAU RAUTITAN PX  $\varnothing$  16 mm with one battery charge\*.**

### System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

### Compression heads for all common systems

Full range of REMS compression heads for all common compression sleeve systems (page 248 – 249). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

### Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 248). No need to change compression heads. Extremely simple, saves time.

### Design

Compact, handy, light. REMS Ax-Press 25 22V ACC drive machine with battery weighs only 3.0 kg, only 28 cm long REMS Ax-Press 25 L 22V ACC drive machine with battery weighs only 3.2 kg, only 31 cm long REMS Ax-Press 25 22V ACC and REMS Ax-Press 25 L 22V ACC with 40 mm stroke respectively REMS Ax-Press 25 22V ACC with preset compression head position for pressing compression sleeve connectors with a clamping distance  $a \leq 82$  mm in one action REMS Ax-Press 25 L 22V ACC with selectable compression head position for pressing compression sleeve connectors with a clamping distance  $a \leq 116$  mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. LED work light for illuminating the work place. Swivelling compression device for working in confined area. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

### Drive

Enormous pressing force for fast and perfect jointing. Thrust force REMS Ax-Press 25 22V 20 kN, thrust force REMS Ax-Press 25 L 22V 13 kN. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

### Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings, 4.4 Ah for approx. 880 pressings, 5.0 Ah for approx. 1000 pressings, 9.0 Ah for approx. 1800 pressings REHAU RAUTITAN PX  $\varnothing$  16 mm with one battery charge\*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240V, 90W. Rapid charger 100 – 240V, 290W, for shorter charging times, as accessory. Voltage supply 220 – 240V/21.6 V, 15 A output, for mains operation instead of Li-Ion battery 21.6 V, as accessory.

### Expanding

Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems

REMS Ax-Press 25 22V ACC



**←ACC→**  
Automatic Circuit Control

with automatic circuit control  
and charging status check

e.g.  
aquatherm,  
General Fittings,  
IVT,  
REHAU,  
REVEL,  
Seppelfricke,  
TECE,  
TIEMME,  
Würth

**REMS TECHNOLOGY**  
**LI-ION 22V**

REMS Ax-Press 25 L 22V ACC




**←ACC→**  
Automatic Circuit Control

with automatic circuit control  
and charging status check

e.g.  
AC-FIX,  
BARBI,  
FERRO systems  
BRASELI,  
Brass & Fittings,  
EUROP'FLUIDES,  
Fittings Estándar,  
PLÁSTICOS FERRO,  
Velta

**REMS TECHNOLOGY**  
**LI-ION 22V**

German Quality Product



### Supply format

**REMS Ax-Press 25 22 V ACC Basic-Pack.** Cordless axial press 20 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance  $a \leq 82$  mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	€
	573022R220	<b>1.590,00</b>

Other voltages on request.



Info

### Supply format

**REMS Ax-Press 25 L 22 V ACC Basic-Pack.** Cordless axial press 13 kN for producing compression sleeve joints Ø 12 – 40 mm. 40 mm stroke, for pressing compression sleeve connections with a clamping distance  $a \leq 116$  mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220 – 240 V or 110 V, 50 – 60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.	€
	573023R220	<b>1.590,00</b>

Other voltages on request.



Info

### Accessories

Description	Art.-No.	€
<b>REMS compression heads</b> see page 248 – 249.		
<b>REMS Ax-Press 25 22 V ACC drive unit,</b> $a \leq 82$ mm, without battery	573020R22	<b>1.140,00</b>
<b>REMS Ax-Press 25 L 22 V ACC drive unit,</b> $a \leq 116$ mm, without battery	573021R22	<b>1.140,00</b>
<b>Battery Li-Ion 21.6 V, 2.5 Ah</b>	571571R22	<b>272,00</b>
<b>Battery Li-Ion 21.6 V, 4.4 Ah</b>	571574R22	<b>392,00</b>
<b>Battery Li-Ion 21.6 V, 5.0 Ah</b>	571581R22	<b>326,00</b>
<b>Battery Li-Ion 21.6 V, 9.0 Ah</b>	571583R22	<b>435,00</b>
<b>Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W</b>	571585R220	<b>185,00</b>
<b>Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W</b>	571587R220	<b>435,00</b>
<b>Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A,</b> for mains operation instead of battery Li-Ion 21.6 V.	571567R220	<b>435,00</b>
<b>Steel case with insert</b>	578290R	<b>116,00</b>
<b>REMS Lumen 2800 22 V,</b> cordless LED flood light, see page 111		

