Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22V Technology. For battery and corded operation.

Axial compression

Ø 12-32 mm

REMS Ax-Press 30 22V – up to Ø 32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*.

Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

High pressing force for perfect pressing in seconds, e.g. Ø 26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-lon 22 V Technology. Highly resistant Li-lon 21.6 V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-lon 21.6 V, 2.5 Ah battery for approx. 220 pressings, 4.4 Ah for approx. 380 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100-240V, 90W. Rapid charger 100-240V, 290W, for shorter charging times, as accessory. Voltage supply $220-240V/21.6V, 15\,A$ output, for mains operation instead of Li-lon battery $21.6\,V,$ as accessory.

Supply format

REMS Ax-Press 30 22V Basic-Pack. Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve Ø 12-32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-lon 21.6 V, 2.5 Ah, rapid charger 220-240V, 50-60 Hz, 70W. In sturdy steel case.

€	ArtNo.
2.230,00	573018R220



German Quality Product







Accessories

Description	ArtNo.	€	
REMS Ax-Press 30 22V drive unit, without battery	573008R22	1.660,00	
Battery Li-lon 21.6 V, 2.5 Ah	571571 R22	272,00	
Battery Li-lon 21.6 V, 4.4 Ah	571574R22	392,00	
Battery Li-lon 21.6 V, 5.0 Ah	571581 R22	326,00	
Battery Li-lon 21.6 V, 9.0 Ah	571583R22	435,00	
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W	571585R220	185,00	
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W	571587R220	435,00	
Voltage supply 220 – 240 V/21.6 V, 50 – 60 Hz, 15 A, for mains operation instead of battery Li-lon 21.6 V.	571567 R220	435,00	
Steel case with insert	573282R	116,00	
REMS Lumen 2800 22 V, cordless LED flood light, see page 111			

REMS compression heads					
Compression sleeve system	Compression head	ArtNo.	€		
Brasstech Raptor/ Metalpex/ Raptor 2/ MULTItermoSAN	ME 14 (pack of 2) ME 16 (pack of 2) ME 20 (pack of 2) ME 26 (pack of 2) ME 32 (pack of 2)	573100 573102 573106 573108 573110	114,00 114,00 114,00 114,00 125,00		
General Fittings Serie 5400	ME 14 (pack of 2) ME 16 (pack of 2) ME 20 (pack of 2) ME 26 (pack of 2) ME 32 (pack of 2)	573100 573102 573106 573108 573110	114,00 114,00 114,00 114,00 125,00		



REMS compression heads					
Compression sleeve system	Compression head	ArtNo.	€		
Georg Fischer pfci	ME 16 (pack of 2)	573102	114,00		
ALUPEX-EXPRESS/	ME 20 (pack of 2)	573106	114,00		
Alupex Gas System	ME 26 (pack of 2)	573108	114,00		
Logstor	ME 16 (pack of 2)	573102	114,00		
	LR 20 (pack of 2)	573430	114,00		
	LR 22 (pack of 2)	573432	114,00		
	LR 25 (pack of 2)	573434	114,00		
	LR 28 (pack of 2)	573436	114,00		
	LR 32 (pack of 2)	573438	125,00		