

Description	Art.-No.	€
<b>REMS Simplex 2.</b> Robust, handy drilling stand for core drilling up to Ø 202 mm. Description see page 310.	183700R	<b>1.070,00</b>
<b>REMS Titan.</b> Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Description see page 310.	183600R	<b>1.630,00</b>
<b>Titan drilling template</b> for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	<b>60,50</b>
<b>Carbide masonry drills Ø 15 mm SDS-plus</b> for hammer anchors M12	079018	<b>29,60</b>
<b>Hammer anchor M12 (pack of 50)</b> , for concrete	079005R50	<b>116,00</b>
<b>Setting iron for hammer anchor M12</b>	182050R	<b>16,90</b>
<b>Carbide masonry drill Ø 20 mm SDS-plus</b> for splaying anchors M12	079019	<b>66,60</b>
<b>Splaying anchor M12 (pack of 10)</b> , for masonry, reusable	079006R10	<b>108,00</b>
<b>Quick clamping set 160</b> for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.	079010	<b>76,40</b>
<b>Quick clamping set 500</b> for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	<b>56,80</b>
<b>Titan vacuum fastening</b> , consisting of cover plate with nipple for 3/8" screw connection and sealing ring for base plate.	183603R	<b>105,00</b>
<b>Vacuum pump</b> , for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	<b>2.010,00</b>
<b>Laser drilling centre pointer</b>	183604R	<b>137,00</b>
<b>Drilling start aid G ½ TDKB</b> , with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145R	<b>96,60</b>
<b>Carbide masonry drill Ø 8 mm</b> for drilling aid	079013	<b>19,90</b>
<b>Single open ended wrench size 41</b> for loosening the universal diamond core drilling crowns	079003	<b>40,30</b>
<b>Light loosening ring</b> , for light loosening of the diamond core crown	180015	<b>21,70</b>
<b>Drilling crown extension 200 mm</b>	180155R	<b>64,30</b>
<b>Sharpening stone</b> for diamond core drilling crowns	079012	<b>68,00</b>
<b>Circular spirit level</b> , magnetic, for aligning the drill stand	182010R	<b>79,10</b>
<b>REMS Pull 2 M</b> , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		

