

for all common pressfitting systems

**Select REMS pressing tongs Mini/  
REMS pressing rings yourself!**

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 183) required for driving REMS pressing rings. All pressing rings S (PR-2B) marked with \*\* can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

**REMS pressing tongs Mini (PZ-2B)**

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFlz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

**REMS pressing ring S (PR-2B)**

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183.

**Traceability according to EN 1775:2007**

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



German Quality Product



REMS Mini pressing tongs (PZ-2B)



REMS pressing ring S (PR-2B), continuously swivellable


**Confirmation of suitability**

See page 239.


**Hold-Harmless and Indemnification Agreement**

See page 240.





Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971



Example REMS pressing tongs Mini V: "V" imprint on pressed fitting for traceability according to EN 1775:2007

**REMS pressing tongs Mini**  
**REMS pressing rings**

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
<b>A</b>				
Aalberts integrated piping systems	U 14		578372	184,00
VSH MultiPress	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	U 40		578386	249,00
	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
Aalberts integrated piping systems	U 16		578374	174,00
VSH MultiPress Gas	U 20		578378	174,00
	U 25		578380	174,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
Aalberts integrated piping systems	V 12		578324	155,00
VSH SudoPress Carbon	V 15		578328	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
Aalberts integrated piping systems	V 12		578324	155,00
VSH SudoPress Copper	V 14		578326	155,00
	VG 14		578338	155,00
	V 15		578328	155,00
	V 16		578330	155,00
	VG 16		578340	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
Aalberts integrated piping systems	V 12		578324	155,00
VSH SudoPress Copper Gas	V 14		578326	155,00
	VG 14		578338	155,00
	V 15		578328	155,00
	V 16		578330	155,00
	VG 16		578340	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00
	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00
	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
Aalberts integrated piping systems	V 15		578328	155,00
VSH SudoPress Stainless	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
Aalberts integrated piping systems	M 12		578310	155,00
VSH XPress Carbon	M 15		578312	155,00
	M 18 <sup>1)</sup>		578314	155,00
	M 22		578316	155,00
	M 28 <sup>1)</sup>		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Aalberts integrated piping systems	M 12		578310	155,00
VSH XPress Copper	M 15		578312	155,00
	M 18 <sup>1)</sup>		578314	155,00
	M 22		578316	155,00
	M 28 <sup>1)</sup>		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
Aalberts integrated piping systems	M 15		578312	155,00
VSH XPress Copper Gas	M 18 <sup>1)</sup>		578314	155,00
	M 22		578316	155,00
	M 28 <sup>1)</sup>		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
Aalberts integrated piping systems	M 15		578312	155,00
VSH XPress Stainless	M 18 <sup>1)</sup>		578314	155,00
	M 22		578316	155,00
	M 28 <sup>1)</sup>		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
Aalberts integrated piping systems	M 15		578312	155,00
VSH XPress Stainless Gas	M 18 <sup>1)</sup>		578314	155,00
	M 22		578316	155,00
	M 28 <sup>1)</sup>		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
AC-FIX PRESS (Global Piping Systems)	H 12		578396	168,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	RfZ 12		578490	194,00
	RfZ 16		578492	194,00
	RfZ 20		578494	194,00
	RfZ 25		578496	194,00
	RfZ 32		578498	194,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	VX 16		578552	215,00
	VX 20		578554	215,00
AC-FIX PRESS DUO (Global Piping Systems)	RfZ 16		578492	194,00
	RfZ 20		578494	194,00
	RfZ 25		578496	194,00
	RfZ 32		578498	194,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400	168,00
	H 18		578404	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	RfZ 16		578492	194,00
	RfZ 20		578494	194,00
	RfZ 25		578496	194,00
	RfZ 32		578498	194,00
	U 16		578374	174,00
	U 18		578376	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
ACOME MT	AcZ 12		578608	194,00
	AcZ 16		578610	194,00
	AcZ 20		578612	194,00
	AcZ 25		578614	194,00

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AHLSSELL	M 12		578310	155,00	ALB	TH 16		578352 R	186,00
A-press	M 15		578312	155,00	Sistema Multicapa	TH 18		578356	186,00
elförzinkad M	M 18		578314	155,00	para calefacción y sanitario	TH 20		578358 R	186,00
	M 22		578316	155,00		TH 26		578362 R	186,00
	M 28		578318	155,00		TH 32		578364	186,00
	M 35		578390	188,00		TH 40		578624	247,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		H 16		578400	168,00
AHLSSELL	V 12		578324	155,00		H 18		578404	168,00
A-press	V 15		578328	155,00		H 20		578406	168,00
elförzinkad V	V 18		578332	155,00		H 26		578410	168,00
	V 22		578334	155,00		H 32		578412	168,00
	V 28		578336	155,00		U 16		578374	174,00
	V 35		578604	188,00		U 18		578376	174,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		U 20		578378	174,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		U 26 <sup>7)</sup>		578392	205,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		U 32		578382	205,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		U 40		578386	249,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00					
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	ALB	TH 16		578352 R	186,00
AHLSSELL	M 12		578310	155,00	Sistema Multicapa	TH 20		578358 R	186,00
A-press koppar M	M 15		578312	155,00	para gas	TH 26		578362 R	186,00
	M 18		578314	155,00		TH 32		578364	186,00
	M 22		578316	155,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 28		578318	155,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	M 35		578390	188,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		H 16		578400	168,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		H 20		578406	168,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		H 26		578410	168,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		H 32		578412	168,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		U 16		578374	174,00
AHLSSELL	V 12		578324	155,00		U 18		578376	174,00
A-press koppar V	V 15		578328	155,00		U 20		578378	174,00
	V 18		578332	155,00		U 26 <sup>7)</sup>		578392	205,00
	V 22		578334	155,00		U 32		578382	205,00
	V 28		578336	155,00					
	V 35		578604	188,00	ALTECH Altech	RFz 12		578490	194,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		RFz 16		578492	194,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		RFz 20		578494	194,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		RFz 25		578496	194,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	APE MULTYGAS	TH 16		578352 R	186,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	Serie AP Gas	TH 20		578358 R	186,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		TH 26		578362 R	186,00
AHLSSELL	M 15		578312	155,00		TH 32		578364	186,00
A-press rostfritt	M 18		578314	155,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 22		578316	155,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	M 28		578318	155,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	M 35		578390	188,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	APE Serie AP	B 16		578468	203,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		B 20		578472	203,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		B 26		578474	224,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		H 16		578400	168,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		H 20		578406	168,00
AIRBEL	M 15		578312	155,00		H 26		578410	168,00
PRESSCLIM	M 18		578314	155,00		H 32		578412	168,00
	M 22		578316	155,00		TH 16		578352 R	186,00
	M 28		578318	155,00		TH 18		578356	186,00
	M 35		578390	188,00		TH 20		578358 R	186,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		TH 26		578362 R	186,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		TH 32		578364	186,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
AIRBEL	M 15		578312	155,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
SERTINOX	M 18		578314	155,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	M 22		578316	155,00		U 16		578374	174,00
	M 28		578318	155,00		U 20		578378	174,00
	M 35		578390	188,00					
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00					
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00					
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00					
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00					
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
APE Serie APL	H 16		578400	168,00	
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 25		578408	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	AQUATECHNIK Press-fitting metal	H 16		578400	168,00
		H 20		578406	168,00
		H 26		578410	168,00
H 32			578412	168,00	
TH 16			578352 R	186,00	
TH 20			578358 R	186,00	
TH 26			578362 R	186,00	
TH 32			578364	186,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
U 16			578374	174,00	
U 20			578378	174,00	
U 26 <sup>7)</sup>			578392	205,00	
U 32		578382	205,00		
AQUATECHNIK Universal	B 16		578468	203,00	
	B 20		578472	203,00	
	B 26		578474	224,00	
	B 32		578476	224,00	
	F 16		578456	178,00	
	F 20		578460	178,00	
	F 26		578462	192,00	
	F 32		578464	192,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	H 16		578400	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
U 16		578374	174,00		
U 20		578378	174,00		
U 26 <sup>7)</sup>		578392	205,00		
U 32		578382	205,00		
ARKA DUROsystem	H 16		578400	168,00	
	H 20		578406	168,00	
	H 25		578408	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	Aschl NIR	M 15		578312	155,00
		M 18		578314	155,00
		M 22		578316	155,00
		M 28		578318	155,00
		M 35		578390	188,00
		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
ASSOTHERM IPC-RAC Carbon Steel		M 15		578312	155,00
		M 18		578314	155,00
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
ASSOTHERM IPI-RAX Inox	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	ASSOTHERM IPI-RAX Inox Gas	M 15		578312	155,00
		M 18		578314	155,00
M 22			578316	155,00	
M 28			578318	155,00	
M 35			578390	188,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
ASSOTHERM IPM-Multistrato		H 16		578400	168,00
		H 20		578406	168,00
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	THL 32		578368	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		
U 16		578374	174,00		
U 20		578378	174,00		
U 26 <sup>7)</sup>		578392	205,00		
U 32		578382	205,00		
ASSOTHERM IPR-RAA Copper	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	ASSOTHERM IPR-RAA Copper Gas	M 15		578312	155,00
		M 18		578314	155,00
M 22			578316	155,00	
M 28			578318	155,00	
M 35			578390	188,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)		US 3/8"		578534	212,00
		US 1/2"		578536	212,00
	US 3/4"		578538	212,00	
	US 1"		578540	212,00	
ATUSA ITALIA INSTALPRESS CARBON STEEL PRESS FITTINGS	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	ATUSA ITALIA INSTALPRESS STAINLESS STEEL PRESS FITTINGS	M 15		578312	155,00
		M 18		578314	155,00
M 22			578316	155,00	
M 28			578318	155,00	
M 35			578390	188,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
AUSTEC PEX-B, PEX-AL-PEX (AUS)		TH 16		578352 R	186,00
		TH 20		578358 R	186,00
	TH 25		578360	186,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	AUSTEC PEX-AL-PEX GAS (AUS)	TH 16		578352 R	186,00
		TH 20		578358 R	186,00
		TH 25		578360	186,00
		U 16		578374	174,00
		U 20		578378	174,00
U 25			578380	174,00	
U 32			578382	205,00	



System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AYOR	H 12		578396	168,00	Bampi BALPEX	TH 16		578352 R	186,00
FIXOCONNECT	H 16		578400	168,00	Gas	TH 20		578358 R	186,00
Press	H 20		578406	168,00		TH 26		578362 R	186,00
	H 25		578408	168,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	RFz 12		578490	194,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	RFz 16		578492	194,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	RFz 20		578494	194,00	BARBI EASYPRESS	H 12		578396	168,00
	RFz 25		578496	194,00	(Industrial Blansol)	H 16		578400	168,00
	U 16		578374	174,00		H 20		578406	168,00
	U 20		578378	174,00		H 25		578408	168,00
	U 25		578380	174,00		H 32		578412	168,00
AYOR	H 16		578400	168,00		RFz 12		578490	194,00
FIXOMULTIX	H 20		578406	168,00		RFz 16		578492	194,00
	H 26		578410	168,00		RFz 20		578494	194,00
	H 32		578412	168,00		RFz 25		578496	194,00
	TH 16		578352 R	186,00		RFz 32		578498	194,00
	TH 20		578358 R	186,00		U 16		578374	174,00
	TH 26		578362 R	186,00		U 20		578378	174,00
	TH 32		578364	186,00		U 25		578380	174,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		U 32		578382	205,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	BARBI MULTIPLEX	H 14		578398	168,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	(Industrial Blansol)	H 16		578400	168,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		H 18		578404	168,00
	U 16		578374	174,00		H 20		578406	168,00
	U 20		578378	174,00		H 25		578408	168,00
	U 32		578382	205,00		H 26		578410	168,00
	U 40		578386	249,00		H 32		578412	168,00
AYOR	H 16		578400	168,00		RFz 16		578492	194,00
SOMATHERM	H 20		578406	168,00		RFz 18		578638	194,00
FOR YOU -1	H 26		578410	168,00		RFz 20		578494	194,00
	TH 16		578352 R	186,00		RFz 25		578496	194,00
	TH 20		578358 R	186,00		RFz 32		578498	194,00
	TH 26		578362 R	186,00		TH 16		578352 R	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		TH 20		578358 R	186,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		TH 26		578362 R	186,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		TH 32		578364	186,00
	U 16		578374	174,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	U 20		578378	174,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
AYOR	H 12		578396	168,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
SOMATHERM	H 16		578400	168,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
FOR YOU -2	H 20		578406	168,00		U 16		578374	174,00
	H 25		578408	168,00		U 18		578376	174,00
	RFz 12		578490	194,00		U 20		578378	174,00
	RFz 16		578492	194,00		U 25		578380	174,00
	RFz 20		578494	194,00		U 32		578382	205,00
	RFz 25		578496	194,00		U 40		578386	249,00
	U 16		578374	174,00	BEGETUBE/ IVAR	B 14		578466	203,00
	U 20		578378	174,00		B 16		578468	203,00
	U 25		578380	174,00		B 18		578470	203,00
						B 20		578472	203,00
						B 26		578474	224,00
						B 32		578476	224,00
					Béné inox	M 15		578312	155,00
					Série 41	M 18		578314	155,00
						M 22		578316	155,00
						M 28		578318	155,00
						M 35		578390	188,00
						M 15 S (PR-2B)	Mini Z8	574738 R	131,00
						M 18 S (PR-2B)	Mini Z8	574740 R	131,00
						M 22 S (PR-2B)	Mini Z8	574742 R	131,00
						M 28 S (PR-2B)	Mini Z8	574744 R	131,00
						M 35 S (PR-2B)	Mini Z8	574746 R	144,00
					Brass Form	H 16		578400	168,00
					Master-Al-Pex	H 18		578404	168,00
						H 20		578406	168,00
						TH 16		578352 R	186,00
						TH 18		578356	186,00
						TH 20		578358 R	186,00
						TH 26		578362 R	186,00
						TH 32		578364	186,00
						TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
						TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
						TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
						TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
						TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
						U 16		578374	174,00
						U 18		578376	174,00
						U 20		578378	174,00

**B**

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue. See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Brass & Fittings PRESSMAN MultiPress	RFz 16		578492	194,00
	RFz 18		578638	194,00
	ACz 20		578612	194,00
	RFz 25		578496	194,00
	RFz 32		578498	194,00
Brass & Fittings PRESSMAN RetiPress	RFz 16		578492	194,00
	RFz 18		578638	194,00
	ACz 20		578612	194,00
	RFz 25		578496	194,00
	RFz 32		578498	194,00
BRASSTECH MULTItermoSAN	B 16		578468	203,00
	B 20		578472	203,00
Brasspress	B 26		578474	224,00
	B 32		578476	224,00
	F 16		578456	178,00
	F 20		578460	178,00
	F 26		578462	192,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00
	H 16		578400	168,00
	H 18		578404	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	TH 16		578352 R	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 18		578376	174,00
	U 20		578378	174,00
	U 26 <sup>7)</sup>		578392	205,00
U 32		578382	205,00	
<b>C</b>				
Cello Products -B>Press	VUS ½" (OD 15,9 mm)		578566	187,00
	VUS ¾" (OD 22,2 mm)		578568	187,00
	VUS 1" (OD 28,6 mm)		578570	187,00
	VUS 1¼" (OD 34,9 mm)		578606	187,00
CGR DYNAFLU multicouche	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 26 <sup>7)</sup>		578392	205,00
U 32		578382	205,00	
U 40		578386	249,00	
CGR DYNAFLU PER	H 12		578396	168,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	RFz 12		578490	194,00
	RFz 16		578492	194,00
	RFz 20		578494	194,00
	RFz 25		578496	194,00
CHIALI CHIALIPEX	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
Climatrix Climatrix Rhinopex	H 16		578400	168,00
	H 20		578406	168,00
	U 16		578374	174,00
	U 20		578378	174,00
	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Climatrix	TH 11,6		578344	186,00	
	Variotherm		578352 R	186,00	
System TH	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	ClouSet		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	Comap	RFz 12		578490	194,00
	PEX Press	RFz 16		578492	194,00
		RFz 20		578494	194,00
		RFz 25		578496	194,00
	Comap Multiskin	TH 14		578348	186,00
TH 16			578352 R	186,00	
TH 18			578356	186,00	
TH 20			578358 R	186,00	
TH 26			578362 R	186,00	
TH 32			578364	186,00	
THL 32			578368	186,00	
TH 40			578624	247,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
U 14			578372	184,00	
U 16			578374	174,00	
U 18			578376	174,00	
U 20			578378	174,00	
U 32			578382	205,00	
H 14			578398	168,00	
H 16			578400	168,00	
H 18			578404	168,00	
H 20			578406	168,00	
H 26			578410	168,00	
H 32			578412	168,00	
Comap Multiskin Gas		TH 16		578352 R	186,00
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	THL 32		578368	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	U 32		578382	205,00	
	H 16		578400	168,00	
	H 20		578406	168,00	
H 26		578410	168,00		
H 32		578412	168,00		
COMISA Press System	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	H 14		578398	168,00	
	H 16		578400	168,00	
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
H 32		578412	168,00		
B 14		578466	203,00		
B 16		578468	203,00		
B 18		578470	203,00		
B 20		578472	203,00		
B 26		578474	224,00		
B 32		578476	224,00		
COMISA Press System Gas	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
CONEL	M 15		578312	155,00	Conex Bänninger >B< Flex	F 16		578456	178,00	
CONNECT INOX	M 18		578314	155,00		F 18		578458	178,00	
	M 22		578316	155,00		F 20		578460	178,00	
	V 15		578328	155,00		F 32		578464	192,00	
	V 18		578332	155,00		F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	V 22		578334	155,00		F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
CONEL	F 16		578456	178,00		F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
CONNECT	F 20		578460	178,00		H 16		578400	168,00	
MULTI	F 26		578462	192,00		H 18		578404	168,00	
	F 32		578464	192,00		H 20		578406	168,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00		H 25		578408	168,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00		H 32		578412	168,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00		RFz 16		578492	194,00	
	F 32 S (PR-2B)**	Mini Z8	574734 R	144,00		RFz 18		578638	194,00	
	H 16		578400	168,00		RFz 20		578494	194,00	
	H 20		578406	168,00		RFz 25		578496	194,00	
	H 26		578410	168,00		RFz 32		578498	194,00	
	H 32		578412	168,00		TH 16		578352 R	186,00	
	TH 16		578352 R	186,00		TH 18		578356	186,00	
	TH 20		578358 R	186,00		TH 20		578358 R	186,00	
	TH 26		578362 R	186,00		TH 25		578360	186,00	
	TH 32		578364	186,00		TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00		U 16		578374	174,00	
	U 20		578378	174,00		U 18		578376	174,00	
(DN 26)	U 25		578380	174,00		U 20		578378	174,00	
	U 32		578382	205,00		U 25		578380	174,00	
	VP 16		578482	186,00		U 32		578382	205,00	
	VP 20		578484	186,00						
	VP 32		578488	206,00		Conex Bänninger >B< Flex Gas	F 16		578456	178,00
CONEL	F 16		578456	178,00		F 18		578458	178,00	
CONNECT	F 20		578460	178,00		F 20		578460	178,00	
MV2	F 26		578462	192,00		F 32		578464	192,00	
	F 32		578464	192,00		F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00		F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00		F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00		H 16		578400	168,00	
	F 32 S (PR-2B)**	Mini Z8	574734 R	144,00	H 18		578404	168,00		
	TH 16		578352 R	186,00	H 20		578406	168,00		
	TH 20		578358 R	186,00	H 25		578408	168,00		
	TH 26		578362 R	186,00	H 32		578412	168,00		
	TH 32		578364	186,00	RFz 16		578492	194,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	RFz 18		578638	194,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	RFz 20		578494	194,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	RFz 25		578496	194,00		
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	RFz 32		578498	194,00		
Conex Bänninger <A> Press Inox (304)	M 15		578312	155,00	TH 16		578352 R	186,00		
	M 18		578314	155,00	TH 18		578356	186,00		
	M 22		578316	155,00	TH 20		578358 R	186,00		
	M 28		578318	155,00	TH 25		578360	186,00		
	M 35		578390	188,00	TH 32		578364	186,00		
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00		
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	U 16		578374	174,00		
Conex Bänninger <A> Press Inox (316L)	M 15		578312	155,00	U 18		578376	174,00		
	M 18		578314	155,00	U 20		578378	174,00		
	M 22		578316	155,00	U 25		578380	174,00		
	M 28		578318	155,00	U 32		578382	205,00		
	M 35		578390	188,00						
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	Conex Bänninger >B< MaxiPro	BMP ¼"		578700	185,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	BMP ⅜"		578702	185,00		
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	BMP ½"		578704	185,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	BMP ⅝"		578706	185,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	BMP ¾"		578708	185,00		
					BMP ⅞"		578710	185,00		
					BMP 1"		578712	185,00		
					BMP 1 ⅛"		578714	185,00		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Conex Bänninger ->B-< Press	V 12		578324	155,00	
	V 14		578326	155,00	
	V 15		578328	155,00	
	V 16		578330	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	M 15		578312	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	Conex Bänninger ->B-< Press Carbon	V 15		578328	155,00
V 18			578332	155,00	
V 22			578334	155,00	
V 28			578336	155,00	
V 35			578604	188,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	
Conex Bänninger ->B-< Press Gas		V 12		578324	155,00
		V 14		578326	155,00
		V 15		578328	155,00
		V 16		578330	155,00
		V 18		578332	155,00
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	Conex Bänninger ->B-< Press Inox	V 15		578328	155,00
		V 18		578332	155,00
		V 22		578334	155,00
		V 28		578336	155,00
V 35			578604	188,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	
Conex Bänninger ->B-< Press Solar		V 12		578324	155,00
		V 14		578326	155,00
		V 15		578328	155,00
		V 16		578330	155,00
		V 18		578332	155,00
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
<b>D</b>					
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310	155,00	
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	DUOPIPE SYSTEMS DUOFIL MKSYSTEM	U 16		578374	174,00
		U 18		578376	174,00
		U 20		578378	174,00
U 25			578380	174,00	
U 32			578382	205,00	
DW Verbundrohr multitubo systems		U 16		578374	174,00
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
<b>E</b>				
EBRILLE Isomomflex	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	H 26		578410	168,00
	TH 26		578362 R	186,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
EBRILLE Monflex	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	H 26		578410	168,00
	TH 26		578362 R	186,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
EFFEBI	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
EFFEBI-PRESS Aisi316 System M Profile <sup>1)</sup>	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	V 12		578324	155,00
	V 15		578328	155,00
EFFEBI-PRESS Aisi316 System V Profile	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
EFFEBI-PRESS Carbon-S System M Profile <sup>1)</sup>	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	M 12		578310	155,00
	M 15		578312	155,00
EFFEBI-PRESS Carbon-S System V Profile	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
EFFEBI-PRESS Carbon-S System V Profile	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	V 12		578324	155,00
	V 15		578328	155,00
EFFEBI-PRESS COPPER	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
EFFEBI-PRESS UNICO	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	V 12		578324	155,00
	V 15		578328	155,00
EFFEBI-PRESS UNICO	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
EFFEBI-PRESS UNICO	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI EFFEBI-PRESS UNICO (GAS)	V 12		578324	155,00	EFFEBI TOF MULTIPINZA	TH 16		578352 R	186,00
	V 15		578328	155,00		TH 18		578356	186,00
	V 18		578332	155,00		TH 20		578358 R	186,00
	V 22		578334	155,00		TH 25		578360	186,00
	V 28		578336	155,00		TH 26		578362 R	186,00
	V 35		578604	188,00		TH 32		578364	186,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		TH 40		578624	247,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
						TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
						F 16		578456	178,00
	EFFEBI PRESSTIGE	M 15		578312		155,00	F 18		578458
	M 18		578314	155,00	F 20		578460	178,00	
	M 22		578316	155,00	F 26		578462	192,00	
	M 28		578318	155,00	F 32		578464	192,00	
	M 35		578390	188,00	Fz 40		578478	260,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	H 16		578400	168,00	
	V 15		578328	155,00	H 18		578404	168,00	
	V 18		578332	155,00	H 20		578406	168,00	
	V 22		578334	155,00	H 25		578408	168,00	
	V 28		578336	155,00	H 26		578410	168,00	
	V 35		578604	188,00	H 32		578412	168,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	U 16		578374	174,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	U 18		578376	174,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	U 20		578378	174,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	U 25		578380	174,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	U 26 <sup>1)</sup>		578392	205,00	
					U 32		578382	205,00	
EFFEBI PRESSTIGE 4E05	M 15		578312	155,00	U 40		578386	249,00	
	M 18		578314	155,00	B 16		578468	203,00	
	M 22		578316	155,00	B 18		578470	203,00	
	M 28		578318	155,00	B 20		578472	203,00	
	M 35		578390	188,00	B 26		578474	224,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	B 32		578476	224,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	EFIELD	U 16	578374	174,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	MULTILAYER PRESS	U 18	578376	174,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	DINGAS	U 20	578378	174,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		U 25	578380	174,00	
EFFEBI PRESSTIGE-GAS	M 15		578312	155,00		U 32	578382	205,00	
	M 18		578314	155,00	EFIELD	U 16	578374	174,00	
	M 22		578316	155,00	MULTILAYER PRESS	U 18	578376	174,00	
	M 28		578318	155,00	WATER	U 20	578378	174,00	
	M 35		578390	188,00		U 25	578380	174,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		U 32	578382	205,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	Elkhart	VUS ½" (OD 15,9 mm)	578566	187,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	APOLLOXPRESS	VUS ¾" (OD 22,2 mm)	578568	187,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	Fittings Copper	VUS 1" (OD 28,6 mm)	578570	187,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	and Low-Lead Brass	VUS 1¼" (OD 34,9 mm)	578606	187,00	
	V 15		578328	155,00	EMMETI	B 16	578468	203,00	
	V 18		578332	155,00	GERPEX-	B 20	578472	203,00	
	V 22		578334	155,00	FIVPRESS	B 26	578474	224,00	
	V 28		578336	155,00		B 32	578476	224,00	
	V 35		578604	188,00		F 16	578456	178,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		F 20	578460	178,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		H 16	578400	168,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		H 20	578406	168,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		TH 16	578352 R	186,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		TH 20	578358 R	186,00	
						TH 26	578362 R	186,00	
						TH 32	578364	186,00	
						TH 40	578624	247,00	
						U 16	578374	174,00	
						U 20	578378	174,00	
EFFEBI TOF-GAS MULTIPINZA	TH 16		578352 R	186,00	EMPUR	TH 14	578348	186,00	
	TH 20		578358 R	186,00		TH 15	578350	186,00	
	TH 26		578362 R	186,00		TH 16	578352 R	186,00	
	TH 32		578364	186,00		TH 17	578354	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		TH 20	578358 R	186,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		TH 25	578360	186,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		TH 15 S (PR-2B)**	Mini Z8	574780 R	131,00
	H 16		578400	168,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	H 20		578406	168,00		TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00
	H 26		578410	168,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	H 32		578412	168,00		TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	U 16		578374	174,00					
	U 20		578378	174,00					
	U 32		578382	205,00					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Esta Rohr simplesta SH M	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	Esta Rohr simplesta ST M	M 15		578312	155,00
M 18			578314	155,00	
M 22			578316	155,00	
M 28			578318	155,00	
M 35			578390	188,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile <sup>1)</sup>		M 12		578310	155,00
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
M 35 S (PR-2B)	Mini Z8	574746 R	144,00		
EUROTUBI EUROPA Inox Pressfitting System M-Profile <sup>1)</sup>	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	Evans Components Presslok	VAU 15 (½") (OD 12,7 mm)		578630	160,00
VAU 20 (¾") (OD 19,1 mm)			578632	160,00	
VAU 25 (1") (OD 25,4 mm)			578634	160,00	
<b>F</b>					
FAR Rubinetterie PRESSFAR	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 17		578354	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	H 14		578398	168,00	
	H 16		578400	168,00	
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	U 14		578372	184,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	U 40		578386	249,00	
	F.B.Q. BARONIO BQ PRESS SOLAR	V 12		578324	155,00
		V 14		578326	155,00
V 15			578328	155,00	
V 16			578330	155,00	
V 18			578332	155,00	
V 22			578334	155,00	
V 28			578336	155,00	
V 35			578604	188,00	
V 12 S (PR-2B)		Mini Z8	574748 R	131,00	
V 14 S (PR-2B)		Mini Z8	574800 R	131,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 16 S (PR-2B)		Mini Z8	574802 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
F.B.Q. BARONIO BQ PRESS WATER	V 12		578324	155,00	
	V 14		578326	155,00	
	V 15		578328	155,00	
	V 16		578330	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
F.B.Q. BARONIO BQ PRESS GAS	V 12		578324	155,00	
	V 14		578326	155,00	
	V 15		578328	155,00	
	V 16		578330	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 14 S (PR-2B)	Mini Z8	574800 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 16 S (PR-2B)	Mini Z8	574802 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
FERCOFLOOR DUO Press FERCO PEX	Rfz 16		578492	194,00	
	Rfz 20		578494	194,00	
	Rfz 25		578496	194,00	
	Rfz 32		578498	194,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	FERCOFLOOR DUO Press MULTIFER	Rfz 16		578492	194,00
		Rfz 20		578494	194,00
		Rfz 25		578496	194,00
Rfz 32			578498	194,00	
TH 16			578352 R	186,00	
TH 20			578358 R	186,00	
TH 25			578360	186,00	
TH 32			578364	186,00	
TH 40			578624	247,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 25 S (PR-2B)**		Mini Z8	574792 R	131,00	
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
U 16			578374	174,00	
U 18			578376	174,00	
U 20			578378	174,00	
U 25		578380	174,00		
U 32		578382	205,00		
U 40		578386	249,00		
FERRO systems BRASELLI GPF GAS	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
FERRO systems BRASELLI GPF PRESS Pressfitting PEX y MULTICAPA	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
FERRO systems BRASELLI GPF PPSU Pressfitting PEX y MULTICAPA	U 32		578382	205,00	
	U 40		578386	249,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
FERRO systems BRASELLI GPF PRESS Pressfitting PEX FILINOX Instalpress Steel	U 32		578382	205,00	
	U 40		578386	249,00	
	Rfz 16		578492	194,00	
	Rfz 20		578494	194,00	
	Rfz 25		578496	194,00	
	Rfz 32		578498	194,00	
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
FERRO systems BRASELLI GPF PRESS Pressfitting PEX MULTICAPA	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
FILINOX	M 15		578312	155,00	FORZA	V 15		578328	155,00
Instalpress Inox	M 18		578314	155,00	STAINLESS V PRESS (AUS)	V 22		578334	155,00
	M 22		578316	155,00		V 28		578336	155,00
	M 28		578318	155,00		V 35		578604	188,00
	M 35		578390	188,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	FRABO	M 15		578312	155,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	FRABOPRESS 316 GAS M	M 18		578314	155,00
FITTINGS ESTÁNDAR ECO-PRESS	RFz 16		578492	194,00		M 22		578316	155,00
	RFz 20		578494	194,00		M 28		578318	155,00
	RFz 25		578496	194,00		M 35		578390	188,00
	RFz 32		578498	194,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
FITTINGS ESTÁNDAR MULTICAPA	RFz 16		578492	194,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	RFz 18		578638	194,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	RFz 20		578494	194,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	RFz 25		578496	194,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	RFz 32		578498	194,00	FRABO	V 15		578328	155,00
FITTINGS ESTÁNDAR PE-X	RFz 16		578492	194,00	FRABOPRESS 316 GAS V	V 18		578332	155,00
	RFz 20		578494	194,00		V 22		578334	155,00
	RFz 25		578496	194,00		V 28		578336	155,00
	RFz 32		578498	194,00		V 35		578604	188,00
						V 15 S (PR-2B)	Mini Z8	574752 R	131,00
						V 18 S (PR-2B)	Mini Z8	574756 R	131,00
						V 22 S (PR-2B)	Mini Z8	574758 R	131,00
						V 28 S (PR-2B)	Mini Z8	574760 R	131,00
						V 35 S (PR-2B)	Mini Z8	574762 R	144,00
FORNARA ForPress	B 16		578468	203,00	FRABO	M 15		578312	155,00
	B 20		578472	203,00	FRABOPRESS 316 M	M 18		578314	155,00
	B 26		578474	224,00		M 22		578316	155,00
	B 32		578476	224,00		M 28		578318	155,00
	F 16		578456	178,00		M 35		578390	188,00
	F 20		578460	178,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	F 26		578462	192,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	F 32		578464	192,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	FRABO	V 12		578324	155,00
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	FRABOPRESS 316 V	V 15		578328	155,00
	H 16		578400	168,00		V 18		578332	155,00
	H 20		578406	168,00		V 22		578334	155,00
	H 26		578410	168,00		V 28		578336	155,00
	H 32		578412	168,00		V 35		578604	188,00
	TH 16		578352 R	186,00		V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	TH 20		578358 R	186,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	TH 26		578362 R	186,00		V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	TH 32		578364	186,00		V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	FRABO	V 12		578324	155,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	FRABOPRESS CHROME	V 15		578328	155,00
	U 16		578374	174,00		V 18		578332	155,00
	U 20		578378	174,00		V 22		578334	155,00
	U 26 <sup>7)</sup>		578392	205,00		V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	U 32		578382	205,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
						V 18 S (PR-2B)	Mini Z8	574756 R	131,00
						V 22 S (PR-2B)	Mini Z8	574758 R	131,00
						V 28 S (PR-2B)	Mini Z8	574760 R	131,00
						V 35 S (PR-2B)	Mini Z8	574762 R	144,00
FORZA WATER CRIMP (AUS)	K16/P18		578592	194,00	FRABO	M 15		578312	155,00
	K/20		578594	194,00	FRABOPRESS C-STEEL M	M 18		578314	155,00
	K/25		578596	194,00		M 22		578316	155,00
	K32		578598	194,00		M 28		578318	155,00
	K1/40		578600	194,00		M 35		578390	188,00
FORZA STAINLESS WATER CRIMP	K16/P18		578592	194,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	K/20		578594	194,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
FORZA	U 16		578374	174,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
STESSO PEX	U 20		578378	174,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
WATER AND GAS CRIMP AUS)	U 25		578380	174,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	U 32		578382	205,00	FRABO	V 12		578324	155,00
	U 40		578386	249,00	FRABOPRESS C-STEEL V	V 15		578328	155,00
FORZA	K16/P18		578592	194,00		V 18		578332	155,00
GAS CRIMP (AUS)	K/20		578594	194,00		V 22		578334	155,00
	K/25		578596	194,00		V 28		578336	155,00
	K32		578598	194,00		V 35		578604	188,00
	K1/40		578600	194,00		V 12 S (PR-2B)	Mini Z8	574748 R	131,00
FORZA	VAU 15 (OD 12,7 mm)		578630	160,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
COPPER V PRESS (AUS)	VAU 20 (OD 19,1 mm)		578632	160,00		V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	VAU 25 (OD 25,4 mm)		578634	160,00		V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	VAU 32 (OD 31,8 mm)		578636	168,00		V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	131,00		V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	131,00					
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	144,00					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacture.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacture.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacture.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue. See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
FRABO	M 12		578310	155,00
FRABOPRESS	M 15		578312	155,00
GAS M	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
FRABO	V 12		578324	155,00
FRABOPRESS	V 15		578328	155,00
GAS V	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
FRABO	V 12		578324	155,00
FRABOPRESS	V 15		578328	155,00
KOMBI	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
FRABO	M 12		578310	155,00
FRABOPRESS M	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
FRABO	V 15		578328	155,00
FRABOPRESS	V 18		578332	155,00
SOLAR	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
FRABO	V 12		578324	155,00
FRABOPRESS V	V 15		578328	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
Fränkische alpex-duo XS	F 16		578456	178,00
	F 20		578460	178,00
	F 26		578462	192,00
	F 32		578464	192,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	144,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Fränkische	F 16		578456	178,00
alpex F50 PROF1	F 20		578460	178,00
	F 26		578462	192,00
	F 32		578464	192,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00
	F 32 S (PR-2B)**	Mini Z8	574734 R	144,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 20		578378	174,00
(DN 26)	U 25		578380	174,00
	U 32		578382	205,00
	VP 16		578482	186,00
	VP 20		578484	186,00
	VP 32		578488	206,00
Fränkische alpex L	Fz 40		578478	260,00
<b>G</b>				
gabotherm H+S	TH 10		578342	186,00
	TH 12		578346	186,00
	TH 14		578348	186,00
	TH 15		578350	186,00
	TH 16		578352 R	186,00
	TH 17		578354	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	131,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	131,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
	TH 15 S (PR-2B)**	Mini Z8	574780 R	131,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
Gallagher USA	H 12 (3/4")		578396	168,00
YogaPipe ACR	U 14 (3/8")		578372	184,00
	U 16 (1/2")		578374	174,00
	U 18 (5/8")		578376	174,00
	U 20 (3/4")		578378	174,00
	U 25 (7/8")		578380	174,00
	U 32 (1 1/8")		578382	205,00
Geberit Mapress C-STAHl	M 12		578310	155,00
	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
Geberit Mapress C-STAHl Sprinkler nass	M 22		578316	155,00
	M 28		578318	155,00
Geberit Mapress Edelstahl	M 12		578310	155,00
	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00



# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Geberit Mapress Edelstahl Gas	M 15		578312	155,00	General Fittings Serie 5S00	B 16		578468	203,00
	M 18		578314	155,00		B 18		578470	203,00
	M 22		578316	155,00		B 20		578472	203,00
	M 28		578318	155,00		B 26		578474	224,00
	M 35		578390	188,00		B 32		578476	224,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		F 16		578456	178,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		F 20		578460	178,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		F 26		578462	192,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		F 32		578464	192,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		F 16 S (PR-2B)**	Mini Z8	574728 R	131,00
Geberit Mapress Edelstahl Sprinkler	M 22		578316	155,00	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	M 28		578318	155,00	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
Geberit Mapress Kupfer	M 12		578310	155,00	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	M 15		578312	155,00	H 16		578400	168,00	
	M 18		578314	155,00	H 18		578404	168,00	
	M 22		578316	155,00	H 20		578406	168,00	
	M 28		578318	155,00	H 25		578408	168,00	
	M 35		578390	188,00	H 26		578410	168,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	H 32		578412	168,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	TH 16		578352 R	186,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	TH 18		578356	186,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	TH 20		578358 R	186,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	TH 25		578360	186,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	TH 26		578362 R	186,00	
	Geberit Mapress Kupfer Gas	M 15		578312	155,00	TH 32		578364	186,00
		M 18		578314	155,00	TH 40		578624	247,00
		M 22		578316	155,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
M 28			578318	155,00	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
M 35			578390	188,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	U 16		578374	174,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	U 18		578376	174,00	
Geberit Mepla		G 16		578444	187,00	U 20		578378	174,00
		G 20		578446	187,00	U 25		578380	174,00
		G 26		578448	198,00	U 32		578382	205,00
		G 32		578450	212,00	U 40		578386	249,00
		G 40		578452	274,00	General Fittings Trident	H 16		578400
	Geberit Mepla Therm	G 16		578444	187,00		H 20		578406
G 20			578446	187,00	H 26			578410	168,00
G 26			578448	198,00	H 32			578412	168,00
Geberit Volex	TH 16		578352 R	186,00	TH 16			578352 R	186,00
	TH 20		578358 R	186,00	TH 20			578358 R	186,00
	TH 26		578362 R	186,00	TH 26		578362 R	186,00	
General Fittings ST00	H 16		578400	168,00	TH 32		578364	186,00	
	H 20		578406	168,00	TH 40		578624	247,00	
	H 26		578410	168,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	H 32		578412	168,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 16		578352 R	186,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 20		578358 R	186,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	TH 26		578362 R	186,00	U 16		578374	174,00	
	TH 32		578364	186,00	U 20		578378	174,00	
	TH 40		578624	247,00	U 32		578382	205,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	General Fittings Trident Gas	H 16		578400	168,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		H 20		578406	168,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		H 26		578410	168,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		TH 16		578352 R	186,00
	U 16		578374	174,00		TH 20		578358 R	186,00
	U 20		578378	174,00		TH 26		578362 R	186,00
U 32		578382	205,00	TH 32		578364	186,00		
U 40		578386	249,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		
General Fittings Ewoprex	H 16		578400	168,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	H 20		578406	168,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	H 26		578410	168,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	H 32		578412	168,00	U 16		578374	174,00	
	TH 16		578352 R	186,00	U 20		578378	174,00	
	TH 20		578358 R	186,00	U 32		578382	205,00	
	TH 26		578362 R	186,00	Giacomini Raccordi RM	H 16		578400	168,00
	TH 32		578364	186,00		H 20		578406	168,00
	TH 40		578624	247,00		H 26		578410	168,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		H 32		578412	168,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		TH 16		578352 R	186,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		TH 20		578358 R	186,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	TH 26		578362 R	186,00	
	U 16		578374	174,00	TH 32		578364	186,00	
	U 20		578378	174,00	TH 40		578624	247,00	
U 32		578382	205,00	U 16		578374	174,00		
U 40		578386	249,00	U 20		578378	174,00		
				U 32		578382	205,00		
				U 40		578386	249,00		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Giacomini RM MULTIGAS	H 16		578400	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	U 32		578382	205,00	
Giacomini Valvole Giacomini serie R850V	V 15		578328	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	SA 15		578514	186,00	
	SA 18		578518	186,00	
	SA 22		578520	186,00	
	SA 28		578522	186,00	
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
M 35 S (PR-2B)	Mini Z8	574746 R	144,00		
Golan Pipe Systems (Scandinavia)	U 16		578374	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
Alu-Pres	U 40		578386	249,00	
	U 32		578382	205,00	
Grinnell G-PRESS Copper Fittings	VUS ½" (OD 15,9 mm)		578566	187,00	
	VUS ¾" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1½" (OD 34,9 mm)		578606	187,00	
GS Wärmesysteme System TH	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	GS Wärmesysteme System V	V 15		578328	155,00
		V 18		578332	155,00
V 22			578334	155,00	
V 28			578336	155,00	
V 35			578604	188,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	
<b>H</b>					
HASTINIK Hastinik/Hitpress	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
heima24	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
U 20		578378	174,00		
U 32		578382	205,00		
HELIROMA Klimapress	U 16		578374	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	U 40		578386	249,00	
HELIROMA Klimapress PPSU	U 16		578374	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
Henco	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	HE 32		578370 R	223,00	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Herotec tempusPRESS PLUS	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	Rfz 16		578492	194,00
	Rfz 20		578494	194,00
	Rfz 25		578496	194,00
	Rfz 32		578498	194,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
TH 32		578364	186,00	
TH 40		578624	247,00	
TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
U 16		578374	174,00	
U 20		578378	174,00	
U 25		578380	174,00	
U 32		578382	205,00	
U 40		578386	249,00	
Herotec tempusPRESS PLUS PPSU	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
U 16		578374	174,00	
U 20		578378	174,00	
U 25		578380	174,00	
U 32		578382	205,00	
U 40		578386	249,00	
HERZ PIPEFIX	TH 10		578342	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 10 S (PR-2B)**	Mini Z8	574772 R	131,00
TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	
HIDRONIX MULTIGAS	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
HIDRONIX MULTIPIPE	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	H 14		578398	168,00
H 16		578400	168,00	
H 18		578404	168,00	
H 20		578406	168,00	
H 26		578410	168,00	
H 32		578412	168,00	
U 14		578372	184,00	
U 16		578374	174,00	
U 18		578376	174,00	
U 20		578378	174,00	
U 26 <sup>1)</sup>		578392	205,00	
U 32		578382	205,00	
HIDRONIX UNICO	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	H 14		578398	168,00
H 16		578400	168,00	
H 18		578404	168,00	
H 20		578406	168,00	
H 26		578410	168,00	
H 32		578412	168,00	
U 14		578372	184,00	
U 16		578374	174,00	
U 18		578376	174,00	
U 20		578378	174,00	
U 26 <sup>1)</sup>		578392	205,00	
U 32		578382	205,00	
HITEC Sistema Multistrato	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
HITHERM-ISOTUBI NUMEPRESS	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
M 35 S (PR-2B)	Mini Z8	574746 R	144,00	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
HITHERM-ISOTUBI HTpress	M 15		578312	155,00	ICMA Sempigas	TH 16		578352 R	186,00
	M 18		578314	155,00		TH 20		578358 R	186,00
	M 22		578316	155,00		TH 25		578360	186,00
	M 28		578318	155,00		TH 26		578362 R	186,00
	M 35		578390	188,00		TH 32		578364	186,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		Idrosanitaria Bonomi Homegas	TH 16		578352 R
HITHERM-ISOTUBI HTfire	M 15		578312	155,00	TH 20			578358 R	186,00
	M 18		578314	155,00	TH 26			578362 R	186,00
	M 22		578316	155,00	TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00
	M 28		578318	155,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	M 35		578390	188,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	Idrosanitaria Bonomi Idropress	TH 16		578352 R	186,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 18		578356	186,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 20		578358 R	186,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		TH 26		578362 R	186,00
HITHERM-ISOTUBI HTair	M 15		578312	155,00	TH 32		578364	186,00	
	M 18		578314	155,00	TH 40		578624	247,00	
	M 22		578316	155,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	M 28		578318	155,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	M 35		578390	188,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	IDROSISTEMI Ta-Press	TH 16		578352 R	186,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 20		578358 R	186,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 26		578362 R	186,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		TH 32		578364	186,00
Hopewell press fit system	M 15		578312	155,00		TH 40		578624	247,00
	M 18		578314	155,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	M 22		578316	155,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	M 28		578318	155,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	M 35		578390	188,00		F 16		578456	178,00
hp praski BAVARIA-press	TH 10		578342	186,00		F 20		578460	178,00
	TH 12		578346	186,00	F 26		578462	192,00	
	TH 14		578348	186,00	F 32		578464	192,00	
	TH 16		578352 R	186,00	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	TH 17		578354	186,00	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	TH 20		578358 R	186,00	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	TH 25		578360	186,00	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	TH 26		578362 R	186,00	Fz 40		578478	260,00	
	TH 32		578364	186,00	H 16		578400	168,00	
	TH 40		578624	247,00	H 20		578406	168,00	
	TH 10 S (PR-2B)**	Mini Z8	574772 R	131,00	H 26		578410	168,00	
	TH 12 S (PR-2B)**	Mini Z8	574776 R	131,00	H 32		578412	168,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	U 16		578374	174,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	U 20		578378	174,00	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00	U 26 <sup>7)</sup>		578392	205,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	U 32		578382	205,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	U 40		578386	249,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	B 16		578468	203,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	B 20		578472	203,00	
					B 26		578474	224,00	
				B 32		578476	224,00		
ICMA Sempiter	H 16		578400	168,00	IDROTRADE Storm Multipinza	H 16		578400	168,00
	H 20		578406	168,00		H 20		578406	168,00
	H 25		578408	168,00		H 26		578410	168,00
	H 26		578410	168,00		H 32		578412	168,00
	H 32		578412	168,00		TH 16		578352 R	186,00
	TH 16		578352 R	186,00		TH 20		578358 R	186,00
	TH 20		578358 R	186,00		TH 26		578362 R	186,00
	TH 25		578360	186,00		TH 32		578364	186,00
	TH 26		578362 R	186,00		THL 32		578368	186,00
	TH 32		578364	186,00		TH 40		578624	247,00
	TH 40		578624	247,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	U 16		578374	174,00	
	U 16		578374	174,00	U 20		578378	174,00	
	U 20		578378	174,00	IDROTRADE StormPRES <sup>1)</sup>	M 15		578312	155,00
	U 25		578380	174,00		M 18		578314	155,00
	U 26 <sup>7)</sup>		578392	205,00		M 22		578316	155,00
	U 32		578382	205,00		M 28		578318	155,00
U 40		578386	249,00	M 35			578390	188,00	
				M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
				M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
				M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
				M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
				M 35 S (PR-2B)		Mini Z8	574746 R	144,00	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
IVAR Plastic Multi Press PMP	TH 16		578352 R	186,00	<b>J</b>	Jäger - Aquatec	H 14	578398	168,00		
	TH 20		578358 R	186,00		Aquapress H	H 16	578400	168,00		
	TH 25		578360	186,00			H 17	578402	168,00		
	TH 26		578362 R	186,00			H 18	578404	168,00		
	TH 32		578364	186,00			H 20	578406	168,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00			H 26	578410	168,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00			H 32	578412	168,00		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00			U 40	578386	249,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00			Jäger - Aquatec	M 15	578312	155,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00			C-Stahl	M 18	578314	155,00	
	F 16		578456	178,00			Press Typ M	M 22	578316	155,00	
	F 20		578460	178,00				M 28	578318	155,00	
	F 26		578462	192,00				M 35	578390	188,00	
	F 32		578464	192,00				M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00				M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00				M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00				M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00				M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	H 16		578400	168,00			Jäger - Aquatec	M 15	578312	155,00	
	H 20		578406	168,00			Edelstahl	M 18	578314	155,00	
	H 25		578408	168,00			Press Typ M	M 22	578316	155,00	
	H 26		578410	168,00				M 28	578318	155,00	
	H 32		578412	168,00				M 35	578390	188,00	
	U 16		578374	174,00				M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	U 20		578378	174,00				M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	U 25		578380	174,00				M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	U 26 <sup>7)</sup>		578392	205,00				M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	U 32		578382	205,00				M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	B 16		578468	203,00			Jäger - Aquatec	V 15	578328	155,00	
	B 20		578472	203,00			Kupfer	V 18	578332	155,00	
	B 26		578474	224,00			Press Typ V	V 22	578334	155,00	
	B 32		578476	224,00				V 28	578336	155,00	
	IVAR Plastic Multi Press Leak (PMPL)	TH 16		578352 R		186,00		V 35	578604	188,00	
		TH 20		578358 R		186,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
		TH 26		578362 R		186,00		V 18 S (PR-2B)	Mini Z8	574756 R	131,00
		TH 32		578364		186,00		V 22 S (PR-2B)	Mini Z8	574758 R	131,00
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00		V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00		V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00		Jansen AG	TH 14	578348	186,00		
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00		JANSEN COMISA	TH 16	578352 R	186,00		
F 16			578456	178,00			TH 20	578358 R	186,00		
F 20			578460	178,00			TH 26	578362 R	186,00		
F 26			578462	192,00			TH 32	578364	186,00		
F 32			578464	192,00			TH 40	578624	247,00		
F 16 S (PR-2B)**		Mini Z8	574728 R	131,00			TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
F 20 S (PR-2B)**		Mini Z8	574730 R	131,00			TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
F 26 S (PR-2B)**		Mini Z8	574732 R	131,00			TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
F 32 S (PR-2B)		Mini Z8	574734 R	144,00			TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
H 16			578400	168,00			TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
H 20			578406	168,00		Jaraflex-	TH 14	578348	186,00		
H 26			578410	168,00		Presssystem	TH 16	578352 R	186,00		
H 32			578412	168,00			TH 17	578354	186,00		
U 16			578374	174,00			TH 18	578356	186,00		
U 20			578378	174,00			TH 20	578358 R	186,00		
U 26 <sup>7)</sup>			578392	205,00			TH 25	578360	186,00		
U 32			578382	205,00			TH 26	578362 R	186,00		
B 16			578468	203,00			TH 32	578364	186,00		
B 20			578472	203,00			TH 40	578624	247,00		
B 26			578474	224,00			TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
B 32			578476	224,00			TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
IVT Edelstahl- Presssystem		M 15		578312	155,00		TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00	
		M 18		578314	155,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
		M 22		578316	155,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
		M 28		578318	155,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
		M 35		578390	188,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
		M 15 S (PR-2B)	Mini Z8	574738 R	131,00	JUNGWOO	VUS ½" (OD 15,9 mm)	578566	187,00		
		M 18 S (PR-2B)	Mini Z8	574740 R	131,00	JWPress	VUS ¾" (OD 22,2 mm)	578568	187,00		
		M 22 S (PR-2B)	Mini Z8	574742 R	131,00		VUS 1" (OD 28,6 mm)	578570	187,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		VUS 1¼" (OD 34,9 mm)	578606	187,00			
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00							
	IVT PRIPRESS	TH 16		578352 R	186,00						
		TH 20		578358 R	186,00						
		TH 26		578362 R	186,00						
		TH 32		578364	186,00						
		TH 40		578624	247,00						
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00							
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00							
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00							
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00							

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



**REMS pressing tongs Mini**  
**REMS pressing rings**

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
<b>K</b>						
KAN KAN-therm Press LBP	TH 14		578348	186,00		
	TH 16		578352 R	186,00		
	TH 20		578358 R	186,00		
	TH 25		578360	186,00		
	TH 26		578362 R	186,00		
	TH 32		578364	186,00		
	TH 40		578624	247,00		
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		
	U 14		578372	184,00		
	U 16		578374	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 26 <sup>7)</sup>		578392	205,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
	KAN KAN-therm Inox	M 15		578312	155,00	
		M 18 <sup>1)</sup>		578314	155,00	
		M 22		578316	155,00	
		M 28 <sup>1)</sup>		578318	155,00	
		M 35		578390	188,00	
		M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
		M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
		M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
		M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
		M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
		KAN KAN-therm Steel	M 12		578310	155,00
			M 15		578312	155,00
	M 18 <sup>1)</sup>			578314	155,00	
	M 22			578316	155,00	
	M 28 <sup>1)</sup>			578318	155,00	
	M 35			578390	188,00	
	M 12 S (PR-2B)		Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)	Mini Z8		574744 R	131,00		
M 35 S (PR-2B)	Mini Z8		574746 R	144,00		
KAN KAN-therm UltraPRESS	TH 14			578348	186,00	
	TH 16			578352 R	186,00	
	TH 20			578358 R	186,00	
	TH 25			578360	186,00	
	TH 26			578362 R	186,00	
	TH 32			578364	186,00	
	TH 40			578624	247,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		
	U 14		578372	184,00		
	U 16		578374	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 26 <sup>7)</sup>		578392	205,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
	KE KELIT COPPERFIX Kupfer	M 15		578312	155,00	
		M 18		578314	155,00	
		M 22		578316	155,00	
		M 28		578318	155,00	
		M 35		578390	188,00	
		M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
		M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
		M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
		M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	KE KELIT KELIX KELIX KELOX	U 16		578374	174,00	
		U 18		578376	174,00	
		U 20		578378	174,00	
		U 25		578380	174,00	
U 32			578382	205,00		
U 40			578386	249,00		
KE KELIT KELOX-PPSU-W		U 16		578374	174,00	
		U 18		578376	174,00	
		U 20		578378	174,00	
	U 25		578380	174,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
KE KELIT KELOX-ULTRAX	U 16		578374	174,00		
	U 18		578376	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
KE KELIT KELOX-ULTRAX-W	U 16		578374	174,00		
	U 18		578376	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
KE KELIT KELOX-WINDOW-U	U 16		578374	174,00		
	U 18		578376	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 32		578382	205,00		
	U 40		578386	249,00		
KE KELIT KELOX-WINDOW-W	U 16		578374	174,00		
	U 18		578376	174,00		
	U 20		578378	174,00		
	U 25		578380	174,00		
	U 32		578382	205,00		
	U 40		578386	249,00		

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
KE KELIT steelFIX C-Stahl	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
KE KELIT steelFIX Edelstahl	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
KEMBLA KemPress (AUS)	VAU 15 (OD 12,7 mm)		578630	160,00	
	VAU 20 (OD 19,1 mm)		578632	160,00	
	VAU 25 (OD 25,4 mm)		578634	160,00	
	VAU 32 (OD 31,8 mm)		578636	168,00	
	KEMBLA KemPress Gas (AUS)	VAU 15 (OD 12,7 mm)		578630	160,00
VAU 20 (OD 19,1 mm)			578632	160,00	
VAU 25 (OD 25,4 mm)			578634	160,00	
VAU 32 (OD 31,8 mm)			578636	168,00	
KISAN Kisan KD		KI 16		578524	197,00
	KI 20		578526	197,00	
	KI 25		578528	197,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	KISAN Kisan WL	KI 16		578524	197,00
KI 20			578526	197,00	
KI 25			578528	197,00	
KI 32			578530	266,00	
TH 16			578352 R	186,00	
TH 20			578358 R	186,00	
KISAN Kisan WM	TH 25		578360	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	
	KISAN Kisan WR	KI 16		578524	197,00
		KI 20		578526	197,00
		KI 25		578528	197,00
		KI 32		578530	266,00
TH 16			578352 R	186,00	
TH 20			578358 R	186,00	
TH 25			578360	186,00	
TH 32			578364	186,00	
TH 40			578624	247,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
KISAN Kistal C	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
KISAN Kistal Inox	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
LEGEND-PRESS press fitting system	VUS 1/2" (OD 15,9 mm)		578566	187,00	
	VUS 3/4" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1 1/4" (OD 34,9 mm)		578606	187,00	
	LK Systems LK ->B-Press	V 12		578324	155,00
		V 15		578328	155,00
		V 18		578332	155,00
		V 22		578334	155,00
		V 28		578336	155,00
		V 35		578604	188,00
		V 12 S (PR-2B)	Mini Z8	574748 R	131,00
		V 15 S (PR-2B)	Mini Z8	574752 R	131,00
		V 18 S (PR-2B)	Mini Z8	574756 R	131,00
		V 22 S (PR-2B)	Mini Z8	574758 R	131,00
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)	Mini Z8	574762 R	144,00		

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
LK Systems	V 12		578324	155,00	Meier Tobler	H 16		578400	168,00
LK >B-Press	V 15		578328	155,00	Metalplast - Stramax	H 20		578406	168,00
Elförzinkat	V 18		578332	155,00	Serie MM	H 25		578408	168,00
	V 22		578334	155,00		H 32		578412	168,00
	V 28		578336	155,00		RFz 16		578492	194,00
	V 35		578604	188,00		RFz 20		578494	194,00
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		RFz 25		578496	194,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		RFz 32		578498	194,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		TH 16		578352 R	186,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		TH 20		578358 R	186,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		TH 25		578360	186,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		TH 32		578364	186,00
LK Systems	V 15		578328	155,00		TH 40		578624	247,00
LK >B-Press	V 18		578332	155,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
Gas	V 22		578334	155,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	V 28		578336	155,00		TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	V 35		578604	188,00		TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		U 16		578374	174,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		U 20		578378	174,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		U 25		578380	174,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		U 32		578382	205,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		U 40		578386	249,00
LK Systems	TH 16		578352 R	186,00	METALGRUP	U 16		578374	174,00
LK Universal	TH 20		578358 R	186,00	Permatubo	U 18		578376	174,00
	TH 25		578360	186,00		U 20		578378	174,00
	TH 32		578364	186,00		U 25		578380	174,00
	TH 40		578624	247,00		U 32		578382	205,00
						U 40		578386	249,00
					METALGRUP	RFz 16		578492	194,00
					PexGrup	RFz 20		578494	194,00
						RFz 25		578496	194,00
						RFz 32		578498	194,00
					METALGRUP	U 16		578374	174,00
					MultiGrup	U 18		578376	174,00
						U 20		578378	174,00
						U 25		578380	174,00
						U 32		578382	205,00
					Mueller Streamline	VUS ½" (OD 15,9 mm)		578566	187,00
					PRS Copper Press	VUS ¾" (OD 22,2 mm)		578568	187,00
						VUS 1" (OD 28,6 mm)		578570	187,00
						VUS 1¼" (OD 34,9 mm)		578606	187,00
					MULTITHERM	TH 16		578352 R	186,00
					PRESSSYSTEM	TH 20		578358 R	186,00
						TH 26		578362 R	186,00
						TH 32		578364	186,00
						TH 40		578624	247,00
						TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
						TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
						TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
						TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
					Multicapas Industrial	RFz 16		578492	194,00
					AIS PEX	RFz 20		578494	194,00
						RFz 25		578496	194,00
						RFz 32		578498	194,00
						U 16		578374	174,00
						U 20		578378	174,00
						U 25		578380	174,00
						U 32		578382	205,00
					Multicapas Industrial	H 16		578400	168,00
					AIS XPRT	H 20		578406	168,00
						H 25		578408	168,00
						H 32		578412	168,00
						RFz 16		578492	194,00
						RFz 20		578494	194,00
						RFz 25		578496	194,00
						RFz 32		578498	194,00
						TH 16		578352 R	186,00
						TH 20		578358 R	186,00
						TH 25		578360	186,00
						TH 32		578364	186,00
						TH 40		578624	247,00
						TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
						TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
						TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
						TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
						TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
						H 14		578398	168,00
						H 16		578400	168,00
						H 18		578404	168,00
						H 20		578406	168,00
						H 26		578410	168,00
						H 32		578412	168,00
						U 14		578372	184,00
						U 16		578374	174,00
						U 18		578376	174,00
						U 20		578378	174,00
						U 25		578380	174,00
						U 32		578382	205,00
						U 40		578386	249,00

**M**

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Multicap Industrial multitubo systems MC	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	U 40		578386	249,00	
Multicap Industrial multitubo systems MM	H 16		578400	168,00	
	H 20		578406	168,00	
	H 25		578408	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	RFz 16		578492	194,00	
	RFz 20		578494	194,00	
	RFz 25		578496	194,00	
	RFz 32		578498	194,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
		U 16		578374	174,00
		U 20		578378	174,00
		U 25		578380	174,00
		U 32		578382	205,00
		U 40		578386	249,00
	multipipe Deutschland multipipe mp	TH 16		578352 R	186,00
		TH 20		578358 R	186,00
		TH 26		578362 R	186,00
TH 32			578364	186,00	
TH 40			578624	247,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
<b>N</b>					
NEUTHERM MEKUPRESS-HT	H 16		578400	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
NIBCO Press System Copper	VUS ½" (OD 15,9 mm)		578566	187,00	
	VUS ¾" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1½" (OD 34,9 mm)		578606	187,00	
NICOLL FLUXO	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
NUPI Industrie Italiane Multinupi	B 16		578468	203,00	
	B 18		578470	203,00	
	B 20		578472	203,00	
	B 26		578474	224,00	
	B 32		578476	224,00	
	F 16		578456	178,00	
	F 18		578458	178,00	
	F 20		578460	178,00	
	F 26		578462	192,00	
	F 32		578464	192,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	H 16		578400	168,00	
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 25		578408	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00		
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00		
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		
	U 14		578372	184,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 26 <sup>7)</sup>		578392	205,00	
	U 32		578382	205,00	
	U 40		578386	249,00	
Nussbaum Optifitt-Press	VMP ¾" (OD 17,2 mm)		578660	215,00	
	VMP ½" G (OD 21,3 mm)		578666 R	215,00	
	VMPz ¾" (OD 26,9 mm)		578664	215,00	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Nussbaum Optiflex-Flowpress	VRX 16		578640	196,00
	VRX 20		578642	196,00
	VRX 25		578644	215,00
	VRX 32		578646	215,00
Nussbaum Optipress	V 15		578328	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
Nussbaum Optipress Gaz	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	V 15		578328	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
Nussbaum Optipress-Therm	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	V 15		578328	155,00
	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
O	V 35 (PR-2B)	Mini Z8	578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00
	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 26 A		578430	215,00
	H 32 A		578432	215,00
P	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 26 A		578430	215,00
	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 32 A		578432	215,00
Pegler Yorkshire > Aalberts integrated piping systems	H 16 A		578420	215,00
	H 20 A		578426	215,00
	H 26 A		578430	215,00
	H 32 A		578432	215,00
	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
PERFILMEX PERFILALUPEX	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
PERFILMEX PERFILPRESS	U 32		578382	205,00
	U 40		578386	249,00
	M 15		578312	155,00
	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
PEXTUBE PexTube	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	RFz 16		578492	194,00
	RFz 20		578494	194,00
	RFz 25		578496	194,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Pipelife C-PRESS	M 15		578312	155,00	PLÁSTICOS FERRO	U 16		578374	174,00
	M 18		578314	155,00	FERROPLAST	U 20		578378	174,00
	M 22		578316	155,00	GF MULT Pressfitting	U 25		578380	174,00
	M 28		578318	155,00	MULTICAPA	U 32		578382	205,00
	M 35		578390	188,00	PLÁSTICOS FERRO	U 16		578374	174,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	FERROPLAST	U 20		578378	174,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	GF PPSU	U 25		578380	174,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	Pressfitting PEX y MULTICAPA	U 32		578382	205,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	PLÁSTICOS FERRO	RFz 16		578492	194,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	FERROPLAST	RFz 20		578494	194,00
Pipelife RADOPRESS	TH 16		578352 R	186,00	GF PRESS	RFz 25		578496	194,00
	TH 18		578356 R	186,00	Pressfitting PEX	RFz 32		578498	194,00
	TH 20		578358 R	186,00	PLUMBING PLUS	K16/P18		578592	194,00
	TH 26		578362 R	186,00	EZIPEX Crimp (AUS)	K/20		578594	194,00
	TH 32		578364 R	186,00		K/25		578596	194,00
	TH 40		578624	247,00		K32		578598	194,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		K1/40		578600	194,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	PLUMBING PLUS	K16/P18		578592	194,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	EZIPEX Gas (AUS)	K/20		578594	194,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		K/25		578596	194,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		K32		578598	194,00
Pipetec Connect	TH 16		578352 R	186,00		K1/40		578600	194,00
	TH 20		578358 R	186,00	PLUMBING PLUS	Yz 16 UNI		578740	194,00
	TH 26		578362 R	186,00	UNIPEX	Yz 20 UNI		578742	194,00
	TH 32		578364 R	186,00	Water & Gas (AUS)	Yz 25 UNI		578744	194,00
	TH 40		578624	247,00		Yz 32 UNI		578746	194,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	160,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	EZIPRESS Gas (AUS)	VAU 20 (OD 19,1 mm)		578632	160,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		VAU 25 (OD 25,4 mm)		578634	160,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		VAU 32 (OD 31,8 mm)		578636	168,00
	U 16		578378	174,00		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	131,00
	U 20		578382	205,00		VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	131,00
PLASTICA ALFA Multipex	TH 16		578352 R	186,00		VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	144,00
	TH 20		578358 R	186,00	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	160,00
	TH 26		578362 R	186,00	EZIPRESS Solar (AUS)	VAU 20 (OD 19,1 mm)		578632	160,00
	TH 32		578364 R	186,00		VAU 25 (OD 25,4 mm)		578634	160,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	144,00
PLASTICA ALFA Multipex Air	TH 16		578352 R	186,00	PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	160,00
	TH 20		578358 R	186,00	EZIPRESS Water (AUS)	VAU 20 (OD 19,1 mm)		578632	160,00
	TH 26		578362 R	186,00		VAU 25 (OD 25,4 mm)		578634	160,00
	TH 32		578364 R	186,00		VAU 32 (OD 31,8 mm)		578636	168,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	144,00
PLASTICA ALFA Multipexalfa Gas	TH 16		578352 R	186,00	POLYPIPE	TH 10		578342	186,00
	TH 20		578358 R	186,00	POLYSURE	TH 15		578350	186,00
	TH 26		578362 R	186,00		TH 22		578588	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		TH 28		578590	186,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	POLYSAN	M 15		578312	155,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00	Handelsges. m.b.H. & Co KG (Krems/Österreich)	M 18		578314	155,00
PLASTICA ALFA Multipexalfa Gas protek	TH 16		578352 R	186,00		M 22		578316	155,00
	TH 20		578358 R	186,00		M 28		578318	155,00
	TH 26		578362 R	186,00		M 35		578390	188,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	C Stahl-Press-System M	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
PLASTICA ALFA Multipex Plus	TH 16		578352 R	186,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	TH 20		578358 R	186,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	TH 26		578362 R	186,00	POLYSAN	M 15		578312	155,00
	TH 32		578364 R	186,00	Handelsges. m.b.H. & Co KG (Krems/Österreich)	M 18		578314	155,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		M 22		578316	155,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		M 28		578318	155,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		M 35		578390	188,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	TH 16		578352 R	186,00	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	TH 20		578358 R	186,00	Press-System 1.4520	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	TH 26		578362 R	186,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
TH 32		578364 R	186,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
PLASTICA ALFA Multipex Thermo	TH 16		578352 R	186,00	POLYSAN	M 15		578312	155,00
	TH 20		578358 R	186,00	Handelsges. m.b.H. & Co KG (Krems/Österreich)	M 18		578314	155,00
	TH 26		578362 R	186,00		M 22		578316	155,00
	TH 32		578364 R	186,00		M 28		578318	155,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		M 35		578390	188,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	Press-System 1.4520	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	TH 16		578352 R	186,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	TH 20		578358 R	186,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	TH 26		578362 R	186,00	POLYSAN	M 15		578312	155,00
TH 32		578364 R	186,00	Handelsges. m.b.H. & Co KG (Krems/Österreich)	M 18		578314	155,00	
TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		M 22		578316	155,00	
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		M 28		578318	155,00	
TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00		M 35		578390	188,00	
TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
PLASTICA ALFA Multipex Thermo Plus	TH 16		578352 R	186,00	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	TH 20		578358 R	186,00	Press-System Gas	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	TH 26		578362 R	186,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	TH 32		578364 R	186,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00					
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00					
	TH 26 S (PR-2B)**	Mini Z8	574798 R	144,00					
	TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00					
	TH 16		578352 R	186,00					
	TH 20		578358 R	186,00					
	TH 26		578362 R	186,00					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer. \*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue. See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
POLYSAN- Edelstahl Press-System Wasser	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 17		578354	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	POLYSAN- Press-System	TH 26		578362 R	186,00
		TH 32		578364	186,00
		TH 40		578624	247,00
		TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
TH 17 S (PR-2B)**		Mini Z8	574784 R	131,00	
TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00		
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
TH 32 S (PR-2B)**	Mini Z8	574798 R	144,00		
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 17		578354	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	POLYSAN-Henco- Press-System	TH 26		578362 R	186,00
		HE 32		578370 R	223,00
		HEz 40 <sup>3)</sup>		578572	324,00
		TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
		TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
TH 17 S (PR-2B)**		Mini Z8	574784 R	131,00	
TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00		
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
POLYSAN (España) „Rainbow“	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	U 40		578386	249,00	
	Prandelli Multyrama Pf	H 14		578398	168,00
H 16			578400	168,00	
H 18			578404	168,00	
H 20			578406	168,00	
H 26			578410	168,00	
H 32			578412	168,00	
U 40			578386	249,00	
Prandelli Multyrama Pfm		H 16		578400	168,00
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 18		578376	174,00	
	U 20		578378	174,00	
	U 40		578386	249,00	
PURMO Cleverfit Radial	F 16		578456	178,00	
	F 20		578460	178,00	
	F 26		578462	192,00	
	F 32		578464	192,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	H 16		578400	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 17		578354	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 40		578624	247,00	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
U 16		578374	174,00		
U 20		578378	174,00		
U 32		578382	205,00		
VP 16		578482	186,00		
VP 20		578484	186,00		
VP 32		578488	206,00		

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
<b>R</b>					
Raccorderie Metalliche aesPRES <sup>1)</sup>	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
Raccorderie Metalliche inoxPRES <sup>1)</sup>	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
Raccorderie Metalliche MARINEPRES <sup>1)</sup>	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
Raccorderie Metalliche steelPRES <sup>1)</sup>	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
RBM Tita-fix	B 14		578466	203,00	
	B 16		578468	203,00	
	B 18		578470	203,00	
	B 20		578472	203,00	
	B 26		578474	224,00	
	F 16		578456	178,00	
	F 18		578458	178,00	
	F 20		578460	178,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	H 14		578398	168,00	
	H 16		578400	168,00	
	H 18		578404	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
TH 26		578362 R	186,00		
TH 32		578364	186,00		
TH 40		578624	247,00		
TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		
U 14		578372	184,00		
U 16		578374	174,00		
U 18		578376	174,00		
U 20		578378	174,00		
RBM Tita-gas	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	Redi Nicoll Fluxo	TH 14		578348	186,00
		TH 16		578352 R	186,00
TH 18			578356	186,00	
TH 20			578358 R	186,00	
TH 26			578362 R	186,00	
TH 32			578364	186,00	
TH 40			578624	247,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	



# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Redi Nicoll Fluxo Gas	TH 16		578352 R	186,00	Rubinetterie	M 15		578312	155,00	
	TH 20		578358 R	186,00	Bresciane	M 18		578314	155,00	
	TH 26		578362 R	186,00	Bonomi	M 22		578316	155,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	TURBO STEEL	M 28		578318	155,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	M 35		578390	188,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
					M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
RIFENG LD PRESS FITTING (F8)	LD 16		578652	192,00	M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
	LD 20		578654	192,00	M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
	LD 25		578656	192,00	M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
RIFENG U PRESS FITTING (F5)	U 14		578372	184,00	Rubinetterie	B 14		578466	203,00	
	U 16		578374	174,00	Bresciane	B 16		578468	203,00	
	U 18		578376	174,00	Bonomi	B 18		578470	203,00	
	U 20		578378	174,00	TURBO PRESS	B 20		578472	203,00	
	U 25		578380	174,00	B 26		578474	224,00		
	U 32		578382	205,00	B 32		578476	224,00		
	U 40		578386	249,00	H 14		578398	168,00		
RIFENG TH PRESS FITTING (F9)	TH 16		578352 R	186,00	H 16		578400	168,00		
	TH 20		578358 R	186,00	H 18		578404	168,00		
	TH 25		578360	186,00	H 20		578406	168,00		
	TH 26		578362 R	186,00	H 26		578410	168,00		
	TH 32		578364	186,00	H 32		578412	168,00		
	TH 40		578624	247,00	TH 14		578348	186,00		
RIQUIER A SERTIR	RFz 12		578490	194,00	TH 16		578352 R	186,00		
	RFz 16		578492	194,00	TH 18		578356	186,00		
	RFz 20		578494	194,00	TH 20		578358 R	186,00		
	RFz 25		578496	194,00	TH 26		578362 R	186,00		
RIQUIER Système multicouche	TH 16		578352 R	186,00	TH 32		578364	186,00		
	TH 20		578358 R	186,00	TH 40		578624	247,00		
	TH 26		578362 R	186,00	TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
	TH 32		578364	186,00	TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
	TH 40		578624	247,00	TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	U 14		578372	184,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	U 16		578374	174,00		
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	U 18		578376	174,00		
	U 16		578374	174,00	U 20		578378	174,00		
	U 20		578378	174,00	U 26 <sup>7)</sup>		578392	205,00		
	U 32		578382	205,00	U 32		578382	205,00		
	U 40		578386	249,00	Rubinetterie	TH 16		578352 R	186,00	
Roth PressCheck	RN 14		578434	174,00	Bresciane	TH 20		578358 R	186,00	
	RN 16		578454	174,00	Bonomi	TH 26		578362 R	186,00	
	RN 17		578436	174,00	TURBO PRESS	TH 32		578364	186,00	
	RN 20		578438	174,00	GAS	TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00
	RN 25/26		578440	174,00	TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
	RN 32		578442	205,00	TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
Rubinetterie	M 15		578312	155,00	TH 32 S (PR-2B)		Mini Z8	574798 R	144,00	
Bresciane	M 18		578314	155,00						
Bonomi	M 22		578316	155,00						
TURBO CuNi	M 28		578318	155,00						
	M 35		578390	188,00						
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00						
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00						
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00						
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00						
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00						
Rubinetterie	M 15		578312	155,00						
Bresciane	M 18		578314	155,00						
Bonomi	M 22		578316	155,00						
TURBO INOX	M 28		578318	155,00						
	M 35		578390	188,00						
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00						
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00						
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00						
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00						
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00						
Rubinetterie	M 15		578312	155,00						
Bresciane	M 18		578314	155,00						
Bonomi	M 22		578316	155,00						
TURBO INOX GAS	M 28		578318	155,00						
	M 35		578390	188,00						
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00						
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00						
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00						
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00						
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00						

**S**

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA 3fit-Press Pb-free Serie 25000	B 16		578468	203,00	SANHA-NiroSan Industry Presssystem Serie 18000	SA 15		578514	186,00	
	B 20		578472	203,00		SA 18		578518	186,00	
	B 26		578474	224,00		SA 22		578520	186,00	
	B 32		578476	224,00		SA 28		578522	186,00	
	F 16		578456	178,00		M 15 <sup>1)</sup>		578312	155,00	
	F 20		578460	178,00		M 18 <sup>1)</sup>		578314	155,00	
	F 26		578462	192,00		M 22 <sup>1)</sup>		578316	155,00	
	F 32		578464	192,00		M 28		578318	155,00	
	Fz 40		578478	260,00		M 35		578390	188,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	H 16		578400	168,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	H 20		578406	168,00		V 15 <sup>1)</sup>		578328	155,00	
	H 26		578410	168,00		V 18 <sup>1)</sup>		578332	155,00	
	H 32		578412	168,00		V 22 <sup>1)</sup>		578334	155,00	
	TH 16		578352 R	186,00		V 28		578336	155,00	
	TH 20		578358 R	186,00		V 35		578604	188,00	
	TH 26		578362 R	186,00		V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	TH 32		578364	186,00		V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	TH 40		578624	247,00		V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		SANHA-NiroSan- Presssystem Serie 9000	SA 15		578514	186,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00			SA 18		578518	186,00
	U 16		578374	174,00			SA 22		578520	186,00
	U 20		578378	174,00			SA 28		578522	186,00
	U 26 <sup>7)</sup>		578392	205,00			M 15 <sup>1)</sup>		578312	155,00
	U 32		578382	205,00			M 18 <sup>1)</sup>		578314	155,00
	U 40		578386	249,00			M 22 <sup>1)</sup>		578316	155,00
							M 28		578318	155,00
							M 35		578390	188,00
							M 15 S (PR-2B)	Mini Z8	574738 R	131,00
							M 18 S (PR-2B)	Mini Z8	574740 R	131,00
							M 22 S (PR-2B)	Mini Z8	574742 R	131,00
							M 28 S (PR-2B)	Mini Z8	574744 R	131,00
							M 35 S (PR-2B)	Mini Z8	574746 R	144,00
							V 15 <sup>1)</sup>		578328	155,00
				V 18 <sup>1)</sup>		578332	155,00			
				V 22 <sup>1)</sup>		578334	155,00			
				V 28		578336	155,00			
				V 35		578604	188,00			
				V 15 S (PR-2B)	Mini Z8	574752 R	131,00			
				V 18 S (PR-2B)	Mini Z8	574756 R	131,00			
				V 22 S (PR-2B)	Mini Z8	574758 R	131,00			
				V 28 S (PR-2B)	Mini Z8	574760 R	131,00			
				V 35 S (PR-2B)	Mini Z8	574762 R	144,00			
				SANHA-NiroSan SF Presssystem Serie 19000 (silicone free)	SA 15		578514	186,00		
					SA 18		578518	186,00		
					SA 22		578520	186,00		
					SA 28		578522	186,00		
					M 15 <sup>1)</sup>		578312	155,00		
					M 18 <sup>1)</sup>		578314	155,00		
					M 22 <sup>1)</sup>		578316	155,00		
					M 28		578318	155,00		
					M 35		578390	188,00		
					M 15 S (PR-2B)	Mini Z8	574738 R	131,00		
					M 18 S (PR-2B)	Mini Z8	574740 R	131,00		
					M 22 S (PR-2B)	Mini Z8	574742 R	131,00		
					M 28 S (PR-2B)	Mini Z8	574744 R	131,00		
					M 35 S (PR-2B)	Mini Z8	574746 R	144,00		
					V 15 <sup>1)</sup>		578328	155,00		
				V 18 <sup>1)</sup>		578332	155,00			
				V 22 <sup>1)</sup>		578334	155,00			
				V 28		578336	155,00			
				V 35		578604	188,00			
				V 15 S (PR-2B)	Mini Z8	574752 R	131,00			
				V 18 S (PR-2B)	Mini Z8	574756 R	131,00			
				V 22 S (PR-2B)	Mini Z8	574758 R	131,00			
				V 28 S (PR-2B)	Mini Z8	574760 R	131,00			
				V 35 S (PR-2B)	Mini Z8	574762 R	144,00			
SANHA Heavy Steel Press	VMP ½" G (OD 21,3 mm)		578666 R	215,00	SANHA NiroTherm Serie 91000	SA 15		578514	186,00	
	VMPz ¾" (OD 26,9 mm)		578664	215,00		SA 18		578518	186,00	
SANHA Heavy Steel Press Gas	VMP ½" G (OD 21,3 mm) <sup>1)</sup>		578666 R	215,00		SA 22		578520	186,00	
	VMPz ¾" (OD 26,9 mm)		578664	215,00		SA 28		578522	186,00	
SANHA-NiroSan Gas Presssystem Serie 17000	SA 15		578514	186,00		M 15 <sup>1)</sup>		578312	155,00	
	SA 18		578518	186,00		M 18 <sup>1)</sup>		578314	155,00	
	SA 22		578520	186,00		M 22 <sup>1)</sup>		578316	155,00	
	SA 28		578522	186,00		M 28		578318	155,00	
	M 15 <sup>1)</sup>		578312	155,00		M 35		578390	188,00	
	M 18 <sup>1)</sup>		578314	155,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 22 <sup>1)</sup>		578316	155,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 28		578318	155,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 35		578390	188,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		V 15 <sup>1)</sup>		578328	155,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	V 18 <sup>1)</sup>		578332	155,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	V 22 <sup>1)</sup>		578334	155,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	V 28		578336	155,00		
	V 15 <sup>1)</sup>		578328	155,00	V 35		578604	188,00		
	V 18 <sup>1)</sup>		578332	155,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		
	V 22 <sup>1)</sup>		578334	155,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		
	V 28		578336	155,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
	V 35		578604	188,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		

**REMS pressing tongs Mini**  
**REMS pressing rings**

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
SANHA NiroTherm Industry Serie 98000	SA 15		578514	186,00	SANHA-Press Pressfittings Serie 6000	SA 12		578510	270,00
	SA 18		578518	186,00		SA 14		578512	270,00
	SA 22		578520	186,00		SA 15		578514	186,00
	SA 28		578522	186,00		SA 16		578516	186,00
	M 15 <sup>1)</sup>		578312	155,00		SA 18		578518	186,00
	M 18 <sup>1)</sup>		578314	155,00		SA 22		578520	186,00
	M 22 <sup>1)</sup>		578316	155,00		SA 28		578522	186,00
	M 28		578318	155,00		SA 28		578522	186,00
	M 35		578390	188,00		M 12		578310	155,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		M 15 <sup>1)</sup>		578312	155,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00		M 18 <sup>1)</sup>		578314	155,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		M 22 <sup>1)</sup>		578316	155,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		M 28		578318	155,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00		M 35		578390	188,00
	V 15 <sup>1)</sup>		578328	155,00		M 12 S (PR-2B)	Mini Z8	574736 R	131,00
	V 18 <sup>1)</sup>		578332	155,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	V 22 <sup>1)</sup>		578334	155,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	V 28		578336	155,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	V 35		578604	188,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		V 12		578324	155,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		VG 14		578338	155,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		V 15 <sup>1)</sup>		578328	155,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		V 16		578330	155,00
	SANHA-Press Chrom Serie 16000	SA 12		578510		270,00	VG 16		578340
SA 15			578514	186,00	V 18 <sup>1)</sup>		578332	155,00	
SA 18			578518	186,00	V 22 <sup>1)</sup>		578334	155,00	
SA 22			578520	186,00	V 28		578336	155,00	
SA 28			578522	186,00	V 35		578604	188,00	
M 12			578310	155,00	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
M 15 <sup>1)</sup>			578312	155,00	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00	
M 18 <sup>1)</sup>			578314	155,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
M 22 <sup>1)</sup>			578316	155,00	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00	
M 28			578318	155,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
M 12 S (PR-2B)		Mini Z8	574736 R	131,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	SANHA-Press SOLAR Pressfittings Serie 12000/ Serie 13000	SA 12		578510	270,00
M 28 S (PR-2B)		Mini Z8	574744 R	131,00		SA 15		578514	186,00
V 12			578324	155,00		SA 18		578518	186,00
V 15 <sup>1)</sup>			578328	155,00		SA 22		578520	186,00
V 18 <sup>1)</sup>			578332	155,00		SA 28		578522	186,00
V 22 <sup>1)</sup>			578334	155,00		M 12		578310	155,00
V 28			578336	155,00		M 15 <sup>1)</sup>		578312	155,00
V 12 S (PR-2B)		Mini Z8	574748 R	131,00		M 18 <sup>1)</sup>		578314	155,00
V 15 S (PR-2B)		Mini Z8	574752 R	131,00		M 22 <sup>1)</sup>		578316	155,00
V 18 S (PR-2B)		Mini Z8	574756 R	131,00		M 28		578318	155,00
V 22 S (PR-2B)		Mini Z8	574758 R	131,00		M 35		578390	188,00
V 28 S (PR-2B)		Mini Z8	574760 R	131,00		M 12 S (PR-2B)	Mini Z8	574736 R	131,00
SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000	SA 12		578510	270,00		M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	SA 14		578512	270,00		M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	SA 15		578514	186,00		M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	SA 16		578516	186,00		M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	SA 18		578518	186,00		M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	SA 22		578520	186,00		V 12		578324	155,00
	SA 28		578522	186,00		V 14		578326	155,00
	M 12		578310	155,00		VG 14		578338	155,00
	M 15 <sup>1)</sup>		578312	155,00		V 15 <sup>1)</sup>		578328	155,00
	M 18 <sup>1)</sup>		578314	155,00		V 16		578330	155,00
	M 22 <sup>1)</sup>		578316	155,00		VG 16		578340	155,00
	M 28		578318	155,00		V 18 <sup>1)</sup>		578332	155,00
	M 35		578390	188,00		V 22 <sup>1)</sup>		578334	155,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	V 28		578336	155,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	V 35		578604	188,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 12		578324	155,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 14		578326	155,00	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	VG 14		578338	155,00					
	V 15 <sup>1)</sup>		578328	155,00					
	V 16		578330	155,00					
	VG 16		578340	155,00					
V 18 <sup>1)</sup>		578332	155,00						
V 22 <sup>1)</sup>		578334	155,00						
V 28		578336	155,00						
V 35		578604	188,00						
V 12 S (PR-2B)	Mini Z8	574748 R	131,00						
VG 14 S (PR-2B)	Mini Z8	574750 R	131,00						
V 15 S (PR-2B)	Mini Z8	574752 R	131,00						
VG 16 S (PR-2B)	Mini Z8	574754 R	131,00						
V 18 S (PR-2B)	Mini Z8	574756 R	131,00						
V 22 S (PR-2B)	Mini Z8	574758 R	131,00						
V 28 S (PR-2B)	Mini Z8	574760 R	131,00						
V 35 S (PR-2B)	Mini Z8	574762 R	144,00						

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA PURAPRESS Serie 8000	SA 12		578510	270,00	
	SA 14		578512	270,00	
	SA 15		578514	186,00	
	SA 16		578516	186,00	
	SA 18		578518	186,00	
	SA 22		578520	186,00	
	SA 28		578522	186,00	
	M 12 <sup>1)</sup>		578310	155,00	
	M 15 <sup>1)</sup>		578312	155,00	
	M 18 <sup>1)</sup>		578314	155,00	
	M 22 <sup>1)</sup>		578316	155,00	
	M 28 <sup>1)</sup>		578318	155,00	
	M 35 <sup>1)</sup>		578390	188,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	V 12		578324	155,00	
	V 14		578326	155,00	
	VG 14		578338	155,00	
	V 15 <sup>1)</sup>		578328	155,00	
	V 16		578330	155,00	
	VG 16		578340	155,00	
	V 18 <sup>1)</sup>		578332	155,00	
	V 22 <sup>1)</sup>		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	SANHA-Therm Serie 24000	SA 12		578510	270,00
		SA 15		578514	186,00
		SA 18		578518	186,00
SA 22			578520	186,00	
SA 28			578522	186,00	
M 12			578310	155,00	
M 15 <sup>1)</sup>			578312	155,00	
M 18 <sup>1)</sup>			578314	155,00	
M 22 <sup>1)</sup>			578316	155,00	
M 28			578318	155,00	
M 35			578390	188,00	
M 12 S (PR-2B)		Mini Z8	574736 R	131,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00	
M 28 S (PR-2B)		Mini Z8	574744 R	131,00	
M 35 S (PR-2B)		Mini Z8	574746 R	144,00	
V 12			578324	155,00	
V 15 <sup>1)</sup>			578328	155,00	
V 18 <sup>1)</sup>			578332	155,00	
V 22 <sup>1)</sup>			578334	155,00	
V 28			578336	155,00	
V 35			578604	188,00	
V 12 S (PR-2B)		Mini Z8	574748 R	131,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	
SANHA-Therm Industry Serie 28000		SA 12		578510	270,00
		SA 15		578514	186,00
		SA 18		578518	186,00
		SA 22		578520	186,00
		SA 28		578522	186,00
		M 12		578310	155,00
		M 15 <sup>1)</sup>		578312	155,00
		M 18 <sup>1)</sup>		578314	155,00
		M 22 <sup>1)</sup>		578316	155,00
		M 28		578318	155,00
		M 35		578390	188,00
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	V 12		578324	155,00	
	V 15 <sup>1)</sup>		578328	155,00	
	V 18 <sup>1)</sup>		578332	155,00	
	V 22 <sup>1)</sup>		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
SANITOP PERMATUBO INOX	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	
	SANPRO THPRESS	TH 16		578352 R	186,00
		TH 20		578358 R	186,00
TH 26			578362 R	186,00	
TH 32			578364	186,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		
SATEC SK VITerm	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	U 40		578386	249,00	
SAVEUR REFLEX PEX Water	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 32		578364	186,00	
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 32		578364	186,00	
Schütz duo-flex tri-o-flex	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 17		578354	186,00	
	TH 20		578358 R	186,00	
	TH 25		578360	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		
Schwer Fittings AQUApress	M 12		578310	155,00	
	M 15		578312	155,00	
	M 18		578314	155,00	
	M 22		578316	155,00	
	M 28		578318	155,00	
	M 35		578390	188,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	
M 18 S (PR-2B)	Mini Z8	574740 R	131,00		
M 22 S (PR-2B)	Mini Z8	574742 R	131,00		
M 28 S (PR-2B)	Mini Z8	574744 R	131,00		
M 35 S (PR-2B)	Mini Z8	574746 R	144,00		
Seppelfricke > Aalberts integrated piping systems					
SESTA SESTA GAS	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
SESTA sistema multistrato	H 16		578400	168,00	
	H 20		578406	168,00	
	TH 14		578348	186,00	
	TH 16		578352 R	186,00	
	TH 18		578356	186,00	
	TH 20		578358 R	186,00	
SIGMA LI Premium	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	U 25		578380	174,00	
	U 32		578382	205,00	
	SLOVARM PEX-THERM	U 16		578374	174,00
		U 20		578378	174,00
H 26			578410	168,00	
U 32			578382	205,00	
H 16			578400	168,00	
H 20			578406	168,00	
H 26			578410	168,00	
H 32			578412	168,00	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
STANDARD HIDRAULICA MultiStandard	H 16		578400	168,00	TDM BRASS Serie 2600	H 16		578400	168,00	
	H 20		578406	168,00		H 18		578404	168,00	
	H 25		578408	168,00		H 20		578406	168,00	
	H 32		578412	168,00		H 25		578408	168,00	
	RFz 16		578492	194,00		H 26		578410	168,00	
	RFz 20		578494	194,00		H 32		578412	168,00	
	RFz 25		578496	194,00		TH 16		578352 R	186,00	
	RFz 32		578498	194,00		TH 18		578356	186,00	
	TH 16		578352 R	186,00		TH 20		578358 R	186,00	
	TH 20		578358 R	186,00		TH 25		578360	186,00	
	TH 25		578360	186,00		TH 26		578362 R	186,00	
	TH 32		578364	186,00		THL 32		578368	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		TH 16 S (PR-2B)**		574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00		TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
	U 16		578374	174,00		TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	U 18		578376	174,00		U 16		578374	174,00	
	U 20		578378	174,00		U 18		578376	174,00	
	U 25		578380	174,00		U 20		578378	174,00	
	U 32		578382	205,00		U 25		578380	174,00	
	U 40		578386	249,00		U 26 <sup>7)</sup>		578392	205,00	
	U 32		578382	205,00		U 32		578382	205,00	
	steeltrade Presssystem Edelstahl Kontur M	M 15		578312		155,00	TDM BRASS Serie 1700 gas	TH 16		578352 R
M 18 <sup>1)</sup>			578314	155,00	TH 20			578358 R	186,00	
M 22			578316	155,00	TH 26			578362 R	186,00	
M 28 <sup>1)</sup>			578318	155,00	THL 32			578368	186,00	
M 35			578390	188,00	TH 16 S (PR-2B)**	Mini Z8		574782 R	131,00	
M 15 S (PR-2B)		Mini Z8	574738 R	131,00	TH 20 S (PR-2B)**	Mini Z8		574788 R	131,00	
M 18 S (PR-2B)		Mini Z8	574740 R	131,00	TH 26 S (PR-2B)**	Mini Z8		574794 R	131,00	
M 22 S (PR-2B)		Mini Z8	574742 R	131,00						
M 28 S (PR-2B)		Mini Z8	574744 R	131,00						
M 35 S (PR-2B)		Mini Z8	574746 R	144,00						
STELBI Polikraft	H 16		578400	168,00	TermaConcept TC-PRESS	Basic E01 <sup>1)</sup>		578618	321,00	
	H 20		578406	168,00		THERMOLUTZ	H 14		578398	168,00
	H 26		578410	168,00	H 16			578400	168,00	
	TH 16		578352 R	186,00	TH 20			578358 R	186,00	
	TH 20		578358 R	186,00	TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	
	TH 26		578362 R	186,00						
	TH 32		578364	186,00						
	TH 40		578624	247,00						
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00						
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00						
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00						
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00						
	U 16		578374	174,00						
	U 20		578378	174,00						
	U 26 <sup>7)</sup>		578392	205,00						
	STELBI Stelgas	TH 16		578352 R	186,00		TE-SA TE-SA press serie 800	TH 14		578348
TH 20			578358 R	186,00	TH 16				578352 R	186,00
TH 26			578362 R	186,00	TH 18			578356	186,00	
TH 16 S (PR-2B)**		Mini Z8	574782 R	131,00	TH 20			578358 R	186,00	
TH 20 S (PR-2B)**		Mini Z8	574788 R	131,00	TH 26			578362 R	186,00	
TH 26 S (PR-2B)**		Mini Z8	574794 R	131,00	TH 32			578364	186,00	
					TH 40			578624	247,00	
STH Westco COPPER PRESS	M 15		578312	155,00	THERMACOME ACOPEX ALU	H 16		578400	168,00	
	M 22		578316	155,00		H 20		578406	168,00	
	M 28		578318	155,00		H 26		578410	168,00	
	M 35		578390	188,00		H 32		578412	168,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00		TH 16		578352 R	186,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00		TH 20		578358 R	186,00	
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00		TH 26		578362 R	186,00	
M 35 S (PR-2B)	Mini Z8	574746 R	144,00	TH 32		578364	186,00			
				U 16		578374	174,00			
				U 20		578378	174,00			
				U 32		578382	205,00			
<b>T</b>					TIEMME 1650 AL-COBRAPEX	TH 14		578348	186,00	
	TDM BRASS Serie 1600	H 16		578400		168,00	TH 16		578352 R	186,00
		H 18		578404		168,00	TH 18		578356	186,00
		H 20		578406		168,00	TH 20		578358 R	186,00
		H 25		578408		168,00	TH 25		578360	186,00
		H 26		578410		168,00	TH 26		578362 R	186,00
		H 32		578412		168,00	THL 32		578368	186,00
		TH 16		578352 R		186,00	TH 40		578624	247,00
		TH 18		578356		186,00	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
		TH 20		578358 R		186,00	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
		TH 25		578360		186,00	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
		TH 26		578362 R		186,00	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
		THL 32		578368		186,00	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
		TH 40		578624		247,00	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
		TH 16 S (PR-2B)**	Mini Z8	574782 R		131,00				
		TH 18 S (PR-2B)**	Mini Z8	574786 R		131,00				
		TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00					
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00						
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00						
	U 16		578374	174,00						
	U 18		578376	174,00						
	U 20		578378	174,00						
	U 25		578380	174,00						
	U 26 <sup>7)</sup>		578392	205,00						
	U 32		578382	205,00						

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TIEMME 1650 AL-COBRAPEX GAS	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	THL 32		578368	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
TIGRE ALPEX GAS	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
TKM Systemtechnik	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
TRA Multi TRA+	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 20		578378	174,00
U 25		578380	174,00	
U 26 <sup>7)</sup>		578392	205,00	
U 32		578382	205,00	
U 40		578386	249,00	
TRA MULTITRAPRESS	U 16		578374	174,00
	U 18		578376	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	U 40		578386	249,00
TRA TRAPRESS	H 12		578396	168,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	Rfz 12		578490	194,00
	Rfz 16		578492	194,00
	Rfz 20		578494	194,00
	Rfz 25		578496	194,00
	Rfz 32		578498	194,00
Tradelink TradePex Crimp Water	K16/P18		578592	194,00
	K/20		578594	194,00
	K/25		578596	194,00
	K32		578598	194,00
	K1/40		578600	194,00
Tradelink TradePex Crimp Gas	K16/P18		578592	194,00
	K/20		578594	194,00
	K/25		578596	194,00
	K32		578598	194,00
	K1/40		578600	194,00
TUBIPLAST ITALY MULTILAYER PIPE	H 16		578400	168,00
	H 18		578404	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	U 16		578374	174,00
	U 18		578376	174,00
U 20		578378	174,00	
U 26 <sup>7)</sup>		578392	205,00	
U 32		578382	205,00	
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352 R	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TWEETOP	U 16		578374	174,00
	U 20		578378	174,00
	U 25		578380	174,00
	U 32		578382	205,00
	U 40		578386	249,00
<b>U</b>				
UNICAL AG MAX-MULTIPEX	U 16		578374	174,00
	U 20		578378	174,00
	H 26		578410	168,00
	U 26 <sup>7)</sup>		578392	205,00
	U 32		578382	205,00
UNIDELTA DELTAPRESS	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
UNIDELTA DELTAPRESS GAS	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
U 16		578374	174,00	
U 20		578378	174,00	
U 32		578382	205,00	
U 40		578386	249,00	
UNIDELTA DELTAPRESS GAS	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
H 32		578412	168,00	
U 16		578374	174,00	
U 20		578378	174,00	
U 32		578382	205,00	
Uponor	UP 14		578576	174,00
	UP 16		578578	174,00
	UP 20		578582	174,00
	UP 25		578584	174,00
	UP 32		578586	205,00
	U 40		578386	249,00
<b>V</b>				
Valsir Bravopress	B 16		578468	203,00
	B 20		578472	203,00
	B 26		578474	224,00
	B 32		578476	224,00
	F 16		578456	178,00
	F 20		578460	178,00
	F 26		578462	192,00
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	H 32 V		578602	215,00
TH 16		578352 R	186,00	
TH 20		578358 R	186,00	
TH 26		578362 R	186,00	
TH 32		578364	186,00	
U 16		578374	174,00	
U 20		578378	174,00	
U 26 <sup>7)</sup>		578392	205,00	
U 32		578382	205,00	
Valsir PEXAL	H 14		578398	168,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 26		578410	168,00
	H 32		578412	168,00
	H 32 V		578602	215,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	U 16		578374	174,00
	U 20		578378	174,00
	U 26 <sup>7)</sup>		578392	205,00
	U 32		578382	205,00

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Van Marcke NV SYSTEMPEX	TH 16		578352 R	186,00	Viega MegaPress 316 (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00	
	TH 20		578358 R	186,00		VMPz ¾" (OD 26,9 mm)		578664	215,00	
	TH 26		578362 R	186,00		Viega MegaPress 316 FKM	VMP ½" G (OD 21,3 mm)		578666 R	215,00
	TH 32		578364	186,00			VMPz ¾" (OD 26,9 mm)		578664	215,00
	TH 40		578624	247,00		(ASTM) <sup>51</sup>			578664	182,50
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00		Viega MegaPress CuNi (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00		VMPz ¾" (OD 26,9 mm)		578664	215,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00		Viega MegaPress FKM (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	VMPz ¾" (OD 26,9 mm)		578664	215,00			
Van Marcke NV Tubipress	M 12		578310	155,00	Viega MegaPresG (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00	
	M 15		578312	155,00	VMPz ¾" (OD 26,9 mm)		578664	215,00		
	M 18		578314	155,00	Viega Megapress (EN) <sup>41</sup>	VMP ¾" (OD 17,2 mm)		578660	215,00	
	M 22		578316	155,00	VMP ½" G (OD 21,3 mm)		578666 R	215,00		
	M 28		578318	155,00	VMPz ¾" (OD 26,9 mm)		578664	215,00		
	M 35		578390	188,00	Viega MegapressS (EN) <sup>41</sup>	VMP ¾" (OD 17,2 mm)		578660	215,00	
	M 12 S (PR-2B)	Mini Z8	574736 R	131,00	VMP ½" G (OD 21,3 mm)		578666 R	215,00		
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	VMPz ¾" (OD 26,9 mm)		578664	215,00		
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	Viega Pexfit	VX 16		578552	215,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	VX 20		578554	215,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	VX 25		578556	215,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	Viega Pexfit G	VX 16		578552	215,00	
					VX 20		578554	215,00		
					VX 25		578556	215,00		
Variotherm System TH	TH 11,6		578344	186,00	Viega Prestabo	V 12		578324	155,00	
	TH 16		578352 R	186,00	V 15		578328	155,00		
	TH 20		578358 R	186,00	V 18		578332	155,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	V 22		578334	155,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	V 28		578336	155,00		
VESBO CARBON	M 15		578312	155,00	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		
	M 18		578314	155,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		
	M 22		578316	155,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		
	M 28		578318	155,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
	M 35		578390	188,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	Viega Profipress	V 12		578324	155,00	
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	VG 14		578338	155,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	V 15		578328	155,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	VG 16		578340	155,00		
					V 18		578332	155,00		
VESBO INOX	M 15		578312	155,00	V 22		578334	155,00		
	M 18		578314	155,00	V 28		578336	155,00		
	M 22		578316	155,00	V 35		578604	188,00		
	M 28		578318	155,00	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		
	M 35		578390	188,00	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00		
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00		
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
					V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
VESBO MULTIPRESS TH-U	TH 16		578352 R	186,00	Viega Profipress G	V 12		578324	155,00	
	TH 20		578358 R	186,00	VG 14		578338	155,00		
	TH 26		578362 R	186,00	V 15		578328	155,00		
	TH 32		578364	186,00	VG 16		578340	155,00		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	V 18		578332	155,00		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	V 22		578334	155,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	V 28		578336	155,00		
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	V 35		578604	188,00		
	U 16		578374	174,00	V 12 S (PR-2B)	Mini Z8	574748 R	131,00		
	U 20		578378	174,00	VG 14 S (PR-2B)	Mini Z8	574750 R	131,00		
	U 26 <sup>71</sup>		578392	205,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		
U 32		578382	205,00	VG 16 S (PR-2B)	Mini Z8	574754 R	131,00			
VESBO VPREMIUM	U 16		578374	174,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		
	U 20		578378	174,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
	U 25		578380	174,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
	U 32		578382	205,00	V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
	U 40		578386	249,00	Viega Profipress S	V 12		578324	155,00	
Viega Fonterra	VX 12		578550	215,00	V 15		578328	155,00		
	VP 14/15		578480	186,00	V 18		578332	155,00		
	VP 16/17		578482	186,00	V 22		578334	155,00		
	VP 20		578484	186,00	V 28		578336	155,00		
	VP 25		578486	186,00	V 35		578604	188,00		
					V 12 S (PR-2B)	Mini Z8	574748 R	131,00		
Viega MegaPress (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00	V 15 S (PR-2B)	Mini Z8	574752 R	131,00		
	VMPz ¾" (OD 26,9 mm)		578664	215,00	V 18 S (PR-2B)	Mini Z8	574756 R	131,00		
Viega MegaPress 304 FKM (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	215,00	V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
	VMPz ¾" (OD 26,9 mm)		578664	215,00	V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
				V 35 S (PR-2B)	Mini Z8	574762 R	144,00			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

<sup>1)</sup> Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

<sup>2)</sup> For taking suitable pressing inserts.

<sup>3)</sup> Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

<sup>4)</sup> For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>5)</sup> For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>6)</sup> Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

<sup>7)</sup> Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Viega Profipress Therm	V 12		578324	155,00	
	V 15		578328	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
Viega ProPress (ASTM) <sup>51</sup>	VUS ½" (OD 15,9 mm)		578566	187,00	
	VUS ¾" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1¼" (OD 34,9 mm)		578606	187,00	
	VUS ½" S (PR-2B) (OD 15,9 mm)	Mini Z8	574764 R	131,00	
	VUS ¾" S (PR-2B) (OD 22,2 mm)	Mini Z8	574766 R	131,00	
	VUS 1" S (PR-2B) (OD 28,6 mm)	Mini Z8	574768 R	131,00	
VUS 1¼" S (PR-2B) (OD 34,9 mm)	Mini Z8	574770 R	131,00		
Viega ProPress 304 FKM (ASTM) <sup>51</sup>	VUS ½" (OD 15,9 mm)		578566	187,00	
	VUS ¾" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1¼" (OD 34,9 mm)		578606	187,00	
Viega ProPress 316 (ASTM) <sup>51</sup>	VUS ½" (OD 15,9 mm)		578566	187,00	
	VUS ¾" (OD 22,2 mm)		578568	187,00	
	VUS 1" (OD 28,6 mm)		578570	187,00	
	VUS 1¼" (OD 34,9 mm)		578606	187,00	
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		578630	160,00	
	VAU 20 (OD 19,1 mm)		578632	160,00	
	VAU 25 (OD 25,4 mm)		578634	160,00	
	VAU 32 (OD 31,8 mm)		578636	168,00	
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	131,00	
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	131,00	
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	144,00	
VAU 32 S (PR-2B) (OD 31,8 mm)	Mini Z8	574856 R	144,00		
Viega PropressG GAS System AUS	VAU 15 (OD 12,7 mm)		578630	160,00	
	VAU 20 (OD 19,1 mm)		578632	160,00	
	VAU 25 (OD 25,4 mm)		578634	160,00	
	VAU 32 (OD 31,8 mm)		578636	168,00	
Viega Raxinox	VRX 16		578640	196,00	
	VRX 20		578642	196,00	
	VRX 25		578644	215,00	
	VRX 32		578646	215,00	
Viega Raxofix	VRX 16		578640	196,00	
	VRX 20		578642	196,00	
	VRX 25		578644	215,00	
	VRX 32		578646	215,00	
Viega Sanfix	VP 16/17		578482	186,00	
	VP 20		578484	186,00	
	VP 25		578486	186,00	
	VP 32		578488	206,00	
Viega Sanfix Fosta	VP 16/17		578482	186,00	
	VP 20		578484	186,00	
	VP 25		578486	186,00	
	VP 32		578488	206,00	
Viega Sanpress	V 12		578324	155,00	
	V 15		578328	155,00	
	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 12 S (PR-2B)	Mini Z8	574748 R	131,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	
	Viega Sanpress Inox	V 15		578328	155,00
V 18			578332	155,00	
V 22			578334	155,00	
V 28			578336	155,00	
V 35			578604	188,00	
V 15 S (PR-2B)		Mini Z8	574752 R	131,00	
V 18 S (PR-2B)		Mini Z8	574756 R	131,00	
V 22 S (PR-2B)		Mini Z8	574758 R	131,00	
V 28 S (PR-2B)		Mini Z8	574760 R	131,00	
V 35 S (PR-2B)		Mini Z8	574762 R	144,00	
Viega Sanpress Inox G		V 15		578328	155,00
		V 18		578332	155,00
		V 22		578334	155,00
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
V 22 S (PR-2B)	Mini Z8	574758 R	131,00		
V 28 S (PR-2B)	Mini Z8	574760 R	131,00		
V 35 S (PR-2B)	Mini Z8	574762 R	144,00		
Viega Smartpress	VX 16		578552	215,00	
	VX 20		578554	215,00	
	VX 25		578556	215,00	
	V 15		578328	155,00	
Viega Temponox	V 18		578332	155,00	
	V 22		578334	155,00	
	V 28		578336	155,00	
	V 35		578604	188,00	
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00	
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00	
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00	
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00	
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Viessmann	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
Vogel & Noot EASYTEC	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	

VSH > Aalberts integrated piping systems

### W

Watts MTR	TH 16		578352 R	186,00
Art press	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
WATTS	US ¾"		578534	212,00
RADIANT	US ½"		578536	212,00
Watts WaterPEX	US ¾"		578538	212,00
	US 1"		578540	212,00
WATTS	US ¾"		578534	212,00
RADIANT	US ½"		578536	212,00
Watts	US ¾"		578538	212,00
RadiantPEX	US 1"		578540	212,00
WATTS	U 16 (½")		578374	174,00
RADIANT	U 20 (¾")		578378	174,00
Watts	U 25 (¾")		578380	174,00
RadiantPEX-AL	U 32 (1")		578382	205,00
Wavin	B 16		578468	203,00
Tigris K5/M5	B 20		578472	203,00
	B 32		578476	224,00
	H 16		578400	168,00
	H 20		578406	168,00
	H 25		578408	168,00
	H 32		578412	168,00
	TH 16		578352 R	186,00
	TH 20		578358 R	186,00
	TH 25		578360	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
TH 25 S (PR-2B)**	Mini Z8	574792 R	131,00	
TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
U 16		578374	174,00	
U 20		578378	174,00	
U 25		578380	174,00	
U 32		578382	205,00	
U 40		578386	249,00	
UP 16		578578	174,00	
UP 20		578582	174,00	
UP 25		578584	174,00	
UP 32		578586	205,00	
WEECON	M 15		578312	155,00
PRESS-C-Stahl	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	WEECON	M 15		578312
PRESS-Edelstahl	M 18		578314	155,00
	M 22		578316	155,00
	M 28		578318	155,00
	M 35		578390	188,00
	M 15 S (PR-2B)	Mini Z8	574738 R	131,00
	M 18 S (PR-2B)	Mini Z8	574740 R	131,00
	M 22 S (PR-2B)	Mini Z8	574742 R	131,00
	M 28 S (PR-2B)	Mini Z8	574744 R	131,00
	M 35 S (PR-2B)	Mini Z8	574746 R	144,00
	WEECON	V 15		578328
PRESS-Kupfer	V 18		578332	155,00
	V 22		578334	155,00
	V 28		578336	155,00
	V 35		578604	188,00
	V 15 S (PR-2B)	Mini Z8	574752 R	131,00
	V 18 S (PR-2B)	Mini Z8	574756 R	131,00
	V 22 S (PR-2B)	Mini Z8	574758 R	131,00
	V 28 S (PR-2B)	Mini Z8	574760 R	131,00
	V 35 S (PR-2B)	Mini Z8	574762 R	144,00

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
WEM	U 16		578374	174,00
WIELAND-WERKE cuprotherm CTX	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 14 S (PR-2B)**	Mini Z8	574778 R	131,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
WKS-Press	TH 14		578348	186,00
	TH 16		578352 R	186,00
	TH 17		578354	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	WÜRTH	TH 16		578352 R
Würth	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	HE 32		578370 R	223,00

### X

XtraConnect	F 16		578456	178,00	
	F 20		578460	178,00	
	F 26		578462	192,00	
	F 32		578464	192,00	
	F 16 S (PR-2B)**	Mini Z8	574728 R	131,00	
	F 20 S (PR-2B)**	Mini Z8	574730 R	131,00	
	F 26 S (PR-2B)**	Mini Z8	574732 R	131,00	
	F 32 S (PR-2B)	Mini Z8	574734 R	144,00	
	H 16		578400	168,00	
	H 20		578406	168,00	
	H 26		578410	168,00	
	H 32		578412	168,00	
	TH 16		578352 R	186,00	
	TH 20		578358 R	186,00	
	TH 26		578362 R	186,00	
	TH 32		578364	186,00	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00	
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00	
	U 16		578374	174,00	
	U 20		578378	174,00	
	(DN 26)	U 25		578380	174,00
		U 32		578382	205,00
		VP 16		578482	186,00
		VP 20		578484	186,00
		VP 32		578488	206,00

### Y

YX COPPER	Yz 16 UNI		578740	194,00
UNIPEX Water & Gas	Yz 20 UNI		578742	194,00
(AUS)	Yz 25 UNI		578744	194,00
	Yz 32 UNI		578746	194,00

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
<b>Z</b>				
ZEWOTHERM	TH 12		578346	186,00
Zewo Press Premium	TH 16		578352 R	186,00
	TH 17		578354	186,00
	TH 18		578356	186,00
	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 40		578624	247,00
	TH 12 S (PR-2B)**	Mini Z8	574776 R	131,00
	TH 16 S (PR-2B)**		574782 R	131,00
	TH 17 S (PR-2B)**	Mini Z8	574784 R	131,00
	TH 18 S (PR-2B)**	Mini Z8	574786 R	131,00
	TH 20 S (PR-2B)**		574788 R	131,00
TH 26 S (PR-2B)**		574794 R	131,00	
TH 32 S (PR-2B)		574798 R	144,00	
ZEWOTHERM	TH 16		578352 R	186,00
Zewo Press PPSU	TH 20		578358 R	186,00
	TH 26		578362 R	186,00
	TH 32		578364	186,00
	TH 16 S (PR-2B)**	Mini Z8	574782 R	131,00
	TH 20 S (PR-2B)**	Mini Z8	574788 R	131,00
	TH 26 S (PR-2B)**	Mini Z8	574794 R	131,00
	TH 32 S (PR-2B)	Mini Z8	574798 R	144,00
ZURN	US ¾"		578534	212,00
INDUSTRIES	US ½"		578536	212,00
ZURN PEX	US ¾"		578538	212,00
	US 1"		578540	212,00

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

### Accessories

Description	Art.-No.	€
<b>Adapter tongs Mini Z8</b> for driving REMS pressing rings S (PR-2B)	574700R	<b>152,00</b>
<b>Steel case</b> with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	<b>102,00</b>
<b>L-Boxx system case</b> with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	<b>154,00</b>
<b>Steel case</b> with insert for 8 pressing tongs Mini/ cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R	<b>102,00</b>
<b>L-Boxx system case</b> with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659R	<b>154,00</b>

