High quality universal diamond core drilling crowns. Inductively soldered. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other

Ø 32-300 mm

REMS Universal diamond core drilling crowns – Inductively soldered. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1% female. Drilling depth 420 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 1½ male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).









Supply format

REMS Universal diamond core drilling crown. Inductively soldered, resolderable. Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1½ female. Drilling depth 420 mm. In a carton.

Dritting depth 420 mm. in a cartor	1.		
Ø × drilling depth × connection	Number of segments	ArtNo.	€
UDKB 32 × 420 × UNC 11/4	4	181010R	151,00
UDKB 42 × 420 × UNC 11/4	4	181015R	141,00
UDKB 52 × 420 × UNC 11/4	5	181020R	150,00
UDKB 62 × 420 × UNC 11/4	6	181025R	163,00
UDKB 72 × 420 × UNC 11/4	7	181030R	185,00
UDKB 82 × 420 × UNC 11/4	7	181035R	200,00
UDKB 92 × 420 × UNC 11/4	8	181040R	226,00
UDKB 102 × 420 × UNC 11/4	8	181045R	231,00
UDKB 112 × 420 × UNC 11/4	9	181050R	245,00
UDKB 122 × 420 × UNC 11/4	10	181055R	276,00
UDKB 127 × 420 × UNC 11/4	10	181059R	287,00
UDKB 132 × 420 × UNC 11/4	11	181060R	299,00
UDKB 152 × 420 × UNC 11/4	12	181065R	356,00
UDKB 162 × 420 × UNC 11/4	12	181070R	376,00
UDKB 182 × 420 × UNC 11/4	12	181075R	417,00
UDKB 200 × 420 × UNC 11/4	12	181080R	441,00
UDKB 225 × 420 × UNC 11/4	13	181085R	540,00
UDKB 250 × 420 × UNC 11/4	14	181090R	560,00
UDKB 300 × 420 × UNC 11/4	22	181095R	730,00





Accessories

180015	21,70
180155R	64,30
180052	33,10
180056	30,00
180053	50.70
180054	117,00
180057R	117,00
079012	68,00
079003	40,30
	180052 180056 180053 180054 180057R 079012

 $\label{lem:conditional} Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.$



All prices excl. VAT 313