

Universal manual axial press for producing compression sleeve joints.

Axial compression Ø 12 – 32 mm

**REMS Ax-Press HK – universal up to Ø 22 mm**  
Ultra small, ultra light, ultra handy. Only 1.1 kg

**REMS Ax-Press H – universal up to Ø 32 mm.**  
Handy and light. Only 1.4 kg.

**Complete assortment of REMS compression heads, quickly interchangeable.**

### System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

### Compression heads

Full range of REMS compression heads for all common compression sleeve systems (page 298 – 299). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

### Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (page 298). No need to change compression heads. Extremely simple, saves time.

### Design

Compact, job site proven. Handy and light. REMS Ax-Press HK drive unit only 1.1 kg. REMS Ax-Press H drive unit only 1.4 kg. Works anywhere, free-hand, also in tight spots. 66 mm stroke. Quick-acting forward and release for easy, fast operation. Selectable compression head position for pressing compression sleeve connectors with a clamping distance of ≤ 161 mm in one action and for double pressings. Quick-change compression heads and pressing inserts without tools. Secure fit of compression heads and pressing inserts by spring catch. REMS Ax-Press H with overload protection.

### Expanding

Various pipe expanders and complete range of REMS expanding heads for all common compression sleeve systems (page 303 – 307).



### Supply format

**REMS Ax-Press HK drive unit.** Axial press for single-handed operation for producing compression sleeve joints Ø 12 – 22 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

|  | Art.-No. | €      |
|--|----------|--------|
|  | 574302R  | 221,00 |

### Supply format

**REMS Ax-Press H drive unit.** Manual axial press for producing compression sleeve joints Ø 12 – 32 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

|  | Art.-No. | €      |
|--|----------|--------|
|  | 574300RX | 309,00 |

### Accessories

| Description                                                                  | Art.-No. | €     |
|------------------------------------------------------------------------------|----------|-------|
| <b>Compression heads</b> see page 298 – 299.                                 |          |       |
| <b>Carrying bag</b> for REMS Ax-Press HK/H drive unit and compression heads  | 574437R  | 48,70 |
| <b>Case</b> with inlay for REMS Ax-Press HK drive unit and compression heads | 574352R  | 68,70 |

German Quality Product

