

Description	Art.-No.	€
REMS Simplex 2. Robust, handy drilling stand for core drilling up to Ø 202 mm. Description see page 310.	183700R	1.017,24
REMS Titan. Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials up to Ø 300 mm. For high demands. Description see page 310.	183600R	1.546,62
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	57,61
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	28,13
Hammer anchor M12 (pack of 50) , for concrete	079005R50	109,82
Setting iron for hammer anchor M12	182050R	16,09
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	63,42
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	102,76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	72,76
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	54,08
Titan vacuum fastening , consisting of cover plate with nipple for 3/8" screw connection and sealing ring for base plate.	183603R	99,44
Vacuum pump , for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	1.909,92
Laser drilling centre pointer	183604R	129,75
Drilling start aid G 1/2 TDKB , with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145R	91,97
Carbide masonry drill Ø 8 mm for drilling aid	079013	18,89
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	38,35
Light loosening ring , for light loosening of the diamond core crown	180015	20,66
Drilling crown extension 200 mm	180155R	61,19
Sharpening stone for diamond core drilling crowns	079012	64,67
Circular spirit level , magnetic, for aligning the drill stand	182010R	75,26
REMS Pull 2 M , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324		

