

Accessories

For REMS Picus S1, REMS Picus S3, REMS Picus SR,
REMS Picus S2/3,5 and other makes

Description	Art.-No.	€
Water pressure tank for 10 ltr of water, for wet drilling without water connection	182006R	220,00
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	61,50
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	30,10
Hammer anchor M12 (pack of 50) , for concrete	079005R50	118,00
Setting iron for hammer anchor M12	182050R	17,20
Carbide masonry drill Ø 20 mm SDS-plus for splaying anchors M12	079019	67,70
Splaying anchor M12 (pack of 10) , for masonry, reusable	079006R10	111,00
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	77,60
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607R	70,50
Titan vacuum fastening , consisting of cover plate with nipple for 3/8" screw connection and sealing ring for base plate.	183603R	106,00
Vacuum pump , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m³/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183670R220	2.040,00
Laser drilling centre pointer	183604R	139,00
Drilling start aid G ½ UDKB , with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 180160 R), with carbide masonry drill Ø 8 mm	180140R	98,00
Carbide masonry drill Ø 8 mm for drilling aid	079013	20,20
Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	079003	40,90
Light loosening ring , for light loosening of the diamond core crown	180015	22,10
Drilling crown extension 200 mm	180155R	65,30
Sharpening stone for diamond core drilling crowns	079012	69,00
Circular spirit level , magnetic, for aligning the drill stand	182010R	80,20
Suction rotor for dust extraction with G ½ male connecting thread, UNC 1¼ male connecting thread and with connection for REMS Pull 2 and other suitable extractors.	180160R	186,00
Water suction device , for wet drilling up to Ø 170 mm, consisting of water collection ring with pressure ring, rubber washer Ø 200 mm and universal pressure pad for all REMS drilling stands.	183606R	420,00
Rubber washer Ø 200 mm (pack of 10) , for water suction device	183675R10	79,50
Detect B . Electronic bore hole centre tracking device, for exact determination of the in and out centres of through-bores, see page 370.		
Dust protection doors , see page 120.		
REMS Pull 2 L / M , dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 374		

