Description	ArtNo.	€
REMS Simplex 2. Robust, handy drilling stand for core		
drilling up to Ø 202 mm. Description see page 310.	183700 R	1,017.24
<b>REMS Titan.</b> Robust, highly stable drilling stand for core drilling in steel-reinforced concrete and other materials		
up to Ø 300 mm. For high demands. Description see		
page 310.	183600 R	1,546.62
<b>Titan drilling template</b> for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	57.61
Carbide masonry drills Ø 15 mm SDS-plus	070010	20.12
for hammer anchors M12  Hammer anchor M12 (pack of 50), for concrete	079018 079005R50	28.13 109.82
Setting iron for hammer anchor M12	182050R	16.09
Carbide masonry drill Ø 20 mm SDS-plus	070010	(2.42
for splaying anchors M12  Splaying anchor M12 (pack of 10), for masonry,	079019	63.42
reusable	079006R10	102.76
reasable		102.70
Quick clamping set 160 for fastening the drilling stand		102170
<b>Quick clamping set 160</b> for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm	079010	72.76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand	079010	
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm,		72.76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	079010 183607R	72.76
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for 3/6" screw connection and sealing ring	183607R	72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for 3/6" screw connection and sealing ring		72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%),	183607R	72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free,	183607R	72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 – 60 Hz, 250 W, splash water-protected, inside	183607R	72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50−60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC	183607R	72.76 54.08 99.44
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183607 R 183603 R	72.76 54.08 99.44 1,909.92
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid 6 ½ TDKB, with bores for extracting	183607R 183603R	72.76 54.08 99.44 1,909.92
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide	183607R 183603R	72.76 54.08 99.44 1,909.92 129.75
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 - 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid	183607R 183603R 183670R220 183674R	72.76 54.08
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 - 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid  Single open ended wrench size 41 for loosening	183607R  183603R  183670R220  183604R  180145R  079013	72.76 54.08 99.44 1,909.92 129.75 91.97 18.89
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 - 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid  Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	183607R  183603R  183670R220  183604R  180145R	72.76 54.08 99.44 1,909.92 129.75
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50-60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid  Single open ended wrench size 41 for loosening the universal diamond core drilling crowns  Light loosening ring, for light loosening of the diamond core crown	183607R  183603R  183670R220  183604R  180145R  079013  079003  180015	72.76 54.08 99.44 1,909.92 129.75 91.97 18.89 38.35 20.66
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid  Single open ended wrench size 41 for loosening the universal diamond core drilling crowns  Light loosening ring, for light loosening of the diamond core crown  Drilling crown extension 200 mm	183607R  183603R  183670R220  183604R  180145R  079013  079003  180015  180155R	72.76 54.08 99.44 1,909.92 129.75 91.97 18.89 38.35 20.66 61.19
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.  Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers  Titan vacuum fastening, consisting of cover plate with nipple for ¾" screw connection and sealing ring for base plate.  Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 - 60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.  Laser drilling centre pointer  Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm  Carbide masonry drill Ø 8 mm for drilling aid	183607R  183603R  183670R220  183604R  180145R  079013  079003  180015	72.76 54.08 99.44 1,909.92 129.75 91.97 18.89 38.35 20.66

**REMS Pull 2 M,** dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 324



318