

Compact, handy power tool for core drilling, e.g. in concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. With speed regulation. Dry or wet drilling, hand held or with drill stand. For trade and industry.

Concrete, steel-reinforced concrete	≤ Ø 162 (200) mm
Masonry and other materials	≤ Ø 250 mm

REMS Universal diamond core drilling crowns,
also suitable for drive machines of other makes,
see page 312–314.

REMS Picus SR – Core drilling instead of chiselling.
**Easy, fast, vibration-free, e.g. 200 mm in steel-reinforced
concrete Ø 62 mm in only 3 min. With speed regulation.**

1 system – 4 applications.

Ideal for plumbers.

Universal use

Universal drive machine for dry or wet drilling, hand held or with drill stand.
Can be used anywhere, in narrow angles, flush with the wall. Extremely versatile
and efficient, e.g. drilling in steel-reinforced concrete, masonry and other
materials. For pipeline and cable ducting, ventilation channels, test core drilling.

System advantage

Only **one** type of universal diamond core drilling crowns for all REMS Picus
drive machines and other suitable makes of drive machines. Therefore simple,
low cost storage. No confusion possible.

Design

Compact, handy drive machine for vibration-free core drilling, with drilling crown
connecting thread UNC 1 1/4 male, BSPP 1/2 female. Robust, suitable for the building
site. Extra light, only 6.4 kg. Simple, fast work, e.g. 200 mm in steel-reinforced
concrete Ø 62 mm in only 3 min. Practical spade handle and stabiliser for hand
held drilling. Throat Ø 60 mm for holding the drive machine in the drill stand.
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the
REMS Titan drill stand. Water supply for wet drilling, with adjustable shut-off valve
and quick-coupling with water stop and hose connection 1/2".

Drive

Robust, powerful 2200 W universal motor. Overheating protection by temperature
monitoring of the motor's field winding with a PTC resistor (Positive Temperature
Coefficient). Stable, maintenance-free, 2-step gear. Blocking protection by safety
slip clutch. Tip switch with lock. Connecting cable with integrated personal
protection switch (PRCD).

Speed-Regulation

Stepless electronic speed regulation of the drive machine for selecting the speed
according to the material. The speed is steplessly adjustable on the dial: 250 rpm
to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear). The electronic speed
control that is being used keeps the selected speed constant, also under load. The
speed of the drilling crown is kept at the nominal value until it meets with resistance
and drops below a critical value. The drive motor stops. When the load on the drive
unit is relieved again, the drill runs back up to nominal speed so that work can
continue immediately at nominal speed (Patent EP 2 085 191). Advantage: The
optimum drilling speed (load speed) selected for the respective material and the
drilling crown diameter remains constant for the entire duration of the drilling.
For the best drilling performance and maximum life of the drilling crowns.

Multifunction electronics

Multifunction electronics with start-up current limiting for soft starting for delicate
drilling start, automatic idle speed limiting for noise reduction and preservation
of the motor, overload and blocking protection for motor and gear.

Universal diamond core drilling crowns

Universally usable for dry and wet drilling, hand held or with drill stand.
Optionally REMS Universal diamond core drilling crowns, inductively soldered,
resolderable or REMS Universal diamond core drilling crowns LS, laser welded,
high temperature-resistant (page 312–314). Connecting thread UNC 1 1/4 female.
Drilling depth 420 mm. Specially developed, high quality diamond segments with
high diamond percentage and special bonding, for excellent drilling performance
and very long life. Ideal for universal applications in steel-reinforced concrete
and masonry. Adapter for using the REMS Universal diamond core drilling crowns
in drive machines of other makes, as accessory. Light loosening ring, for light
loosening of the diamond core crown, as accessory.

Dust extraction in accordance with EN 60335-2-69

When working with mineral building materials, e.g. concrete, steel-reinforced
concrete, masonry and screed, a high degree of mineral dust containing quartz is
produced which is harmful to the health. Inhalation of quartz fine dust is harmful
to the health. EN 60335-2-69 prescribes the use of at least one safety extractor of
dust class M for the extraction of health hazardous dusts with an exposure limit/
work place limit of > 0.1 mg/m³. Observe the national regulations.

Suction rotor for dust extraction in dry drilling with connection for REMS Pull 2
and other suitable extractors, as accessory (page 311). REMS Pull 2 M, wet and
dry dust extractor, certified for extracting health hazardous dusts of dust class M
(page 324).

Patent EP 2 085 191



German Quality Product



Info

With speed regulation for the best
drilling performance and maximum life
of the drilling crowns.



REMS Simplex 2



REMS Titan

Drilling start aid

Drilling start aid G ½ UDKB, with bores for extracting the drilling dust from the bore hole by a suction rotor for dust extraction, with carbide masonry drill Ø 8 mm, as accessory.

Drill stand

REMS Simplex 2 or REMS Titan drill stands can be used optionally (page 310).

Water extractor unit

Water extractor unit for wet drilling up to Ø 170 mm, consisting of a water collector ring with connection for REMS Pull 2 or other suitable wet extractors, compression ring, rubber washer Ø 200 mm, adaptable to diameter of the drill crown and universal pressure pad for all REMS drill stands, as accessory.



REMS Picus SR Basic-Pack



REMS Picus SR Set Titan



REMS Picus SR Set 62-82-132 Titan

Supply format

REMS Picus SR Basic-Pack. For core drilling in concrete, steel-reinforced concrete ≤ Ø 162 (200) mm, masonry and other materials ≤ Ø 250 mm. For dry or wet drilling, hand held or with drill stand. Drive machine with drilling crown connection thread UNC 1¼ male, G ½ female, maintenance-free 2-step gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 2200 W. Stepless electronic speed regulation 250 rpm to 500 rpm (1st gear) or 600 rpm to 1200 rpm (2nd gear), overheating protection. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Spacer set. Single open ended wrench size 32. In sturdy steel case.

Art.-No.	€
183010R110G	1,712.70

Other voltages on request.

Supply format

REMS Picus SR Set Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete.

Art.-No.	€
183022R220G	3,093.24

Other voltages on request.

Supply format

REMS Picus SR Set 62+82+132 Titan. REMS Picus SR Basic-Pack with REMS Titan drilling stand including fastening kit for masonry and concrete and REMS Universal diamond core drilling crowns UDKB Ø 62+82+132 mm.

Art.-No.	€
183023R220G	3,581.10

Other voltages on request.

Accessories

Description	Art.-No.	€
REMS Picus SR drive unit	183000R220	1,328.64
Spacer set for additional stabilisation of the REMS Picus SR drive unit on the REMS Titan drill stand, consisting of spacer and 2 cylinder head screws M 8×65	183632R	48.58
Steel case with inlay	180600R	128.71
REMS Universal diamond core drilling crowns , inductively soldered, resolderable, see page 312.		
REMS universal diamond core drilling crowns LS , laser welded, high temperature-resistant, see page 314.		
REMS Pull 2 L / M , dry and wet extractors, see page 324		
Additional accessories see page 310–311.		

