REMS Power-Ex-Press P-CEF ACC

Compact, handy power tool for fast, easy expanding of pipes/rings. For trade and industry. For the building site and the workshop.

Cold Expansion Fittings made of plastic (P-CEF)

Ø 16-63 mm Ø $\frac{1}{2}$ -2" s ≤ 6.3 mm

REMS Power-Ex-Press P-CEF ACC – Fast, easy electric expanding up to Ø 63 mm. With automatic return. For Uponor Quick & Easy and Giacomini GX System.

Expander heads

Large expanding capacity up to Ø 63 mm. Automatic, gradual expansion until reaching the given end position which is determined by the expander head. Use of the REMS P-CEF expander heads and suitable expander heads of other makes for: Expander $50-63\,\text{mm}$, 2", for holding the REMS P-CEF expander heads $50-63\,\text{mm}$, 2" and suitable expander heads of other makes. Expander $16-40\,\text{mm}$, $\frac{1}{2}-1\frac{1}{2}$ ", for holding the REMS P-CEF expander heads $16-40\,\text{mm}$, $\frac{1}{2}-1\frac{1}{2}$ " and suitable expander heads of other makes, as an accessory.

Execution

Compact, robust, job site-proven. Small in size, slender design, drive unit only 5.6 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip.

Drive

High pressing force for fast, perfect expanding. Thrust force 34 kN. Powerful electro-mechanical drive with automatic return (ACC), with proven universal motor, 450 W, maintenance-free gear with safety slipping clutch and in-feed system with machine screw spindle. Safety tip switch.



German Quality Product



Supply format

REMS Power-Ex-Press P-CEF ACC Basic-Pack. Electro-hydraulic pipe expander 34 kN for expanding tubes/coils of the Uponor Quick & Easy system Ø 16-63 mm, Ø $\frac{1}{2}-2^n$, s $\leq 6.3 \text{ mm}$. Electro-hydraulic drive with automatic retraction, ith proven universal motor 230 V or 110 V, 50-60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Expanding device 50-63 mm, 2^n Without expander heads. In sturdy steel case

xpanding device 50–63 mm, Z. without expander neads	s. In Sturay	steet case.
	ArtNo.	€
	575017R110G	1,462.54

Note assembly instructions of system supplier. Battery tube expander for other systems on request. Other voltages on request.



Description	ArtNo.	€
Expander 16 – 40 mm, $\frac{1}{2}$ – $\frac{1}{2}$", for holding the P-CEF expander heads $16 - 40$ mm, $\frac{1}{2}$ – $\frac{1}{2}$ "	575100R	122.48
Expander heads P-CEF see page 257.		
Steel case with insert	575278R	110.03





