

for all common pressfitting systems

**Select REMS pressing tongs Mini/
REMS pressing rings yourself!**

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 183) required for driving REMS pressing rings. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

REMS pressing tongs Mini (PZ-2B)

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFlz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

REMS pressing ring S (PR-2B)

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183.

Traceability according to EN 1775:2007

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



Patent EP 1 952 948
Patent EP 2 347 862

German Quality Product



REMS Mini pressing tongs (PZ-2B)



REMS pressing ring S (PR-2B), continuously swivellable


Confirmation of suitability

See page 239.


Hold-Harmless and Indemnification Agreement

See page 240.





Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971



Example REMS pressing tongs Mini V: "V" imprint on pressed fitting for traceability according to EN 1775:2007

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
A				
Aalberts integrated piping systems	U 14		578372	174.38
VSH MultiPress	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
Aalberts integrated piping systems	U 16		578374	165.66
VSH MultiPress Gas	U 20		578378	165.66
	U 25		578380	165.66
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
Aalberts integrated piping systems	V 12		578324	146.98
VSH SudoPress Carbon	V 15		578328	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
Aalberts integrated piping systems	V 12		578324	146.98
VSH SudoPress Copper	V 14		578326	146.98
	VG 14		578338	146.98
	V 15		578328	146.98
	V 16		578330	146.98
	VG 16		578340	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51
	VG 14 S (PR-2B)	Mini Z8	574750 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51
	VG 16 S (PR-2B)	Mini Z8	574754 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
Aalberts integrated piping systems	V 12		578324	146.98
VSH SudoPress Copper	V 14		578326	146.98
Gas	VG 14		578338	146.98
	V 15		578328	146.98
	V 16		578330	146.98
	VG 16		578340	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51
	VG 14 S (PR-2B)	Mini Z8	574750 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51
	VG 16 S (PR-2B)	Mini Z8	574754 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
Aalberts integrated piping systems	V 15		578328	146.98
VSH SudoPress	V 18		578332	146.98
Stainless	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
Aalberts integrated piping systems	M 12		578310	146.98
VSH XPress Carbon	M 15		578312	146.98
	M 18 ¹⁾		578314	146.98
	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Aalberts integrated piping systems	M 12		578310	146.98
VSH XPress Copper	M 15		578312	146.98
	M 18 ¹⁾		578314	146.98
	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Aalberts integrated piping systems	M 15		578312	146.98
VSH XPress Copper	M 18 ¹⁾		578314	146.98
Gas	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Aalberts integrated piping systems	M 15		578312	146.98
VSH XPress Stainless	M 18 ¹⁾		578314	146.98
	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Aalberts integrated piping systems	M 15		578312	146.98
VSH XPress Stainless	M 18 ¹⁾		578314	146.98
Gas	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
AC-FIX PRESS (Global Piping Systems)	H 12		578396	159.75
	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 32		578412	159.75
	RfZ 12		578490	184.45
	RfZ 16		578492	184.45
	RfZ 20		578494	184.45
	RfZ 25		578496	184.45
	RfZ 32		578498	184.45
	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	VX 16		578552	204.17
	VX 20		578554	204.17
AC-FIX PRESS DUO (Global Piping Systems)	RfZ 16		578492	184.45
	RfZ 20		578494	184.45
	RfZ 25		578496	184.45
	RfZ 32		578498	184.45
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 32		578412	159.75
	RfZ 16		578492	184.45
	RfZ 20		578494	184.45
	RfZ 25		578496	184.45
	RfZ 32		578498	184.45
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
ACOME MT	AcZ 12		578608	184.45
	AcZ 16		578610	184.45
	AcZ 20		578612	184.45
	AcZ 25		578614	184.45

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
AHLSSELL A-press elförzinkad M	M 12		578310	146.98	ALB	TH 16		578352 R	177.08	
	M 15		578312	146.98	Sistema Multicapa	TH 18		578356	177.08	
	M 18		578314	146.98	para calefacción y sanitario	TH 20		578358 R	177.08	
	M 22		578316	146.98		TH 26		578362 R	177.08	
	M 28		578318	146.98		TH 32		578364	177.08	
	M 35		578390	178.12		TH 40		578624	234.69	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		H 16		578400	159.75	
AHLSSELL A-press elförzinkad V	V 12		578324	146.98		H 18		578404	159.75	
	V 15		578328	146.98		H 20		578406	159.75	
	V 18		578332	146.98		H 26		578410	159.75	
	V 22		578334	146.98		H 32		578412	159.75	
	V 28		578336	146.98		U 16		578374	165.66	
	V 35		578604	178.12		U 18		578376	165.66	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		U 20		578378	165.66	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		U 26 ⁷⁾		578392	194.31	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		U 32		578382	194.31	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		U 40		578386	236.66	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		ALB	TH 16	578352 R	177.08	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	Sistema Multicapa	TH 20		578358 R	177.08	
AHLSSELL A-press koppar M	M 12		578310	146.98	para gas	TH 26		578362 R	177.08	
	M 15		578312	146.98		TH 32		578364	177.08	
	M 18		578314	146.98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 22		578316	146.98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 28		578318	146.98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 35		578390	178.12		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51		H 16		578400	159.75	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		H 20		578406	159.75	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		H 26		578410	159.75	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		H 32		578412	159.75	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		U 16		578374	165.66	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		U 20		578378	165.66	
AHLSSELL A-press koppar V	V 12		578324	146.98		U 26 ⁷⁾		578392	194.31	
	V 15		578328	146.98		U 32		578382	194.31	
	V 18		578332	146.98		ALTECH Altech	RFz 12	578490	184.45	
	V 22		578334	146.98			RFz 16	578492	184.45	
	V 28		578336	146.98			RFz 20	578494	184.45	
	V 35		578604	178.12			RFz 25	578496	184.45	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		APE MULTYGAS	TH 16	578352 R	177.08	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		Serie AP Gas	TH 20	578358 R	177.08	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51			TH 26	578362 R	177.08	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51			TH 32	578364	177.08	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51			TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96			TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
AHLSSELL A-press rostfritt	M 15		578312	146.98			TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	M 18		578314	146.98			TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	M 22		578316	146.98		APE Serie AP	B 16	578468	193.28	
	M 28		578318	146.98			B 20	578472	193.28	
	M 35		578390	178.12			B 26	578474	213.00	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51			H 16	578400	159.75	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51			H 20	578406	159.75	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51			H 26	578410	159.75	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51			H 32	578412	159.75	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96			TH 16	578352 R	177.08	
AIRBEL PRESSCLIM	M 15		578312	146.98			TH 18	578356	177.08	
	M 18		578314	146.98			TH 20	578358 R	177.08	
	M 22		578316	146.98			TH 26	578362 R	177.08	
	M 28		578318	146.98			TH 32	578364	177.08	
	M 35		578390	178.12			TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51			TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51			TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51			TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51			TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96			U 16	578374	165.66	
AIRBEL SERTINOX	M 15		578312	146.98			U 20	578378	165.66	
	M 18		578314	146.98						
	M 22		578316	146.98						
	M 28		578318	146.98						
	M 35		578390	178.12						
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51						
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51						
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51						
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96						

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
APE Serie APL	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 18		578376	165.66
U 20		578378	165.66	
AQUATECHNIK Press-fitting metal	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 20		578378	165.66
	U 26 ⁷⁾		578392	194.31
	U 32		578382	194.31
	AQUATECHNIK Universal	B 16		578468
B 20			578472	193.28
B 26			578474	213.00
B 32			578476	213.00
F 16			578456	168.68
F 20			578460	168.68
F 26			578462	182.48
F 32			578464	182.48
F 16 S (PR-2B)**		Mini Z8	574728 R	124.51
F 20 S (PR-2B)**		Mini Z8	574730 R	124.51
F 26 S (PR-2B)**		Mini Z8	574732 R	124.51
F 32 S (PR-2B)		Mini Z8	574734 R	136.96
H 16			578400	159.75
H 20			578406	159.75
H 26			578410	159.75
H 32			578412	159.75
TH 16			578352 R	177.08
TH 20			578358 R	177.08
TH 26			578362 R	177.08
TH 32			578364	177.08
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51
TH 26 S (PR-2B)**		Mini Z8	574794 R	124.51
TH 32 S (PR-2B)		Mini Z8	574798 R	136.96
U 16			578374	165.66
U 20			578378	165.66
U 26 ⁷⁾			578392	194.31
U 32		578382	194.31	
ARKA DUROsystem	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 20		578378	165.66
Aschl NIR	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
	ASSOTHERM IPC-RAC Carbon Steel	M 15		578312
M 18			578314	146.98
M 22			578316	146.98
M 28			578318	146.98
M 35			578390	178.12
M 15 S (PR-2B)		Mini Z8	574738 R	124.51
M 18 S (PR-2B)		Mini Z8	574740 R	124.51
M 22 S (PR-2B)		Mini Z8	574742 R	124.51
M 28 S (PR-2B)		Mini Z8	574744 R	124.51
M 35 S (PR-2B)		Mini Z8	574746 R	136.96

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
ASSOTHERM IPI-RAX Inox	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	ASSOTHERM IPI-RAX Inox Gas	M 15		578312	146.98
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
ASSOTHERM IPM-Multistrato		H 16		578400	159.75
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	THL 32		578368	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31		
ASSOTHERM IPR-RAA Copper	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	ASSOTHERM IPR-RAA Copper Gas	M 15		578312	146.98
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)		US 3/8"		578534	201.16
	US 1/2"		578536	201.16	
	US 3/4"		578538	201.16	
	US 1"		578540	201.16	
ATUSA ITALIA INSTALPRESS CARBON STEEL PRESS FITTINGS	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	ATUSA ITALIA INSTALPRESS STAINLESS STEEL PRESS FITTINGS	M 15		578312	146.98
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
AUSTEC PEX-B, PEX-AL-PEX (AUS)		TH 16		578352 R	177.08
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 32		578364	177.08	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	AUSTEC PEX-AL-PEX GAS (AUS)	TH 16		578352 R	177.08
		TH 20		578358 R	177.08
		TH 25		578360	177.08
TH 32			578364	177.08	
U 16			578374	165.66	
U 20			578378	165.66	
U 25			578380	165.66	
U 32			578382	194.31	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AYOR FIXOCONNECT Press	H 12		578396	159.75	Bampi BALPEX Gas	TH 16		578352 R	177.08
	H 16		578400	159.75		TH 20		578358 R	177.08
	H 20		578406	159.75		TH 26		578362 R	177.08
	H 25		578408	159.75		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	RFz 12		578490	184.45		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	RFz 16		578492	184.45		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	RFz 20		578494	184.45		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	RFz 25		578496	184.45		U 16		578374	165.66
	U 16		578374	165.66		U 20		578378	165.66
	U 20		578378	165.66		U 25		578380	165.66
AYOR FIXOMULTIX	H 16		578400	159.75	BARBI EASYPRESS (Industrial Blansol)	H 12		578396	159.75
H 20		578406	159.75	H 16			578400	159.75	
H 26		578410	159.75	H 20			578406	159.75	
H 32		578412	159.75	H 25			578408	159.75	
TH 16		578352 R	177.08	H 32			578412	159.75	
TH 20		578358 R	177.08	RFz 12			578490	184.45	
TH 26		578362 R	177.08	RFz 16			578492	184.45	
TH 32		578364	177.08	RFz 20			578494	184.45	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	RFz 25			578496	184.45	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	RFz 32			578498	184.45	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	U 16		578374	165.66		
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	U 20		578378	165.66		
AYOR SOMATHERM FOR YOU -1	U 16		578374	165.66	U 25		578380	165.66	
H 16		578400	159.75	U 32		578382	194.31		
H 20		578406	159.75	U 40		578386	236.66		
H 26		578410	159.75	BARBI MULTIPEX (Industrial Blansol)	H 14		578398	159.75	
TH 16		578352 R	177.08		H 16		578400	159.75	
TH 20		578358 R	177.08		H 18		578404	159.75	
TH 26		578362 R	177.08		H 20		578406	159.75	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		H 25		578408	159.75	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		H 26		578410	159.75	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		H 32		578412	159.75	
U 16		578374	165.66		RFz 16		578492	184.45	
U 20		578378	165.66		RFz 18		578638	184.45	
AYOR SOMATHERM FOR YOU -2	U 25		578380		165.66	RFz 20		578494	184.45
H 12		578396	159.75	RFz 25		578496	184.45		
H 16		578400	159.75	RFz 32		578498	184.45		
H 20		578406	159.75	TH 16		578352 R	177.08		
H 25		578408	159.75	TH 20		578358 R	177.08		
RFz 12		578490	184.45	TH 26		578362 R	177.08		
RFz 16		578492	184.45	TH 32		578364	177.08		
RFz 20		578494	184.45	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		
RFz 25		578496	184.45	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		
U 16		578374	165.66	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		
U 20		578378	165.66	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		
U 25		578380	165.66	U 16		578374	165.66		
				U 18		578376	165.66		
				U 20		578378	165.66		
				U 25		578380	165.66		
				U 32		578382	194.31		
				U 40		578386	236.66		
B					BEGETUBE/ IVAR	B 14		578466	193.28
Bampi BALPEX serie LP	TH 16		578352 R	177.08	B 16		578468	193.28	
TH 18		578356	177.08	B 18		578470	193.28		
TH 20		578358 R	177.08	B 20		578472	193.28		
TH 26		578362 R	177.08	B 26		578474	213.00		
TH 32		578364	177.08	B 32		578476	213.00		
TH 40		578624	234.69	Béné inox Série 41	M 15		578312	146.98	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		M 18		578314	146.98	
TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51		M 22		578316	146.98	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		M 28		578318	146.98	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		M 35		578390	178.12	
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
U 16		578374	165.66		M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
U 18		578376	165.66		M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
U 20		578378	165.66		M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
U 26 ⁷⁾		578392	194.31		M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
U 32		578382	194.31	Brass Form Master-Al-Pex	H 16		578400	159.75	
Bampi BALPEX serie MP	TH 16		578352 R	177.08	H 18		578404	159.75	
TH 18		578356	177.08	H 20		578406	159.75		
TH 20		578358 R	177.08	TH 16		578352 R	177.08		
TH 26		578362 R	177.08	TH 18		578356 R	177.08		
TH 32		578364	177.08	TH 20		578358 R	177.08		
TH 40		578624	234.69	TH 26		578362 R	177.08		
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	TH 32		578364	177.08		
TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		
				TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		
				U 16		578374	165.66		
				U 18		578376	165.66		
				U 20		578378	165.66		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Brass & Fittings PRESSMAN MultiPress	RFz 16		578492	184.45
	RFz 18		578638	184.45
	ACz 20		578612	184.45
	RFz 25		578496	184.45
	RFz 32		578498	184.45
Brass & Fittings PRESSMAN RetiPress	RFz 16		578492	184.45
	RFz 18		578638	184.45
	ACz 20		578612	184.45
	RFz 25		578496	184.45
	RFz 32		578498	184.45
BRASSTECH MULTItermoSAN	B 16		578468	193.28
	B 20		578472	193.28
Brasspress	B 26		578474	213.00
	B 32		578476	213.00
	F 16		578456	168.68
	F 20		578460	168.68
	F 26		578462	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 26 ⁷⁾		578392	194.31
U 32		578382	194.31	

C

Cello Products -B>Press	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
	VUS 1" (OD 28,6 mm)		578570	177.50	
	VUS 1¼" (OD 34,9 mm)		578606	177.50	
CGR DYNAFLU multicouche	H 16		578400	159.75	
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31		
U 40		578386	236.66		
CGR DYNAFLU PER	H 12		578396	159.75	
	H 16		578400	159.75	
	H 20		578406	159.75	
	H 25		578408	159.75	
	RFz 12		578490	184.45	
	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
	CHIALI CHIALIPEX	TH 16		578352 R	177.08
	TH 20		578358 R	177.08	
TH 26		578362 R	177.08		
TH 32		578364	177.08		
TH 40		578624	234.69		
Climatrix Climatrix Rhinopex	H 16		578400	159.75	
	H 20		578406	159.75	
	U 16		578374	165.66	
	U 20		578378	165.66	
	TH 14		578348	177.08	
	TH 16		578352 R	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Climatrix	TH 11,6		578344	177.08
	Variotherm		578352 R	177.08
System TH	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	ClouSet		578352 R	177.08
Comap PEX Press	TH 16		578356	177.08
	TH 18		578358 R	177.08
	TH 20		574782 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	RFz 12		578490	184.45
	RFz 16		578492	184.45
Comap Multiskin	RFz 20		578494	184.45
	RFz 25		578496	184.45
	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	THL 32		578368	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
Comap Multiskin Gas	U 14		578372	174.38
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 32		578382	194.31
	H 14		578398	159.75
	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
TH 32		578364	177.08	
THL 32		578368	177.08	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
COMISA Press System	U 16		578374	165.66
	U 20		578378	165.66
	U 32		578382	194.31
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
TH 40		578624	234.69	
TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
H 14		578398	159.75	
H 16		578400	159.75	
H 18		578404	159.75	
H 20		578406	159.75	
H 26		578410	159.75	
H 32		578412	159.75	
B 14		578466	193.28	
B 16		578468	193.28	
B 18		578470	193.28	
B 20		578472	193.28	
B 26		578474	213.00	
B 32		578476	213.00	
COMISA Press System Gas	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
CONEL	M 15		578312	146.98	Conex Bänninger >B< Flex	F 16		578456	168.68
CONNECT INOX	M 18		578314	146.98		F 18		578458	168.68
	M 22		578316	146.98		F 20		578460	168.68
	V 15		578328	146.98		F 32		578464	182.48
	V 18		578332	146.98		F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	V 22		578334	146.98		F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
CONEL	F 16		578456	168.68		F 32 S (PR-2B)	Mini Z8	574734 R	136.96
CONNECT	F 20		578460	168.68		H 16		578400	159.75
MULTI	F 26		578462	182.48		H 18		578404	159.75
	F 32		578464	182.48		H 20		578406	159.75
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	H 25		578408	159.75	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	H 32		578412	159.75	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	RFz 16		578492	184.45	
	F 32 S (PR-2B)**	Mini Z8	574734 R	136.96	RFz 18		578638	184.45	
	H 16		578400	159.75	RFz 20		578494	184.45	
	H 20		578406	159.75	RFz 25		578496	184.45	
	H 26		578410	159.75	RFz 32		578498	184.45	
	H 32		578412	159.75	TH 16		578352 R	177.08	
	TH 16		578352 R	177.08	TH 18		578356	177.08	
	TH 20		578358 R	177.08	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	TH 25		578360	177.08	
	TH 32		578364	177.08	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	U 16		578374	165.66	
	U 20		578378	165.66	U 18		578376	165.66	
(DN 26)	U 25		578380	165.66	U 20		578378	165.66	
	U 32		578382	194.31	U 25		578380	165.66	
	VP 16		578482	176.56	U 32		578382	194.31	
	VP 20		578484	176.56	Conex Bänninger >B< Flex Gas	F 16		578456	168.68
	VP 32		578488	195.25	F 18		578458	168.68	
CONEL	F 16		578456	168.68	F 20		578460	168.68	
CONNECT	F 20		578460	168.68	F 32		578464	182.48	
MV2	F 26		578462	182.48	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
	F 32		578464	182.48	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	H 16		578400	159.75	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	H 18		578404	159.75	
	F 32 S (PR-2B)**	Mini Z8	574734 R	136.96	H 20		578406	159.75	
	TH 16		578352 R	177.08	H 25		578408	159.75	
	TH 20		578358 R	177.08	H 32		578412	159.75	
	TH 26		578362 R	177.08	RFz 16		578492	184.45	
	TH 32		578364	177.08	RFz 18		578638	184.45	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	RFz 20		578494	184.45	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	RFz 25		578496	184.45	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	RFz 32		578498	184.45	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	TH 16		578352 R	177.08	
Conex Bänninger <A> Press Inox (304)	M 15		578312	146.98	TH 18		578356	177.08	
	M 18		578314	146.98	TH 20		578358 R	177.08	
	M 22		578316	146.98	TH 25		578360	177.08	
	M 28		578318	146.98	TH 32		578364	177.08	
	M 35		578390	178.12	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	U 16		578374	165.66	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	U 18		578376	165.66	
Conex Bänninger <A> Press Inox (316L)	M 15		578312	146.98	U 20		578378	165.66	
	M 18		578314	146.98	U 25		578380	165.66	
	M 22		578316	146.98	U 32		578382	194.31	
	M 28		578318	146.98	Conex Bänninger >B< MaxiPro	BMP ¼"		578700	175.53
	M 35		578390	178.12	BMP ⅜"		578702	175.53	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	BMP ½"		578704	175.53	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	BMP ⅝"		578706	175.53	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	BMP ¾"		578708	175.53	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	BMP 1"		578710	175.53	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	BMP 1 1/8"		578712	175.53	
								578714	175.53

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Conex Bänninger >B< Press	V 12		578324	146.98	
	V 14		578326	146.98	
	V 15		578328	146.98	
	V 16		578330	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	M 15		578312	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	Conex Bänninger >B< Press Carbon	V 15		578328	146.98
V 18			578332	146.98	
V 22			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)		Mini Z8	574762 R	136.96	
Conex Bänninger >B< Press Gas		V 12		578324	146.98
		V 14		578326	146.98
		V 15		578328	146.98
		V 16		578330	146.98
		V 18		578332	146.98
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
Conex Bänninger >B< Press Inox	V 15		578328	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	Conex Bänninger >B< Press Solar	V 12		578324	146.98
		V 14		578326	146.98
		V 15		578328	146.98
		V 16		578330	146.98
		V 18		578332	146.98
V 22			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 12 S (PR-2B)		Mini Z8	574748 R	124.51	
V 14 S (PR-2B)		Mini Z8	574800 R	124.51	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 16 S (PR-2B)		Mini Z8	574802 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
D					
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310	146.98	
	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	DUOPIPE SYSTEMS	U 16		578374	165.66
	DUOFIL MKSYSTEM	U 18		578376	165.66
		U 20		578378	165.66
	U 25		578380	165.66	
	U 32		578382	194.31	
DW Verbundrohr multitubo systems	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
E				
EBRILLE Isomomflex	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	H 26		578410	159.75
	TH 26		578362 R	177.08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
EBRILLE Monflex	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	H 26		578410	159.75
	TH 26		578362 R	177.08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
EFFEBI	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
EFFEBI-PRESS	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
	V 12		578324	146.98
	V 15		578328	146.98
Aisi316 System M Profile ¹⁾	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
EFFEBI	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
	M 12		578310	146.98
	M 15		578312	146.98
EFFEBI-PRESS Carbon-S	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
System M Profile ¹⁾	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
	V 12		578324	146.98
	V 15		578328	146.98
EFFEBI-PRESS Carbon-S System V Profile	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
EFFEBI	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
	V 12		578324	146.98
	V 14		578326	146.98
EFFEBI-PRESS COPPER	V 15		578328	146.98
	V 16		578330	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
EFFEBI-PRESS UNICO	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
	V 12		578324	146.98
	V 15		578328	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
V 35 S (PR-2B)	Mini Z8	574762 R	136.96	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI	V 12		578324	146.98	EFFEBI	TH 16		578352 R	177.08
EFFEBI-PRESS	V 15		578328	146.98	TOF	TH 18		578356	177.08
UNICO	V 18		578332	146.98	MULTIPINZA	TH 20		578358 R	177.08
(GAS)	V 22		578334	146.98		TH 25		578360	177.08
	V 28		578336	146.98		TH 26		578362 R	177.08
	V 35		578604	178.12		TH 32		578364	177.08
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		TH 40		578624	234.69
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
EFFEBI	M 15		578312	146.98		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
PRESTIGE	M 18		578314	146.98		F 16		578456	168.68
	M 22		578316	146.98		F 18		578458	168.68
	M 28		578318	146.98		F 20		578460	168.68
	M 35		578390	178.12		F 26		578462	182.48
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		F 32		578464	182.48
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		Fz 40		578478	247.15
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	V 15		578328	146.98		F 32 S (PR-2B)	Mini Z8	574734 R	136.96
	V 18		578332	146.98		H 16		578400	159.75
	V 22		578334	146.98		H 18		578404	159.75
	V 28		578336	146.98		H 20		578406	159.75
	V 35		578604	178.12		H 25		578408	159.75
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		H 26		578410	159.75
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		H 32		578412	159.75
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		U 16		578374	165.66
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		U 18		578376	165.66
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		U 20		578378	165.66
EFFEBI	M 15		578312	146.98		U 25		578380	165.66
PRESTIGE 4E05	M 18		578314	146.98		U 26 ¹⁾		578392	194.31
	M 22		578316	146.98		U 32		578382	194.31
	M 28		578318	146.98		U 40		578386	236.66
	M 35		578390	178.12		B 16		578468	193.28
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		B 18		578470	193.28
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		B 20		578472	193.28
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		B 26		578474	213.00
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		B 32		578476	213.00
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	EFIELD	U 16		578374	165.66
EFFEBI	M 15		578312	146.98	MULTILAYER PRESS	U 18		578376	165.66
PRESTIGE-GAS	M 18		578314	146.98	DINGAS	U 20		578378	165.66
	M 22		578316	146.98		U 25		578380	165.66
	M 28		578318	146.98		U 32		578382	194.31
	M 35		578390	178.12	EFIELD	U 16		578374	165.66
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	MULTILAYER PRESS	U 18		578376	165.66
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	WATER	U 20		578378	165.66
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		U 25		578380	165.66
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		U 32		578382	194.31
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	Elkhart	VUS 1/2" (OD 15.9 mm)		578566	177.50
	V 15		578328	146.98	APOLLOXPRESS	VUS 3/4" (OD 22.2 mm)		578568	177.50
	V 18		578332	146.98	Fittings Copper	VUS 1" (OD 28.6 mm)		578570	177.50
	V 22		578334	146.98	and Low-Lead Brass	VUS 1 1/4" (OD 34.9 mm)		578606	177.50
	V 28		578336	146.98	EMMETI	B 16		578468	193.28
	V 35		578604	178.12	GERPEX-	B 20		578472	193.28
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	FIVPRESS	B 26		578474	213.00
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		B 32		578476	213.00
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		F 16		578456	168.68
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		F 20		578460	168.68
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		H 16		578400	159.75
EFFEBI	TH 16		578352 R	177.08		H 20		578406	159.75
TOF-GAS	TH 20		578358 R	177.08		TH 16		578352 R	177.08
MULTIPINZA	TH 26		578362 R	177.08		TH 20		578358 R	177.08
	TH 32		578364	177.08		TH 26		578362 R	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		TH 32		578364	177.08
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		TH 40		578624	234.69
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		U 16		578374	165.66
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		U 20		578378	165.66
	H 16		578400	159.75	EMPUR	TH 14		578348	177.08
	H 20		578406	159.75		TH 15		578350	177.08
	H 26		578410	159.75		TH 16		578352 R	177.08
	H 32		578412	159.75		TH 17		578354	177.08
	U 16		578374	165.66		TH 20		578358 R	177.08
	U 20		578378	165.66		TH 25		578360	177.08
	U 32		578382	194.31		TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
						TH 15 S (PR-2B)**	Mini Z8	574780 R	124.51
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
						TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
						TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Esta Rohr simplesta SH M	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	Esta Rohr simplesta ST M	M 15		578312	146.98
		M 18		578314	146.98
		M 22		578316	146.98
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile ¹⁾		M 12		578310	146.98
		M 15		578312	146.98
		M 18		578314	146.98
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	EUROTUBI EUROPA Inox Pressfitting System M-Profile ¹⁾	M 15		578312	146.98
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
Evans Components		VAU 15 (½") (OD 12,7 mm)		578630	151.86
Presslok		VAU 20 (¾") (OD 19,1 mm)		578632	151.86
		VAU 25 (1") (OD 25,4 mm)		578634	151.86
F					
FAR Rubinetterie PRESSFAR	TH 14		578348	177.08	
	TH 16		578352 R	177.08	
	TH 17		578354	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	H 14		578398	159.75	
	H 16		578400	159.75	
	H 18		578404	159.75	
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	U 14		578372	174.38	
	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
	F.B.Q. BARONIO BQ PRESS SOLAR	V 12		578324	146.98
		V 14		578326	146.98
		V 15		578328	146.98
		V 16		578330	146.98
		V 18		578332	146.98
		V 22		578334	146.98
		V 28		578336	146.98
		V 35		578604	178.12
		V 12 S (PR-2B)	Mini Z8	574748 R	124.51
		V 14 S (PR-2B)	Mini Z8	574800 R	124.51
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 16 S (PR-2B)		Mini Z8	574802 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)		Mini Z8	574762 R	136.96	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
F.B.Q. BARONIO BQ PRESS WATER	V 12		578324	146.98	
	V 14		578326	146.98	
	V 15		578328	146.98	
	V 16		578330	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	F.B.Q. BARONIO BQ PRESS GAS	V 12		578324	146.98
		V 14		578326	146.98
		V 15		578328	146.98
		V 16		578330	146.98
		V 18		578332	146.98
		V 22		578334	146.98
V 28			578336	146.98	
V 35			578604	178.12	
V 12 S (PR-2B)		Mini Z8	574748 R	124.51	
V 14 S (PR-2B)		Mini Z8	574800 R	124.51	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 16 S (PR-2B)		Mini Z8	574802 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
FERCOFLOOR DUO Press FERCO PEX	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
	RFz 32		578498	184.45	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
FERCOFLOOR DUO Press MULTIFER	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
	RFz 32		578498	184.45	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
FERRO systems BRASELLI GPF GAS	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
FERRO systems BRASELLI GPF PPSU Pressfitting PEX y MULTICAPA	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
	FERRO systems BRASELLI GPF PRESS Pressfitting PEX FILINOX Instalpress Steel	RFz 16		578492	184.45
RFz 20			578494	184.45	
RFz 25			578496	184.45	
RFz 32			578498	184.45	
M 15			578312	146.98	
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)	Mini Z8	574746 R	136.96		

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
FILINOX Instalpress Inox	M 15		578312	146.98	FORZA STAINLESS V PRESS (AUS)	V 15		578328	146.98
	M 18		578314	146.98		V 22		578334	146.98
	M 22		578316	146.98		V 28		578336	146.98
	M 28		578318	146.98		V 35		578604	178.12
	M 35		578390	178.12		V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		V 35 S (PR-2B)	Mini Z8	574762 R	136.96
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		FRABO FRABOPRESS 316 GAS M	M 15		578312
M 35 S (PR-2B)	Mini Z8	574746 R	136.96	M 18			578314	146.98	
				M 22			578316	146.98	
				M 28			578318	146.98	
				M 35			578390	178.12	
				M 15 S (PR-2B)	Mini Z8		574738 R	124.51	
				M 18 S (PR-2B)	Mini Z8		574740 R	124.51	
				M 22 S (PR-2B)	Mini Z8		574742 R	124.51	
				M 28 S (PR-2B)	Mini Z8		574744 R	124.51	
				M 35 S (PR-2B)	Mini Z8	574746 R	136.96		
FITTINGS ESTÁNDAR ECO-PRESS	RFz 16		578492	184.45	FRABO FRABOPRESS 316 GAS V	V 15		578328	146.98
	RFz 20		578494	184.45		V 18		578332	146.98
	RFz 25		578496	184.45		V 22		578334	146.98
	RFz 32		578498	184.45		V 28		578336	146.98
						V 35		578604	178.12
FITTINGS ESTÁNDAR MULTICAPA	RFz 16		578492	184.45	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	RFz 18		578638	184.45	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	RFz 20		578494	184.45	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	RFz 25		578496	184.45	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	RFz 32		578498	184.45	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
FITTINGS ESTÁNDAR PE-X	RFz 16		578492	184.45	FRABO FRABOPRESS 316 M	M 15		578312	146.98
	RFz 20		578494	184.45		M 18		578314	146.98
	RFz 25		578496	184.45		M 22		578316	146.98
	RFz 32		578498	184.45		M 28		578318	146.98
FORNARA ForPress	B 16		578468	193.28	M 35		578390	178.12	
	B 20		578472	193.28	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	B 26		578474	213.00	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	B 32		578476	213.00	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	F 16		578456	168.68	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	F 20		578460	168.68	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	F 26		578462	182.48	FRABO FRABOPRESS 316 V	V 12		578324	146.98
	F 32		578464	182.48		V 15		578328	146.98
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51		V 18		578332	146.98
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51		V 22		578334	146.98
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51		V 28		578336	146.98
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96		V 35		578604	178.12
	H 16		578400	159.75		V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	H 20		578406	159.75		V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	H 26		578410	159.75		V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	H 32		578412	159.75		V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	TH 16		578352 R	177.08		V 28 S (PR-2B)	Mini Z8	574760 R	124.51
TH 20		578358 R	177.08	V 35 S (PR-2B)		Mini Z8	574762 R	136.96	
TH 26		578362 R	177.08	FRABO FRABOPRESS CHROME		V 12		578324	146.98
TH 32		578364	177.08			V 15		578328	146.98
TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51			V 18		578332	146.98
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51			V 22		578334	146.98
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51			V 28		578336	146.98
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	V 35		578604	178.12		
U 16		578374	165.66	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		
U 20		578378	165.66	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		
U 26 ⁷⁾		578392	194.31	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		
U 32		578382	194.31	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
FORZA WATER CRIMP (AUS)	K16/P18		578592	184.45	FRABO FRABOPRESS C-STEEL M	M 15		578312	146.98
	K/20		578594	184.45		M 18		578314	146.98
	K/25		578596	184.45		M 22		578316	146.98
	K32		578598	184.45		M 28		578318	146.98
FORZA STAINLESS WATER CRIMP	K1/40		578600	184.45	M 35		578390	178.12	
	K16/P18		578592	184.45	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	K/20		578594	184.45	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
					M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
FORZA STRESSO PEX WATER AND GAS CRIMP AUS)	U 16		578374	165.66	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	U 20		578378	165.66	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	U 25		578380	165.66	FRABO FRABOPRESS C-STEEL V	V 12		578324	146.98
	U 32		578382	194.31		V 15		578328	146.98
U 40		578386	236.66	V 18			578332	146.98	
				V 22			578334	146.98	
				V 28			578336	146.98	
FORZA GAS CRIMP (AUS)	K16/P18		578592	184.45	V 35		578604	178.12	
	K/20		578594	184.45	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	K/25		578596	184.45	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	K32		578598	184.45	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
FORZA COPPER V PRESS (AUS)	K1/40		578600	184.45	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	VAU 15 (OD 12,7 mm)		578630	151.86	FORZA COPPER V PRESS (AUS)	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	VAU 20 (OD 19,1 mm)		578632	151.86		V 35 S (PR-2B)	Mini Z8	574762 R	136.96
	VAU 25 (OD 25,4 mm)		578634	151.86					
	VAU 32 (OD 31,8 mm)		578636	159.75					
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124.51					
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124.51					
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136.96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
FRABO	M 12		578310	146.98
FRABOPRESS	M 15		578312	146.98
GAS M	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
FRABO	V 12		578324	146.98
FRABOPRESS	V 15		578328	146.98
GAS V	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
FRABO	V 12		578324	146.98
FRABOPRESS	V 15		578328	146.98
KOMBI	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
FRABO	M 12		578310	146.98
FRABOPRESS M	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
FRABO	V 15		578328	146.98
FRABOPRESS	V 18		578332	146.98
SOLAR	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
FRABO	V 12		578324	146.98
FRABOPRESS V	V 15		578328	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96
Fränkische alpex-duo XS	F 16		578456	168.68
	F 20		578460	168.68
	F 26		578462	182.48
	F 32		578464	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	F 32 S (PR-2B)**	Mini Z8	574734 R	136.96
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Fränkische	F 16		578456	168.68
alpex F50 PROFIL	F 20		578460	168.68
	F 26		578462	182.48
	F 32		578464	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	F 32 S (PR-2B)**	Mini Z8	574734 R	136.96
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 20		578378	165.66
(DN 26)	U 25		578380	165.66
	U 32		578382	194.31
	VP 16		578482	176.56
	VP 20		578484	176.56
	VP 32		578488	195.25
Fränkische alpex L	Fz 40		578478	247.15
G				
gabotherm H+S	TH 10		578342	177.08
	TH 12		578346	177.08
	TH 14		578348	177.08
	TH 15		578350	177.08
	TH 16		578352 R	177.08
	TH 17		578354	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124.51
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124.51
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 15 S (PR-2B)**	Mini Z8	574780 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
Gallagher USA	H 12 (3/4")		578396	159.75
YogaPipe ACR	U 14 (3/8")		578372	174.38
	U 16 (1/2")		578374	165.66
	U 18 (5/8")		578376	165.66
	U 20 (3/4")		578378	165.66
	U 25 (7/8")		578380	165.66
	U 32 (1 1/8")		578382	194.31
Geberit Mapress C-STAHL	M 12		578310	146.98
	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Geberit Mapress C-STAHL Sprinkler nass	M 22		578316	146.98
	M 28		578318	146.98
Geberit Mapress Edelstahl	M 12		578310	146.98
	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Geberit Mapress Edelstahl Gas	M 15		578312	146.98	General Fittings Serie 5S00	B 16		578468	193.28
	M 18		578314	146.98		B 18		578470	193.28
	M 22		578316	146.98		B 20		578472	193.28
	M 28		578318	146.98		B 26		578474	213.00
	M 35		578390	178.12		B 32		578476	213.00
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		F 16		578456	168.68
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		F 20		578460	168.68
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		F 26		578462	182.48
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		F 32		578464	182.48
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
Geberit Mapress Edelstahl Sprinkler	M 22		578316	146.98	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	M 28		578318	146.98	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
Geberit Mapress Kupfer	M 12		578310	146.98	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	M 15		578312	146.98	H 16		578400	159.75	
	M 18		578314	146.98	H 18		578404	159.75	
	M 22		578316	146.98	H 20		578406	159.75	
	M 28		578318	146.98	H 25		578408	159.75	
	M 35		578390	178.12	H 26		578410	159.75	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	H 32		578412	159.75	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 16		578352 R	177.08	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	TH 18		578356	177.08	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	TH 20		578358 R	177.08	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	TH 25		578360	177.08	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	TH 26		578362 R	177.08	
	Geberit Mapress Kupfer Gas	M 15		578312	146.98	TH 32		578364	177.08
		M 18		578314	146.98	TH 40		578624	234.69
		M 22		578316	146.98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
M 28			578318	146.98	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
M 35			578390	178.12	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	U 16		578374	165.66	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	U 18		578376	165.66	
Geberit Mepla	G 16		578444	177.50	U 20		578378	165.66	
	G 20		578446	177.50	U 25		578380	165.66	
	G 26		578448	188.40	U 32		578382	194.31	
	G 32		578450	201.16	U 40		578386	236.66	
	G 40		578452	260.33	General Fittings Trident	H 16		578400	159.75
Geberit Mepla Therm	G 16		578444	177.50		H 20		578406	159.75
	G 20		578446	177.50		H 26		578410	159.75
	G 26		578448	188.40		H 32		578412	159.75
Geberit Volex	TH 16		578352 R	177.08		TH 16		578352 R	177.08
	TH 20		578358 R	177.08		TH 20		578358 R	177.08
	TH 26		578362 R	177.08		TH 26		578362 R	177.08
General Fittings ST00	H 16		578400	159.75		TH 32		578364	177.08
	H 20		578406	159.75		TH 40		578624	234.69
	H 26		578410	159.75		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	H 32		578412	159.75	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 16		578352 R	177.08	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 20		578358 R	177.08	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	TH 26		578362 R	177.08	U 16		578374	165.66	
	TH 32		578364	177.08	U 20		578378	165.66	
	TH 40		578624	234.69	U 32		578380	165.66	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	U 40		578386	236.66	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	General Fittings Trident Gas	H 16		578400	159.75
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		H 20		578406	159.75
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		H 26		578410	159.75
	U 16		578374	165.66		TH 16		578352 R	177.08
	U 20		578378	165.66		TH 20		578358 R	177.08
U 32		578380	194.31	TH 26			578362 R	177.08	
U 40		578386	236.66	TH 32			578364	177.08	
General Fittings Ewoprex	H 16		578400	159.75		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	H 20		578406	159.75		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	H 26		578410	159.75		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	H 32		578412	159.75	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	TH 16		578352 R	177.08	U 16		578374	165.66	
	TH 20		578358 R	177.08	U 20		578378	165.66	
	TH 26		578362 R	177.08	U 32		578380	165.66	
	TH 32		578364	177.08	U 40		578386	236.66	
	TH 40		578624	234.69	Giacomini Raccordi RM Giacomini	H 16		578400	159.75
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		H 20		578406	159.75
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		H 26		578410	159.75
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		H 32		578412	159.75
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		TH 16		578352 R	177.08
	U 16		578374	165.66		TH 20		578358 R	177.08
	U 20		578378	165.66		TH 26		578362 R	177.08
U 32		578380	194.31	TH 32			578364	177.08	
U 40		578386	236.66	TH 40			578624	234.69	
				U 16			578374	165.66	
				U 20		578378	165.66		
				U 32		578380	165.66		
				U 40		578386	236.66		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Giacomini RM MULTIGAS	H 16		578400	159.75	
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 32		578382	194.31	
	Giacomini Valvole Giacomini serie R850V	V 15		578328	146.98
		V 18		578332	146.98
V 22			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)		Mini Z8	574762 R	136.96	
SA 15			578514	176.56	
SA 18			578518	176.56	
SA 22			578520	176.56	
SA 28			578522	176.56	
M 15			578312	146.98	
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)	Mini Z8	574740 R	124.51		
M 22 S (PR-2B)	Mini Z8	574742 R	124.51		
M 28 S (PR-2B)	Mini Z8	574744 R	124.51		
M 35 S (PR-2B)	Mini Z8	574746 R	136.96		
Golan Pipe Systems (Scandinavia)	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
Alu-Press	U 40		578386	236.66	
Grinnell G-PRESS Copper Fittings	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
	VUS 1" (OD 28,6 mm)		578570	177.50	
	VUS 1½" (OD 34,9 mm)		578606	177.50	
GS Wärmesysteme System TH	TH 14		578348	177.08	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
GS Wärmesysteme System V	V 15		578328	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
H					
HASTINIK Hastinik/Hitpress	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
heima24	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
U 20		578378	165.66		
U 32		578382	194.31		
HELIROMA Klimapress	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
HELIROMA Klimapress PPSU	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
Henco	TH 14		578348	177.08	
	TH 16		578352 R	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	HE 32		578370 R	212.06	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Herotec tempusPRESS PLUS	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 32		578412	159.75
	RfZ 16		578492	184.45
	RfZ 20		578494	184.45
	RfZ 25		578496	184.45
	RfZ 32		578498	184.45
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
U 16		578374	165.66	
U 20		578378	165.66	
U 25		578380	165.66	
U 32		578382	194.31	
U 40		578386	236.66	
Herotec tempusPRESS PLUS PPSU	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
U 16		578374	165.66	
U 20		578378	165.66	
U 25		578380	165.66	
U 32		578382	194.31	
U 40		578386	236.66	
HERZ PIPEFIX	TH 10		578342	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
HIDRONIX MULTIGAS	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
HIDRONIX MULTIPIPE	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	H 14		578398	159.75
H 16		578400	159.75	
H 18		578404	159.75	
H 20		578406	159.75	
H 26		578410	159.75	
H 32		578412	159.75	
U 14		578372	174.38	
U 16		578374	165.66	
U 18		578376	165.66	
U 20		578378	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
HIDRONIX UNICO	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	H 14		578398	159.75
	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
H 32		578412	159.75	
U 14		578372	174.38	
U 16		578374	165.66	
U 18		578376	165.66	
U 20		578378	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
HITEC Sistema Multistrato	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
HITHERM-ISOTUBI NUMEPRESS	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
M 35 S (PR-2B)	Mini Z8	574746 R	136.96	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
HITHERM-ISOTUBI HTpress	M 15		578312	146.98	ICMA Sempigas	TH 16		578352 R	177.08
	M 18		578314	146.98		TH 20		578358 R	177.08
	M 22		578316	146.98		TH 25		578360	177.08
	M 28		578318	146.98		TH 26		578362 R	177.08
	M 35		578390	178.12		TH 32		578364	177.08
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		IDrosanitaria Bonomi Homegas	TH 16		578352 R
HITHERM-ISOTUBI HTfire	M 15		578312	146.98	TH 20			578358 R	177.08
	M 18		578314	146.98	TH 26			578362 R	177.08
	M 22		578316	146.98	TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51
	M 28		578318	146.98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 35		578390	178.12	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	IDrosanitaria Bonomi Idropress	TH 16		578352 R	177.08
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		TH 18		578356	177.08
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		TH 20		578358 R	177.08
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		TH 26		578362 R	177.08
HITHERM-ISOTUBI HTair	M 15		578312	146.98	TH 32		578364	177.08	
	M 18		578314	146.98	TH 40		578624	234.69	
	M 22		578316	146.98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 28		578318	146.98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 35		578390	178.12	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	IDROSISTEMI Ta-Press	TH 16		578352 R	177.08
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		TH 20		578358 R	177.08
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		TH 26		578362 R	177.08
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		TH 32		578364	177.08
Hopewell press fit system	M 15		578312	146.98		TH 40		578624	234.69
	M 18		578314	146.98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	M 22		578316	146.98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	M 28		578318	146.98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	M 35		578390	178.12		F 16		578456	168.68
hp praski BAVARIA-press	TH 10		578342	177.08		F 20		578460	168.68
	TH 12		578346	177.08	F 26		578462	182.48	
	TH 14		578348	177.08	F 32		578464	182.48	
	TH 16		578352 R	177.08	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
	TH 17		578354	177.08	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	TH 20		578358 R	177.08	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
	TH 25		578360	177.08	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	TH 26		578362 R	177.08	Fz 40		578478	247.15	
	TH 32		578364	177.08	H 16		578400	159.75	
	TH 40		578624	234.69	H 20		578406	159.75	
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124.51	H 26		578410	159.75	
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124.51	H 32		578412	159.75	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	U 16		578374	165.66	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	U 20		578378	165.66	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51	U 26 ⁷⁾		578392	194.31	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	U 32		578382	194.31	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	U 40		578386	236.66	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	B 16		578468	193.28	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	B 20		578472	193.28	
					B 26		578474	213.00	
				B 32		578476	213.00		
ICMA Sempiter	H 16		578400	159.75	IDROTRADE Storm Multipinza	H 16		578400	159.75
	H 20		578406	159.75		H 20		578406	159.75
	H 25		578408	159.75		H 26		578410	159.75
	H 26		578410	159.75		H 32		578412	159.75
	H 32		578412	159.75		TH 16		578352 R	177.08
	TH 16		578352 R	177.08		TH 20		578358 R	177.08
	TH 20		578358 R	177.08		TH 26		578362 R	177.08
	TH 25		578360	177.08		TH 32		578364	177.08
	TH 26		578362 R	177.08		THL 32		578368	177.08
	TH 32		578364	177.08		TH 40		578624	234.69
	TH 40		578624	234.69	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	U 16		578374	165.66	
	U 16		578374	165.66	U 20		578378	165.66	
	U 20		578378	165.66	IDROTRADE StormPRES ¹⁾	M 15		578312	146.98
	U 25		578380	165.66		M 18		578314	146.98
	U 26 ⁷⁾		578392	194.31		M 22		578316	146.98
	U 32		578382	194.31		M 28		578318	146.98
U 40		578386	236.66	M 35			578390	178.12	
				M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
				M 18 S (PR-2B)	Mini Z8	574740 R	124.51		
				M 22 S (PR-2B)	Mini Z8	574742 R	124.51		
				M 28 S (PR-2B)	Mini Z8	574744 R	124.51		
				M 35 S (PR-2B)	Mini Z8	574746 R	136.96		

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
IDROTRADE StormSTEEL ¹⁾	M 12		578310	146.98	
	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	ILTA INOX/CHIBRO Pressfitting Cuni	M 15		578312	146.98
M 18			578314	146.98	
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
ILTA INOX/CHIBRO Pressfitting inox		M 15		578312	146.98
		M 18		578314	146.98
		M 22		578316	146.98
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	Instantor Press System	TH 16		578352 R	177.08
		TH 20		578358 R	177.08
		TH 26		578362 R	177.08
TH 32			578364	177.08	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124.51	
Instantor Copper Press Imperial	VI 1/2" (OD 14,7 mm)		578716	175.53	
	VI 3/4" (OD 21,0 mm)		578718	175.53	
	VI 1" (OD 27,4 mm)		578720	175.53	
	VI 1/2" S (PR-2B)	Mini Z8	574850 R	124.51	
	VI 3/4" S (PR-2B)	Mini Z8	574852 R	124.51	
	VI 1" S (PR-2B)	Mini Z8	574854 R	124.51	
Instantor Copper Press Metric	M 15		578312	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
IPA IPANA Press	TH 10		578342	177.08	
	TH 11,6		578344	177.08	
	TH 12		578346	177.08	
	TH 14		578348	177.08	
	TH 15		578350	177.08	
	TH 16		578352 R	177.08	
	TH 17		578354	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 22		578588	177.08	
	TH 25		578360	177.08	
	TH 26		578362 R	177.08	
	TH 28		578590	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124.51	
	TH 11,6 S (PR-2B)**	Mini Z8	574774 R	124.51	
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124.51	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	
	TH 15 S (PR-2B)**	Mini Z8	574780 R	124.51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 22 S (PR-2B)**	Mini Z8	574790 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 28 S (PR-2B)**	Mini Z8	574796 R	136.96	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96	
	IPA Thu IPANA Press	TH 16		578352 R	177.08
		TH 20		578358 R	177.08
		TH 26		578362 R	177.08
		TH 32		578364	177.08
TH 40			578624	234.69	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)**		Mini Z8	574798 R	136.96	
IPALPEX (Industrie du Plastique et Accessoires)		TH 14		578348	177.08
		TH 16		578352 R	177.08
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	THL 32		578368	177.08	
	TH 40		578624	234.69	
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	K16/P18		578592	184.45	
	IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18		578592	184.45
		K/20		578594	184.45
		K/25		578596	184.45
		K32		578598	184.45
		K1/40		578600	184.45

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18		578592	184.45
	K/20		578594	184.45
	K/25		578596	184.45
ISOTUBI NUMEPRESS	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
IVAR ALPEX-GAS	B 20		578472	193.28
	B 26		578474	213.00
	B 32		578476	213.00
IVAR Ivar-Press	B 14		578466	193.28
	B 16		578468	193.28
	B 18		578470	193.28
	B 20		578472	193.28
	B 26		578474	213.00
	B 32		578476	213.00
IVAR MULTI PRESS GAS ITALIA	Fz 40		578478	247.15
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	U 16		578374	165.66
	U 20		578378	165.66
	IVAR Multi Press MP	TH 16		578352 R
TH 18			578356	177.08
TH 20			578358 R	177.08
TH 25			578360	177.08
TH 26			578362 R	177.08
TH 32			578364	177.08
TH 40			578624	234.69
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51
TH 18 S (PR-2B)**		Mini Z8	574786 R	124.51
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51
TH 25 S (PR-2B)**		Mini Z8	574792 R	124.51
TH 26 S (PR-2B)**		Mini Z8	574794 R	124.51
TH 32 S (PR-2B)		Mini Z8	574798 R	136.96
F 16			578456	168.68
F 18			578458	168.68
F 20			578460	168.68
F 26		578462	182.48	
F 32		578464	182.48	
Fz 40		578478	247.15	
F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
H 16		578400	159.75	
H 18		578404	159.75	
H 20		578406	159.75	
H 25		578408	159.75	
H 26		578410	159.75	
H 32		578412	159.75	
U 16		578374	165.66	
U 18		578376	165.66	
U 20		578378	165.66	
U 25		578380	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
U 40		578386	236.66	
B 16		578468	193.28	
B 18		578470	193.28	
B 20		578472	193.28	
B 26		578474	213.00	
B 32		578476	213.00	
IVAR Multi Press Leak (MPL)	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	F 16		578456	168.68
	F 20		578460	168.68
	F 26		578462	182.48
	F 32		578464	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
H 16		578400	159.75	
H 20		578406	159.75	
H 26		578410	159.75	
H 32		578412	159.75	
U 16		578374	165.66	
U 20		578378	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
B 16		578468	193.28	
B 20		578470	193.28	
B 26		578474	213.00	
B 32		578476	213.00	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
IVAR Plastic Multi Press PMP	TH 16		578352 R	177.08	J	Jäger - Aquatec	H 14	578398	159.75		
	TH 20		578358 R	177.08		Aquapress H	H 16	578400	159.75		
	TH 25		578360	177.08			H 17	578402	159.75		
	TH 26		578362 R	177.08			H 18	578404	159.75		
	TH 32		578364	177.08			H 20	578406	159.75		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51			H 26	578410	159.75		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51			H 32	578412	159.75		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51			U 40	578386	236.66		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51			Jäger - Aquatec	M 15	578312	146.98	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96			C-Stahl	M 18	578314	146.98	
	F 16		578456	168.68			Press Typ M	M 22	578316	146.98	
	F 20		578460	168.68				M 28	578318	146.98	
	F 26		578462	182.48				M 35	578390	178.12	
	F 32		578464	182.48				M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51				M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51				M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51				M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96				M 35 S (PR-2B)	Mini Z8	574746 R	136.96
	H 16		578400	159.75			Jäger - Aquatec	M 15	578312	146.98	
	H 20		578406	159.75			Edelstahl	M 18	578314	146.98	
	H 25		578408	159.75			Press Typ M	M 22	578316	146.98	
	H 26		578410	159.75				M 28	578318	146.98	
	H 32		578412	159.75				M 35	578390	178.12	
	U 16		578374	165.66				M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	U 20		578378	165.66				M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	U 25		578380	165.66				M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	U 26 ⁷⁾		578392	194.31				M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	U 32		578382	194.31				M 35 S (PR-2B)	Mini Z8	574746 R	136.96
	B 16		578468	193.28			Jäger - Aquatec	V 15	578328	146.98	
	B 20		578472	193.28			Kupfer	V 18	578332	146.98	
	B 26		578474	213.00			Press Typ V	V 22	578334	146.98	
	B 32		578476	213.00				V 28	578336	146.98	
	IVAR Plastic Multi Press Leak (PMPL)	TH 16		578352 R		177.08		V 35	578604	178.12	
		TH 20		578358 R		177.08		V 15 S (PR-2B)	Mini Z8	574752 R	124.51
		TH 26		578362 R		177.08		V 18 S (PR-2B)	Mini Z8	574756 R	124.51
		TH 32		578364		177.08		V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	Jansen AG	TH 14	578348	177.08			
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	JANSEN COMISA	TH 16	578352 R	177.08			
	F 16		578456	168.68		TH 20	578358 R	177.08			
	F 20		578460	168.68		TH 26	578362 R	177.08			
	F 26		578462	182.48		TH 32	578364	177.08			
	F 32		578464	182.48		TH 40	578624	234.69			
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51		TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51		
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		
	H 16		578400	159.75		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		
	H 20		578406	159.75	Jaraflex-	TH 14	578348	177.08			
	H 26		578410	159.75	Presssystem	TH 16	578352 R	177.08			
	H 32		578412	159.75		TH 17	578354	177.08			
	U 16		578374	165.66		TH 18	578356	177.08			
	U 20		578378	165.66		TH 20	578358 R	177.08			
	U 26 ⁷⁾		578392	194.31		TH 25	578360	177.08			
	U 32		578382	194.31		TH 26	578362 R	177.08			
	B 16		578468	193.28		TH 32	578364	177.08			
	B 20		578472	193.28		TH 40	578624	234.69			
	B 26		578474	213.00		TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51		
	B 32		578476	213.00		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		
IVT Edelstahl- Presssystem	M 15		578312	146.98		TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51		
	M 18		578314	146.98		TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51		
	M 22		578316	146.98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		
	M 28		578318	146.98		TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51		
	M 35		578390	178.12		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	JUNGWOO	VUS ½" (OD 15,9 mm)	578566	177.50			
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	JWPress	VUS ¾" (OD 22,2 mm)	578568	177.50			
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		VUS 1" (OD 28,6 mm)	578570	177.50			
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96		VUS 1¼" (OD 34,9 mm)	578606	177.50			
IVT PRIPRESS	TH 16		578352 R	177.08							
	TH 20		578358 R	177.08							
	TH 26		578362 R	177.08							
	TH 32		578364	177.08							
	TH 40		578624	234.69							
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51							
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51							
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51							
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96							

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
K				
KAN	TH 14		578348	177.08
KAN-therm Press LBP	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
	U 14		578372	174.38
	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 26 ⁷⁾		578392	194.31
	U 32		578382	194.31
	U 40		578386	236.66
KAN	M 15		578312	146.98
KAN-therm Inox	M 18 ¹⁾		578314	146.98
	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KAN	M 12		578310	146.98
KAN-therm Steel	M 15		578312	146.98
	M 18 ¹⁾		578314	146.98
	M 22		578316	146.98
	M 28 ¹⁾		578318	146.98
	M 35		578390	178.12
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KAN	TH 14		578348	177.08
KAN-therm UltraPRESS	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
	U 14		578372	174.38
	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 26 ⁷⁾		578392	194.31
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	M 15		578312	146.98
COPPERFIX	M 18		578314	146.98
Kupfer	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KE KELIT	U 16		578374	165.66
KELIT KELOX	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	U 16		578374	165.66
KELOX-PPSU-W	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	U 16		578374	165.66
KELOX-ULTRAX	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	U 16		578374	165.66
KELOX-ULTRAX-W	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	U 16		578374	165.66
KELOX-WINDOW-U	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
KE KELIT	U 16		578374	165.66
KELOX-WINDOW-W	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
KE KELIT	M 15		578312	146.98
steelFIX	M 18		578314	146.98
C-Stahl	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KE KELIT	M 15		578312	146.98
steelFIX	M 18		578314	146.98
Edelstahl	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KEMBLA	VAU 15 (OD 12,7 mm)		578630	151.86
KemPress	VAU 20 (OD 19,1 mm)		578632	151.86
(AUS)	VAU 25 (OD 25,4 mm)		578634	151.86
	VAU 32 (OD 31,8 mm)		578636	159.75
KEMBLA	VAU 15 (OD 12,7 mm)		578630	151.86
KemPress Gas	VAU 20 (OD 19,1 mm)		578632	151.86
(AUS)	VAU 25 (OD 25,4 mm)		578634	151.86
	VAU 32 (OD 31,8 mm)		578636	159.75
KISAN	KI 16		578524	187.36
Kisan KD	KI 20		578526	187.36
	KI 25		578528	187.36
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
KISAN	KI 16		578524	187.36
Kisan WL	KI 20		578526	187.36
	KI 25		578528	187.36
	KI 32		578530	252.44
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
KISAN	KI 16		578524	187.36
Kisan WM	KI 20		578526	187.36
	KI 25		578528	187.36
	KI 32		578530	252.44
KISAN	U 20		578378	165.66
Kisan WR	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
KISAN	M 15		578312	146.98
Kistal C	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
KISAN	M 15		578312	146.98
Kistal Inox	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
L				
LEGEND-PRESS	VUS ½" (OD 15,9 mm)		578566	177.50
press fitting	VUS ¾" (OD 22,2 mm)		578568	177.50
system	VUS 1" (OD 28,6 mm)		578570	177.50
	VUS 1¼" (OD 34,9 mm)		578606	177.50
LK Systems	V 12		578324	146.98
LK >B-Press	V 15		578328	146.98
	V 18		578332	146.98
	V 22		578334	146.98
	V 28		578336	146.98
	V 35		578604	178.12
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
LK Systems	V 12		578324	146.98	Meier Tobler	H 16		578400	159.75
LK >B-Press	V 15		578328	146.98	Metalplast - Stramax	H 20		578406	159.75
Elförzinkat	V 18		578332	146.98	Serie MM	H 25		578408	159.75
	V 22		578334	146.98		H 32		578412	159.75
	V 28		578336	146.98		RFz 16		578492	184.45
	V 35		578604	178.12		RFz 20		578494	184.45
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		RFz 25		578496	184.45
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		RFz 32		578498	184.45
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		TH 16		578352 R	177.08
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		TH 20		578358 R	177.08
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		TH 25		578360	177.08
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		TH 32		578364	177.08
LK Systems	V 15		578328	146.98		TH 40		578624	234.69
LK >B-Press	V 18		578332	146.98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
Gas	V 22		578334	146.98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	V 28		578336	146.98		TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	V 35		578604	178.12		TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		U 16		578374	165.66
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		U 20		578378	165.66
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		U 25		578380	165.66
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		U 32		578382	194.31
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		U 40		578386	236.66
LK Systems	TH 16		578352 R	177.08	METALGRUP	U 16		578374	165.66
LK Universal	TH 20		578358 R	177.08	Permatubo	U 18		578376	165.66
	TH 25		578360	177.08		U 20		578378	165.66
	TH 32		578364	177.08		U 25		578380	165.66
	TH 40		578624	234.69		U 32		578382	194.31
						U 40		578386	236.66
					METALGRUP	RFz 16		578492	184.45
					PexGrup	RFz 20		578494	184.45
						RFz 25		578496	184.45
						RFz 32		578498	184.45
					METALGRUP	U 16		578374	165.66
					MultiGrup	U 18		578376	165.66
						U 20		578378	165.66
						U 25		578380	165.66
						U 32		578382	194.31
					Mueller Streamline	VUS ½" (OD 15,9 mm)		578566	177.50
					PRS Copper Press	VUS ¾" (OD 22,2 mm)		578568	177.50
						VUS 1" (OD 28,6 mm)		578570	177.50
						VUS 1¼" (OD 34,9 mm)		578606	177.50
					MULTITHERM	TH 16		578352 R	177.08
					PRESSSYSTEM	TH 20		578358 R	177.08
						TH 26		578362 R	177.08
						TH 32		578364	177.08
						TH 40		578624	234.69
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
						TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
						TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
					Multicapas Industrial	RFz 16		578492	184.45
					AIS PEX	RFz 20		578494	184.45
						RFz 25		578496	184.45
						RFz 32		578498	184.45
						U 16		578374	165.66
						U 20		578378	165.66
						U 25		578380	165.66
						U 32		578382	194.31
					Multicapas Industrial	H 16		578400	159.75
					AIS XPRT	H 20		578406	159.75
						H 25		578408	159.75
						H 32		578412	159.75
						RFz 16		578492	184.45
						RFz 20		578494	184.45
						RFz 25		578496	184.45
						RFz 32		578498	184.45
						TH 16		578352 R	177.08
						TH 20		578358 R	177.08
						TH 25		578360	177.08
						TH 32		578364	177.08
						TH 40		578624	234.69
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
						TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
						TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
						TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
						H 14		578398	159.75
						H 16		578400	159.75
						H 18		578404	159.75
						H 20		578406	159.75
						H 26		578410	159.75
						H 32		578412	159.75
						U 14		578372	174.38
						U 16		578374	165.66
						U 18		578376	165.66
						U 20		578378	165.66
						U 25		578380	165.66
						U 32		578382	194.31
						U 40		578386	236.66

M

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Multicap Industrial multitubo systems MC	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
Multicap Industrial multitubo systems MM	H 16		578400	159.75	
	H 20		578406	159.75	
	H 25		578408	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
	RFz 32		578498	184.45	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 40		578386	236.66	
	multipipe Deutschland multipipe mp	TH 16		578352 R	177.08
		TH 20		578358 R	177.08
		TH 26		578362 R	177.08
		TH 32		578364	177.08
		TH 40		578624	234.69
		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
		TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
TH 32 S (PR-2B)		Mini Z8	574798 R	136.96	
N					
NEUTHERM MEKUPRESS-HT		H 16		578400	159.75
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
NIBCO Press System Copper	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
	VUS 1" (OD 28,6 mm)		578570	177.50	
	VUS 1½" (OD 34,9 mm)		578606	177.50	
NICOLL FLUXO	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
NUPI Industrie Italiane Multinupi	B 16		578468	193.28	
	B 18		578470	193.28	
	B 20		578472	193.28	
	B 26		578474	213.00	
	B 32		578476	213.00	
	F 16		578456	168.68	
	F 18		578458	168.68	
	F 20		578460	168.68	
	F 26		578462	182.48	
	F 32		578464	182.48	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	H 16		578400	159.75	
	H 18		578404	159.75	
	H 20		578406	159.75	
	H 25		578408	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		
TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96		
U 14		578372	174.38		
U 16		578374	165.66		
U 18		578376	165.66		
U 20		578378	165.66		
U 25		578380	165.66		
U 26 ⁷⁾		578392	194.31		
U 32		578382	194.31		
U 40		578386	236.66		
Nussbaum	VMP ¾" (OD 17,2 mm)		578660	204.17	
Optifitt-Press	VMP ½" G (OD 21,3 mm)		578666 R	204.17	
	VMPz ¾" (OD 26,9 mm)		578664	204.17	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Nussbaum Optiflex-Flowpress	VRX 16		578640	186.42	
	VRX 20		578642	186.42	
	VRX 25		578644	204.17	
	VRX 32		578646	204.17	
Nussbaum Optipress	V 15		578328	146.98	
	V 18		578332	146.98	
AquaPlus	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	Nussbaum Optipress Gaz	V 15		578328	146.98
		V 18		578332	146.98
V 22			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
Nussbaum Optipress-Therm	V 15		578328	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
O	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
	H 26 A		578430	204.17	
	H 32 A		578432	204.17	
Oventrop Cofit P	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
	H 26 A		578430	204.17	
Oventrop Cofit PD	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
	H 26 A		578430	204.17	
Oventrop Cofit PDK	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
	H 26 A		578430	204.17	
Oventrop Cofit PD-HT	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
	H 32 A		578432	204.17	
Oventrop Cofit PDK-HT	H 16 A		578420	204.17	
	H 20 A		578426	204.17	
P					
PBTube SERTIPRESS	RFz 12		578490	184.45	
	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
PBTube SERTI-STEEL ¹⁾	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
Pegler Yorkshire > Aalberts integrated piping systems	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	PERFEXIM	U 16	578374	165.66	
	PERFEKT	U 20	578378	165.66	
	SYSTEM	U 25	578380	165.66	
		U 32	578382	194.31	
PERFEXIM PERFEKT SYSTEM PLUS	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
PERFILTUBO PERFILALUPEX	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 18		578376	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
PERFILTUBO PERFILPRESS	U 40		578386	236.66	
	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
PEXTUBE PexTube	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	RFz 16		578492	184.45	
	RFz 20		578494	184.45	
	RFz 25		578496	184.45	
	RFz 32		578498	184.45	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
Pipelife C-PRESS	M 15		578312	146.98	PLÁSTICOS FERRO FERROPLAST GPF MULT Pressfitting MULTICAPA	U 16		578374	165.66		
	M 18		578314	146.98		U 20		578378	165.66		
	M 22		578316	146.98		U 25		578380	165.66		
	M 28		578318	146.98		U 32		578382	194.31		
	M 35		578390	178.12		PLÁSTICOS FERRO FERROPLAST GPF PPSU Pressfitting PEX y MULTICAPA	U 16		578374	165.66	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51			U 20		578378	165.66	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51			U 25		578380	165.66	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51			U 32		578382	194.31	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51			PLÁSTICOS FERRO FERROPLAST GPF PRESS Pressfitting PEX PLUMBING PLUS EZIPEX Crimp (AUS)	RFz 16		578492	184.45
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96				RFz 20		578494	184.45
Pipelife RADOPRESS	TH 16		578352 R	177.08	RFz 25			578496	184.45		
	TH 18		578356	177.08	RFz 32			578498	184.45		
	TH 20		578358 R	177.08	PLUMBING PLUS EZIPEX Gas (AUS)	K16/P18			578592	184.45	
	TH 26		578362 R	177.08		K/20			578594	184.45	
	TH 32		578364	177.08		K/25		578596	184.45		
	TH 40		578624	234.69		K32		578598	184.45		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		K1/40		578600	184.45		
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51		PLUMBING PLUS EZIPEX Gas (AUS)	K16/P18		578592	184.45	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	K/20			578594	184.45		
	TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	K/25			578596	184.45		
TH 32 S (PR-2B)**	Mini Z8	574799 R	136.96	K32			578598	184.45			
Pipetec Connect	TH 16		578352 R	177.08	K1/40			578600	184.45		
	TH 20		578358 R	177.08	PLUMBING PLUS UNIPEX Water & Gas (AUS)		Yz 16 UNI		578740	184.45	
	TH 26		578362 R	177.08		Yz 20 UNI		578742	184.45		
	TH 32		578364	177.08		Yz 25 UNI		578744	184.45		
	TH 40		578624	234.69		Yz 32 UNI		578746	184.45		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		PLUMBING PLUS EZIPEX Gas (AUS)	VAU 15 (OD 12,7 mm)		578630	151.86	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51			VAU 20 (OD 19,1 mm)		578632	151.86	
	TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	VAU 25 (OD 25,4 mm)			578634	151.86		
	TH 32 S (PR-2B)**	Mini Z8	574799 R	136.96	VAU 32 (OD 31,8 mm)			578636	159.75		
	PLASTICA ALFA Multipex	U 16		578378	165.66		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124.51	
U 20			578379	165.66	VAU 20 S (PR-2B)** (OD 19,1 mm)		Mini Z8	574806 R	124.51		
U 32			578382	194.31	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136.96			
PLASTICA ALFA Multipex Air		TH 16		578352 R	177.08	PLUMBING PLUS EZIPEX Solar (AUS)	VAU 15 (OD 12,7 mm)		578630	151.86	
		TH 20		578358 R	177.08		VAU 20 (OD 19,1 mm)		578632	151.86	
		TH 26		578362 R	177.08		VAU 25 (OD 25,4 mm)		578634	151.86	
		TH 32		578364	177.08		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124.51	
		TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124.51	
		TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136.96	
PLASTICA ALFA Multipexalfa Gas		TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	PLUMBING PLUS EZIPEX Water (AUS)	VAU 15 (OD 12,7 mm)		578630	151.86	
	TH 16		578352 R	177.08	VAU 20 (OD 19,1 mm)			578632	151.86		
	TH 20		578358 R	177.08	VAU 25 (OD 25,4 mm)			578634	151.86		
	TH 26		578362 R	177.08	VAU 32 (OD 31,8 mm)			578636	159.75		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	VAU 15 S (PR-2B) (OD 12,7 mm)		Mini Z8	574804 R	124.51		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	VAU 20 S (PR-2B)** (OD 19,1 mm)		Mini Z8	574806 R	124.51		
	PLASTICA ALFA Multipexalfa Gas protek	TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	POLYPIPE POLYSURE	TH 10		578342	177.08	
		TH 16		578352 R	177.08		TH 15		578350	177.08	
		TH 20		578358 R	177.08		TH 22		578588	177.08	
		TH 26		578362 R	177.08		TH 28		578590	177.08	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51	POLYSAN Handelsoges. m.b.H. & Co KG (Krems/Österreich)		M 15		578312	146.98	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51			M 18		578314	146.98	
TH 26 S (PR-2B)**		Mini Z8	574798 R	136.96		M 22		578316	146.98		
PLASTICA ALFA Multipex Plus		TH 16		578352 R		177.08	M 28		578318	146.98	
		TH 20		578358 R		177.08	M 35		578390	178.12	
		TH 26		578362 R		177.08	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	TH 32		578364	177.08	CStahl-Press-	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	System M	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	M 28 S (PR-2B)	Mini Z8	574744 R	124.51			
PLASTICA ALFA Multipex Thermo	TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	M 35 S (PR-2B)	Mini Z8	574746 R	136.96			
	TH 16		578352 R	177.08	POLYSAN Handelsoges. m.b.H. & Co KG (Krems/Österreich)	M 15		578312	146.98		
	TH 20		578358 R	177.08		M 18		578314	146.98		
	TH 26		578362 R	177.08		M 22		578316	146.98		
	TH 32		578364	177.08		M 28		578318	146.98		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		M 35		578390	178.12		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	PLASTICA ALFA Multipex Thermo Plus	TH 26 S (PR-2B)**	Mini Z8	574798 R	136.96	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
		TH 16		578352 R	177.08	Press-System	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
		TH 20		578358 R	177.08	1.4520	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
TH 26			578362 R	177.08	M 35 S (PR-2B)	Mini Z8	574746 R	136.96			
TH 32			578364	177.08	POLYSAN Handelsoges. m.b.H. & Co KG (Krems/Österreich)	M 15		578312	146.98		
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51		M 18		578314	146.98		
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51		M 22		578316	146.98		
TH 26 S (PR-2B)**		Mini Z8	574798 R	136.96		M 28		578318	146.98		
PLASTICA ALFA Multipex Plus		TH 32 S (PR-2B)**	Mini Z8	574799 R		136.96	M 35		578390	178.12	
		TH 16		578352 R		177.08	POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	TH 20		578358 R	177.08	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124.51		
	TH 26		578362 R	177.08	Press-System	M 22 S (PR-2B)	Mini Z8	574742 R	124.51		
	TH 32		578364	177.08	1.4520	M 28 S (PR-2B)	Mini Z8	574744 R	124.51		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	M 35 S (PR-2B)	Mini Z8	574746 R	136.96			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
POLYSAN	M 15		578312	146.98
Handelsges.	M 18		578314	146.98
m.b.H. & Co KG	M 22		578316	146.98
(Krems/Öster- reich)	M 28		578318	146.98
	M 35		578390	178.12
POLYSAN- Edelstahl	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
Press-System	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
Wasser	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
POLYSAN	TH 14		578348	177.08
Handelsges.	TH 16		578352 R	177.08
m.b.H. & Co KG	TH 17		578354	177.08
(Krems/Öster- reich)	TH 18		578356	177.08
	TH 20		578358 R	177.08
POLYSAN- Press-System	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136.96
POLYSAN	TH 14		578348	177.08
Handelsges.	TH 16		578352 R	177.08
m.b.H. & Co KG	TH 17		578354	177.08
(Krems/Öster- reich)	TH 18		578356	177.08
	TH 20		578358 R	177.08
POLYSAN-Henco- Press-System	TH 26		578362 R	177.08
	HE 32		578370 R	212.06
	HEz 40 ³⁾		578572	307.66
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
POLYSAN (España) „Rainbow“	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
Prandelli Multyrama Pf	H 14		578398	159.75
	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	U 40		578386	236.66
Prandelli Multyrama Pfm	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 40		578386	236.66
PURMO Cleverfit Radial	F 16		578456	168.68
	F 20		578460	168.68
	F 26		578462	182.48
	F 32		578464	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 17		578354	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 20		578378	165.66
	U 32		578382	194.31
	VP 16		578482	176.56
	VP 20		578484	176.56
	VP 32		578488	195.25

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
R				
Raccorderie Metalliche aesPRES ¹⁾	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Raccorderie Metalliche inoxPRES ¹⁾	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Raccorderie Metalliche MARINEPRES ¹⁾	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
Raccorderie Metalliche steelPRES ¹⁾	M 15		578312	146.98
	M 18		578314	146.98
	M 22		578316	146.98
	M 28		578318	146.98
	M 35		578390	178.12
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96
RBM Tita-fix	B 14		578466	193.28
	B 16		578468	193.28
	B 18		578470	193.28
	B 20		578472	193.28
	B 26		578474	213.00
	F 16		578456	168.68
	F 18		578458	168.68
	F 20		578460	168.68
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	H 14		578398	159.75
	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 14		578372	174.38
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
RBM Tita-gas	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 14		578372	174.38
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
Redi Nicoll Fluxo	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Redi Nicoll Fluxo Gas	TH 16		578352 R	177.08	Rubinetterie	M 15		578312	146.98
	TH 20		578358 R	177.08	Bresciane	M 18		578314	146.98
	TH 26		578362 R	177.08	Bonomi	M 22		578316	146.98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	TURBO STEEL	M 28		578318	146.98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	M 35		578390	178.12	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
RIFENG LD PRESS FITTING (F8)	LD 16		578652	182.69	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	LD 20		578654	182.69	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	LD 25		578656	182.69	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
RIFENG U PRESS FITTING (F5)	U 14		578372	174.38	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	U 16		578374	165.66	Rubinetterie	B 14		578466	193.28
	U 18		578376	165.66	Bresciane	B 16		578468	193.28
	U 20		578378	165.66	Bonomi	B 18		578470	193.28
	U 25		578380	165.66	TURBO PRESS	B 20		578472	193.28
	U 32		578382	194.31	B 26		578474	213.00	
RIFENG TH PRESS FITTING (F9)	TH 16		578352 R	177.08	B 32		578476	213.00	
	TH 20		578358 R	177.08	H 14		578398	159.75	
	TH 25		578360	177.08	H 16		578400	159.75	
	TH 26		578362 R	177.08	H 18		578404	159.75	
	TH 32		578364	177.08	H 20		578406	159.75	
	TH 40		578624	234.69	H 26		578410	159.75	
RIQUIER A SERTIR	RFz 12		578490	184.45	H 32		578412	159.75	
	RFz 16		578492	184.45	TH 14		578348	177.08	
	RFz 20		578494	184.45	TH 16		578352 R	177.08	
	RFz 25		578496	184.45	TH 18		578356	177.08	
RIQUIER Système multicouche	TH 16		578352 R	177.08	TH 20		578358 R	177.08	
	TH 20		578358 R	177.08	TH 26		578362 R	177.08	
	TH 26		578362 R	177.08	TH 32		578364	177.08	
	TH 32		578364	177.08	TH 40		578624	234.69	
	TH 40		578624	234.69	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	U 14		578372	174.38	
	U 16		578374	165.66	U 16		578374	165.66	
	U 20		578378	165.66	U 18		578376	165.66	
	U 32		578382	194.31	U 20		578378	165.66	
	U 40		578386	236.66	U 26 ⁷⁾		578392	194.31	
				U 32		578382	194.31		
Roth PressCheck	RN 14		578434	165.66	Rubinetterie	TH 16		578352 R	177.08
	RN 16		578454	165.66	Bresciane	TH 20		578358 R	177.08
	RN 17		578436	165.66	Bonomi	TH 26		578362 R	177.08
	RN 20		578438	165.66	TURBO PRESS	TH 32		578364	177.08
	RN 25/26		578440	165.66	GAS	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	RN 32		578442	194.31	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
Rubinetterie Bresciane	M 15		578312	146.98	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 18		578314	146.98	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 22		578316	146.98	S				
	M 28		578318	146.98	SA.MI PLASTIC	TH 14		578348	177.08
	M 35		578390	178.12	TH 16		578352 R	177.08	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 18		578356	177.08	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	TH 20		578358 R	177.08	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	TH 26		578362 R	177.08	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	TH 32		578364	177.08	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	TH 40		578624	234.69	
Rubinetterie Bresciane	M 15		578312	146.98	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51	
	M 18		578314	146.98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 22		578316	146.98	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51	
	M 28		578318	146.98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 35		578390	178.12	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	SA.MI PLASTIC	TH 16		578352 R	177.08
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	Multistrato Gas	TH 20		578358 R	177.08
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	TH 26		578362 R	177.08	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	TH 32		578364	177.08	
Rubinetterie Bresciane	M 15		578312	146.98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 18		578314	146.98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 22		578316	146.98	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 28		578318	146.98	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 35		578390	178.12	SA.MI PLASTIC	TH 16		578352 R	177.08
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	Multistrato Gas	TH 20		578358 R	177.08
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	TH 26		578362 R	177.08	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	TH 32		578364	177.08	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
Rubinetterie Bresciane	M 15		578312	146.98	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 18		578314	146.98	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	M 22		578316	146.98	SA.MI PLASTIC	TH 16		578352 R	177.08
	M 28		578318	146.98	Multistrato Gas	TH 20		578358 R	177.08
	M 35		578390	178.12	TH 26		578362 R	177.08	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	TH 32		578364	177.08	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA 3fit-Press Pb-free Serie 25000	B 16		578468	193.28	
	B 20		578472	193.28	
	B 26		578474	213.00	
	B 32		578476	213.00	
	F 16		578456	168.68	
	F 20		578460	168.68	
	F 26		578462	182.48	
	F 32		578464	182.48	
	Fz 40		578478	247.15	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	H 16		578400	159.75	
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 40		578624	234.69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 20		578378	165.66	
	U 26 ⁷⁾		578392	194.31	
	U 32		578382	194.31	
	U 40		578386	236.66	
	SANHA 3fit-Press PPSU Serie 35000	B 16		578468	193.28
		B 20		578472	193.28
		B 26		578474	213.00
		B 32		578476	213.00
		F 16		578456	168.68
		F 20		578460	168.68
		F 26		578462	182.48
		F 32		578464	182.48
F 16 S (PR-2B)**		Mini Z8	574728 R	124.51	
F 20 S (PR-2B)**		Mini Z8	574730 R	124.51	
F 26 S (PR-2B)**		Mini Z8	574732 R	124.51	
F 32 S (PR-2B)		Mini Z8	574734 R	136.96	
H 16			578400	159.75	
H 20			578406	159.75	
H 26			578410	159.75	
H 32			578412	159.75	
TH 16			578352 R	177.08	
TH 20			578358 R	177.08	
TH 26			578362 R	177.08	
TH 32			578364	177.08	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)		Mini Z8	574798 R	136.96	
U 16			578374	165.66	
U 20			578378	165.66	
U 26 ⁷⁾			578392	194.31	
U 32			578382	194.31	
SANHA Heavy Steel Press		VMP ½" G (OD 21,3 mm)		578666 R	204.17
		VMPz ¾" (OD 26,9 mm)		578664	204.17
		VMP ½" G (OD 21,3 mm) ¹⁾		578666 R	204.17
SANHA Heavy Steel Press Gas		VMPz ¾" (OD 26,9 mm)		578664	204.17
		VMPz ¾" (OD 26,9 mm)		578664	204.17
SANHA-NiroSan Gas Presssystem Serie 17000		SA 15		578514	176.56
		SA 18		578518	176.56
		SA 22		578520	176.56
		SA 28		578522	176.56
		M 15 ¹⁾		578312	146.98
		M 18 ¹⁾		578314	146.98
	M 22 ¹⁾		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	V 15 ¹⁾		578328	146.98	
	V 18 ¹⁾		578332	146.98	
	V 22 ¹⁾		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA-NiroSan Industry Presssystem Serie 18000	SA 15		578514	176.56	
	SA 18		578518	176.56	
	SA 22		578520	176.56	
	SA 28		578522	176.56	
	M 15 ¹⁾		578312	146.98	
	M 18 ¹⁾		578314	146.98	
	M 22 ¹⁾		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	V 15 ¹⁾		578328	146.98	
	V 18 ¹⁾		578332	146.98	
	V 22 ¹⁾		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	SANHA-NiroSan- Presssystem Serie 9000	SA 15		578514	176.56
		SA 18		578518	176.56
		SA 22		578520	176.56
		SA 28		578522	176.56
		M 15 ¹⁾		578312	146.98
		M 18 ¹⁾		578314	146.98
M 22 ¹⁾			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
SANHA-NiroSan SF Presssystem Serie 19000 (silicone free)		SA 15		578514	176.56
	SA 18		578518	176.56	
	SA 22		578520	176.56	
	SA 28		578522	176.56	
	M 15 ¹⁾		578312	146.98	
	M 18 ¹⁾		578314	146.98	
	M 22 ¹⁾		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	SANHA NiroTherm Serie 91000	SA 15		578514	176.56
SA 18			578518	176.56	
SA 22			578520	176.56	
SA 28			578522	176.56	
M 15 ¹⁾			578312	146.98	
M 18 ¹⁾			578314	146.98	
M 22 ¹⁾			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
V 15 ¹⁾			578328	146.98	
V 18 ¹⁾		578332	146.98		
V 22 ¹⁾		578334	146.98		
V 28		578336	146.98		
V 35		578604	178.12		
V 15 S (PR-2B)	Mini Z8	574752 R	124.51		
V 18 S (PR-2B)	Mini Z8	574756 R	124.51		
V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
V 35 S (PR-2B)	Mini Z8	574762 R	136.96		

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA PURAPRESS Serie 8000	SA 12		578510	256.39	
	SA 14		578512	256.39	
	SA 15		578514	176.56	
	SA 16		578516	176.56	
	SA 18		578518	176.56	
	SA 22		578520	176.56	
	SA 28		578522	176.56	
	M 12 ¹⁾		578310	146.98	
	M 15 ¹⁾		578312	146.98	
	M 18 ¹⁾		578314	146.98	
	M 22 ¹⁾		578316	146.98	
	M 28 ¹⁾		578318	146.98	
	M 35 ¹⁾		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	V 12		578324	146.98	
	V 14		578326	146.98	
	VG 14		578338	146.98	
	V 15 ¹⁾		578328	146.98	
	V 16		578330	146.98	
	VG 16		578340	146.98	
	V 18 ¹⁾		578332	146.98	
	V 22 ¹⁾		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	VG 14 S (PR-2B)	Mini Z8	574750 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	VG 16 S (PR-2B)	Mini Z8	574754 R	124.51	
V 18 S (PR-2B)	Mini Z8	574756 R	124.51		
V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
SANHA-Therm Serie 24000	SA 12		578510	256.39	
	SA 15		578514	176.56	
	SA 18		578518	176.56	
	SA 22		578520	176.56	
	SA 28		578522	176.56	
	M 12		578310	146.98	
	M 15 ¹⁾		578312	146.98	
	M 18 ¹⁾		578314	146.98	
	M 22 ¹⁾		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	V 12		578324	146.98	
	V 15 ¹⁾		578328	146.98	
	V 18 ¹⁾		578332	146.98	
	V 22 ¹⁾		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	SANHA-Therm Industry Serie 28000	SA 12		578510	256.39
		SA 15		578514	176.56
		SA 18		578518	176.56
		SA 22		578520	176.56
SA 28			578522	176.56	
M 12			578310	146.98	
M 15 ¹⁾			578312	146.98	
M 18 ¹⁾			578314	146.98	
M 22 ¹⁾			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 12 S (PR-2B)		Mini Z8	574736 R	124.51	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
V 12			578324	146.98	
V 15 ¹⁾			578328	146.98	
V 18 ¹⁾			578332	146.98	
V 22 ¹⁾			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 12 S (PR-2B)		Mini Z8	574748 R	124.51	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)		Mini Z8	574762 R	136.96	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
SANITOP PERMATUBO INOX	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
SANPRO THPRESS	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
SATEC SK VITerm	TH 16		578352 R	177.08	
	TH 18		578356	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	U 40		578386	236.66	
SAVEUR REFLEX PEX Water	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
Schütz duo-flex tri-o-flex	TH 14		578348	177.08	
	TH 16		578352 R	177.08	
	TH 17		578354	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
Schwer Fittings AQUApress	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	M 12		578310	146.98	
M 15	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
M 35 S (PR-2B)	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	SEppelfricke	> Aalberts integrated piping systems			
	SESTA SESTA GAS	TH 14		578348	177.08
		TH 16		578352 R	177.08
		TH 20		578358 R	177.08
		TH 26		578362 R	177.08
	SESTA sistema multistrato	TH 32		578364	177.08
		H 16		578400	159.75
		H 20		578406	159.75
		TH 14		578348	177.08
TH 16			578352 R	177.08	
TH 18			578356	177.08	
TH 20			578358 R	177.08	
TH 26			578362 R	177.08	
TH 32			578364	177.08	
TH 40			578624	234.69	
SIGMA LI Premium	U 16		578374	165.66	
	U 20		578378	165.66	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578360	177.08	
	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
SLOVARM PEX-THERM	U 16		578374	165.66	
	U 20		578378	165.66	
	U 25		578380	165.66	
	U 32		578382	194.31	
	U 16		578400	159.75	
	U 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TIEMME 1650 AL-COBRAPEX GAS	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	THL 32		578368	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
TIGRE ALPEX GAS	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
TKM Systemtechnik	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
TRA Multi TRA+	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 25		578360	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
U 16		578374	165.66	
U 20		578378	165.66	
U 25		578380	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
U 40		578386	236.66	
TRA MULTITRAPRESS	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
TRA TRAPRESS	H 12		578396	159.75
	H 16		578400	159.75
	H 20		578406	159.75
	H 25		578408	159.75
	H 32		578412	159.75
	Rfz 12		578490	184.45
	Rfz 16		578492	184.45
	Rfz 20		578494	184.45
	Rfz 25		578496	184.45
	Rfz 32		578498	184.45
Tradelink	K16/P18		578592	184.45
	K/20		578594	184.45
	K/25		578596	184.45
	K32		578598	184.45
TradePex Crimp Water	K1/40		578600	184.45
	K16/P18		578592	184.45
	K/20		578594	184.45
	K/25		578596	184.45
Tradelink TradePex Crimp Gas	K32		578598	184.45
	K1/40		578600	184.45
	K16/P18		578592	184.45
	K/20		578594	184.45
TUBIPLAST ITALY MULTILAYER PIPE	H 16		578400	159.75
	H 18		578404	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	U 16		578374	165.66
	U 18		578376	165.66
	U 20		578378	165.66
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352 R	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TWEETOP	U 16		578374	165.66
	U 20		578378	165.66
	U 25		578380	165.66
	U 32		578382	194.31
	U 40		578386	236.66
U				
UNICAL AG MAX-MULTIPEX	U 16		578374	165.66
	U 20		578378	165.66
	H 26		578410	159.75
	U 26 ⁷⁾		578392	194.31
	U 32		578382	194.31
UNIDELTA DELTAPRESS	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
UNIDELTA DELTAPRESS GAS	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
UNIDELTA DELTAPRESS GAS	H 32		578412	159.75
	U 16		578374	165.66
	U 20		578378	165.66
	U 32		578382	194.31
	U 40		578386	236.66
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
Uponor	UP 14		578576	165.66
	UP 16		578578	165.66
	UP 20		578582	165.66
	UP 25		578584	165.66
	UP 32		578586	194.31
	U 40		578386	236.66
V				
Valsir Bravopress	B 16		578468	193.28
	B 20		578472	193.28
	B 26		578474	213.00
	B 32		578476	213.00
	F 16		578456	168.68
	F 20		578460	168.68
	F 26		578462	182.48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	H 32 V		578602	204.17
Valsir PEXAL	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	U 16		578374	165.66
	U 20		578378	165.66
	U 26 ⁷⁾		578392	194.31
	U 32		578382	194.31
	H 14		578398	159.75
	H 16		578400	159.75
	H 20		578406	159.75
	H 26		578410	159.75
	H 32		578412	159.75
	H 32 V		578602	204.17
	TH 16		578352 R	177.08
TH 20		578358 R	177.08	
TH 26		578362 R	177.08	
TH 32		578364	177.08	
U 16		578374	165.66	
U 20		578378	165.66	
U 26 ⁷⁾		578392	194.31	
U 32		578382	194.31	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Van Marcke NV SYSTEMPEX	TH 16		578352 R	177.08	Viega MegaPress 316 (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17	
	TH 20		578358 R	177.08		VMPz ¾" (OD 26,9 mm)		578664	204.17	
	TH 26		578362 R	177.08		Viega MegaPress 316 FKM	VMP ½" G (OD 21,3 mm)		578666 R	204.17
	TH 32		578364	177.08		VMPz ¾" (OD 26,9 mm)		578664	204.17	
	TH 40		578624	234.69		(ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	182.50
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51		VMPz ¾" (OD 26,9 mm)		578664	204.17	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51		Viega MegaPress CuNi (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51		VMPz ¾" (OD 26,9 mm)		578664	204.17	
Van Marcke NV Tubipress	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	Viega MegaPress FKM (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17	
	M 12		578310	146.98	VMPz ¾" (OD 26,9 mm)		578664	204.17		
	M 15		578312	146.98	Viega MegaPresG (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17	
	M 18		578314	146.98	VMPz ¾" (OD 26,9 mm)		578664	204.17		
	M 22		578316	146.98	Viega Megapress (EN) ⁴¹	VMP ¾" (OD 17,2 mm)		578660	204.17	
	M 28		578318	146.98	VMP ½" G (OD 21,3 mm)		578666 R	204.17		
	M 35		578390	178.12	VMPz ¾" (OD 26,9 mm)		578664	204.17		
	M 12 S (PR-2B)	Mini Z8	574736 R	124.51	Viega MegapressS (EN) ⁴¹	VMP ¾" (OD 17,2 mm)		578660	204.17	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	VMP ½" G (OD 21,3 mm)		578666 R	204.17		
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	VMPz ¾" (OD 26,9 mm)		578664	204.17		
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	Viega Pexfit	VX 16		578552	204.17	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	VX 20		578554	204.17		
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	VX 25		578556	204.17		
	Variotherm System TH	TH 11,6		578344	177.08	Viega Pexfit G	VX 16		578552	204.17
TH 16			578352 R	177.08	VX 20		578554	204.17		
TH 20			578358 R	177.08	VX 25		578556	204.17		
TH 16 S (PR-2B)**		Mini Z8	574782 R	124.51	Viega Prestabo	V 12		578324	146.98	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51	V 15		578328	146.98		
VESBO CARBON	M 15		578312	146.98	V 18		578332	146.98		
	M 18		578314	146.98	V 22		578334	146.98		
	M 22		578316	146.98	V 28		578336	146.98		
	M 28		578318	146.98	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		
	M 35		578390	178.12	V 14 S (PR-2B)	Mini Z8	574750 R	124.51		
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	V 16 S (PR-2B)	Mini Z8	574754 R	124.51		
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
	VESBO INOX	M 15		578312	146.98	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
M 18			578314	146.98	Viega Profipress	V 12		578324	146.98	
M 22			578316	146.98	VG 14		578338	146.98		
M 28			578318	146.98	V 15		578328	146.98		
M 35			578390	178.12	V 18		578332	146.98		
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	V 22		578334	146.98		
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	V 28		578336	146.98		
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	V 35		578604	178.12		
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	VG 14 S (PR-2B)	Mini Z8	574750 R	124.51		
VESBO MULTIPRESS TH-U		TH 16		578352 R	177.08	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
		TH 20		578358 R	177.08	VG 16 S (PR-2B)	Mini Z8	574754 R	124.51	
		TH 26		578362 R	177.08	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	TH 32		578364	177.08	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	V 28 S (PR-2B)	Mini Z8	574760 R	124.51		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	Viega Profipress G	V 12		578324	146.98	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	VG 14		578338	146.98		
	U 16		578374	165.66	V 15		578328	146.98		
	U 20		578378	165.66	VG 16		578340	146.98		
	U 26 ⁷⁾		578392	194.31	V 18		578332	146.98		
VESBO VPREMIUM	U 32		578382	194.31	V 22		578334	146.98		
	U 40		578386	236.66	V 28		578336	146.98		
	U 16		578374	165.66	V 35		578604	178.12		
	U 20		578378	165.66	V 12 S (PR-2B)	Mini Z8	574748 R	124.51		
	U 25		578380	165.66	VG 14 S (PR-2B)	Mini Z8	574750 R	124.51		
Viega Fonterra	VP 14/15		578480	176.56	V 15 S (PR-2B)	Mini Z8	574752 R	124.51		
	VP 16/17		578482	176.56	VG 16 S (PR-2B)	Mini Z8	574754 R	124.51		
	VP 20		578484	176.56	V 18 S (PR-2B)	Mini Z8	574756 R	124.51		
	VP 25		578486	176.56	V 22 S (PR-2B)	Mini Z8	574758 R	124.51		
	Viega MegaPress (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	VMPz ¾" (OD 26,9 mm)		578664	204.17	V 35 S (PR-2B)	Mini Z8	574762 R	136.96		
Viega MegaPress 304 FKM (ASTM) ⁵¹	VMP ½" G (OD 21,3 mm)		578666 R	204.17	Viega Profipress S	V 12		578324	146.98	
VMPz ¾" (OD 26,9 mm)		578664	204.17	V 15		578328	146.98			
			182.50	V 18		578332	146.98			
				V 22		578334	146.98			
				V 28		578336	146.98			
				V 35		578604	178.12			
				V 12 S (PR-2B)	Mini Z8	574748 R	124.51			
				V 15 S (PR-2B)	Mini Z8	574750 R	124.51			
				V 18 S (PR-2B)	Mini Z8	574752 R	124.51			
				V 22 S (PR-2B)	Mini Z8	574754 R	124.51			
				V 28 S (PR-2B)	Mini Z8	574756 R	124.51			
				V 35 S (PR-2B)	Mini Z8	574758 R	124.51			
				V 28 S (PR-2B)	Mini Z8	574760 R	124.51			
				V 35 S (PR-2B)	Mini Z8	574762 R	136.96			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

⁴⁾ For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

⁵⁾ For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

⁶⁾ Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

⁷⁾ Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Viega Profipress Therm	V 12		578324	146.98	
	V 15		578328	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
Viega ProPress (ASTM) ⁵¹	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
	VUS 1" (OD 28,6 mm)		578570	177.50	
	VUS 1¼" (OD 34,9 mm)		578606	177.50	
Viega ProPress 304 FKM (ASTM) ⁵¹	VUS ½" S (PR-2B) (OD 15,9 mm)	Mini Z8	574764 R	124.51	
	VUS ¾" S (PR-2B) (OD 22,2 mm)	Mini Z8	574766 R	124.51	
	VUS 1" S (PR-2B) (OD 28,6 mm)	Mini Z8	574768 R	124.51	
	VUS 1¼" S (PR-2B) (OD 34,9 mm)	Mini Z8	574770 R	124.51	
	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
Viega ProPress 316 (ASTM) ⁵¹	VUS 1" (OD 28,6 mm)		578570	177.50	
	VUS 1¼" (OD 34,9 mm)		578606	177.50	
	VUS ½" (OD 15,9 mm)		578566	177.50	
	VUS ¾" (OD 22,2 mm)		578568	177.50	
Viega Propress WATER System AUS	VAU 15 (OD 12,7 mm)		578630	151.86	
	VAU 20 (OD 19,1 mm)		578632	151.86	
	VAU 25 (OD 25,4 mm)		578634	151.86	
	VAU 32 (OD 31,8 mm)		578636	159.75	
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124.51	
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124.51	
Viega PropressGAS System AUS	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136.96	
	VAU 32 S (PR-2B) (OD 31,8 mm)	Mini Z8	574856 R	136.96	
	VAU 15 (OD 12,7 mm)		578630	151.86	
	VAU 20 (OD 19,1 mm)		578632	151.86	
Viega Raxinox	VRX 16		578640	186.42	
	VRX 20		578642	186.42	
	VRX 25		578644	204.17	
	VRX 32		578646	204.17	
Viega Raxofix	VRX 16		578640	186.42	
	VRX 20		578642	186.42	
	VRX 25		578644	204.17	
	VRX 32		578646	204.17	
Viega Sanfix	VP 16/17		578482	176.56	
	VP 20		578484	176.56	
	VP 25		578486	176.56	
	VP 32		578488	195.25	
Viega Sanfix Fosta	VP 16/17		578482	176.56	
	VP 20		578484	176.56	
	VP 25		578486	176.56	
	VP 32		578488	195.25	
Viega Sanpress	V 12		578324	146.98	
	V 15		578328	146.98	
	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124.51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	
	Viega Sanpress Inox	V 15		578328	146.98
		V 18		578332	146.98
V 22			578334	146.98	
V 28			578336	146.98	
V 35			578604	178.12	
V 15 S (PR-2B)		Mini Z8	574752 R	124.51	
V 18 S (PR-2B)		Mini Z8	574756 R	124.51	
V 22 S (PR-2B)		Mini Z8	574758 R	124.51	
V 28 S (PR-2B)		Mini Z8	574760 R	124.51	
V 35 S (PR-2B)		Mini Z8	574762 R	136.96	
Viega Sanpress Inox G		V 15		578328	146.98
		V 18		578332	146.98
		V 22		578334	146.98
		V 28		578336	146.98
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
Viega Smartpress	VX 16		578552	204.17	
	VX 20		578554	204.17	
	VX 25		578556	204.17	
	V 15		578328	146.98	
Viega Temponox	V 18		578332	146.98	
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Viessmann	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
Vogel & Noot EASYTEC	TH 16		578352 R	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
VSH	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96

VSH > Aalberts integrated piping systems

W

Watts MTR Art press	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
WATTS RADIANT	US ¾"		578534	201.16	
	US ½"		578536	201.16	
Watts WaterPEX	US ¾"		578538	201.16	
	US 1"		578540	201.16	
WATTS RADIANT	US ¾"		578534	201.16	
	US ½"		578536	201.16	
Watts RadiantPEX	US ¾"		578538	201.16	
	US 1"		578540	201.16	
WATTS RADIANT	U 16 (½")		578374	165.66	
	U 20 (¾")		578378	165.66	
Watts RadiantPEX-AL	U 25 (¾")		578380	165.66	
	U 32 (1")		578382	194.31	
Wavin Tigris K5/M5	B 16		578468	193.28	
	B 20		578472	193.28	
	B 32		578476	213.00	
	H 16		578400	159.75	
	H 20		578406	159.75	
	H 25		578408	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 25		578364	177.08	
	TH 32		578624	234.69	
	WEECON PRESS-C-Stahl	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
TH 20 S (PR-2B)**		Mini Z8	574788 R	124.51	
TH 25 S (PR-2B)**		Mini Z8	574792 R	124.51	
TH 32 S (PR-2B)		Mini Z8	574798 R	136.96	
U 16			578374	165.66	
U 20			578378	165.66	
U 25			578380	165.66	
U 32			578382	194.31	
UP 16			578578	165.66	
UP 20			578582	165.66	
UP 25			578584	165.66	
UP 32			578586	194.31	
WEECON PRESS-Edelstahl	M 15		578312	146.98	
	M 18		578314	146.98	
	M 22		578316	146.98	
	M 28		578318	146.98	
	M 35		578390	178.12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124.51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124.51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124.51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124.51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136.96	
	WEECON PRESS-Kupfer	M 15		578312	146.98
		M 18		578314	146.98
M 22			578316	146.98	
M 28			578318	146.98	
M 35			578390	178.12	
M 15 S (PR-2B)		Mini Z8	574738 R	124.51	
M 18 S (PR-2B)		Mini Z8	574740 R	124.51	
M 22 S (PR-2B)		Mini Z8	574742 R	124.51	
M 28 S (PR-2B)		Mini Z8	574744 R	124.51	
M 35 S (PR-2B)		Mini Z8	574746 R	136.96	
WEECON PRESS-Kupfer		V 15		578328	146.98
		V 18		578332	146.98
	V 22		578334	146.98	
	V 28		578336	146.98	
	V 35		578604	178.12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124.51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124.51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124.51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124.51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136.96	

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
WEM	U 16		578374	165.66
WIELAND-WERKE cuprotherm CTX	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124.51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
WKS-Press	TH 14		578348	177.08
	TH 16		578352 R	177.08
	TH 17		578354	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	WÜRTH	TH 16		578352 R
Würth	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	HE 32		578370 R	212.06

X

XtraConnect	F 16		578456	168.68	
	F 20		578460	168.68	
	F 26		578462	182.48	
	F 32		578464	182.48	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124.51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124.51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124.51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136.96	
	H 16		578400	159.75	
	H 20		578406	159.75	
	H 26		578410	159.75	
	H 32		578412	159.75	
	TH 16		578352 R	177.08	
	TH 20		578358 R	177.08	
	TH 26		578362 R	177.08	
	TH 32		578364	177.08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96	
	U 16		578374	165.66	
	U 20		578378	165.66	
	(DN 26)	U 25		578380	165.66
		U 32		578382	194.31
		VP 16		578482	176.56
		VP 20		578484	176.56
		VP 32		578488	195.25

Y

YX COPPER	Yz 16 UNI		578740	184.45
UNIPEX Water & Gas	Yz 20 UNI		578742	184.45
(AUS)	Yz 25 UNI		578744	184.45
	Yz 32 UNI		578746	184.45

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Z				
ZEWOTHERM	TH 12		578346	177.08
Zewo Press Premium	TH 16		578352 R	177.08
	TH 17		578354	177.08
	TH 18		578356	177.08
	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 40		578624	234.69
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124.51
	TH 16 S (PR-2B)**		574782 R	124.51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124.51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124.51
	TH 20 S (PR-2B)**		574788 R	124.51
	TH 26 S (PR-2B)**		574794 R	124.51
TH 32 S (PR-2B)		574798 R	136.96	
ZEWOTHERM	TH 16		578352 R	177.08
Zewo Press PPSU	TH 20		578358 R	177.08
	TH 26		578362 R	177.08
	TH 32		578364	177.08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124.51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124.51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124.51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136.96
ZURN	US ¾"		578534	201.16
INDUSTRIES	US ½"		578536	201.16
ZURN PEX	US ¾"		578538	201.16
	US 1"		578540	201.16

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

** Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

Accessories

Description	Art.-No.	€
Adapter tongs Mini Z8 for driving REMS pressing rings S (PR-2B)	574700R	144.28
Steel case with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	96.53
L-Boxx system case with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	146.36
Steel case with insert for 8 pressing tongs Mini/ cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R	96.53
L-Boxx system case with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659R	146.36

