REMS Universal diamond core drilling crowns LS

For REMS Picus S1, REMS Picus SR, REMS Picus S3, REMS Picus S2/3,5 and other makes

High quality universal diamond core drilling crowns. Laser welded. Universally usable for dry and wet drilling, hand held or with drill stand. Ideal for universal applications in steel-reinforced concrete, masonry and many types of material. For installation, metalwork, industry.

Concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed and other

Ø 32-200 mm

REMS universal diamond core drilling crowns LS laser welded. Diamond segments with conical cut for fast, easy and quiet drilling. Versatile for many types of material. Ideal for plumbers.

Universally usable for many materials, for dry and wet drilling, hand held or with drill stand.

Single connecting thread UNC 1¼ female. Drilling depth 420 mm.

Specially developed, high quality diamond segments with high diamond percentage and special bonding, for excellent drilling performance and very long life. Ideal for universal applications in steel-reinforced concrete and masonry.

Diamond segments with conical cut ("roof shape") for fast, easy and quiet drilling. Inductively soldered on fully automatic soldering machines for constant high quality of the soldered connection. Drilling tubes with soldered diamond segments can be resoldered by simple hard soldering.

Light loosening ring, for light loosening of the diamond core crowns, as accessory.

Drive through all REMS Picus drive machines and suitable drive machines of other makes having connecting thread UNC 11/4 male. Adapter for using REMS Universal diamond core drilling crowns in drive machines having other connecting threads/other tool holders, as accessory.

Suck off dusts that occur during dry drilling with REMS Pull 2 M safety vacuum cleaner, certified for extracting health hazardous dusts of dust class M (page 324).









Supply format

REMS Universal diamond core drilling crown. Laser welded! High temperatureresistant! Universally usable for dry and wet drilling, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connecting thread UNC 1¼ female. Drilling depth 420 mm. In a carton.

Britting depth 420 min. In d curtor			
Ø × drilling depth × connection	Number of segments	ArtNo.	€
UDKB LS 32 × 420 × UNC 11/4	1	181410 R	157.72
UDKB LS 42 × 420 × UNC 11/4	4	181415 R	147.34
UDKB LS 52 × 420 × UNC 11/4	5	181420 R	156.69
UDKB LS 62 × 420 × UNC 11/4	6	181425R	170.18
UDKB LS 72 × 420 × UNC 11/4	6	181430R	193.02
UDKB LS 82 × 420 × UNC 11/4	7	181435R	209.62
UDKB LS 92 × 420 × UNC 11/4	8	181440 R	236.61
UDKB LS 102 × 420 × UNC 11/4	9	181445R	242.84
UDKB LS 112 × 420 × UNC 11/4	9	181450R	256.33
UDKB LS 122 × 420 × UNC 11/4	10	181455R	289.55
UDKB LS 127 × 420 × UNC 11/4	10	181459R	300.97
UDKB LS 132 × 420 × UNC 11/4	10	181460R	313.42
UDKB LS 152 × 420 × UNC 11/4	11	181465R	372.59
UDKB LS 162 × 420 × UNC 11/4	12	181470R	394.39
UDKB LS 182 × 420 × UNC 11/4	13	181475R	476.39
UDKB LS 200 × 420 × UNC 11/4	14	181480R	503.38





Accessories

lo.	ArtNo.	scription
		ght loosening ring, for light loosening
5 20	180015	the diamond core crown
ir 61	180155R	illing crown extension 200 mm
2 31	180052	apter UNC 1¼ male to G ½ male
6 28	180056	apter UNC 1¼ male to G ½ female
3 48	180053	lapter UNC 1¼ male for Hilti BI, adapter for us e REMS universal diamond core drilling crowns Hilti drive machines with BI tool holder.
4 111	180054	lapter UNC 1¼ male for Hilti BU, adapter for us e REMS universal diamond core drilling crowns Hilti drive machines with BU tool holder.
7R 111	180057R	lapter UNC 1¼ male for Hilti BL, adapter for us e REMS universal diamond core drilling crowns Hilti drive machines with BL tool holder.
2 64	079012	arpening stone for diamond core drilling crow
3 38	079003	
-		ngle open ended wrench size 41 for UDKB

Additional adapters for using REMS Universal diamond core drilling crowns in drive machines of other makes, on request.

