

REMS expander heads P REMS expander heads P-CEF

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 273), REMS Ex-Press P 22 V ACC cordless pipe expander (page 274–275) and by suitable pipe expanders of other makes.

| Compression sleeve system | Expander head P Ø × s | Art.-No. | € |
|--|-------------------------------|----------|---------------|
| aquatherm grey pipe PB/PE-RT-Rohre | AT P 14 × 2.0 | 150828 | 125,00 |
| | AT P 16 × 2.0 | 150842 | 125,00 |
| | AT P 18 × 2.0 | 150873 | 125,00 |
| | AT P 20 × 2.0 | 150882 | 125,00 |
| | AT P 25 × 2.3 | 150912 | 125,00 |
| aquatherm grey pipe Mehrschicht- Metallverbundrohre (MYR) | AT V 16 × 2.4 | 150843 | 125,00 |
| | AT V 20 × 2.4 | 150883 | 125,00 |
| | AT V 25 × 2.7 | 150913 | 125,00 |
| | AT V 32 × 3.2 | 150957 | 135,00 |
| | AT V 40 × 3.5 | 150958 | 148,00 |
| General Fittings Serie 3400 PEX Gold-Fix | RH HIS 16 × 2.2 | 150849 | 125,00 |
| | RH HIS 20 × 2.8 | 150888 | 125,00 |
| | RH HIS 25 × 3.5 | 150916 | 125,00 |
| | RH HIS 32 × 4.4 | 150945 | 125,00 |
| General Fittings Serie 3400 PEX/AL/PEX Gold-Fix | RH MKV 16.2 × 2.6 | 150858 | 125,00 |
| | RH MKV 20 × 2.9 | 150897 | 125,00 |
| | RH MKV 25 × 3.7 | 150926 | 125,00 |
| | RH MKV 32 × 4.7 | 150952 | 125,00 |
| General Fittings Serie 3400 PEX Gold-Therm | RH HAS 17 × 2.0 | 150868 | 125,00 |
| | RH HAS 20 × 2.0 | 150887 | 125,00 |
| HERZ QUICK FIX | HC P 16 × 2.0 | 150806 | 125,00 |
| | HC P 20 × 2.0 | 150807 | 125,00 |
| | HC P 26 × 3.0 | 150808 | 125,00 |
| | HC P 32 × 3.0 | 150809 | 125,00 |
| IVT PRINETO | IV 16 × 2.2/17 × 2.8 | 150845 | 125,00 |
| | IV 20 × 2.8/21 × 3.4 | 150885 | 125,00 |
| | IV 25 × 3.5/26 × 4.0 | 150914 | 125,00 |
| | IV 32 × 4.4/33 × 4.9 | 150943 | 135,00 |
| REHAU RAUTHERM (série S 5) | RH 12 × 1.1 | 150812 | 125,00 |
| | RH 16 × 1.5 | 150846 | 125,00 |
| | RH 20 × 1.9 | 150886 | 125,00 |
| | RH 25 × 2.3 (RH HAS 25 × 2.3) | 150915 | 125,00 |
| | RH 32 × 2.9 (RH HAS 32 × 2.9) | 150944 | 125,00 |
| REHAU RAUTHERM S (REHAU HAS) | RH HAS 17 × 2.0 | 150868 | 125,00 |
| | RH HAS 20 × 2.0 | 150887 | 125,00 |
| | RH HAS 25 × 2.3 | 150915 | 125,00 |
| | RH HAS 32 × 2.9 | 150944 | 125,00 |
| REHAU RAUTITAN flex/ RAUTITAN gas flex/ RAUTITAN pink/ RAUTITAN his | RH HIS 16 × 2.2 | 150849 | 125,00 |
| | RH HIS 20 × 2.8 | 150888 | 125,00 |
| | RH HIS 25 × 3.5 | 150916 | 125,00 |
| | RH HIS 32 × 4.4 | 150945 | 125,00 |
| | RH HIS 40 × 5.5 | 150946 | 135,00 |
| REHAU RAUTITAN stabil/ RAUTITAN gas stabil | RH MKV 16.2 × 2.6 | 150858 | 125,00 |
| | RH MKV 20 × 2.9 | 150897 | 125,00 |
| | RH MKV 25 × 3.7 | 150926 | 125,00 |
| | RH MKV 32 × 4.7 | 150952 | 125,00 |
| | RH MKV 40 × 6.0 | 150947 | 135,00 |
| REHAU (GBR) EVERLOC | RH 16 × 1.5 | 150846 | 125,00 |
| | RH 20 × 1.9 | 150886 | 125,00 |
| | RH 25 × 2.3 (RH HAS 25 × 2.3) | 150915 | 125,00 |
| | RH 32 × 2.9 (RH HAS 32 × 2.9) | 150944 | 125,00 |
| REVEL | RH HIS 16 × 2.2 | 150849 | 125,00 |
| | RH HIS 20 × 2.8 | 150888 | 125,00 |
| | RH HIS 25 × 3.5 | 150916 | 125,00 |
| | RH HIS 32 × 4.4 | 150945 | 125,00 |
| Seppelfricke SD Sistemi Italia Neroflex | RH HIS 16 × 2.2 | 150849 | 125,00 |
| | RH HIS 20 × 2.8 | 150888 | 125,00 |
| | RH HIS 25 × 3.5 | 150916 | 125,00 |
| | RH HIS 32 × 4.4 | 150945 | 125,00 |
| Seppelfricke SD Sistemi Italia Sylver | RH MKV 16.2 × 2.6 | 150858 | 125,00 |
| | RH MKV 20 × 2.9 | 150897 | 125,00 |
| | RH MKV 25 × 3.7 | 150926 | 125,00 |
| | RH MKV 32 × 4.7 | 150952 | 125,00 |
| TECE TECEflex | TC 12/14 | 150826 | 125,00 |
| | TC 16 | 150855 | 125,00 |
| | TC 18/20 | 150894 | 125,00 |
| | TC 25 | 150923 | 125,00 |
| | TC 32 | 150950 | 125,00 |
| TIEMME Serie 3430 Assialpex | RH HIS 16 × 2.2 | 150849 | 125,00 |
| | RH HIS 20 × 2.8 | 150888 | 125,00 |
| | RH HIS 25 × 3.5 | 150916 | 125,00 |
| | RH HIS 32 × 4.4 | 150945 | 125,00 |

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.

Accessories for REMS pipe expander and other makes

Choose expander heads yourself!

Search for the required compression sleeve system in the table below and select the correct expander heads.



German Quality Product

REMS expander heads P

Complete assortment of REMS expander heads P for all common compression sleeve systems. Quickly interchangeable, without tools. The REMS expander heads are system-specific and comply with the requirements of the respective compression sleeve system. Thus perfect system-conformity, exact expanding. Conical angle 18°. Driven by REMS Ex-Press P hand pipe expander (page 273), REMS Ex-Press P 22 V ACC cordless pipe expander (page 274–275) and by suitable pipe expanders of other makes.

| Compression sleeve system | Expander head P Ø × s | Art.-No. | € |
|---------------------------|-----------------------|----------|---------------|
| Würth PRINETO | IV 16 × 2.2/17 × 2.8 | 150845 | 125,00 |
| | IV 20 × 2.8/21 × 3.4 | 150885 | 125,00 |
| | IV 25 × 3.5/26 × 4.0 | 150914 | 125,00 |
| | IV 32 × 4.4/33 × 4.9 | 150943 | 135,00 |

System-specific and/or national differences of the wall thickness (s) of tubes need to be considered selecting expander heads. REMS expander heads P for additional compression sleeve systems on request.



REMS expander heads P-CEF

Full range of REMS P-CEF expander heads for easy expanding of pipes/rings. Quick-change, without tools. The REMS P-CEF expander heads are system-specific and correspond to the requirements of the respective systems. Therefore, perfectly system-conformant, exact expanding. Conical angle 20°. Driven by REMS Ex-Press P-CEF 22 V ACC cordless pipe expander (page 274–275), REMS Power-Ex-Press P-CEF ACC electro-hydraulic pipe expander (page 276) and by suitable pipe expanders of other makes.

| Compression sleeve system | Expander head P-CEF Ø × s | Art.-No. | € |
|--------------------------------|---------------------------|----------|---------------|
| Giacomini GX System | P-CEF 16 × 1.8 | 150960R | 135,00 |
| | P-CEF 20 × 1.9 | 150961R | 135,00 |
| | P-CEF 25 × 2.3 | 150962R | 135,00 |
| | P-CEF 32 × 2.9 | 150963R | 135,00 |
| | P-CEF 40 × 3.7 | 150968R | 148,00 |
| | | | |
| Uponor Quick & Easy | P-CEF 16 × 1.8 | 150960R | 135,00 |
| | P-CEF 20 × 1.9 | 150961R | 135,00 |
| | P-CEF 25 × 2.3 | 150962R | 135,00 |
| | P-CEF 32 × 2.9 | 150963R | 135,00 |
| | P-CEF 40 × 3.7 | 150968R | 148,00 |
| | | | |

Expander drive P-CEF (taper angle 20°), for holding the P-CEF expander heads 16–40 mm, ½–1½"

System-related and/or national differences of the wall thickness s of the pipes must be considered in the selection of the expander heads.