

for all common pressfitting systems

**Select REMS pressing tongs Mini/  
REMS pressing rings yourself!**

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 183) required for driving REMS pressing rings. All pressing rings S (PR-2B) marked with \*\* can also be driven with the manual radial press REMS Eco-Press (page 185) using the adapter tong Z8.

Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

**REMS pressing tongs Mini (PZ-2B)**

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFlz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

**REMS pressing ring S (PR-2B)**

REMS pressing ring S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 183.

**Traceability according to EN 1775:2007**

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



German Quality Product



REMS Mini pressing tongs (PZ-2B)



REMS pressing ring S (PR-2B), continuously swivellable


**Confirmation of suitability**

See page 239.


**Hold-Harmless and Indemnification Agreement**

See page 240.





Pressing tongs with teeth prevent formation of burr on the pressfitting. Patent EP 2 027 971



Example REMS pressing tongs Mini V: "V" imprint on pressed fitting for traceability according to EN 1775:2007

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
<b>A</b>										
Aalberts integrated piping systems VSH MultiPress	U 14		578372	174,38	Aalberts integrated piping systems VSH XPress Copper	M 12		578310	146,98	
	U 16		578374	165,66		M 15		578312	146,98	
	U 20		578378	165,66		M 18 <sup>1)</sup>		578314	146,98	
	U 25		578380	165,66		M 22		578316	146,98	
	U 32		578382	194,31		M 28 <sup>1)</sup>		578318	146,98	
	U 40		578386	236,66		M 35		578390	178,12	
	TH 14		578348	177,08		M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	TH 16		578352 R	177,08		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	TH 20		578358 R	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	TH 25		578360	177,08		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	TH 32		578364	177,08		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	TH 40		578624	234,69		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51						
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		Aalberts integrated piping systems	M 15		578312	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		VSH XPress Copper	M 18 <sup>1)</sup>		578314	146,98
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		Gas	M 22		578316	146,98
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 28 <sup>1)</sup>			578318	146,98		
					M 35			578390	178,12	
Aalberts integrated piping systems VSH MultiPress Gas	U 16		578374	165,66	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		
	U 20		578378	165,66	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		
	U 25		578380	165,66	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		
	TH 16		578352 R	177,08	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		
	TH 20		578358 R	177,08	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51						
Aalberts integrated piping systems	V 12		578324	146,98	VSH XPress Stainless	M 22		578316	146,98	
VSH SudoPress Carbon	V 15		578328	146,98		M 28 <sup>1)</sup>		578318	146,98	
V 18		578332	146,98	M 35		578390	178,12			
V 22		578334	146,98	M 15 S (PR-2B)	Mini Z8	574738 R	124,51			
V 28		578336	146,98	M 18 S (PR-2B)	Mini Z8	574740 R	124,51			
V 35		578604	178,12	M 22 S (PR-2B)	Mini Z8	574742 R	124,51			
V 12 S (PR-2B)	Mini Z8	574748 R	124,51	M 28 S (PR-2B)	Mini Z8	574744 R	124,51			
V 15 S (PR-2B)	Mini Z8	574752 R	124,51	M 35 S (PR-2B)	Mini Z8	574746 R	136,96			
V 18 S (PR-2B)	Mini Z8	574756 R	124,51							
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	Aalberts integrated piping systems	M 15		578312	146,98		
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	VSH XPress Stainless	M 18 <sup>1)</sup>		578314	146,98		
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	Gas	M 22		578316	146,98		
					M 28 <sup>1)</sup>		578318	146,98		
					M 35		578390	178,12		
Aalberts integrated piping systems VSH SudoPress Copper	V 12		578324	146,98	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		
	V 14		578326	146,98	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		
	VG 14		578338	146,98	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		
	V 15		578328	146,98	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		
	V 16		578330	146,98	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		
	VG 16		578340	146,98						
	V 18		578332	146,98	AC-FIX PRESS (Global Piping Systems)	H 12		578396	159,75	
	V 22		578334	146,98	H 16		578400	159,75		
	V 28		578336	146,98	H 20		578406	159,75		
	V 35		578604	178,12	H 25		578408	159,75		
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	H 32		578412	159,75		
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51	RfZ 12		578490	184,45		
	VG 14 S (PR-2B)	Mini Z8	574750 R	124,51	RfZ 16		578492	184,45		
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	RfZ 20		578494	184,45		
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51	RfZ 25		578496	184,45		
	VG 16 S (PR-2B)	Mini Z8	574754 R	124,51	RfZ 32		578498	184,45		
V 18 S (PR-2B)	Mini Z8	574756 R	124,51	U 16		578374	165,66			
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	U 20		578378	165,66			
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	U 25		578380	165,66			
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	U 32		578382	194,31			
Aalberts integrated piping systems VSH SudoPress Copper Gas	V 12		578324	146,98	VX 16		578552	204,17		
	V 14		578326	146,98	VX 20		578554	204,17		
	VG 14		578338	146,98	AC-FIX PRESS DUO (Global Piping Systems)	RfZ 16		578492	184,45	
	V 15		578328	146,98	RfZ 20		578494	184,45		
	V 16		578330	146,98	RfZ 25		578496	184,45		
	VG 16		578340	146,98	RfZ 32		578498	184,45		
	V 18		578332	146,98	TH 16		578352 R	177,08		
	V 22		578334	146,98	TH 20		578358 R	177,08		
	V 28		578336	146,98	TH 25		578360	177,08		
	V 35		578604	178,12	TH 26		578362 R	177,08		
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	TH 32		578364	177,08		
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
	VG 14 S (PR-2B)	Mini Z8	574750 R	124,51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
	VG 16 S (PR-2B)	Mini Z8	574754 R	124,51	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
V 18 S (PR-2B)	Mini Z8	574756 R	124,51	U 16		578374	165,66			
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	U 20		578378	165,66			
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	U 25		578380	165,66			
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	U 32		578382	194,31			
Aalberts integrated piping systems VSH SudoPress Stainless	V 15		578328	146,98	AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400	159,75	
	V 18		578332	146,98	H 18		578404	159,75		
	V 22		578334	146,98	H 20		578406	159,75		
	V 28		578336	146,98	H 25		578408	159,75		
	V 35		578604	178,12	H 32		578412	159,75		
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	RfZ 16		578492	184,45		
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	RfZ 20		578494	184,45		
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	RfZ 25		578496	184,45		
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	U 16		578374	165,66		
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	U 18		578376	165,66			
Aalberts integrated piping systems VSH XPress Carbon	M 12		578310	146,98	U 20		578378	165,66		
	M 15		578312	146,98	U 25		578380	165,66		
	M 18 <sup>1)</sup>		578314	146,98	U 32		578382	194,31		
	M 22		578316	146,98						
	M 28 <sup>1)</sup>		578318	146,98	ACOME MT	AcZ 12		578608	184,45	
	M 35		578390	178,12	AcZ 16		578610	184,45		
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	AcZ 20		578612	184,45		
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	AcZ 25		578614	184,45		
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51						
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51						
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
AHLSSELL A-press elföorzinkad M	M 12		578310	146,98	ALB	TH 16		578352 R	177,08
	M 15		578312	146,98	Sistema Multicapa	TH 18		578356	177,08
	M 18		578314	146,98	para calefacción y sanitario	TH 20		578358 R	177,08
	M 22		578316	146,98		TH 26		578362 R	177,08
	M 28		578318	146,98		TH 32		578364	177,08
	M 35		578390	178,12		TH 40		578624	234,69
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		H 16		578400	159,75
AHLSSELL A-press elföorzinkad V	V 12		578324	146,98		H 18		578404	159,75
	V 15		578328	146,98		H 20		578406	159,75
	V 18		578332	146,98		H 26		578410	159,75
	V 22		578334	146,98		H 32		578412	159,75
	V 28		578336	146,98		U 16		578374	165,66
	V 35		578604	178,12		U 18		578376	165,66
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		U 20		578378	165,66
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		U 26 <sup>1)</sup>		578392	194,31
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		U 32		578382	194,31
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 40		578386	236,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51					
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	ALB	TH 16		578352 R	177,08
AHLSSELL A-press koppar M	M 12		578310	146,98	Sistema Multicapa	TH 20		578358 R	177,08
	M 15		578312	146,98	para gas	TH 26		578362 R	177,08
	M 18		578314	146,98		TH 32		578364	177,08
	M 22		578316	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 28		578318	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 35		578390	178,12		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		H 16		578400	159,75
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		H 20		578406	159,75
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		H 26		578410	159,75
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		H 32		578412	159,75
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		U 16		578374	165,66
AHLSSELL A-press koppar V	V 12		578324	146,98		U 18		578376	165,66
	V 15		578328	146,98		U 20		578378	165,66
	V 18		578332	146,98		U 26 <sup>1)</sup>		578392	194,31
	V 22		578334	146,98		U 32		578382	194,31
	V 28		578336	146,98					
	V 35		578604	178,12	ALTECH Altech	RFz 12		578490	184,45
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		RFz 16		578492	184,45
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		RFz 20		578494	184,45
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		RFz 25		578496	184,45
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	APE MULTYGAS	TH 16		578352 R	177,08
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	Serie AP Gas	TH 20		578358 R	177,08
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		TH 26		578362 R	177,08
AHLSSELL A-press rostfritt	M 15		578312	146,98		TH 32		578364	177,08
	M 18		578314	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 22		578316	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 28		578318	146,98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 35		578390	178,12		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	APE Serie AP	B 16		578468	193,28
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		B 20		578472	193,28
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		B 26		578474	213,00
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		H 16		578400	159,75
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		H 20		578406	159,75
AIRBEL PRESSCLIM	M 15		578312	146,98		H 26		578410	159,75
	M 18		578314	146,98		H 32		578412	159,75
	M 22		578316	146,98		TH 16		578352 R	177,08
	M 28		578318	146,98		TH 18		578356	177,08
	M 35		578390	178,12		TH 20		578358 R	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 26		578362 R	177,08
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 32		578364	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
AIRBEL SERTINOX	M 15		578312	146,98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	M 18		578314	146,98		U 16		578374	165,66
	M 22		578316	146,98		U 20		578378	165,66
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
APE Serie APL	H 16		578400	159,75	ASSOTHERM IPI-RAX Inox	M 15		578312	146,98	
	H 18		578404	159,75		M 18		578314	146,98	
	H 20		578406	159,75		M 22		578316	146,98	
	H 25		578408	159,75		M 28		578318	146,98	
	H 26		578410	159,75		M 35		578390	178,12	
	H 32		578412	159,75		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	TH 16		578352 R	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	TH 18		578356	177,08		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	TH 20		578358 R	177,08		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	TH 25		578360	177,08		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	TH 26		578362 R	177,08						
	TH 32		578364	177,08		ASSOTHERM	M 15		578312	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		IPI-RAX	M 18		578314	146,98
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51		Inox Gas	M 22		578316	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 28		578318	146,98	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		M 35		578390	178,12	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	U 16		578374	165,66		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	U 18		578376	165,66		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	U 20		578378	165,66		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
AQUATECHNIK Press-fitting metal	H 16		578400	159,75	ASSOTHERM IPM-Multistrato	H 16		578400	159,75	
	H 20		578406	159,75		H 20		578406	159,75	
	H 26		578410	159,75		H 26		578410	159,75	
	H 32		578412	159,75		H 32		578412	159,75	
	TH 16		578352 R	177,08		TH 16		578352 R	177,08	
	TH 20		578358 R	177,08		TH 20		578358 R	177,08	
	TH 26		578362 R	177,08		TH 26		578362 R	177,08	
	TH 32		578364	177,08		TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		THL 32		578368	177,08	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 40		578624	234,69	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	U 16		578374	165,66		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	U 20		578378	165,66		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 26 <sup>7)</sup>		578392	194,31		U 16		578374	165,66	
U 32		578382	194,31	U 20		578378	165,66			
AQUATECHNIK Universal	B 16		578468	193,28	ASSOTHERM IPR-RA Copper	U 26 <sup>7)</sup>		578392	194,31	
	B 20		578472	193,28		U 32		578382	194,31	
	B 26		578474	213,00		M 15		578312	146,98	
	B 32		578476	213,00		M 18		578314	146,98	
	F 16		578456	168,68		M 22		578316	146,98	
	F 20		578460	168,68		M 28		578318	146,98	
	F 26		578462	182,48		M 35		578390	178,12	
	F 32		578464	182,48		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	H 16		578400	159,75		ASSOTHERM	M 15		578312	146,98
	H 20		578406	159,75		IPR-RA	M 18		578314	146,98
	H 26		578410	159,75		Copper Gas	M 22		578316	146,98
	H 32		578412	159,75		M 28		578318	146,98	
	TH 16		578352 R	177,08		M 35		578390	178,12	
	TH 20		578358 R	177,08		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	TH 26		578362 R	177,08		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	TH 32		578364	177,08		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)	US 3/8"		578534	201,16
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		US 1/2"		578536	201,16	
	U 16		578374	165,66		US 3/4"		578538	201,16	
	U 20		578378	165,66		US 1"		578540	201,16	
	U 26 <sup>7)</sup>		578392	194,31		ATUSA ITALIA	M 15		578312	146,98
	U 32		578382	194,31		INSTALPRESS	M 18		578314	146,98
ARKA DUROsystem	H 16		578400	159,75	CARBON STEEL	M 22		578316	146,98	
	H 20		578406	159,75	M 28		578318	146,98		
	H 25		578408	159,75	PRESS FITTINGS	M 35		578390	178,12	
	H 26		578410	159,75	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		
	H 32		578412	159,75	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		
	TH 16		578352 R	177,08	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		
	TH 20		578358 R	177,08	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		
	TH 25		578360	177,08	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		
	TH 26		578362 R	177,08	ATUSA ITALIA	M 15		578312	146,98	
	TH 32		578364	177,08	INSTALPRESS	M 18		578314	146,98	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	STAINLESS STEEL	M 22		578316	146,98	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	PRESS FITTINGS	M 28		578318	146,98	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	M 35		578390	178,12		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		
	U 16		578374	165,66	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		
	U 20		578378	165,66	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		
	Aschl NIR	M 15		578312	146,98	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
		M 18		578314	146,98	AUSTEC	TH 16		578352 R	177,08
M 22			578316	146,98	PEX-B, PEX-AL-PEX (AUS)	TH 20		578358 R	177,08	
M 28			578318	146,98	TH 25		578360	177,08		
M 35			578390	178,12	TH 32		578364	177,08		
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	U 16		578374	165,66		
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	U 20		578378	165,66		
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	U 25		578380	165,66		
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	U 32		578382	194,31		
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	AUSTEC	TH 16		578352 R	177,08	
ASSOTHERM IPC-RAC Carbon Steel		M 15		578312	146,98	PEX-AL-PEX GAS (AUS)	TH 20		578358 R	177,08
	M 18		578314	146,98	TH 25		578360	177,08		
	M 22		578316	146,98	TH 32		578364	177,08		
	M 28		578318	146,98	U 16		578374	165,66		
	M 35		578390	178,12	U 20		578378	165,66		
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	U 25		578380	165,66		
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	U 32		578382	194,31		
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51						
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						



System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
AYOR FIXOCONNECT Press	H 12		578396	159,75	Bampi BALPEX Gas	TH 16		578352 R	177,08	
	H 16		578400	159,75		TH 20		578358 R	177,08	
	H 20		578406	159,75		TH 26		578362 R	177,08	
	H 25		578408	159,75		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	RFz 12		578490	184,45		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	RFz 16		578492	184,45		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	RFz 20		578494	184,45		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	RFz 25		578496	184,45		U 16		578374	165,66	
	U 16		578374	165,66		U 20		578378	165,66	
	U 20		578378	165,66		U 25		578380	165,66	
	U 25		578380	165,66		BARBI EASYPRESS (Industrial Blansol)	H 12		578396	159,75
	AYOR FIXOMULTIX	H 16		578400			159,75	H 16		578400
H 20			578406	159,75	H 20			578406	159,75	
H 26			578410	159,75	H 25			578408	159,75	
H 32			578412	159,75	H 32			578412	159,75	
TH 16			578352 R	177,08	RFz 12			578490	184,45	
TH 20			578358 R	177,08	RFz 16			578492	184,45	
TH 26			578362 R	177,08	RFz 20			578494	184,45	
TH 32			578364	177,08	RFz 25			578496	184,45	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	RFz 32			578498	184,45	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	U 16			578374	165,66	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124,51	U 20			578378	165,66	
TH 32 S (PR-2B)		Mini Z8	574798 R	136,96	U 25		578380	165,66		
U 16		578374	165,66	U 32		578382	194,31			
U 20		578378	165,66	BARBI MULTIPEX (Industrial Blansol)	H 14		578398	159,75		
AYOR SOMATHERM FOR YOU -1	H 16		578400		159,75	H 16		578400	159,75	
	H 20		578406		159,75	H 18		578404	159,75	
	H 26		578410		159,75	H 20		578406	159,75	
	TH 16		578352 R		177,08	H 25		578408	159,75	
	TH 20		578358 R		177,08	H 26		578410	159,75	
	TH 26		578362 R		177,08	H 32		578412	159,75	
	TH 16 S (PR-2B)**	Mini Z8	574782 R		124,51	RFz 16		578492	184,45	
	TH 20 S (PR-2B)**	Mini Z8	574788 R		124,51	RFz 18		578638	184,45	
	TH 26 S (PR-2B)**	Mini Z8	574794 R		124,51	RFz 20		578494	184,45	
	U 16		578374		165,66	RFz 25		578496	184,45	
	U 20		578378		165,66	RFz 32		578498	184,45	
	AYOR SOMATHERM FOR YOU -2	H 12		578396	159,75	TH 16		578352 R	177,08	
H 16			578400	159,75	TH 20		578358 R	177,08		
H 20			578406	159,75	TH 26		578362 R	177,08		
H 25			578408	159,75	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
RFz 12			578490	184,45	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
RFz 16			578492	184,45	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
RFz 20			578494	184,45	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
RFz 25			578496	184,45	U 16		578374	165,66		
U 16			578374	165,66	U 18		578376	165,66		
U 20			578378	165,66	U 20		578378	165,66		
U 25			578380	165,66	U 25		578380	165,66		
<b>B</b>					BEGETUBE/ IVAR	B 14		578466	193,28	
Bampi BALPEX serie LP	TH 16		578352 R	177,08		B 16		578468	193,28	
	TH 18		578356	177,08		B 18		578470	193,28	
	TH 20		578358 R	177,08		B 20		578472	193,28	
	TH 26		578362 R	177,08		B 26		578474	213,00	
	TH 32		578364	177,08		B 32		578476	213,00	
	TH 40		578624	234,69		Béné inox Série 41	M 15		578312	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51			M 18		578314	146,98
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51			M 22		578316	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51			M 28		578318	146,98
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51			M 35		578390	178,12
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96			M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 16		578374	165,66	M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
U 18		578376	165,66	M 22 S (PR-2B)	Mini Z8		574742 R	124,51		
U 20		578378	165,66	M 28 S (PR-2B)	Mini Z8		574744 R	124,51		
U 26 <sup>7)</sup>		578392	194,31	M 35 S (PR-2B)	Mini Z8		574746 R	136,96		
U 32		578382	194,31	Brass Form Master-Al-Pex	H 16			578400	159,75	
Bampi BALPEX serie MP	TH 16		578352 R		177,08		H 18		578404	159,75
	TH 18		578356		177,08	H 20		578406	159,75	
	TH 20		578358 R		177,08	TH 16		578352 R	177,08	
	TH 26		578362 R		177,08	TH 18		578356 R	177,08	
	TH 32		578364		177,08	TH 20		578358 R	177,08	
	TH 40		578624		234,69	TH 26		578362 R	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R		124,51	TH 32		578364	177,08	
	TH 18 S (PR-2B)**	Mini Z8	574786 R		124,51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R		124,51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R		124,51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R		136,96	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
					TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
				U 16		578374	165,66			
				U 18		578376	165,66			
				U 20		578378	165,66			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Brass & Fittings PRESSMAN MultiPress	RFz 16		578492	184,45
	RFz 18		578638	184,45
	ACz 20		578612	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
Brass & Fittings PRESSMAN RetiPress	RFz 16		578492	184,45
	RFz 18		578638	184,45
	ACz 20		578612	184,45
	RFz 25		578496	184,45
	RFz 32		578498	184,45
BRASSTECH MULTItermoSAN	B 16		578468	193,28
	B 20		578472	193,28
Brasspress	B 26		578474	213,00
	B 32		578476	213,00
	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 <sup>7)</sup>		578392	194,31
U 32		578382	194,31	
<b>C</b>				
Cello Products -B>Press	VUS ½" (OD 15,9 mm)		578566	177,50
	VUS ¾" (OD 22,2 mm)		578568	177,50
	VUS 1" (OD 28,6 mm)		578570	177,50
	VUS 1¼" (OD 34,9 mm)		578606	177,50
CGR DYNAFLU multicouche	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 26 <sup>7)</sup>		578392	194,31
U 32		578382	194,31	
U 40		578386	236,66	
CGR DYNAFLU PER	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	RFz 12		578490	184,45
	RFz 16		578492	184,45
	RFz 20		578494	184,45
	RFz 25		578496	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
CHIALI CHIALIPEX	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	H 16		578400	159,75
	H 20		578406	159,75
	U 16		578374	165,66
Climatrix Climatrix Rhinopex	U 20		578378	165,66
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Climatrix	TH 11,6		578344	177,08	
	Variotherm		578352 R	177,08	
System TH	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	ClouSet		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	Comap	RFz 12		578490	184,45
	PEX Press	RFz 16		578492	184,45
RFz 20			578494	184,45	
RFz 25			578496	184,45	
Comap Multiskin	TH 14		578348	177,08	
	TH 16		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	THL 32		578368	177,08	
	TH 40		578624	234,69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 14		578372	174,38	
	U 16		578374	165,66	
U 18		578376	165,66		
U 20		578378	165,66		
U 32		578382	194,31		
H 14		578398	159,75		
H 16		578400	159,75		
H 18		578404	159,75		
H 20		578406	159,75		
H 26		578410	159,75		
H 32		578412	159,75		
Comap Multiskin Gas	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	THL 32		578368	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 16		578374	165,66	
	U 20		578378	165,66	
	U 32		578382	194,31	
	H 16		578400	159,75	
H 20		578406	159,75		
H 26		578410	159,75		
H 32		578412	159,75		
COMISA Press System	TH 14		578348	177,08	
	TH 16		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
H 14		578398	159,75		
H 16		578400	159,75		
H 18		578404	159,75		
H 20		578406	159,75		
H 26		578410	159,75		
H 32		578412	159,75		
B 14		578466	193,28		
B 16		578468	193,28		
B 18		578470	193,28		
B 20		578472	193,28		
B 26		578474	213,00		
B 32		578476	213,00		
COMISA Press System Gas	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
CONEL	M 15		578312	146,98	Conex Bänninger >B< Flex	F 16		578456	168,68
CONNECT INOX	M 18		578314	146,98		F 18		578458	168,68
	M 22		578316	146,98		F 20		578460	168,68
	V 15		578328	146,98		F 32		578464	182,48
	V 18		578332	146,98		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	V 22		578334	146,98		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
CONEL	F 16		578456	168,68		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
CONNECT	F 20		578460	168,68		H 16		578400	159,75
MULTI  (DN 26)	F 26		578462	182,48		H 18		578404	159,75
	F 32		578464	182,48		H 20		578406	159,75
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		H 25		578408	159,75
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		H 32		578412	159,75
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		RFz 16		578492	184,45
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96	RFz 18		578638	184,45	
	H 16		578400	159,75	RFz 20		578494	184,45	
	H 20		578406	159,75	RFz 25		578496	184,45	
	H 26		578410	159,75	RFz 32		578498	184,45	
	H 32		578412	159,75	TH 16		578352 R	177,08	
	TH 16		578352 R	177,08	TH 18		578356	177,08	
	TH 20		578358 R	177,08	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	TH 25		578360	177,08	
	TH 32		578364	177,08	TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 16		578374	165,66	U 16		578374	165,66	
	U 20		578378	165,66	U 18		578376	165,66	
	U 25		578380	165,66	U 20		578378	165,66	
	U 32		578382	194,31	U 25		578380	165,66	
	VP 16		578482	176,56	U 32		578382	194,31	
VP 20		578484	176,56	Conex Bänninger >B< Flex Gas	F 16		578456	168,68	
VP 32		578488	195,25		F 18		578458	168,68	
CONEL	F 16		578456		168,68	F 20		578460	168,68
CONNECT	F 20		578460		168,68	F 32		578464	182,48
MV2	F 26		578462		182,48	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 32		578464		182,48	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 16 S (PR-2B)**	Mini Z8	574728 R		124,51	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	F 20 S (PR-2B)**	Mini Z8	574730 R		124,51	H 16		578400	159,75
	F 26 S (PR-2B)**	Mini Z8	574732 R		124,51	H 18		578404	159,75
	F 32 S (PR-2B)**	Mini Z8	574734 R		136,96	H 20		578406	159,75
	TH 16		578352 R		177,08	H 25		578408	159,75
	TH 20		578358 R		177,08	H 32		578412	159,75
	TH 26		578362 R		177,08	RFz 16		578492	184,45
	TH 32		578364	177,08	RFz 18		578638	184,45	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	RFz 20		578494	184,45		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	RFz 25		578496	184,45		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	RFz 32		578498	184,45		
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	TH 16		578352 R	177,08		
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TH 18		578356	177,08		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	TH 20		578358 R	177,08		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 25		578360	177,08		
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	TH 32		578364	177,08		
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
CONEX BÄNNINGER	M 15		578312	146,98	U 16		578374	165,66	
<A> Press Inox (304)	M 18		578314	146,98	U 18		578376	165,66	
	M 22		578316	146,98	U 20		578378	165,66	
	M 28		578318	146,98	U 25		578380	165,66	
	M 35		578390	178,12	U 32		578382	194,31	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	BMP ¼"		578700	175,53	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	BMP ⅜"		578702	175,53	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	BMP ½"		578704	175,53	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	BMP ¾"		578706	175,53	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	BMP 1"		578708	175,53	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	BMP ⅝"		578710	175,53	
CONEX BÄNNINGER	M 15		578312	146,98	BMP 1 1/8"		578712	175,53	
<A> Press Inox (316L)	M 18		578314	146,98	BMP 1 1/4"		578714	175,53	
	M 22		578316	146,98					
	M 28		578318	146,98					
	M 35		578390	178,12					
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51					
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51					
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51					
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51					
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96					

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Conex Bänninger >B< Press	V 12		578324	146,98	
	V 14		578326	146,98	
	V 15		578328	146,98	
	V 16		578330	146,98	
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	M 15		578312	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	Conex Bänninger >B< Press Carbon	V 15		578328	146,98
		V 18		578332	146,98
		V 22		578334	146,98
V 28			578336	146,98	
V 35			578604	178,12	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
Conex Bänninger >B< Press Gas		V 12		578324	146,98
		V 14		578326	146,98
		V 15		578328	146,98
		V 16		578330	146,98
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	Conex Bänninger >B< Press Inox	V 15		578328	146,98
		V 18		578332	146,98
		V 22		578334	146,98
		V 28		578336	146,98
V 35			578604	178,12	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
Conex Bänninger >B< Press Solar		V 12		578324	146,98
		V 14		578326	146,98
		V 15		578328	146,98
		V 16		578330	146,98
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
<b>D</b>					
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310	146,98	
	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	DUOPIPE SYSTEMS DUOFIL MKSYSTEM	U 16		578374	165,66
		U 18		578376	165,66
U 20			578378	165,66	
U 25			578380	165,66	
U 32			578382	194,31	
DW Verbundrohr multitubo systems		U 16		578374	165,66
	U 18		578376	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
<b>E</b>				
EBRILLE Isomomflex	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	H 26		578410	159,75
	TH 26		578362 R	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EBRILLE Monflex	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	H 26		578410	159,75
	TH 26		578362 R	177,08
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EFFEBI	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
EFFEBI-PRESS	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	V 12		578324	146,98
	V 15		578328	146,98
Aisi316 System M Profile <sup>1)</sup>	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
EFFEBI	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	M 12		578310	146,98
	M 15		578312	146,98
EFFEBI-PRESS Carbon-S System M Profile <sup>1)</sup>	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
EFFEBI	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	V 12		578324	146,98
	V 15		578328	146,98
EFFEBI-PRESS Carbon-S System V Profile	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
EFFEBI	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	V 12		578324	146,98
	V 14		578326	146,98
EFFEBI-PRESS COPPER	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
EFFEBI EFFEBI-PRESS UNICO	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
	V 12		578324	146,98
	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
EFFEBI	V 12		578324	146,98	EFFEBI	TH 16		578352 R	177,08
EFFEBI-PRESS	V 15		578328	146,98	TOF	TH 18		578356	177,08
UNICO	V 18		578332	146,98	MULTIPINZA	TH 20		578358 R	177,08
(GAS)	V 22		578334	146,98		TH 25		578360	177,08
	V 28		578336	146,98		TH 26		578362 R	177,08
	V 35		578604	178,12		TH 32		578364	177,08
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		TH 40		578624	234,69
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
EFFEBI	M 15		578312	146,98		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
PRESSTIGE	M 18		578314	146,98		F 16		578456	168,68
	M 22		578316	146,98		F 18		578458	168,68
	M 28		578318	146,98		F 20		578460	168,68
	M 35		578390	178,12		F 26		578462	182,48
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		F 32		578464	182,48
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		Fz 40		578478	247,15
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	V 15		578328	146,98		F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	V 18		578332	146,98		H 16		578400	159,75
	V 22		578334	146,98		H 18		578404	159,75
	V 28		578336	146,98		H 20		578406	159,75
	V 35		578604	178,12		H 25		578408	159,75
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		H 26		578410	159,75
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		H 32		578412	159,75
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 16		578374	165,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		U 18		578376	165,66
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		U 20		578378	165,66
EFFEBI	M 15		578312	146,98		U 25		578380	165,66
PRESSTIGE 4E05	M 18		578314	146,98		U 26 <sup>1)</sup>		578392	194,31
	M 22		578316	146,98		U 32		578382	194,31
	M 28		578318	146,98		U 40		578386	236,66
	M 35		578390	178,12		B 16		578468	193,28
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		B 18		578470	193,28
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		B 20		578472	193,28
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		B 26		578474	213,00
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		B 32		578476	213,00
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	EFIELD	U 16		578374	165,66
EFFEBI	M 15		578312	146,98	MULTILAYER PRESS	U 18		578376	165,66
PRESSTIGE-GAS	M 18		578314	146,98	DINGAS	U 20		578378	165,66
	M 22		578316	146,98		U 25		578380	165,66
	M 28		578318	146,98		U 32		578382	194,31
	M 35		578390	178,12	EFIELD	U 16		578374	165,66
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	MULTILAYER PRESS	U 18		578376	165,66
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	WATER	U 20		578378	165,66
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		U 25		578380	165,66
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		U 32		578382	194,31
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	Elkhart	VUS 1/2" (OD 15,9 mm)		578566	177,50
	V 15		578328	146,98	APOLLOXPRESS	VUS 3/4" (OD 22,2 mm)		578568	177,50
	V 18		578332	146,98	Fittings Copper	VUS 1" (OD 28,6 mm)		578570	177,50
	V 22		578334	146,98	and Low-Lead Brass	VUS 1 1/4" (OD 34,9 mm)		578606	177,50
	V 28		578336	146,98	EMMETI	B 16		578468	193,28
	V 35		578604	178,12	GERPEX-	B 20		578472	193,28
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	FIVPRESS	B 26		578474	213,00
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		B 32		578476	213,00
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		F 16		578456	168,68
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		F 20		578460	168,68
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		H 16		578400	159,75
EFFEBI	TH 16		578352 R	177,08		H 20		578406	159,75
TOF-GAS	TH 20		578358 R	177,08		TH 16		578352 R	177,08
MULTIPINZA	TH 26		578362 R	177,08		TH 20		578358 R	177,08
	TH 32		578364	177,08		TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 32		578364	177,08
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 40		578624	234,69
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		U 16		578374	165,66
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		U 20		578378	165,66
	H 16		578400	159,75	EMPUR	TH 14		578348	177,08
	H 20		578406	159,75		TH 15		578350	177,08
	H 26		578410	159,75		TH 16		578352 R	177,08
	H 32		578412	159,75		TH 17		578354	177,08
	U 16		578374	165,66		TH 20		578358 R	177,08
	U 20		578378	165,66		TH 25		578360	177,08
	U 32		578382	194,31		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
						TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
						TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
						TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Esta Rohr simplesta SH M	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	Esta Rohr simplesta ST M	M 15		578312	146,98
		M 18		578314	146,98
		M 22		578316	146,98
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile <sup>1)</sup>		M 12		578310	146,98
		M 15		578312	146,98
		M 18		578314	146,98
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	EUROTUBI EUROPA Inox Pressfitting System M-Profile <sup>1)</sup>	M 15		578312	146,98
M 18			578314	146,98	
M 22			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
Evans Components		VAU 15 (½") (OD 12,7 mm)		578630	151,86
Presslok		VAU 20 (¾") (OD 19,1 mm)		578632	151,86
		VAU 25 (1") (OD 25,4 mm)		578634	151,86
<b>F</b>					
FAR Rubinetterie PRESSFAR	TH 14		578348	177,08	
	TH 16		578352 R	177,08	
	TH 17		578354	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	H 14		578398	159,75	
	H 16		578400	159,75	
	H 18		578404	159,75	
	H 20		578406	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	U 14		578372	174,38	
	U 16		578374	165,66	
	U 18		578376	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
	U 40		578386	236,66	
	F.B.Q. BARONIO BQ PRESS SOLAR	V 12		578324	146,98
		V 14		578326	146,98
		V 15		578328	146,98
		V 16		578330	146,98
		V 18		578332	146,98
		V 22		578334	146,98
		V 28		578336	146,98
		V 35		578604	178,12
		V 12 S (PR-2B)	Mini Z8	574748 R	124,51
		V 14 S (PR-2B)	Mini Z8	574800 R	124,51
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 16 S (PR-2B)		Mini Z8	574802 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
F.B.Q. BARONIO BQ PRESS WATER	V 12		578324	146,98
	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
F.B.Q. BARONIO BQ PRESS GAS	V 12		578324	146,98
	V 14		578326	146,98
	V 15		578328	146,98
	V 16		578330	146,98
	V 18		578332	146,98
	V 22		578334	146,98
	V 28		578336	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 14 S (PR-2B)	Mini Z8	574800 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 16 S (PR-2B)	Mini Z8	574802 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
FERCOFLOOR DUO Press FERCO PEX	RfZ 16		578492	184,45
	RfZ 20		578494	184,45
	RfZ 25		578496	184,45
	RfZ 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERCOFLOOR DUO Press MULTIFER	RfZ 16		578492	184,45
	RfZ 20		578494	184,45
	RfZ 25		578496	184,45
	RfZ 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERRO systems BRASELLI GPF GAS	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
FERRO systems BRASELLI GPF PPSU Pressfitting PEX y MULTICAPA	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	FERRO systems BRASELLI GPF PRESS Pressfitting PEX FILINOX Instalpress Steel	RfZ 16		578492
RfZ 20			578494	184,45
RfZ 25			578496	184,45
RfZ 32			578498	184,45
M 15			578312	146,98
M 18			578314	146,98
M 22			578316	146,98
M 28			578318	146,98
M 35			578390	178,12
M 15 S (PR-2B)		Mini Z8	574738 R	124,51
M 18 S (PR-2B)		Mini Z8	574740 R	124,51
M 22 S (PR-2B)		Mini Z8	574742 R	124,51
M 28 S (PR-2B)		Mini Z8	574744 R	124,51
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
FILINOX Instalpress Inox	M 15		578312	146,98	FORZA STAINLESS V PRESS (AUS)	V 15		578328	146,98	
	M 18		578314	146,98		V 22		578334	146,98	
	M 22		578316	146,98		V 28		578336	146,98	
	M 28		578318	146,98		V 35		578604	178,12	
	M 35		578390	178,12		V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		FRABO FRABOPRESS 316 GAS M	M 15		578312	146,98
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	M 18			578314	146,98		
				M 22			578316	146,98		
				M 28			578318	146,98		
				M 35			578390	178,12		
				M 15 S (PR-2B)	Mini Z8		574738 R	124,51		
				M 18 S (PR-2B)	Mini Z8		574740 R	124,51		
				M 22 S (PR-2B)	Mini Z8		574742 R	124,51		
				M 28 S (PR-2B)	Mini Z8		574744 R	124,51		
				M 35 S (PR-2B)	Mini Z8	574746 R	136,96			
FITTINGS ESTÁNDAR ECO-PRESS	RFz 16		578492	184,45	FRABO FRABOPRESS 316 GAS V	V 15		578328	146,98	
	RFz 20		578494	184,45		V 18		578332	146,98	
	RFz 25		578496	184,45		V 22		578334	146,98	
	RFz 32		578498	184,45		V 28		578336	146,98	
						V 35		578604	178,12	
						V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
FITTINGS ESTÁNDAR MULTICAPA	RFz 16		578492	184,45	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
	RFz 18		578638	184,45	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
	RFz 20		578494	184,45	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
	RFz 25		578496	184,45	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
	RFz 32		578498	184,45	FRABO FRABOPRESS 316 M	M 15		578312	146,98	
						M 18		578314	146,98	
				M 22			578316	146,98		
				M 28			578318	146,98		
				M 35			578390	178,12		
				M 15 S (PR-2B)		Mini Z8	574738 R	124,51		
				M 18 S (PR-2B)		Mini Z8	574740 R	124,51		
				M 22 S (PR-2B)		Mini Z8	574742 R	124,51		
				M 28 S (PR-2B)		Mini Z8	574744 R	124,51		
				M 35 S (PR-2B)	Mini Z8	574746 R	136,96			
FITTINGS ESTÁNDAR PE-X	RFz 16		578492	184,45	FRABO FRABOPRESS 316 V	V 12		578324	146,98	
	RFz 20		578494	184,45		V 15		578328	146,98	
	RFz 25		578496	184,45		V 18		578332	146,98	
	RFz 32		578498	184,45		V 22		578334	146,98	
						V 28		578336	146,98	
						V 35		578604	178,12	
FORNARA ForPress	B 16		578468	193,28	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		
	B 20		578472	193,28	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
	B 26		578474	213,00	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
	B 32		578476	213,00	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
	F 16		578456	168,68	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
	F 20		578460	168,68	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
	F 26		578462	182,48	FRABO FRABOPRESS CHROME	M 15		578312	146,98	
	F 32		578464	182,48		M 18		578314	146,98	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		M 22		578316	146,98	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		M 28		578318	146,98	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		M 35		578390	178,12	
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	H 16		578400	159,75		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	H 20		578406	159,75		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	H 26		578410	159,75		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	H 32		578412	159,75	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		
	TH 16		578352 R	177,08	FRABO FRABOPRESS C-STEEL M	V 12		578324	146,98	
	TH 20		578358 R	177,08		V 15		578328	146,98	
	TH 26		578362 R	177,08		V 18		578332	146,98	
	TH 32		578364	177,08		V 22		578334	146,98	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		V 28		578336	146,98	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		V 35		578604	178,12	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
U 16		578374	165,66	V 18 S (PR-2B)		Mini Z8	574756 R	124,51		
U 20		578378	165,66	V 22 S (PR-2B)	Mini Z8	574758 R	124,51			
U 26 <sup>7)</sup>		578392	194,31	V 28 S (PR-2B)	Mini Z8	574760 R	124,51			
U 32		578382	194,31	V 35 S (PR-2B)	Mini Z8	574762 R	136,96			
FORZA WATER CRIMP (AUS)	K16/P18		578592	184,45	FRABO FRABOPRESS C-STEEL V	V 12		578324	146,98	
	K/20		578594	184,45		V 15		578328	146,98	
	K/25		578596	184,45		V 18		578332	146,98	
	K32		578598	184,45		V 22		578334	146,98	
	K1/40		578600	184,45		V 28		578336	146,98	
FORZA STAINLESS WATER CRIMP	K16/P18		578592	184,45		V 35		578604	178,12	
	K/20		578594	184,45		V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	U 16		578374	165,66		V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	U 20		578378	165,66		V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	U 25		578380	165,66	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
FORZA STRESSO PEX WATER AND GAS CRIMP AUS)	U 32		578382	194,31	FRABO FRABOPRESS C-STEEL V	V 28		578336	146,98	
	U 40		578386	236,66		V 35		578604	178,12	
	FORZA GAS CRIMP (AUS)	K16/P18		578592		184,45	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
		K/20		578594		184,45	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
		K/25		578596		184,45	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
K32			578598	184,45		V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
K1/40			578600	184,45		V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
FORZA COPPER V PRESS (AUS)	VAU 15 (OD 12,7 mm)		578630	151,86		V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	VAU 20 (OD 19,1 mm)		578632	151,86		FRABO FRABOPRESS 316 GAS M	M 15		578312	146,98
	VAU 25 (OD 25,4 mm)		578634	151,86	M 18			578314	146,98	
	VAU 32 (OD 31,8 mm)		578636	159,75	M 22			578316	146,98	
	VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51	M 28			578318	146,98	
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51	M 35			578390	178,12	
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96	M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
					M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
					M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
				M 28 S (PR-2B)	Mini Z8		574744 R	124,51		
				M 35 S (PR-2B)	Mini Z8	574746 R	136,96			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

# Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
FRABO	M 12		578310	146,98
FRABOPRESS	M 15		578312	146,98
GAS M	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
FRABO	V 12		578324	146,98
FRABOPRESS	V 15		578328	146,98
GAS V	V 18		578332	146,98
	V 22		578336	146,98
	V 28		578338	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
FRABO	V 12		578324	146,98
FRABOPRESS	V 15		578328	146,98
KOMBI	V 18		578332	146,98
	V 22		578336	146,98
	V 28		578338	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
FRABO	M 12		578310	146,98
FRABOPRESS M	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
FRABO	V 15		578328	146,98
FRABOPRESS	V 18		578332	146,98
SOLAR	V 22		578336	146,98
	V 28		578338	146,98
	V 35		578604	178,12
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
FRABO	V 12		578324	146,98
FRABOPRESS V	V 15		578328	146,98
	V 18		578332	146,98
	V 22		578336	146,98
	V 28		578338	146,98
	V 35		578604	178,12
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96
Fränkische alpex-duo XS	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Fränkische	F 16		578456	168,68
alpex F50 PROF1	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)**	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
(DN 26)	U 25		578380	165,66
	U 32		578382	194,31
	VP 16		578482	176,56
	VP 20		578484	176,56
	VP 32		578488	195,25
Fränkische alpex L	Fz 40		578478	247,15

## G

gabotherm H+S	TH 10		578342	177,08
	TH 12		578346	177,08
	TH 14		578348	177,08
	TH 15		578350	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
Gallagher USA	H 12 (1/4")		578396	159,75
YogaPipe ACR	U 14 (3/8")		578372	174,38
	U 16 (1/2")		578374	165,66
	U 18 (5/8")		578376	165,66
	U 20 (3/4")		578378	165,66
	U 25 (7/8")		578380	165,66
	U 32 (1 1/8")		578382	194,31
Geberit Mapress C-STAHL	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Geberit Mapress C-STAHL Sprinkler nass	M 22		578316	146,98
	M 28		578318	146,98
Geberit Mapress Edelstahl	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96



# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Geberit Mapress Edelstahl Gas	M 15		578312	146,98	General Fittings Serie 5S00	B 16		578468	193,28	
	M 18		578314	146,98		B 18		578470	193,28	
	M 22		578316	146,98		B 20		578472	193,28	
	M 28		578318	146,98		B 26		578474	213,00	
	M 35		578390	178,12		B 32		578476	213,00	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		F 16		578456	168,68	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		F 20		578460	168,68	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		F 26		578462	182,48	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		F 32		578464	182,48	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	
Geberit Mapress Edelstahl Sprinkler	M 22		578316	146,98		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	
	M 28		578318	146,98		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	
Geberit Mapress Kupfer	M 12		578310	146,98		F 32 S (PR-2B)	Mini Z8	574734 R	136,96	
	M 15		578312	146,98		H 16		578400	159,75	
	M 18		578314	146,98		H 18		578404	159,75	
	M 22		578316	146,98		H 20		578406	159,75	
	M 28		578318	146,98		H 25		578408	159,75	
	M 35		578390	178,12		H 26		578410	159,75	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		H 32		578412	159,75	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16		578352 R	177,08	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 18		578356	177,08	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 20		578358 R	177,08	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 25		578360	177,08	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		TH 26		578362 R	177,08	
	Geberit Mapress Kupfer Gas	M 15		578312		146,98	TH 32		578364	177,08
		M 18		578314		146,98	TH 40		578624	234,69
		M 22		578316		146,98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
		M 28		578318		146,98	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
M 35			578390	178,12		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51		U 16		578374	165,66	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96		U 18		578376	165,66	
Geberit Mepla	G 16		578444	177,50		U 20		578378	165,66	
	G 20		578446	177,50		U 25		578380	165,66	
	G 26		578448	188,40		U 32		578382	194,31	
	G 32		578450	201,16		U 40		578386	236,66	
	G 40		578452	260,33		General Fittings Trident	H 16		578400	159,75
Geberit Mepla Therm	G 16		578444	177,50			H 20		578406	159,75
	G 20		578446	177,50	H 26			578410	159,75	
	G 26		578448	188,40	H 32			578412	159,75	
Geberit Volex	TH 16		578352 R	177,08	TH 16			578352 R	177,08	
	TH 20		578358 R	177,08	TH 20			578358 R	177,08	
	TH 26		578362 R	177,08	TH 26			578362 R	177,08	
General Fittings ST00	H 16		578400	159,75	TH 32			578364	177,08	
	H 20		578406	159,75	TH 40			578624	234,69	
	H 26		578410	159,75	TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	
	H 32		578412	159,75	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
	TH 16		578352 R	177,08	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
	TH 20		578358 R	177,08	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
	TH 26		578362 R	177,08	U 16		578374	165,66		
	TH 32		578364	177,08	U 20		578378	165,66		
	TH 40		578624	234,69	U 32		578382	194,31		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	General Fittings Trident Gas	H 16		578400	159,75	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		H 20		578406	159,75	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		H 26		578410	159,75	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 16		578352 R	177,08	
	U 16		578374	165,66		TH 20		578358 R	177,08	
U 20		578378	165,66	TH 26			578362 R	177,08		
U 32		578382	194,31	TH 32			578364	177,08		
U 40		578386	236,66	TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51		
General Fittings Ewoprex	H 16		578400	159,75		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	H 20		578406	159,75		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	H 26		578410	159,75	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
	H 32		578412	159,75	U 16		578374	165,66		
	TH 16		578352 R	177,08	U 20		578378	165,66		
	TH 20		578358 R	177,08	U 32		578382	194,31		
	TH 26		578362 R	177,08	Giacomini Raccordi RM Giacomini	U 40		578386	236,66	
	TH 32		578364	177,08		H 16		578400	159,75	
	TH 40		578624	234,69		H 20		578406	159,75	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		H 26		578410	159,75	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		H 32		578412	159,75	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		TH 16		578352 R	177,08	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 20		578358 R	177,08	
	U 16		578374	165,66		TH 26		578362 R	177,08	
U 20		578378	165,66	TH 32			578364	177,08		
U 32		578382	194,31	TH 40			578624	234,69		
U 40		578386	236,66	U 16		578374	165,66			

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Giacomini RM MULTIGAS	H 16		578400	159,75	
	H 20		578406	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	U 16		578374	165,66	
	U 20		578378	165,66	
	U 32		578382	194,31	
	Giacomini Valvole Giacomini serie R850V	V 15		578328	146,98
		V 18		578332	146,98
		V 22		578334	146,98
V 28			578336	146,98	
V 35			578604	178,12	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
SA 15			578514	176,56	
SA 18			578518	176,56	
SA 22			578520	176,56	
SA 28			578522	176,56	
M 15			578312	146,98	
M 18			578314	146,98	
M 22			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)	Mini Z8	574744 R	124,51		
M 35 S (PR-2B)	Mini Z8	574746 R	136,96		
Golan Pipe Systems (Scandinavia) Alu-Pres	U 16		578374	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
Grinnell G-PRESS Copper Fittings	U 40		578386	236,66	
	VUS ½" (OD 15,9 mm)		578566	177,50	
	VUS ¾" (OD 22,2 mm)		578568	177,50	
	VUS 1" (OD 28,6 mm)		578570	177,50	
	VUS 1½" (OD 34,9 mm)		578606	177,50	
GS Wärmesysteme System TH	TH 14		578348	177,08	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	
GS Wärmesysteme System V	V 15		578328	146,98	
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	<b>H</b>				
HASTINIK Hastinik/Hitpress	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	heima24	TH 16		578352 R	177,08
TH 20			578358 R	177,08	
TH 26			578362 R	177,08	
TH 32			578364	177,08	
TH 40			578624	234,69	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124,51	
TH 32 S (PR-2B)**		Mini Z8	574798 R	136,96	
U 16			578374	165,66	
U 20			578378	165,66	
U 32		578382	194,31		
HELIROMA Klimapress	U 16		578374	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
	U 40		578386	236,66	
HELIROMA Klimapress PPSU	U 16		578374	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
Henco	TH 14		578348	177,08	
	TH 16		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	HE 32		578370 R	212,06	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
Herotec tempusPRESS PLUS	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578412	159,75
	Rfz 16		578492	184,45
	Rfz 20		578494	184,45
	Rfz 25		578496	184,45
	Rfz 32		578498	184,45
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96
Herotec tempusPRESS PLUS PPSU	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	
HERZ PIPEFIX	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	TH 10		578342	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51	
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	
HIDRONIX MULTIGAS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
HIDRONIX MULTIPIPE	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	H 14		578398	159,75
	H 16		578400	159,75
H 18		578404	159,75	
H 20		578406	159,75	
H 26		578410	159,75	
H 32		578412	159,75	
U 14		578372	174,38	
U 16		578374	165,66	
U 18		578376	165,66	
U 20		578378	165,66	
U 26 <sup>1)</sup>		578392	194,31	
U 32		578382	194,31	
HIDRONIX UNICO	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 14		578372	174,38
	U 16		578374	165,66
U 18		578376	165,66	
U 20		578378	165,66	
U 26 <sup>1)</sup>		578392	194,31	
U 32		578382	194,31	
HITEC Sistema Multistrato	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	
HITHERM-ISOTUBI NUMEPRESS	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
HITHERM-ISOTUBI HTpress	M 15		578312	146,98	ICMA Sempigas	TH 16		578352 R	177,08	
	M 18		578314	146,98		TH 20		578358 R	177,08	
	M 22		578316	146,98		TH 25		578360	177,08	
	M 28		578318	146,98		TH 26		578362 R	177,08	
	M 35		578390	178,12		TH 32		578364	177,08	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						
HITHERM-ISOTUBI HTfire	M 15		578312	146,98	Idrosanitaria Bonomi Homegas	TH 16		578352 R	177,08	
	M 18		578314	146,98		TH 20		578358 R	177,08	
	M 22		578316	146,98		TH 26		578362 R	177,08	
	M 28		578318	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	M 35		578390	178,12		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51						
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		Idrosanitaria Bonomi Idropress	TH 16		578352 R	177,08
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96			TH 18		578356	177,08
				TH 20			578358 R	177,08		
				TH 26			578362 R	177,08		
				TH 32			578364	177,08		
				TH 40			578624	234,69		
				TH 16 S (PR-2B)**	Mini Z8		574782 R	124,51		
				TH 20 S (PR-2B)**	Mini Z8		574788 R	124,51		
				TH 26 S (PR-2B)**	Mini Z8		574794 R	124,51		
				TH 32 S (PR-2B)	Mini Z8		574798 R	136,96		
HITHERM-ISOTUBI HTair	M 15		578312	146,98	IDROSISTEMI Ta-Press	TH 16		578352 R	177,08	
	M 18		578314	146,98		TH 20		578358 R	177,08	
	M 22		578316	146,98		TH 26		578362 R	177,08	
	M 28		578318	146,98		TH 32		578364	177,08	
	M 35		578390	178,12		TH 40		578624	234,69	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96						
Hopewell press fit system	M 15		578312	146,98	F 16	F 16		578456	168,68	
	M 18		578314	146,98		F 20		578460	168,68	
	M 22		578316	146,98		F 26		578462	182,48	
	M 28		578318	146,98		F 32		578464	182,48	
	M 35		578390	178,12		F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	
hp praski BAVARIA-press	TH 10		578342	177,08		F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	
	TH 12		578346	177,08		F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	
	TH 14		578348	177,08		F 32 S (PR-2B)	Mini Z8	574734 R	136,96	
	TH 16		578352 R	177,08		Fz 40		578478	247,15	
	TH 17		578354	177,08		H 16		578400	159,75	
	TH 20		578358 R	177,08	H 20		578406	159,75		
	TH 25		578360	177,08	H 26		578410	159,75		
	TH 26		578362 R	177,08	H 32		578412	159,75		
	TH 32		578364	177,08	U 16		578374	165,66		
	TH 40		578624	234,69	U 20		578378	165,66		
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51	U 26 <sup>1)</sup>		578392	194,31		
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51	U 32		578382	194,31		
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	U 40		578386	236,66		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	B 16		578468	193,28		
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	B 20		578472	193,28		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	B 26		578474	213,00		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	B 32		578476	213,00		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	IDROTRADE Storm Multipinza	H 16		578400	159,75	
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	H 20			578406	159,75		
				H 26			578410	159,75		
				H 32			578412	159,75		
				TH 16			578352 R	177,08		
				TH 20			578358 R	177,08		
				TH 26			578362 R	177,08		
				TH 32			578364	177,08		
				THL 32			578368	177,08		
				TH 40			578624	234,69		
ICMA Sempiter	H 16		578400	159,75	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
	H 20		578406	159,75	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
	H 25		578408	159,75	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
	H 26		578410	159,75	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
	H 32		578412	159,75	U 16		578374	165,66		
	TH 16		578352 R	177,08	U 20		578378	165,66		
	TH 20		578358 R	177,08						
	TH 25		578360	177,08	IDROTRADE StormPRES <sup>1)</sup>	M 15		578312	146,98	
	TH 26		578362 R	177,08		M 18		578314	146,98	
	TH 32		578364	177,08		M 22		578316	146,98	
TH 40		578624	234,69	M 28			578318	146,98		
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	M 35			578390	178,12		
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	M 15 S (PR-2B)		Mini Z8	574738 R	124,51		
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	M 18 S (PR-2B)		Mini Z8	574740 R	124,51		
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	M 22 S (PR-2B)		Mini Z8	574742 R	124,51		
U 16		578374	165,66	M 28 S (PR-2B)		Mini Z8	574744 R	124,51		
U 20		578378	165,66	M 35 S (PR-2B)		Mini Z8	574746 R	136,96		
U 25		578380	165,66							
U 26 <sup>1)</sup>		578392	194,31							
U 32		578382	194,31							
U 40		578386	236,66							

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

<sup>1)</sup> Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

<sup>2)</sup> For taking suitable pressing inserts.

<sup>3)</sup> Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

<sup>4)</sup> For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>5)</sup> For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>6)</sup> Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

<sup>7)</sup> Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
IDROTRADE StormSTEEL <sup>1)</sup>	M 12		578310	146,98	
	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	ILTA INOX/CHIBRO Pressfitting Cuni	M 15		578312	146,98
M 18			578314	146,98	
M 22			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
ILTA INOX/CHIBRO Pressfitting inox		M 15		578312	146,98
		M 18		578314	146,98
		M 22		578316	146,98
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	Instantor Press System	TH 16		578352 R	177,08
		TH 20		578358 R	177,08
		TH 26		578362 R	177,08
TH 32			578364	177,08	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124,51	
Instantor Copper Press Imperial	VI 1/2" (OD 14,7 mm)		578716	175,53	
	VI 3/4" (OD 21,0 mm)		578718	175,53	
	VI 1" (OD 27,4 mm)		578720	175,53	
	VI 1/2" S (PR-2B)	Mini Z8	574850 R	124,51	
	VI 3/4" S (PR-2B)	Mini Z8	574852 R	124,51	
	VI 1" S (PR-2B)	Mini Z8	574854 R	124,51	
Instantor Copper Press Metric	M 15		578312	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
IPA IPANA Press	TH 10		578342	177,08	
	TH 11,6		578344	177,08	
	TH 12		578346	177,08	
	TH 14		578348	177,08	
	TH 15		578350	177,08	
	TH 16		578352 R	177,08	
	TH 17		578354	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 22		578588	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 28		578590	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 10 S (PR-2B)**	Mini Z8	574772 R	124,51	
	TH 11,6 S (PR-2B)**	Mini Z8	574774 R	124,51	
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51	
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	
	TH 15 S (PR-2B)**	Mini Z8	574780 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 22 S (PR-2B)**	Mini Z8	574790 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 28 S (PR-2B)**	Mini Z8	574796 R	136,96	
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96	
	IPA Thu IPANA Press	TH 16		578352 R	177,08
		TH 20		578358 R	177,08
		TH 26		578362 R	177,08
		TH 32		578364	177,08
TH 40			578624	234,69	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124,51	
TH 32 S (PR-2B)**		Mini Z8	574798 R	136,96	
IPALPEX (Industrie du Plastique et Accessoires)		TH 14		578348	177,08
	TH 16		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	THL 32		578368	177,08	
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	TH 40		578624	234,69	
	K16/P18		578592	184,45	
IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18		578592	184,45	
	K/20		578594	184,45	
	K/25		578596	184,45	
	K32		578598	184,45	
	K1/40		578600	184,45	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
IPLEX PIPELINES AUSTRALIA Iplex K2	K16/P18		578592	184,45		
	K/20		578594	184,45		
	K/25		578596	184,45		
IVAR ALPEX-GAS	M 15 M 18 M 22 M 28 M 35 M 15 S (PR-2B) M 18 S (PR-2B) M 22 S (PR-2B) M 28 S (PR-2B) M 35 S (PR-2B)		578312	146,98		
		578314	146,98			
		578316	146,98			
		578318	146,98			
		578390	178,12			
		Mini Z8	574738 R	124,51		
		Mini Z8	574740 R	124,51		
		Mini Z8	574742 R	124,51		
		Mini Z8	574744 R	124,51		
		Mini Z8	574746 R	136,96		
		B 20		578472	193,28	
B 26		578474	213,00			
B 32		578476	213,00			
IVAR Ivar-Press	B 14 B 16 B 18 B 20 B 26 B 32 Fz 40		578466	193,28		
		578468	193,28			
		578470	193,28			
		578472	193,28			
		578474	213,00			
		578476	213,00			
IVAR MULTI PRESS GAS ITALIA	TH 16 TH 20 TH 26 H 16 H 20 H 26 U 16 U 20		578352 R	177,08		
		578358 R	177,08			
		578362 R	177,08			
		578400	159,75			
		578406	159,75			
		578410	159,75			
		578374	165,66			
		578378	165,66			
		IVAR Multi Press MP	TH 16 TH 18 TH 20 TH 25 TH 26 TH 32 TH 40 TH 16 S (PR-2B)** TH 18 S (PR-2B)** TH 20 S (PR-2B)** TH 25 S (PR-2B)** TH 26 S (PR-2B)** TH 32 S (PR-2B)** F 16 F 18 F 20 F 26 F 32 Fz 40 F 16 S (PR-2B)** F 20 S (PR-2B)** F 26 S (PR-2B)** F 32 S (PR-2B)** H 16 H 18 H 20 H 25 H 26 H 32 U 16 U 18 U 20 U 25 U 26 <sup>1)</sup> U 32 U 40 B 16 B 18 B 20 B 26 B 32		578352 R	177,08
				578356	177,08	
578358 R	177,08					
578360	177,08					
578362 R	177,08					
578364	177,08					
578624	234,69					
Mini Z8	574782 R			124,51		
Mini Z8	574788 R			124,51		
Mini Z8	574792 R			124,51		
Mini Z8	574794 R			124,51		
Mini Z8	574798 R			136,96		
578456	168,68					
578458	168,68					
578460	168,68					
578462	182,48					
578464	182,48					
578478	247,15					
574728 R	124,51					
574730 R	124,51					
574732 R	124,51					
574734 R	136,96					
578400	159,75					
578406	159,75					
578410	159,75					
578412	159,75					
578374	165,66					
578376	165,66					
578378	165,66					
578380	165,66					
578392	194,31					
578382	194,31					
578386	236,66					
578468	193,28					
578470	193,28					
578472	193,28					
578474	213,00					
578476	213,00					
IVAR Multi Press Leak (MPL)	TH 16 TH 20 TH 26 TH 32 TH 16 S (PR-2B)** TH 20 S (PR-2B)** TH 26 S (PR-2B)** TH 32 S (PR-2B)** F 16 F 20 F 26 F 32 F 16 S (PR-2B)** F 20 S (PR-2B)** F 26 S (PR-2B)** F 32 S (PR-2B)** H 16 H 20 H 26 H 32 U 16 U 20 U 26 <sup>1)</sup> U 32 B 16 B 20 B 26 B 32		578352 R	177,08		
		578358 R	177,08			
		578362 R	177,08			
		578364	177,08			
		574782 R	124,51			
		574788 R	124,51			
		574794 R	124,51			
		574798 R	136,96			
		578456	168,68			
		578460	168,68			
		578462	182,48			
		578464	182,48			
		574728 R	124,51			
574730 R	124,51					
574732 R	124,51					
574734 R	136,96					
578400	159,75					
578406	159,75					
578410	159,75					
578412	159,75					
578374	165,66					
578378	165,66					
578378	165,66					
578392	194,31					
578382	194,31					
578468	193,28					
578470	193,28					
578472	193,28					
578474	213,00					
578476	213,00					

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€		
IVAR Plastic Multi Press PMP	TH 16		578352 R	177,08	<b>J</b>	Jäger - Aquatec	H 14	578398	159,75		
	TH 20		578358 R	177,08		Aquapress H	H 16	578400	159,75		
	TH 25		578360	177,08			H 17	578402	159,75		
	TH 26		578362 R	177,08			H 18	578404	159,75		
	TH 32		578364	177,08			H 20	578406	159,75		
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51			H 26	578410	159,75		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51			H 32	578412	159,75		
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51			U 40	578386	236,66		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51			Jäger - Aquatec	M 15	578312	146,98	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96			C-Stahl	M 18	578314	146,98	
	F 16		578456	168,68			Press Typ M	M 22	578316	146,98	
	F 20		578460	168,68				M 28	578318	146,98	
	F 26		578462	182,48				M 35	578390	178,12	
	F 32		578464	182,48				M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51				M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51				M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51				M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96				M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	H 16		578400	159,75			Jäger - Aquatec	M 15	578312	146,98	
	H 20		578406	159,75			Edelstahl	M 18	578314	146,98	
	H 25		578408	159,75			Press Typ M	M 22	578316	146,98	
	H 26		578410	159,75				M 28	578318	146,98	
	H 32		578412	159,75				M 35	578390	178,12	
	U 16		578374	165,66				M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	U 20		578378	165,66				M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	U 25		578380	165,66				M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	U 26 <sup>7)</sup>		578392	194,31				M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	U 32		578382	194,31				M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	B 16		578468	193,28			Jäger - Aquatec	V 15	578328	146,98	
	B 20		578472	193,28			Kupfer	V 18	578332	146,98	
	B 26		578474	213,00			Press Typ V	V 22	578334	146,98	
	B 32		578476	213,00				V 28	578336	146,98	
	IVAR Plastic Multi Press Leak (PMPL)	TH 16		578352 R		177,08		V 35	578604	178,12	
		TH 20		578358 R		177,08		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
		TH 26		578362 R		177,08		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
		TH 32		578364		177,08		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	Jansen AG	TH 14	578348	177,08			
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	JANSEN COMISA	TH 16	578352 R	177,08			
	F 16		578456	168,68		TH 20	578358 R	177,08			
	F 20		578460	168,68		TH 26	578362 R	177,08			
	F 26		578462	182,48		TH 32	578364	177,08			
	F 32		578464	182,48		TH 40	578624	234,69			
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51		
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
	H 16		578400	159,75		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
	H 20		578406	159,75	Jaraflex-	TH 14	578348	177,08			
	H 26		578410	159,75	Presssystem	TH 16	578352 R	177,08			
	H 32		578412	159,75		TH 17	578354	177,08			
	U 16		578374	165,66		TH 18	578356	177,08			
	U 20		578378	165,66		TH 20	578358 R	177,08			
	U 26 <sup>7)</sup>		578392	194,31		TH 25	578360	177,08			
	U 32		578382	194,31		TH 26	578362 R	177,08			
	B 16		578468	193,28		TH 32	578364	177,08			
	B 20		578472	193,28		TH 40	578624	234,69			
	B 26		578474	213,00		TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51		
	B 32		578476	213,00		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		
IVT Edelstahl- Presssystem	M 15		578312	146,98		TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51		
	M 18		578314	146,98		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51		
	M 22		578316	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
	M 28		578318	146,98		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		
	M 35		578390	178,12		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	JUNGWOOD	VUS ½" (OD 15,9 mm)	578566	177,50			
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	JWPress	VUS ¾" (OD 22,2 mm)	578568	177,50			
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		VUS 1" (OD 28,6 mm)	578570	177,50			
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		VUS 1¼" (OD 34,9 mm)	578606	177,50			
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96							
IVT PRIPRESS	TH 16		578352 R	177,08							
	TH 20		578358 R	177,08							
	TH 26		578362 R	177,08							
	TH 32		578364	177,08							
	TH 40		578624	234,69							
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51							
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51							
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51							
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96							

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.





# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
LK Systems	V 12		578324	146,98	Meier Tobler	H 16		578400	159,75
LK >B-Press	V 15		578328	146,98	Metalplast - Stramax	H 20		578406	159,75
Elförzinkat	V 18		578332	146,98	Serie MM	H 25		578408	159,75
	V 22		578334	146,98		H 32		578412	159,75
	V 28		578336	146,98		RFz 16		578492	184,45
	V 35		578604	178,12		RFz 20		578494	184,45
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		RFz 25		578496	184,45
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		RFz 32		578498	184,45
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		TH 16		578352 R	177,08
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		TH 20		578358 R	177,08
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		TH 25		578360	177,08
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		TH 32		578364	177,08
LK Systems	V 15		578328	146,98		TH 40		578624	234,69
LK >B-Press	V 18		578332	146,98		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
Gas	V 22		578334	146,98		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	V 28		578336	146,98		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	V 35		578604	178,12		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		U 16		578374	165,66
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		U 20		578378	165,66
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		U 25		578380	165,66
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		U 32		578382	194,31
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		U 40		578386	236,66
LK Systems	TH 16		578352 R	177,08	METALGRUP	U 16		578374	165,66
LK Universal	TH 20		578358 R	177,08	Permatubo	U 18		578376	165,66
	TH 25		578360	177,08		U 20		578378	165,66
	TH 32		578364	177,08		U 25		578380	165,66
	TH 40		578624	234,69		U 32		578382	194,31
						U 40		578386	236,66
					METALGRUP	RFz 16		578492	184,45
					PexGrup	RFz 20		578494	184,45
						RFz 25		578496	184,45
						RFz 32		578498	184,45
					METALGRUP	U 16		578374	165,66
					MultiGrup	U 18		578376	165,66
						U 20		578378	165,66
						U 25		578380	165,66
						U 32		578382	194,31
					Mueller Streamline	VUS ½" (OD 15,9 mm)		578566	177,50
					PRS Copper Press	VUS ¾" (OD 22,2 mm)		578568	177,50
						VUS 1" (OD 28,6 mm)		578570	177,50
						VUS 1¼" (OD 34,9 mm)		578606	177,50
					MULTITHERM	TH 16		578352 R	177,08
					PRESSSYSTEM	TH 20		578358 R	177,08
						TH 26		578362 R	177,08
						TH 32		578364	177,08
						TH 40		578624	234,69
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
						TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
						TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
					Multicapas Industrial	RFz 16		578492	184,45
					AIS PEX	RFz 20		578494	184,45
						RFz 25		578496	184,45
						RFz 32		578498	184,45
						U 16		578374	165,66
						U 20		578378	165,66
						U 25		578380	165,66
						U 32		578382	194,31
					Multicapas Industrial	H 16		578400	159,75
					AIS XPRT	H 20		578406	159,75
						H 25		578408	159,75
						H 32		578412	159,75
						RFz 16		578492	184,45
						RFz 20		578494	184,45
						RFz 25		578496	184,45
						RFz 32		578498	184,45
						TH 16		578352 R	177,08
						TH 20		578358 R	177,08
						TH 25		578360	177,08
						TH 32		578364	177,08
						TH 40		578624	234,69
						TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
						TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
						TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
						TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
						TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
						U 16		578374	165,66
						U 20		578378	165,66
						U 25		578380	165,66
						U 32		578382	194,31
						U 40		578386	236,66

### M

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Multicap Industrial multitubo systems MC	U 16		578374	165,66	
	U 18		578376	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
	U 40		578386	236,66	
Multicap Industrial multitubo systems MM	H 16		578400	159,75	
	H 20		578406	159,75	
	H 25		578408	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	RFz 16		578492	184,45	
	RFz 20		578494	184,45	
	RFz 25		578496	184,45	
	RFz 32		578498	184,45	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 16		578374	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
	U 32		578382	194,31	
	U 40		578386	236,66	
	multipipe Deutschland multipipe mp	TH 16		578352 R	177,08
		TH 20		578358 R	177,08
		TH 26		578362 R	177,08
		TH 32		578364	177,08
		TH 40		578624	234,69
		TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)		Mini Z8	574798 R	136,96	
<b>N</b>					
NEUTHERM MEKUPRESS-HT		H 16		578400	159,75
	H 20		578406	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
NIBCO Press System Copper	VUS 1/2" (OD 15,9 mm)		578566	177,50	
	VUS 3/4" (OD 22,2 mm)		578568	177,50	
	VUS 1" (OD 28,6 mm)		578570	177,50	
	VUS 1 1/4" (OD 34,9 mm)		578606	177,50	
NICOLL FLUXO	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
NUPI Industrie Italiane Multinupi	B 16		578468	193,28	
	B 18		578470	193,28	
	B 20		578472	193,28	
	B 26		578474	213,00	
	B 32		578476	213,00	
	F 16		578456	168,68	
	F 18		578458	168,68	
	F 20		578460	168,68	
	F 26		578462	182,48	
	F 32		578464	182,48	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96	
	H 16		578400	159,75	
	H 18		578404	159,75	
	H 20		578406	159,75	
	H 25		578408	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	TH 16		578352 R	177,08	
	TH 18		578356	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 14		578372	174,38	
U 16		578374	165,66		
U 18		578376	165,66		
U 20		578378	165,66		
U 25		578380	165,66		
U 26 <sup>7)</sup>		578392	194,31		
U 32		578382	194,31		
U 40		578386	236,66		
Nussbaum Optifitt-Press	VMP 3/8" (OD 17,2 mm)		578660	204,17	
	VMP 1/2" G (OD 21,3 mm)		578666 R	204,17	
	VMPz 3/4" (OD 26,9 mm)		578664	204,17	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
Nussbaum Optiflex-Flowpress	VRX 16		578640	186,42	
	VRX 20		578642	186,42	
	VRX 25		578644	204,17	
	VRX 32		578646	204,17	
	Nussbaum Optipress	V 15		578328	146,98
		V 18		578332	146,98
	Aquaplus	V 22		578334	146,98
		V 28		578336	146,98
		V 35		578604	178,12
		V 15 S (PR-2B)	Mini Z8	574752 R	124,51
		V 18 S (PR-2B)	Mini Z8	574756 R	124,51
		V 22 S (PR-2B)	Mini Z8	574758 R	124,51
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
Nussbaum Optipress Gaz		V 15		578328	146,98
		V 18		578332	146,98
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
Nussbaum Optipress-Therm	V 15		578328	146,98	
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
O	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
<b>O</b>					
Oventrop Cofit P	H 16 A		578420	204,17	
	H 20 A		578426	204,17	
	H 26 A		578430	204,17	
	H 32 A		578432	204,17	
Oventrop Cofit PD	H 16 A		578420	204,17	
	H 20 A		578426	204,17	
	H 26 A		578430	204,17	
Oventrop Cofit PDK	H 16 A		578420	204,17	
	H 20 A		578426	204,17	
	H 26 A		578430	204,17	
	H 32 A		578432	204,17	
Oventrop Cofit PD-HT	H 16 A		578420	204,17	
	H 20 A		578426	204,17	
Oventrop Cofit PDK-HT	H 16 A		578420	204,17	
	H 20 A		578426	204,17	
<b>P</b>					
PBtub SERTIPRESS	RFz 12		578490	184,45	
	RFz 16		578492	184,45	
	RFz 20		578494	184,45	
	RFz 25		578496	184,45	
PBtub SERTI-STEEL <sup>1)</sup>	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
Pegler Yorkshire > Aalberts integrated piping systems	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	PERFEXIM		578374	165,66	
	PERFEKT		578378	165,66	
SYSTEM	U 25		578380	165,66	
	U 32		578382	194,31	
	PERFEXIM		578374	165,66	
	PERFEKT		578378	165,66	
SYSTEM PLUS	U 25		578380	165,66	
	U 32		578382	194,31	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 25		578360	177,08	
	TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
PERFILTUBO PERFILALUPEX	U 16		578374	165,66	
	U 18		578376	165,66	
	U 20		578378	165,66	
	U 25		578380	165,66	
PERFILTUBO PERFILPRESS	U 32		578382	194,31	
	U 40		578386	236,66	
	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
PEXTUBE PexTube	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	RFz 16		578492	184,45	
	RFz 20		578494	184,45	
	RFz 25		578496	184,45	
	RFz 32		578498	184,45	

**REMS pressing tongs Mini**  
**REMS pressing rings**

Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Pipelife C-PRESS	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Pipelife RADOPRESS	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
Pipetec Connect	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
U 20		578378	165,66	
U 32		578382	194,31	
PLASTICA ALFA Multiplex	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
PLASTICA ALFA Multiplex Air	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
PLASTICA ALFA Multiplexalfa Gas	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
PLASTICA ALFA Multiplexalfa Gas protek	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
PLASTICA ALFA Multiplex Plus	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
PLASTICA ALFA Multiplex Thermo	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
PLASTICA ALFA Multiplex Thermo Plus	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
PLÁSTICOS FERRO	U 16		578374	165,66	
	FERROPLAST	U 20	578378	165,66	
	GPF MULT Pressfitting	U 25	578380	165,66	
	MULTICAPA	U 32	578382	194,31	
PLÁSTICOS FERRO	U 16		578374	165,66	
	FERROPLAST	U 20	578378	165,66	
	GPF PPSU	U 25	578380	165,66	
	Pressfitting PEX y MULTICAPA	U 32	578382	194,31	
PLÁSTICOS FERRO	RFz 16		578492	184,45	
	FERROPLAST	RFz 20	578494	184,45	
	GPF PRESS	RFz 25	578496	184,45	
	Pressfitting PEX	RFz 32	578498	184,45	
PLUMBING PLUS	K16/P18		578592	184,45	
	EZIPEX Crimp (AUS)	K/20	578594	184,45	
		K/25	578596	184,45	
		K/32	578598	184,45	
		K1/40	578600	184,45	
PLUMBING PLUS	K16/P18		578592	184,45	
	EZIPEX Gas (AUS)	K/20	578594	184,45	
		K/25	578596	184,45	
		K/32	578598	184,45	
		K1/40	578600	184,45	
PLUMBING PLUS	Yz 16 UNI		578740	184,45	
	UNIPEX	Yz 20 UNI	578742	184,45	
	Water & Gas (AUS)	Yz 25 UNI	578744	184,45	
		Yz 32 UNI	578746	184,45	
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86	
	EZIPEX Gas (AUS)	VAU 20 (OD 19,1 mm)	578632	151,86	
		VAU 25 (OD 25,4 mm)	578634	151,86	
		VAU 32 (OD 31,8 mm)	578636	159,75	
		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51	
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96	
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86	
	EZIPEX Solar (AUS)	VAU 20 (OD 19,1 mm)	578632	151,86	
		VAU 25 (OD 25,4 mm)	578634	151,86	
		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51
		VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96	
PLUMBING PLUS	VAU 15 (OD 12,7 mm)		578630	151,86	
	EZIPEX Water (AUS)	VAU 20 (OD 19,1 mm)	578632	151,86	
		VAU 25 (OD 25,4 mm)	578634	151,86	
		VAU 32 (OD 31,8 mm)	578636	159,75	
		VAU 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51
	VAU 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51	
	VAU 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96	
POLYPIPE	TH 10		578342	177,08	
	TH 15		578350	177,08	
	TH 22		578588	177,08	
	TH 28		578590	177,08	
POLYSAN	M 15		578312	146,98	
	Handelsges.	M 18	578314	146,98	
	m.b.H. & Co KG	M 22	578316	146,98	
	(Krems/Österreich)	M 28	578318	146,98	
		M 35	578390	178,12	
POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	C Stahl-Press-System M	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
		M 22 S (PR-2B)	Mini Z8	574742 R	124,51
		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
POLYSAN	M 15		578312	146,98	
	Handelsges.	M 18	578314	146,98	
	m.b.H. & Co KG	M 22	578316	146,98	
	(Krems/Österreich)	M 28	578318	146,98	
		M 35	578390	178,12	
POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	Press-System 1.4520	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
		M 35 S (PR-2B)	Mini Z8	574746 R	136,96
POLYSAN	M 15		578312	146,98	
	Handelsges.	M 18	578314	146,98	
	m.b.H. & Co KG	M 22	578316	146,98	
	(Krems/Österreich)	M 28	578318	146,98	
		M 35	578390	178,12	
POLYSAN-	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	Edelstahl	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	Press-System Gas	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
		M 28 S (PR-2B)	Mini Z8	574744 R	124,51
		M 35 S (PR-2B)	Mini Z8	574746 R	136,96

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP 1/2" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

www.rems.de > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
POLYSAN	M 15		578312	146,98
Handelsges.	M 18		578314	146,98
m.b.H. & Co KG	M 22		578316	146,98
(Krems/Öster- reich)	M 28		578318	146,98
	M 35		578390	178,12
POLYSAN- Edelstahl	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
Press-System	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
Wasser	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
POLYSAN	TH 14		578348	177,08
Handelsges.	TH 16		578352 R	177,08
m.b.H. & Co KG	TH 17		578354	177,08
(Krems/Öster- reich)	TH 18		578356	177,08
	TH 20		578358 R	177,08
POLYSAN- Press-System	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)**	Mini Z8	574798 R	136,96
POLYSAN	TH 14		578348	177,08
Handelsges.	TH 16		578352 R	177,08
m.b.H. & Co KG	TH 17		578354	177,08
(Krems/Öster- reich)	TH 18		578356	177,08
	TH 20		578358 R	177,08
POLYSAN-Henco- Press-System	TH 26		578362 R	177,08
	HE 32		578370 R	212,06
	HEz 40 <sup>3)</sup>		578572	307,66
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
POLYSAN (España) „Rainbow“	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
Prandelli Multyrama Pf	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	U 40		578386	236,66
Prandelli Multyrama Pfm	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 40		578386	236,66
PURMO Cleverfit Radial	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 32		578464	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 32		578382	194,31
	VP 16		578482	176,56
	VP 20		578484	176,56
	VP 32		578488	195,25

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
<b>R</b>				
Raccorderie Metalliche aesPRES <sup>1)</sup>	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Raccorderie Metalliche inoxPRES <sup>1)</sup>	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Raccorderie Metalliche MARINEPRES <sup>1)</sup>	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
Raccorderie Metalliche steelPRES <sup>1)</sup>	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
RBM Tita-fix	B 14		578466	193,28
	B 16		578468	193,28
	B 18		578470	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	F 16		578456	168,68
	F 18		578458	168,68
	F 20		578460	168,68
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	H 14		578398	159,75
	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
RBM Tita-gas	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 14		578372	174,38
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
Redi Nicoll Fluxo	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96



# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Redi Nicoll Fluxo Gas	TH 16		578352 R	177,08	Rubinetterie	M 15		578312	146,98
	TH 20		578358 R	177,08	Bresciane	M 18		578314	146,98
	TH 26		578362 R	177,08	Bonomi	M 22		578316	146,98
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TURBO STEEL	M 28		578318	146,98
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	M 35		578390	178,12	
RIFENG LD PRESS FITTING (F8)	LD 16		578652	182,69	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	LD 20		578654	182,69	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	LD 25		578656	182,69	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
RIFENG U PRESS FITTING (F5)	U 14		578372	174,38	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	U 16		578374	165,66	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	U 18		578376	165,66	Rubinetterie	B 14		578466	193,28
	U 20		578378	165,66	Bresciane	B 16		578468	193,28
	U 25		578380	165,66	Bonomi	B 18		578470	193,28
	U 32		578382	194,31	TURBO PRESS	B 20		578472	193,28
RIFENG TH PRESS FITTING (F9)	U 40		578386	236,66	B 26		578474	213,00	
	TH 16		578352 R	177,08	B 32		578476	213,00	
	TH 20		578358 R	177,08	H 14		578398	159,75	
	TH 25		578360	177,08	H 16		578400	159,75	
	TH 26		578362 R	177,08	H 18		578404	159,75	
RIQUIER A SERTIR	TH 32		578364	177,08	H 20		578406	159,75	
	TH 40		578624	234,69	H 26		578410	159,75	
	RFz 12		578490	184,45	H 32		578412	159,75	
	RFz 16		578492	184,45	TH 14		578348	177,08	
RIQUIER Système multicouche	RFz 20		578494	184,45	TH 16		578352 R	177,08	
	RFz 25		578496	184,45	TH 18		578356	177,08	
	TH 16		578352 R	177,08	TH 20		578358 R	177,08	
	TH 20		578358 R	177,08	TH 26		578362 R	177,08	
	TH 26		578362 R	177,08	TH 32		578364	177,08	
	TH 32		578364	177,08	TH 40		578624	234,69	
	TH 40		578624	234,69	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	U 14		578372	174,38	
	U 16		578374	165,66	U 16		578374	165,66	
U 20		578378	165,66	U 18		578376	165,66		
U 32		578382	194,31	U 20		578378	165,66		
U 40		578386	236,66	U 26 <sup>7)</sup>		578392	194,31		
Roth PressCheck	U 32		578382	194,31	U 32		578382	194,31	
	RN 14		578434	165,66	Rubinetterie	TH 16		578352 R	177,08
	RN 16		578454	165,66	Bresciane	TH 20		578358 R	177,08
	RN 17		578436	165,66	Bonomi	TH 26		578362 R	177,08
	RN 20		578438	165,66	TURBO PRESS	TH 32		578364	177,08
	RN 25/26		578440	165,66	GAS	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
RN 32		578442	194,31	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		
Rubinetterie Bresciane Bonomi TURBO CuNi	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 15		578312	146,98	U 14		578372	174,38	
	M 18		578314	146,98	U 16		578374	165,66	
	M 22		578316	146,98	U 18		578376	165,66	
	M 28		578318	146,98	U 20		578378	165,66	
	M 35		578390	178,12	U 26 <sup>7)</sup>		578392	194,31	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	U 32		578382	194,31	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	Rubinetterie	TH 16		578352 R	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Bresciane	TH 20		578358 R	177,08
M 28 S (PR-2B)	Mini Z8	574744 R	124,51	Bonomi	TH 26		578362 R	177,08	
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	TURBO PRESS	TH 32		578364	177,08	
Rubinetterie Bresciane Bonomi TURBO INOX	M 15		578312	146,98	GAS	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	M 18		578314	146,98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 22		578316	146,98	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 28		578318	146,98	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 35		578390	178,12	SA.MI PLASTIC	TH 14		578348	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	TH 16		578352 R	177,08	
M 18 S (PR-2B)	Mini Z8	574740 R	124,51	TH 18		578356	177,08		
M 22 S (PR-2B)	Mini Z8	574742 R	124,51	TH 20		578358 R	177,08		
M 28 S (PR-2B)	Mini Z8	574744 R	124,51	TH 26		578362 R	177,08		
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	TH 32		578364	177,08		
Rubinetterie Bresciane Bonomi TURBO INOX GAS	TH 40		578624	234,69	TH 40		578624	234,69	
	M 15		578312	146,98	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51	
	M 18		578314	146,98	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	M 22		578316	146,98	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51	
	M 28		578318	146,98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 35		578390	178,12	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	SA.MI PLASTIC	TH 16		578352 R	177,08
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Multistrato Gas	TH 20		578358 R	177,08
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	TH 26		578362 R	177,08	
M 35 S (PR-2B)	Mini Z8	574746 R	136,96	TH 32		578364	177,08		
Rubinetterie Bresciane Bonomi TURBO INOX GAS	TH 16		578352 R	177,08	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	M 18		578314	146,98	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	M 22		578316	146,98	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	M 28		578318	146,98	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	M 35		578390	178,12	SA.MI PLASTIC	TH 14		578348	177,08
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	TH 16		578352 R	177,08	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	TH 18		578356	177,08	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	TH 20		578358 R	177,08	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	TH 26		578362 R	177,08	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	TH 32		578364	177,08	

**S**

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA 3fit-Press Pb-free Serie 25000	B 16		578468	193,28	
	B 20		578472	193,28	
	B 26		578474	213,00	
	B 32		578476	213,00	
	F 16		578456	168,68	
	F 20		578460	168,68	
	F 26		578462	182,48	
	F 32		578464	182,48	
	Fz 40		578478	247,15	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96	
	H 16		578400	159,75	
	H 20		578406	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 40		578624	234,69	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 16		578374	165,66	
	U 20		578378	165,66	
	U 26 <sup>7)</sup>		578392	194,31	
	U 32		578382	194,31	
	U 40		578386	236,66	
	SANHA 3fit-Press PPSU Serie 35000	B 16		578468	193,28
		B 20		578472	193,28
		B 26		578474	213,00
		B 32		578476	213,00
		F 16		578456	168,68
		F 20		578460	168,68
		F 26		578462	182,48
		F 32		578464	182,48
F 16 S (PR-2B)**		Mini Z8	574728 R	124,51	
F 20 S (PR-2B)**		Mini Z8	574730 R	124,51	
F 26 S (PR-2B)**		Mini Z8	574732 R	124,51	
F 32 S (PR-2B)		Mini Z8	574734 R	136,96	
H 16			578400	159,75	
H 20			578406	159,75	
H 26			578410	159,75	
H 32			578412	159,75	
TH 16			578352 R	177,08	
TH 20			578358 R	177,08	
TH 26			578362 R	177,08	
TH 32			578364	177,08	
TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51	
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	
TH 26 S (PR-2B)**		Mini Z8	574794 R	124,51	
TH 32 S (PR-2B)		Mini Z8	574798 R	136,96	
U 16			578374	165,66	
U 20			578378	165,66	
U 26 <sup>7)</sup>			578392	194,31	
U 32			578382	194,31	
SANHA Heavy Steel Press		VMP ½" G (OD 21,3 mm)		578666 R	204,17
		VMPz ¾" (OD 26,9 mm)		578664	204,17
		VMP ½" G (OD 21,3 mm) <sup>1)</sup>		578666 R	204,17
SANHA Heavy Steel Press Gas		VMPz ¾" (OD 26,9 mm)		578664	204,17
				578664	204,17
SANHA-NiroSan Gas Presssystem Serie 17000		SA 15		578514	176,56
		SA 18		578518	176,56
		SA 22		578520	176,56
		SA 28		578522	176,56
		M 15 <sup>1)</sup>		578312	146,98
		M 18 <sup>1)</sup>		578314	146,98
	M 22 <sup>1)</sup>		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 15 <sup>1)</sup>		578328	146,98	
	V 18 <sup>1)</sup>		578332	146,98	
	V 22 <sup>1)</sup>		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA-NiroSan Industry Presssystem Serie 18000	SA 15		578514	176,56	
	SA 18		578518	176,56	
	SA 22		578520	176,56	
	SA 28		578522	176,56	
	M 15 <sup>1)</sup>		578312	146,98	
	M 18 <sup>1)</sup>		578314	146,98	
	M 22 <sup>1)</sup>		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 15 <sup>1)</sup>		578328	146,98	
	V 18 <sup>1)</sup>		578332	146,98	
	V 22 <sup>1)</sup>		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	SANHA-NiroSan- Presssystem Serie 9000	SA 15		578514	176,56
		SA 18		578518	176,56
		SA 22		578520	176,56
		SA 28		578522	176,56
		M 15 <sup>1)</sup>		578312	146,98
		M 18 <sup>1)</sup>		578314	146,98
M 22 <sup>1)</sup>			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
V 15 <sup>1)</sup>			578328	146,98	
V 18 <sup>1)</sup>		578332	146,98		
V 22 <sup>1)</sup>		578334	146,98		
V 28		578336	146,98		
V 35		578604	178,12		
V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
SANHA-NiroSan SF Presssystem Serie 19000 (silicone free)	SA 15		578514	176,56	
	SA 18		578518	176,56	
	SA 22		578520	176,56	
	SA 28		578522	176,56	
	M 15 <sup>1)</sup>		578312	146,98	
	M 18 <sup>1)</sup>		578314	146,98	
	M 22 <sup>1)</sup>		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 15 <sup>1)</sup>		578328	146,98	
V 18 <sup>1)</sup>		578332	146,98		
V 22 <sup>1)</sup>		578334	146,98		
V 28		578336	146,98		
V 35		578604	178,12		
V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
SANHA NiroTherm Serie 91000	SA 15		578514	176,56	
	SA 18		578518	176,56	
	SA 22		578520	176,56	
	SA 28		578522	176,56	
	M 15 <sup>1)</sup>		578312	146,98	
	M 18 <sup>1)</sup>		578314	146,98	
	M 22 <sup>1)</sup>		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 15 <sup>1)</sup>		578328	146,98	
V 18 <sup>1)</sup>		578332	146,98		
V 22 <sup>1)</sup>		578334	146,98		
V 28		578336	146,98		
V 35		578604	178,12		
V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
V 35 S (PR-2B)	Mini Z8	574762 R	136,96		

# REMS pressing tongs Mini

## REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA NiroTherm Industry Serie 98000	SA 15		578514	176,56	SANHA-Press Pressfittings Serie 6000	SA 12		578510	256,39	
	SA 18		578518	176,56		SA 14		578512	256,39	
	SA 22		578520	176,56		SA 15		578514	176,56	
	SA 28		578522	176,56		SA 16		578516	176,56	
	M 15 <sup>1)</sup>		578312	146,98		SA 18		578518	176,56	
	M 18 <sup>1)</sup>		578314	146,98		SA 22		578520	176,56	
	M 22 <sup>1)</sup>		578316	146,98		SA 28		578522	176,56	
	M 28		578318	146,98		M 12		578310	146,98	
	M 35		578390	178,12		M 15 <sup>1)</sup>		578312	146,98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		M 18 <sup>1)</sup>		578314	146,98	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		M 22 <sup>1)</sup>		578316	146,98	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		M 28		578318	146,98	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		M 35		578390	178,12	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	V 15 <sup>1)</sup>		578328	146,98		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	V 18 <sup>1)</sup>		578332	146,98		M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	V 22 <sup>1)</sup>		578334	146,98		M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	V 28		578336	146,98		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	V 35		578604	178,12		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		V 12		578324	146,98	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		V 14		578326	146,98	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		VG 14		578338	146,98	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		V 15 <sup>1)</sup>		578328	146,98	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		V 16		578330	146,98	
	SANHA-Press Chrom Serie 16000	SA 12		578510		256,39	VG 16		578340	146,98
		SA 15		578514		176,56	V 18 <sup>1)</sup>		578332	146,98
		SA 18		578518		176,56	V 22 <sup>1)</sup>		578334	146,98
		SA 22		578520		176,56	V 28		578336	146,98
SA 28			578522	176,56	V 35		578604	178,12		
M 12			578310	146,98	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		
M 15 <sup>1)</sup>			578312	146,98	VG 14 S (PR-2B)	Mini Z8	574750 R	124,51		
M 18 <sup>1)</sup>			578314	146,98	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
M 22 <sup>1)</sup>			578316	146,98	VG 16 S (PR-2B)	Mini Z8	574754 R	124,51		
M 28			578318	146,98	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
M 12 S (PR-2B)		Mini Z8	574736 R	124,51	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	SANHA-Press SOLAR Pressfittings Serie 12000/ Serie 13000	SA 12		578510	256,39	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51		SA 15		578514	176,56	
V 12			578324	146,98		SA 18		578518	176,56	
V 15 <sup>1)</sup>			578328	146,98		SA 22		578520	176,56	
V 18 <sup>1)</sup>			578332	146,98		SA 28		578522	176,56	
V 22 <sup>1)</sup>			578334	146,98		M 12		578310	146,98	
V 28			578336	146,98		M 15 <sup>1)</sup>		578312	146,98	
V 12 S (PR-2B)		Mini Z8	574748 R	124,51		M 18 <sup>1)</sup>		578314	146,98	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51		M 22 <sup>1)</sup>		578316	146,98	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51		M 28		578318	146,98	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51		M 35		578390	178,12	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51		M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96		M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000		SA 12		578510		256,39	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
		SA 14		578512		256,39	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	SA 15		578514	176,56		M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	SA 16		578516	176,56		M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	SA 18		578518	176,56		V 12		578324	146,98	
	SA 22		578520	176,56		V 14		578326	146,98	
	SA 28		578522	176,56		VG 14		578338	146,98	
	M 12		578310	146,98		V 15 <sup>1)</sup>		578328	146,98	
	M 15 <sup>1)</sup>		578312	146,98		V 16		578330	146,98	
	M 18 <sup>1)</sup>		578314	146,98		VG 16		578340	146,98	
	M 22 <sup>1)</sup>		578316	146,98		V 18 <sup>1)</sup>		578332	146,98	
	M 28		578318	146,98		V 22 <sup>1)</sup>		578334	146,98	
	M 35		578390	178,12		V 28		578336	146,98	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		V 35		578604	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	V 18 S (PR-2B)	Mini Z8	574756 R	124,51		
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	V 22 S (PR-2B)	Mini Z8	574758 R	124,51		
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	V 28 S (PR-2B)	Mini Z8	574760 R	124,51		
	V 12		578324	146,98	V 35 S (PR-2B)	Mini Z8	574762 R	136,96		
	V 14		578326	146,98						
	VG 14		578338	146,98						
	V 15 <sup>1)</sup>		578328	146,98						
	V 16		578330	146,98						
	VG 16		578340	146,98						
	V 18 <sup>1)</sup>		578332	146,98						
	V 22 <sup>1)</sup>		578334	146,98						
	V 28		578336	146,98						
V 35		578604	178,12							
V 12 S (PR-2B)	Mini Z8	574748 R	124,51							
VG 14 S (PR-2B)	Mini Z8	574750 R	124,51							
V 15 S (PR-2B)	Mini Z8	574752 R	124,51							
VG 16 S (PR-2B)	Mini Z8	574754 R	124,51							
V 18 S (PR-2B)	Mini Z8	574756 R	124,51							
V 22 S (PR-2B)	Mini Z8	574758 R	124,51							
V 28 S (PR-2B)	Mini Z8	574760 R	124,51							
V 35 S (PR-2B)	Mini Z8	574762 R	136,96							

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€	
SANHA PURAPRESS Serie 8000	SA 12		578510	256,39	
	SA 14		578512	256,39	
	SA 15		578514	176,56	
	SA 16		578516	176,56	
	SA 18		578518	176,56	
	SA 22		578520	176,56	
	SA 28		578522	176,56	
	M 12 <sup>1)</sup>		578310	146,98	
	M 15 <sup>1)</sup>		578312	146,98	
	M 18 <sup>1)</sup>		578314	146,98	
	M 22 <sup>1)</sup>		578316	146,98	
	M 28 <sup>1)</sup>		578318	146,98	
	M 35 <sup>1)</sup>		578390	178,12	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 12		578324	146,98	
	V 14		578326	146,98	
	VG 14		578338	146,98	
	V 15 <sup>1)</sup>		578328	146,98	
	V 16		578330	146,98	
	VG 16		578340	146,98	
	V 18 <sup>1)</sup>		578332	146,98	
	V 22 <sup>1)</sup>		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	VG 14 S (PR-2B)	Mini Z8	574750 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	VG 16 S (PR-2B)	Mini Z8	574754 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	SANHA-Therm Serie 24000	SA 12		578510	256,39
		SA 15		578514	176,56
		SA 18		578518	176,56
		SA 22		578520	176,56
SA 28			578522	176,56	
M 12			578310	146,98	
M 15 <sup>1)</sup>			578312	146,98	
M 18 <sup>1)</sup>			578314	146,98	
M 22 <sup>1)</sup>			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 12 S (PR-2B)		Mini Z8	574736 R	124,51	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
V 12			578324	146,98	
V 15 <sup>1)</sup>			578328	146,98	
V 18 <sup>1)</sup>			578332	146,98	
V 22 <sup>1)</sup>			578334	146,98	
V 28			578336	146,98	
V 35			578604	178,12	
V 12 S (PR-2B)		Mini Z8	574748 R	124,51	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
SANHA-Therm Industry Serie 28000		SA 12		578510	256,39
		SA 15		578514	176,56
		SA 18		578518	176,56
		SA 22		578520	176,56
		SA 28		578522	176,56
		M 12		578310	146,98
		M 15 <sup>1)</sup>		578312	146,98
		M 18 <sup>1)</sup>		578314	146,98
		M 22 <sup>1)</sup>		578316	146,98
		M 28		578318	146,98
		M 35		578390	178,12
		M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	V 12		578324	146,98	
	V 15 <sup>1)</sup>		578328	146,98	
	V 18 <sup>1)</sup>		578332	146,98	
	V 22 <sup>1)</sup>		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
SANITOP PERMATUBO INOX	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
	M 35		578390	178,12
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
SANPRO THPRESS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
SATEC SK VITerm	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
SAVEUR REFLEX PEX Water	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
SAVEUR REFLEX PEX-AL-PEX Gas	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 32		578364	177,08
Schütz duo-flex tri-o-flex	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
Schwer Fittings AQUApress	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	M 12		578310	146,98
	M 15		578312	146,98
	M 18		578314	146,98
	M 22		578316	146,98
	M 28		578318	146,98
Seppelfricke > Aalberts integrated piping systems	M 35		578390	178,12
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96
	SESTA	TH 14	578348	177,08
	SESTA GAS	TH 16	578352 R	177,08
		TH 20	578358 R	177,08
	TH 26	578362 R	177,08	
	TH 32	578364	177,08	
SESTA sistema multistrato	H 16		578400	159,75
	H 20		578406	159,75
	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
SIGMA LI Premium	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
SLOVARM PEX-THERM	U 16		578374	165,66
	U 20		578378	165,66
	H 26		578410	159,75
	U 32		578382	194,31
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€			
STANDARD HIDRAULICA MultiStandard	H 16		578400	159,75	TDM BRASS Serie 2600	H 16		578400	159,75			
	H 20		578406	159,75		H 18		578404	159,75			
	H 25		578408	159,75		H 20		578406	159,75			
	H 32		578412	159,75		H 25		578408	159,75			
	RFz 16		578492	184,45		H 26		578410	159,75			
	RFz 20		578494	184,45		H 32		578412	159,75			
	RFz 25		578496	184,45		TH 16		578352 R	177,08			
	RFz 32		578498	184,45		TH 18		578356	177,08			
	TH 16		578352 R	177,08		TH 20		578358 R	177,08			
	TH 20		578358 R	177,08		TH 25		578360	177,08			
	TH 25		578360	177,08		TH 26		578362 R	177,08			
	TH 32		578364	177,08		THL 32		578368	177,08			
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		TH 16 S (PR-2B)**		574782 R	124,51			
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51			
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51			
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51			
	U 16		578374	165,66		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51			
	U 18		578376	165,66		U 16		578374	165,66			
	U 20		578378	165,66		U 18		578376	165,66			
	U 25		578380	165,66		U 20		578378	165,66			
	U 32		578382	194,31		U 25		578380	165,66			
	U 40		578386	236,66		U 26 <sup>7)</sup>		578392	194,31			
	steeltrade Presssystem Edelstahl Kontur M	M 15		578312		146,98	TDM BRASS Serie 1700 gas	TH 16		578352 R	177,08	
		M 18 <sup>1)</sup>		578314		146,98		TH 20		578358 R	177,08	
		M 22		578316		146,98		TH 26		578362 R	177,08	
		M 28 <sup>1)</sup>		578318		146,98		THL 32		578368	177,08	
M 35			578390	178,12	TH 16 S (PR-2B)**	Mini Z8		574782 R	124,51			
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	TH 20 S (PR-2B)**	Mini Z8		574788 R	124,51			
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	TH 26 S (PR-2B)**	Mini Z8		574794 R	124,51			
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	U 16			578374	165,66			
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	U 18			578376	165,66			
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	U 20			578378	165,66			
STELBI Polikraft		H 16		578400	159,75	TermoConcept TC-PRESS		Basic E01 <sup>1)</sup>		578618	305,17	
		H 20		578406	159,75			THERMOLUTZ	H 14		578398	159,75
		H 26		578410	159,75				H 16		578400	159,75
	TH 16		578352 R	177,08	TH 20				578358 R	177,08		
	TH 20		578358 R	177,08	TH 20 S (PR-2B)**		Mini Z8		574788 R	124,51		
	TH 26		578362 R	177,08	TE-SA TE-SA press serie 800		TH 14			578348	177,08	
	TH 32		578364	177,08			TH 16			578352 R	177,08	
	TH 40		578624	234,69			TH 18			578356	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51			TH 20			578358 R	177,08	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51			TH 26			578362 R	177,08	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51			TH 32			578364	177,08	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96			TH 40			578624	234,69	
	U 16		578374	165,66			TH 14 S (PR-2B)**		Mini Z8	574778 R	124,51	
U 20		578378	165,66	TH 16 S (PR-2B)**		Mini Z8	574782 R		124,51			
U 26 <sup>7)</sup>		578392	194,31	TH 18 S (PR-2B)**		Mini Z8	574786 R	124,51				
STELBI Stelgas	TH 16		578352 R	177,08		TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51			
	TH 20		578358 R	177,08		TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51			
	TH 26		578362 R	177,08		TH 32 S (PR-2B)	Mini Z8	574798 R	136,96			
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	THERMACOME ACOPEX ALU	H 16		578400	159,75			
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		H 20		578406	159,75			
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		H 26		578410	159,75			
STH Westco COPPER PRESS	M 15		578312	146,98		H 32		578412	159,75			
	M 22		578316	146,98		TH 16		578352 R	177,08			
	M 28		578318	146,98		TH 20		578358 R	177,08			
	M 35		578390	178,12	TH 26		578362 R	177,08				
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	TH 32		578364	177,08				
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	U 16		578374	165,66				
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	U 20		578378	165,66				
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	U 32		578382	194,31				
	<b>T</b>					TIEMME 1650 AL-COBRAPEX	TH 14		578348	177,08		
	TDM BRASS Serie 1600	H 16		578400	159,75		TH 16		578352 R	177,08		
		H 18		578404	159,75		TH 18		578356	177,08		
		H 20		578406	159,75		TH 20		578358 R	177,08		
		H 25		578408	159,75		TH 25		578360	177,08		
H 26			578410	159,75	TH 26			578362 R	177,08			
H 32			578412	159,75	THL 32			578368	177,08			
TH 16			578352 R	177,08	TH 40			578624	234,69			
TH 18			578356	177,08	TH 14 S (PR-2B)**		Mini Z8	574778 R	124,51			
TH 20			578358 R	177,08	TH 16 S (PR-2B)**		Mini Z8	574782 R	124,51			
TH 25			578360	177,08	TH 18 S (PR-2B)**		Mini Z8	574786 R	124,51			
TH 26			578362 R	177,08	TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51			
THL 32			578368	177,08	TH 25 S (PR-2B)**		Mini Z8	574792 R	124,51			
TH 40			578624	234,69	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51				
TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	TIEMME 1700 COBRAPEX	RFz 12		578490	184,45				
TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51		RFz 16		578492	184,45				
TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		RFz 20		578494	184,45				
TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51		RFz 25		578496	184,45				
TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		RFz 32		578498	184,45				
U 16		578374	165,66		TH 40		578624	234,69				
U 18		578376	165,66									
U 20		578378	165,66									
U 25		578380	165,66									
U 26 <sup>7)</sup>		578392	194,31									
U 32		578382	194,31									

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.



# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TIEMME 1650 AL-COBRAPEX GAS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	THL 32		578368	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TIGRE ALPEX GAS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
TKM Systemtechnik	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
TRA Multi TRA+	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 25		578360	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 25 S (PR-2B)**	Mini Z8	574792 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
U 16		578374	165,66	
U 20		578378	165,66	
U 25		578380	165,66	
U 26 <sup>7)</sup>		578392	194,31	
U 32		578382	194,31	
U 40		578386	236,66	
TRA MULTITRAPRESS	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
TRA TRAPRESS	H 12		578396	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 25		578408	159,75
	H 32		578412	159,75
	Rfz 12		578490	184,45
	Rfz 16		578492	184,45
	Rfz 20		578494	184,45
	Rfz 25		578496	184,45
	Rfz 32		578498	184,45
Tradelink TradePex Crimp Water	K16/P18		578592	184,45
	K/20		578594	184,45
	K/25		578596	184,45
	K32		578598	184,45
	K1/40		578600	184,45
Tradelink TradePex Crimp Gas	K16/P18		578592	184,45
	K/20		578594	184,45
	K/25		578596	184,45
	K32		578598	184,45
	K1/40		578600	184,45
TUBIPLAST ITALY MULTILAYER PIPE	H 16		578400	159,75
	H 18		578404	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 <sup>7)</sup>		578392	194,31
U 32		578382	194,31	
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352 R	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	U 16		578374	165,66
	U 18		578376	165,66
	U 20		578378	165,66
	U 26 <sup>7)</sup>		578392	194,31

System	Pressing tongs Mini/ pressing rings	Driven by adapter tongs	Art.-No.	€
TWEETOP	U 16		578374	165,66
	U 20		578378	165,66
	U 25		578380	165,66
	U 32		578382	194,31
	U 40		578386	236,66
<b>U</b>				
UNICAL AG MAX-MULTIPEX	U 16		578374	165,66
	U 20		578378	165,66
	H 26		578410	159,75
	U 26 <sup>7)</sup>		578392	194,31
	U 32		578382	194,31
UNIDELTA DELTAPRESS	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
UNIDELTA DELTAPRESS GAS	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
UNIDELTA DELTAPRESS GAS	U 16		578374	165,66
	U 20		578378	165,66
	U 32		578382	194,31
	U 40		578386	236,66
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
Uponor	UP 14		578576	165,66
	UP 16		578578	165,66
	UP 20		578582	165,66
	UP 25		578584	165,66
	UP 32		578586	194,31
	U 40		578386	236,66
<b>V</b>				
Valsir Bravopress	B 16		578468	193,28
	B 20		578472	193,28
	B 26		578474	213,00
	B 32		578476	213,00
	F 16		578456	168,68
	F 20		578460	168,68
	F 26		578462	182,48
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	H 32 V		578602	204,17
Valsir PEXAL	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	U 16		578374	165,66
	U 20		578378	165,66
	U 26 <sup>7)</sup>		578392	194,31
	U 32		578382	194,31
	H 14		578398	159,75
	H 16		578400	159,75
	H 20		578406	159,75
	H 26		578410	159,75
	H 32		578412	159,75
	H 32 V		578602	204,17
	TH 16		578352 R	177,08
TH 20		578358 R	177,08	
TH 26		578362 R	177,08	
TH 32		578364	177,08	
U 16		578374	165,66	
U 20		578378	165,66	
U 26 <sup>7)</sup>		578392	194,31	
U 32		578382	194,31	

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Van Marcke NV SYSTEMPEX	TH 16		578352 R	177,08	Viega MegaPress 316 (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17	
	TH 20		578358 R	177,08		VMPz ¾" (OD 26,9 mm)		578664	204,17	
	TH 26		578362 R	177,08		Viega MegaPress 316 FKM	VMP ½" G (OD 21,3 mm)		578666 R	204,17
	TH 32		578364	177,08			VMPz ¾" (OD 26,9 mm)		578664	204,17
	TH 40		578624	234,69		(ASTM) <sup>51</sup>			182,50	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		Viega MegaPress CuNi (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		VMPz ¾" (OD 26,9 mm)		578664	204,17	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		Viega MegaPress FKM (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17
TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	VMPz ¾" (OD 26,9 mm)		578664	204,17			
Van Marcke NV Tubipress	M 12		578310	146,98	Viega MegaPresG (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17	
	M 15		578312	146,98		VMPz ¾" (OD 26,9 mm)		578664	204,17	
	M 18		578314	146,98	Viega Megapress (EN) <sup>41</sup>	VMP ¾" (OD 17,2 mm)		578660	204,17	
	M 22		578316	146,98	VMP ½" G (OD 21,3 mm)		578666 R	204,17		
	M 28		578318	146,98	VMPz ¾" (OD 26,9 mm)		578664	204,17		
	M 35		578390	178,12	Viega MegapressS (EN) <sup>41</sup>	VMP ¾" (OD 17,2 mm)		578660	204,17	
	M 12 S (PR-2B)	Mini Z8	574736 R	124,51		VMP ½" G (OD 21,3 mm)		578666 R	204,17	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	VMPz ¾" (OD 26,9 mm)		578664	204,17		
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	Viega Pexfit	VX 16		578552	204,17	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		VX 20		578554	204,17	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	VX 25		578556	204,17		
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	Viega Pexfit G	VX 16		578552	204,17	
						VX 20		578554	204,17	
						VX 25		578556	204,17	
Variotherm System TH	TH 11,6		578344	177,08	Viega Prestabo	V 12		578324	146,98	
	TH 16		578352 R	177,08		V 15		578328	146,98	
	TH 20		578358 R	177,08		V 18		578332	146,98	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		V 22		578334	146,98	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		V 28		578336	146,98	
VESBO CARBON	M 15		578312	146,98	V 12 S (PR-2B)	Mini Z8	574748 R	124,51		
	M 18		578314	146,98	V 14 S (PR-2B)	Mini Z8	574750 R	124,51		
	M 22		578316	146,98	V 15 S (PR-2B)	Mini Z8	574752 R	124,51		
	M 28		578318	146,98	V 18 S (PR-2B)	Mini Z8	574754 R	124,51		
	M 35		578390	178,12	V 22 S (PR-2B)	Mini Z8	574756 R	124,51		
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	V 28 S (PR-2B)	Mini Z8	574758 R	124,51		
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	V 35 S (PR-2B)	Mini Z8	574760 R	124,51		
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	Viega Profipress	V 12		578324	146,98	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		VG 14		578338	146,98	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		V 15		578328	146,98	
						VG 16		578340	146,98	
				V 18			578332	146,98		
				V 22			578334	146,98		
				V 28			578336	146,98		
				V 35			578604	178,12		
				V 12 S (PR-2B)		Mini Z8	574748 R	124,51		
				VG 14 S (PR-2B)		Mini Z8	574750 R	124,51		
				V 15 S (PR-2B)		Mini Z8	574752 R	124,51		
				VG 16 S (PR-2B)	Mini Z8	574754 R	124,51			
				V 18 S (PR-2B)	Mini Z8	574756 R	124,51			
				V 22 S (PR-2B)	Mini Z8	574758 R	124,51			
				V 28 S (PR-2B)	Mini Z8	574760 R	124,51			
				V 35 S (PR-2B)	Mini Z8	574762 R	136,96			
VESBO INOX	M 15		578312	146,98	Viega Profipress G	V 12		578324	146,98	
	M 18		578314	146,98		VG 14		578338	146,98	
	M 22		578316	146,98		V 15		578328	146,98	
	M 28		578318	146,98		VG 16		578340	146,98	
	M 35		578390	178,12		V 18		578332	146,98	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51		V 22		578334	146,98	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51		V 28		578336	146,98	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51		V 35		578604	178,12	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51		V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96		VG 14 S (PR-2B)	Mini Z8	574750 R	124,51	
						V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
				VG 16 S (PR-2B)	Mini Z8	574754 R	124,51			
				V 18 S (PR-2B)	Mini Z8	574756 R	124,51			
				V 22 S (PR-2B)	Mini Z8	574758 R	124,51			
				V 28 S (PR-2B)	Mini Z8	574760 R	124,51			
				V 35 S (PR-2B)	Mini Z8	574762 R	136,96			
VESBO MULTIPRESS TH-U	TH 16		578352 R	177,08	Viega Profipress S	V 12		578324	146,98	
	TH 20		578358 R	177,08		V 15		578328	146,98	
	TH 26		578362 R	177,08		V 18		578332	146,98	
	TH 32		578364	177,08		V 22		578334	146,98	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51		V 28		578336	146,98	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51		V 35		578604	178,12	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51		V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96		VG 14 S (PR-2B)	Mini Z8	574750 R	124,51	
	U 16		578374	165,66		V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	U 20		578378	165,66		VG 16 S (PR-2B)	Mini Z8	574754 R	124,51	
	U 26 <sup>7)</sup>		578392	194,31		V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
U 32		578382	194,31	V 22 S (PR-2B)	Mini Z8	574758 R	124,51			
				V 28 S (PR-2B)	Mini Z8	574760 R	124,51			
				V 35 S (PR-2B)	Mini Z8	574762 R	136,96			
VESBO VPREMIUM	U 16		578374	165,66						
	U 20		578378	165,66						
	U 25		578380	165,66						
	U 32		578382	194,31						
	U 40		578386	236,66						
Viega Fonterra	VX 12		578550	204,17						
	VP 14/15		578480	176,56						
	VP 16/17		578482	176,56						
	VP 20		578484	176,56						
	VP 25		578486	176,56						
Viega MegaPress (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17						
	VMPz ¾" (OD 26,9 mm)		578664	204,17						
Viega MegaPress 304 FKM (ASTM) <sup>51</sup>	VMP ½" G (OD 21,3 mm)		578666 R	204,17						
	VMPz ¾" (OD 26,9 mm)		578664	204,17						

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

<sup>1)</sup> Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

<sup>2)</sup> For taking suitable pressing inserts.

<sup>3)</sup> Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

<sup>4)</sup> For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>5)</sup> For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.

<sup>6)</sup> Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.

<sup>7)</sup> Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website:

[www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

# REMS pressing tongs Mini REMS pressing rings

## Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€	
Viega Profipress Therm	V 12		578324	146,98	
	V 15		578328	146,98	
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
Viega ProPress (ASTM) <sup>5)</sup>	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	VUS ½" (OD 15,9 mm)		578566	177,50	
	VUS ¾" (OD 22,2 mm)		578568	177,50	
	VUS 1" (OD 28,6 mm)		578570	177,50	
	VUS 1¼" (OD 34,9 mm)		578606	177,50	
Viega ProPress 304 FKM (ASTM) <sup>5)</sup>	VUS ½" S (PR-2B) (OD 15,9 mm)	Mini Z8	574764 R	124,51	
	VUS ¾" S (PR-2B) (OD 22,2 mm)	Mini Z8	574766 R	124,51	
	VUS 1" S (PR-2B) (OD 28,6 mm)	Mini Z8	574768 R	124,51	
	VUS 1¼" S (PR-2B) (OD 34,9 mm)	Mini Z8	574770 R	124,51	
	VUS ½" (OD 15,9 mm)		578566	177,50	
	VUS ¾" (OD 22,2 mm)		578568	177,50	
Viega ProPress 316 (ASTM) <sup>5)</sup>	VUS 1" (OD 28,6 mm)		578570	177,50	
	VUS 1¼" (OD 34,9 mm)		578606	177,50	
	VUA 15 (OD 12,7 mm)		578630	151,86	
	VUA 20 (OD 19,1 mm)		578632	151,86	
	VUA 25 (OD 25,4 mm)		578634	151,86	
	VUA 32 (OD 31,8 mm)		578636	159,75	
Viega Propress WATER System AUS	VUA 15 S (PR-2B) (OD 12,7 mm)	Mini Z8	574804 R	124,51	
	VUA 20 S (PR-2B)** (OD 19,1 mm)	Mini Z8	574806 R	124,51	
	VUA 25 S (PR-2B)** (OD 25,4 mm)	Mini Z8	574808 R	136,96	
	VUA 32 S (PR-2B) (OD 31,8 mm)	Mini Z8	574856 R	136,96	
	VUA 15 (OD 12,7 mm)		578630	151,86	
	VUA 20 (OD 19,1 mm)		578632	151,86	
Viega PropressGAS System AUS	VUA 25 (OD 25,4 mm)		578634	151,86	
	VUA 32 (OD 31,8 mm)		578636	159,75	
	VRX 16		578640	186,42	
	VRX 20		578642	186,42	
Viega Raxofix	VRX 16		578640	186,42	
	VRX 20		578642	186,42	
	VRX 25		578644	204,17	
	VRX 32		578646	204,17	
Viega Sanfix	VP 16/17		578482	176,56	
	VP 20		578484	176,56	
	VP 25		578486	176,56	
	VP 32		578488	195,25	
Viega Sanfix Fosta	VP 16/17		578482	176,56	
	VP 20		578484	176,56	
	VP 25		578486	176,56	
	VP 32		578488	195,25	
Viega Sanpress	V 12		578324	146,98	
	V 15		578328	146,98	
	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 12 S (PR-2B)	Mini Z8	574748 R	124,51	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
	Viega Sanpress Inox	V 15		578328	146,98
		V 18		578332	146,98
V 22			578334	146,98	
V 28			578336	146,98	
V 35			578604	178,12	
V 15 S (PR-2B)		Mini Z8	574752 R	124,51	
V 18 S (PR-2B)		Mini Z8	574756 R	124,51	
V 22 S (PR-2B)		Mini Z8	574758 R	124,51	
V 28 S (PR-2B)		Mini Z8	574760 R	124,51	
V 35 S (PR-2B)		Mini Z8	574762 R	136,96	
Viega Sanpress Inox G		V 15		578328	146,98
		V 18		578332	146,98
		V 22		578334	146,98
		V 28		578336	146,98
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	
Viega Smartpress	VX 16		578552	204,17	
	VX 20		578554	204,17	
	VX 25		578556	204,17	
	V 15		578328	146,98	
Viega Temponox	V 18		578332	146,98	
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
Viessmann	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16		578352 R	177,08
Vogel & Noot EASYTEC	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
VSH	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
	> Aalberts integrated piping systems			

### W

Watts MTR Art press	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
WATTS RADIANT	US ¾"		578534	201,16	
	US ½"		578536	201,16	
Watts WaterPEX	US ¾"		578538	201,16	
	US 1"		578540	201,16	
WATTS RADIANT	US ¾"		578534	201,16	
	US ½"		578536	201,16	
Watts RadiantPEX	US ¾"		578538	201,16	
	US 1"		578540	201,16	
WATTS RADIANT	U 16 (½")		578374	165,66	
	U 20 (¾")		578378	165,66	
Watts RadiantPEX-AL	U 25 (¾")		578380	165,66	
	U 32 (1")		578382	194,31	
Wavin Tigris K5/M5	B 16		578468	193,28	
	B 20		578472	193,28	
	B 32		578476	213,00	
	H 16		578400	159,75	
	H 20		578406	159,75	
	H 25		578408	159,75	
	H 32		578412	159,75	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 25		578364	177,08	
	TH 32		578624	234,69	
	WEECON PRESS-C-Stahl	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
TH 20 S (PR-2B)**		Mini Z8	574788 R	124,51	
TH 25 S (PR-2B)**		Mini Z8	574792 R	124,51	
TH 32 S (PR-2B)		Mini Z8	574798 R	136,96	
U 16			578374	165,66	
U 20			578378	165,66	
U 25			578380	165,66	
U 32			578382	194,31	
U 40			578386	236,66	
UP 16			578578	165,66	
UP 20			578582	165,66	
UP 25			578584	165,66	
UP 32		578586	194,31		
WEECON PRESS-Edelstahl	M 15		578312	146,98	
	M 18		578314	146,98	
	M 22		578316	146,98	
	M 28		578318	146,98	
	M 35		578390	178,12	
	M 15 S (PR-2B)	Mini Z8	574738 R	124,51	
	M 18 S (PR-2B)	Mini Z8	574740 R	124,51	
	M 22 S (PR-2B)	Mini Z8	574742 R	124,51	
	M 28 S (PR-2B)	Mini Z8	574744 R	124,51	
	M 35 S (PR-2B)	Mini Z8	574746 R	136,96	
	WEECON PRESS-Kupfer	M 15		578312	146,98
		M 18		578314	146,98
M 22			578316	146,98	
M 28			578318	146,98	
M 35			578390	178,12	
M 15 S (PR-2B)		Mini Z8	574738 R	124,51	
M 18 S (PR-2B)		Mini Z8	574740 R	124,51	
M 22 S (PR-2B)		Mini Z8	574742 R	124,51	
M 28 S (PR-2B)		Mini Z8	574744 R	124,51	
M 35 S (PR-2B)		Mini Z8	574746 R	136,96	
WEECON PRESS-Kupfer		V 15		578328	146,98
		V 18		578332	146,98
	V 22		578334	146,98	
	V 28		578336	146,98	
	V 35		578604	178,12	
	V 15 S (PR-2B)	Mini Z8	574752 R	124,51	
	V 18 S (PR-2B)	Mini Z8	574756 R	124,51	
	V 22 S (PR-2B)	Mini Z8	574758 R	124,51	
	V 28 S (PR-2B)	Mini Z8	574760 R	124,51	
	V 35 S (PR-2B)	Mini Z8	574762 R	136,96	

# REMS pressing tongs Mini

## REMS pressing rings

### Accessories for REMS radial presses 22 kN

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
WEM	U 16		578374	165,66
WIELAND-WERKE cuprotherm CTX	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 14 S (PR-2B)**	Mini Z8	574778 R	124,51
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
WKS-Press	TH 14		578348	177,08
	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	WÜRTH	TH 16		578352 R
Würth	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	HE 32		578370 R	212,06

### X

XtraConnect	F 16		578456	168,68	
	F 20		578460	168,68	
	F 26		578462	182,48	
	F 32		578464	182,48	
	F 16 S (PR-2B)**	Mini Z8	574728 R	124,51	
	F 20 S (PR-2B)**	Mini Z8	574730 R	124,51	
	F 26 S (PR-2B)**	Mini Z8	574732 R	124,51	
	F 32 S (PR-2B)	Mini Z8	574734 R	136,96	
	H 16		578400	159,75	
	H 20		578406	159,75	
	H 26		578410	159,75	
	H 32		578412	159,75	
	TH 16		578352 R	177,08	
	TH 20		578358 R	177,08	
	TH 26		578362 R	177,08	
	TH 32		578364	177,08	
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51	
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51	
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51	
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96	
	U 16		578374	165,66	
	U 20		578378	165,66	
	(DN 26)	U 25		578380	165,66
		U 32		578382	194,31
		VP 16		578482	176,56
		VP 20		578484	176,56
		VP 32		578488	195,25

### Y

YX COPPER	Yz 16 UNI		578740	184,45
UNIPEX Water & Gas	Yz 20 UNI		578742	184,45
(AUS)	Yz 25 UNI		578744	184,45
	Yz 32 UNI		578746	184,45

System	Pressing tongs Mini / pressing rings	Driven by adapter tongs	Art.-No.	€
<b>Z</b>				
ZEWOTHERM	TH 12		578346	177,08
Zewo Press Premium	TH 16		578352 R	177,08
	TH 17		578354	177,08
	TH 18		578356	177,08
	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 40		578624	234,69
	TH 12 S (PR-2B)**	Mini Z8	574776 R	124,51
	TH 16 S (PR-2B)**		574782 R	124,51
	TH 17 S (PR-2B)**	Mini Z8	574784 R	124,51
	TH 18 S (PR-2B)**	Mini Z8	574786 R	124,51
	TH 20 S (PR-2B)**		574788 R	124,51
	TH 26 S (PR-2B)**		574794 R	124,51
TH 32 S (PR-2B)		574798 R	136,96	
ZEWOTHERM	TH 16		578352 R	177,08
Zewo Press PPSU	TH 20		578358 R	177,08
	TH 26		578362 R	177,08
	TH 32		578364	177,08
	TH 16 S (PR-2B)**	Mini Z8	574782 R	124,51
	TH 20 S (PR-2B)**	Mini Z8	574788 R	124,51
	TH 26 S (PR-2B)**	Mini Z8	574794 R	124,51
	TH 32 S (PR-2B)	Mini Z8	574798 R	136,96
ZURN	US ¾"		578534	201,16
INDUSTRIES	US ½"		578536	201,16
ZURN PEX	US ¾"		578538	201,16
	US 1"		578540	201,16

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations. Read and observe the instructions for use and the installation instructions of the system provider/manufacturer.

\*\* Can also be driven by the REMS Eco-Press manual radial press using the Z8 adapter tongs, see page 185. Observe the national regulations.

- 1) Only pressing tongs from designation "108" (1<sup>st</sup> quarter of 2008), "208" (2<sup>nd</sup> quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- 2) For taking suitable pressing inserts.
- 3) Only pressing tongs from designation "117" (1<sup>st</sup> quarter of 2017), "217" (2<sup>nd</sup> quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- 4) For pipes of the EN technical standard. Observe the instructions for use of the system provider/manufacturer.
- 5) For pipes of the ASTM technical standard. Observe the instructions for use of the system provider/manufacturer.
- 6) Only use Mini pressing tongs identified by "VMP ½" G" on the pressing jaws for gas installations.
- 7) Previous designation: Mini C 26 pressing tongs

The suitability of REMS pressing tools for pressfitting systems: Date 27.10.2023. For the updated situation regarding suitability status check our website: [www.rems.de](http://www.rems.de) > Downloads > Product catalogues, brochures > REMS Catalogue.

See page 183 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

### Accessories

Description	Art.-No.	€
<b>Adapter tongs Mini Z8</b> for driving REMS pressing rings S (PR-2B)	574700R	<b>144,28</b>
<b>Steel case</b> with insert for adapter tongs Mini Z8 and adapter tongs Z8 as well as 6 REMS pressing rings S (PR-2B)	574516R	<b>96,53</b>
<b>L-Boxx system case</b> with inlay for Mini Z8 adapter tongs and Z8 adapter tongs as well as 14 REMS S pressing rings (PR-2B)	574704R	<b>146,36</b>
<b>Steel case</b> with insert for 8 pressing tongs Mini/ cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295R	<b>96,53</b>
<b>L-Boxx system case</b> with insert for 11 pressing tongs Mini and 6 pressing rings S (PR-2B)	578659R	<b>146,36</b>

