REMS Amigo 22V

Powerful, mobile, handy cordless tool for threading with unique support bracket. Ready for use any-where, without vice. Ideal for repair, renovation, job site. Li-lon 22V Technology. For battery and corded operation.

Pipe threads $\frac{1}{8} - 1$ ", 16 - 32 mm Bolt threads 6 - 30 mm, $\frac{1}{4} - 1$ "

Thread types see page 36, 37.

REMS Amigo 22V – mobile, handy, light. Li-lon 22V, 9.0 Ah, 194Wh battery, for approx. 52 ¾" threads with one battery charge*.

System advantage

Only **one** type of small, compact quick-change die heads and only **one** type of dies for all REMS die stocks. Thus efficient and easy stocking. No confusion possible.

Support bracket

Solid, easy to use, supports the die stock against torque in both directions. Secure clamping through angular clamping spindle with self-supporting effect. Very simple mounting of die stock onto support bracket and pipe.

Design

Compact, robust, job site-proven. Can be used anywhere, even without vice. Slender design for working in confined areas. Mobile, handy, light. Drive unit with battery pack weighs only 5.6 kg. Practical D-shaped handle with soft grip. Perfect seating of quick-change die heads. Machine status check with overload protection of the drive unit against too high currents, with overheating protection by motor temperature monitoring (NTC), with electronic battery charging status check by a 2-coloured green/red LED.

Drive

Solid, maintenance-free gear. Powerful battery motor 22 V, with large power reserve, 500W output. High cutting speed 27-20 rpm. Safety tip switch.

Battery or mains operation

REMS Li-lon 22 V Technology, see page 20–25. Highly resistant Li-lon 22 V batteries with 9.0 Ah capacity for long service life. Light and powerful, for 52 3/1" threads with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W, 22 V or 290 W, 22 V, for shorter charging times, as accessory. Voltage supply 220 – 240 V, 22 V, 40 A output, for mains operation instead of Li-lon battery 22 V, as accessory.

Quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Dies

The proven, industructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread-cutting oil

REMS Sanitol and REMS Spezial (page 53). Specially developed for threading. High cooling and lubricating effect. Essential for clean threads and longer service life of dies, tools and machines.

Nipple-threading

Efficient with REMS Nippelspanner 3% – 1" (2") (page 52).



German Quality Product





Supply format

REMS Amigo 22 V Set. Cordless die stock with quick-change die heads. For pipe threads $\frac{1}{6}-1$ ", 16-32 mm, bolt threads 6-30 mm, $\frac{1}{6}-1$ ". For right and left-hand threads. Drive unit with maintenance-free gear, powerful battery motor 22V, 500 W. Safety switch. Right and left-hand rotation, machine status check with overload protection, temperature monitoring, battery charging status check. Li-lon 22V, 9.0 Ah, 194 Wh battery, 100-240V, 50-60 Hz, 90W, 22V rapid charger. Support bracket for both directions. REMS eva quick-change die heads for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R right-hand, for pipe thread taper Pipe Thread ASME B1.20.1 NPT right-hand or for threading electric conduit according to EN 60423 M. In sturdy steel case.

Description	ArtNo.	€
Set R ½ + ¾ +1	530015 R220	1.950,00
Set NPT ½ + ¾ +1	530018R220	1.950,00
Set M 20 + 25 + 32	530016 R220	2.070,00

Other voltages on request.



Accessories

Description	ArtNo.	€
Quick-change die heads, dies, attachment heads for button dies, see page 36-37.		
Akku-Amigo 22 V drive unit,		
without battery	530004R22	1.200,00
Support bracket Amigo 2 Compact	543010	236,00
Battery Li-lon 22 V, 9.0 Ah, 194 Wh	571583R22	415,00
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W, 22 V	571585 R220	199,00
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W, 22 V	571587 R220	429,00
Voltage supply 220 – 240 V, 50 – 60 Hz, 900 W, 22 V, 40 A, for mains operation instead of battery Li-lon 22 V	571578R220	537,00
REG St ¼ - 2", pipe deburrer, see page 105.	731700	156,00
Ratchet lever eva see page 28.	522000	175,00
Thread-cutting oil see page 53.		
REMS Nippelspanner % – 2" see page 52.		
Steel case with inlay	566030R	134,00
REMS Lumen 2800 22V, cordless LED flood light, see pa	ige 119	

