

REMS Lumen 2800 22V

Cordless LED flood light

Powerful, mobile cordless LED flood light with high light intensity. Li-Ion 22V Technology. For battery and corded operation. For the building site and the workshop.

Light flux brightness stage 1	1100 lm
Light flux brightness stage 2	2000 lm
Light flux brightness stage 3	2800 lm

REMS Lumen 2800 22V – lights everywhere. With high light intensity. Mobile, handy, light. For battery and corded operation. Continuous swivel.

Universal use

Powerful, mobile, cordless LED flood light with high light intensity for universal use on the building site or in the workshop. 3 selectable brightness stages, ideal for any application purpose.

Design

Handy, lightweight, cordless LED flood light, only 1.7 kg, with battery only 2.1 kg. Impact-resistant plastic housing. LEDs protected by impact-resistant, unbreakable acrylic glass. Flood light housing swivels through 360°, fixable by wing nuts, for optimum alignment of the light. On/Off switch. Tubular steel frame with plastic plate and pluggable hook, for fastening or hanging the flood light. Practical, non-slip handle. 220–240V, 50–60 Hz, 138 W power supply, for mains operation included. Holder for REMS Li-Ion 21.6 V integrated into the housing for cordless instead of mains operation. In cordless operation with Li-Ion 21.6V, 2.5 Ah, 54 Wh (output). Practical, sturdy, telescopic tripod stand, only 1.9 kg, for accurate positioning of the LED flood light, adjustable height from 615 to 1,590 mm above floor level, collapsible for easy transport, as an accessory.

LED flood light

Modern, energy-saving LED flood light with high light intensity. Lights immediately without switch-on delay. LED brightness selectable in 3 stages. 120° radiation angle for high illumination. Colour temperature 6,500 K. Efficient heat dissipation by high-quality, aluminium, ribbed heat sinks prevents overheating. For continuous operation.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100–240V, 90 W. Rapid charger 100–240V, 290W, for shorter charging times, as accessory.

Description	Operating hours h*		
	Stage 1	Stage 2	Stage 3
Battery Li-Ion 21.6V, 2.5Ah	5.4	2.4	1.6
Battery Li-Ion 21.6V, 4.4Ah	9.6	4.2	2.8
Battery Li-Ion 21.6V, 5.0Ah	10.9	4.8	3.2
Battery Li-Ion 21.6V, 9.0Ah	19.6	8.6	5.7

Supply format

REMS Lumen 2800 22V Set Power-Edition. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Voltage supply 220–240V, 50–60 Hz, 138 W. Without battery, without rapid charger. In a carton.

	Art.-No.	€
	175210R220	144,28

Other voltages on request.

Supply format

REMS Lumen 2800 22V Set. Cordless LED flood light with high light intensity. For battery and corded operation. Light flux ≤ 2800 lm. Battery Li-Ion 21.6 V, 2.5 Ah, rapid charger 220–240V or 110 V, 50–60 Hz, 70 W. Voltage supply 220–240V, 50–60 Hz, 138W. In a carton.

	Art.-No.	€
	175211R220	455,68

Other voltages on request.

Accessories

Description	Art.-No.	€
Battery Li-Ion 21.6V, 2.5 Ah	571571R22	258,46
Battery Li-Ion 21.6V, 4.4 Ah	571574R22	372,64
Battery Li-Ion 21.6V, 5.0 Ah	571581R22	310,36
Battery Li-Ion 21.6V, 9.0 Ah	571583R22	414,16
Rapid charger 100–240V, 50–60 Hz, 90W	571585R220	175,42
Rapid charger 100–240V, 50–60 Hz, 290W	571587R220	414,16
REMS 3B telescopic stand, on a tripod, height-adjustable, collapsible	175230R	31,04

