

REMS pressing tongs Mini Set

Accessories for REMS radial presses 22 kN



Supply format

REMS pressing tongs Mini Set. REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**). Highly durable, made of tenacious, specially hardened special steel. The pressing contours are system-specific and correspond to the pressing contours of the respective press fitting systems. Thus perfect system-conformity, safe press jointing. Driven by all REMS radial presses 22 kN. In L-Boxx system case.

Description	Art.-No.	€
Set ACz 12 + 16 + 20	578081R	713,30
Set B 16 + 20 + 26	578074R	760,00
Set BMP $\frac{1}{4} + \frac{3}{8} + \frac{1}{2} + \frac{5}{8}$"	578090R	863,40
Set BMP $\frac{1}{4} + \frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8} + 1 + 1\frac{1}{8}$"	578091R	1.577,80
Set F 16 + 20 + 26	578072R	679,20
Set G 16 + 20 + 26	578073R	701,90
Set H 16 + 20 + 26	578077R	636,50
Set HA 16 + 20 + 26	578078R	779,00
Set M 15 + 18 + 22 + 28	578059R	747,80
Set M 15 + 18 + 22 + 28 + 35	578055R	927,50
Set M 15 + 22 + 28 + 35	578057R	777,80
Set RFz 12 + 16 + 20	578079R	713,30
Set RFz 16 + 20 + 25	578075R	713,30
Set RN 16 + 20 + 25	578076R	656,30
Set TH 16 + 20 + 26	578069R	690,50
Set U 16 + 20 + 25	578070R	656,30
Set UP 16 + 20 + 25	578071R	656,30
Set V 14 + 16 + 22 + 28	578067R	747,80
Set V 15 + 18 + 22 + 28	578060R	747,80
Set V 15 + 18 + 22 + 28 + 35	578056R	927,50
Set V 15 + 22 + 28 + 35	578058R	777,80
Set VG 14 + 16, V 22 + 28	578068R	747,80
Set VMP $\frac{3}{8} + \frac{1}{2} + \frac{3}{4}$"	578901R	773,30
Set VP 16 + 20 + 25	578095R	687,80
Set VRX 16 + 20 + 25	578094R	735,30

REMS pressing rings S Set

Accessories for REMS radial presses 22 kN



Supply format

REMS pressing rings S Set Mini Z8. REMS pressing rings S (PR-2B), continuously swivellable, with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access. Highly durable, made of tenacious, specially hardened special steel. The pressing contours are system-specific and correspond to the pressing contours of the respective press fitting systems. Thus perfect system-conformity, safe press jointing. Adapter tongs Mini Z8 for driving by all REMS radial presses 22 kN.

Description	Art.-No.	€
REMS pressing rings S Set Mini Z8 in sturdy steel case		
F 16 + 20 + 26	574620R	635,00
M 15 + 18 + 22	574614R	635,00
M 15 + 22 + 28	574618R	635,00
TH 16 + 20 + 26	574622R	635,00
U 16 + 20 + 25	574634R	635,00
U 16 + 20 + 26	574636R	635,00
V 15 + 18 + 22	574612R	635,00
V 15 + 22 + 28	574616R	635,00
REMS pressing rings S Set Mini Z8 in L-Boxx system case		
BMP 6 + 8 + 10 + 12 + 15 + 16 + 18 + 22 + 28	574624R	1.458,00
BMP $\frac{1}{4} + \frac{3}{8} + \frac{1}{2} + \frac{5}{8} + \frac{3}{4} + \frac{7}{8}$ "	574632R	1.022,00
M 12 + 15 + 18 + 22 + 28 + 35	574626R	1.083,00
V 12 + 15 + 18 + 22 + 28 + 35	574628R	1.083,00
V 12 + 14 + 15 + 16 + 18 + 22 + 28 + 35	574630R	1.341,00