

REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521000	210,00
	R 1/4	521010	183,00
	R 3/8	521020	124,00
	R 1/2	521030	129,00
	R 3/4	521040	135,00
	R 1	521050	140,00
	R 1 1/4	521060	146,00
	R 1 1/2	521070	172,00
	R 2	521080	183,00
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521100	252,00
	R 1/4 LH	521110	220,00
	R 3/8 LH	521120	149,00
	R 1/2 LH	521130	155,00
	R 3/4 LH	521140	162,00
	R 1 LH	521150	168,00
	R 1 1/4 LH	521160	176,00
	R 1 1/2 LH	521170	207,00
	R 2 LH	521180	220,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521200	210,00
	NPT 1/4	521210	183,00
	NPT 3/8	521220	124,00
	NPT 1/2	521230	129,00
	NPT 3/4	521240	135,00
	NPT 1	521250	140,00
	NPT 1 1/4	521260	146,00
	NPT 1 1/2	521270	172,00
	NPT 2	521280	183,00
Threads M for electric conduit EN 60423	M 16 x 1.5	521300	162,00
	M 20 x 1.5	521310	162,00
	M 25 x 1.5	521320	168,00
	M 32 x 1.5	521330	176,00
	M 40 x 1.5	521340	207,00
	M 50 x 1.5	521350	219,60



Right-hand pipe thread



Left-hand pipe thread

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8	521002RWS	95,70
	R 1/4	521012RWS	90,30
	R 3/8	521022RWS	90,30
	R 1/2	521032RWS	90,30
	R 3/4	521042RWS	98,90
	R 1	521052RWS	98,90
	R 1 1/4	521062RWS	98,90
	R 1 1/2	521072RWS	98,90
	R 2	521082RWS	98,90
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R 1/8 LH	521102RWS	115,00
	R 1/4 LH	521112RWS	109,00
	R 3/8 LH	521122RWS	109,00
	R 1/2 LH	521132RWS	109,00
	R 3/4 LH	521142RWS	119,00
	R 1 LH	521152RWS	119,00
	R 1 1/4 LH	521162RWS	119,00
	R 1 1/2 LH	521172RWS	119,00
	R 2 LH	521182RWS	119,00
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT 1/8	521202RWS	95,70
	NPT 1/4	521212RWS	90,30
	NPT 3/8	521222RWS	90,30
	NPT 1/2	521232RWS	90,30
	NPT 3/4	521242RWS	98,90
	NPT 1	521252RWS	98,90
	NPT 1 1/4	521262RWS	98,90
	NPT 1 1/2	521272RWS	98,90
	NPT 2	521282RWS	98,90
Threads M for electric conduit EN 60423	M 16 x 1.5	521302RWS	119,00
	M 20 x 1.5	521312RWS	119,00
	M 25 x 1.5	521322RWS	119,00
	M 32 x 1.5	521332RWS	119,00
	M 40 x 1.5	521342RWS	119,00
	M 50 x 1.5	521352RWS	118,68



German Quality Product