REMS quick-change die heads

Accessories for REMS die stocks and other makes

REMS quick-change die heads

Proven technology, high-grade material and precise machining of die head, dies and cover form a unit and ensure an excellent start-cutting performance and easy threading. No stalling of dies. Long, precise pipe guidance for perfect pipe centering. The chip holes which become wider at the outside enable good chip flow and clean threads.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛	521000	**202,41**
	R ¼	521010	**176,46**
	R ⅜	521020	**119,37**
	R ½	521030	**124,56**
	R ¾	521040	**129,75**
	R 1	521050	**134,94**
	R 1¼	521060	**140,13**
	R 1½	521070	**166,08**
	R 2	521080	**176,46**
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ LH	521100	**242,89**
	R ¼ LH	521110	**211,75**
	R ⅜ LH	521120	**143,24**
	R ½ LH	521130	**149,47**
	R ¾ LH	521140	**155,70**
	R 1 LH	521150	**161,93**
	R 1¼ LH	521160	**168,16**
	R 1½ LH	521170	**199,30**
	R 2 LH	521180	**211,75**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT ⅛	521200	**202,41**
	NPT ¼	521210	**176,46**
	NPT ⅜	521220	**119,37**
	NPT ½	521230	**124,56**
	NPT ¾	521240	**129,75**
	NPT 1	521250	**134,94**
	NPT 1¼	521260	**140,13**
	NPT 1½	521270	**166,08**
	NPT 2	521280	**176,46**
Threads M for electric conduit EN 60423	M 16 × 1.5	521300	**155,70**
	M 20 × 1.5	521310	**155,70**
	M 25 × 1.5	521320	**161,93**
	M 32 × 1.5	521330	**168,16**
	M 40 × 1.5	521340	**199,30**
	M 50 × 1.5	521350	**211,75**

Right-hand pipe thread

Left-hand pipe thread

German Quality Product

REMS dies

Accessories for REMS die stocks

REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.	€
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛	521002RWS	**92,38**
	R ¼	521012RWS	**87,19**
	R ⅜	521022RWS	**87,19**
	R ½	521032RWS	**87,19**
	R ¾	521042RWS	**95,50**
	R 1	521052RWS	**95,50**
	R 1¼	521062RWS	**95,50**
	R 1½	521072RWS	**95,50**
	R 2	521082RWS	**95,50**
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ LH	521102RWS	**111,07**
	R ¼ LH	521112RWS	**104,84**
	R ⅜ LH	521122RWS	**104,84**
	R ½ LH	521132RWS	**104,84**
	R ¾ LH	521142RWS	**115,22**
	R 1 LH	521152RWS	**115,22**
	R 1¼ LH	521162RWS	**115,22**
	R 1½ LH	521172RWS	**115,22**
	R 2 LH	521182RWS	**114,18**
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT ⅛	521202RWS	**92,38**
	NPT ¼	521212RWS	**87,19**
	NPT ⅜	521222RWS	**87,19**
	NPT ½	521232RWS	**87,19**
	NPT ¾	521242RWS	**95,50**
	NPT 1	521252RWS	**95,50**
	NPT 1¼	521262RWS	**95,50**
	NPT 1½	521272RWS	**95,50**
	NPT 2	521282RWS	**95,50**
Threads M for electric conduit EN 60423	M 16 × 1.5	521302RWS	**115,22**
	M 20 × 1.5	521312RWS	**115,22**
	M 25 × 1.5	521322RWS	**115,22**
	M 32 × 1.5	521332RWS	**115,22**
	M 40 × 1.5	521342RWS	**115,22**
	M 50 × 1.5	521352RWS	**114,60**

German Quality Product

All prices excl. VAT