Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.

Copper tubes $\leq \emptyset$ 35 mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 1950°C (3500°F)

REMS Blitz - extremely fast soft soldering.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 200 g/h!

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame

Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.



REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes $\leq \emptyset$ 35 mm. Piezo-electric self-lighting. Hose connector BSPP %" LH. Hollow cap nut and socket BSPP %" LH. In blister pack.

·	ArtNo.	Din.
	160010R	30 010,00









Accessories

Description	ArtNo.	Din.			
REMS soldering material see page 267.					
High pressure hose 3 m, BSPP ¾ LH	152106	11 130,00			
Pressure reducer for 5 or 11 kg gas bottles (2 bar)	152109	14 320,00			





REMS Macho

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.

Copper tubes and others $\leq \emptyset$ 64 mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 2500°C

REMS Macho – super fast brazing.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 360 g/h!

Acetylene only

Injection torch burns atmospheric oxygen. Hence only acetylene necessary.

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame

Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others $\leq \emptyset$ 64 mm. Piezo-electric self-lighting. Hose connector BSPP %" LH. Hollow cap nut and socket %" LH. In blister pack.

0011	70 Entrodow cup hat and socket 70 Entrodoct pack.				
			ArtNo.	Din.	
			161010R	33 070,00	

Turbo soldering torch acetylene



German Quality Product





Accessories

REMS soldering material see page 267.