# **REMS Contact 2000**

Compact, powerful electric tool for soft soldering. With safety transformer. For trade and industry. For the building site and the workshop.

| Copper tubes     | Ø 6–54 mm<br>Ø ¼–21⁄8' |
|------------------|------------------------|
| Heating capacity | 900°C (1650°F)         |

### REMS Contact 2000 – the smallest, strongest and fastest unit of its kind. 2000 W soldering power. 4 m long soldering tongs cable.

Handy, compact. Favourable weight, small in size for work and transport. L  $\times$  W  $\times$  H: 210  $\times$  150  $\times$  140 mm.

Enormous heating capacity (900°C) ensures super-fast soldering. Rated power = Soldering capacity = 2000 W! Soldering time, e.g. for  $\emptyset$  18 mm in only 18 s.

Can be used anywhere, with rod electrodes in tight spots also. Ready to solder any time, to be connected to a socket only. No adjustment of soldering current necessary. Wide work radius thanks to 4 m cable length. Flexible cable protector hose.

Indifferent to temperature influences electric control of soldering current.

Prisma-electrodes for universal use, maximum use through favorable seat. Rod-electrodes for working in tight spots. Electrode holders and bolts in stainless steel. Electrodes can be easily replaced.



Prisma-electrodes for universal use, maximum use through favorable seat.

## Electric soldering unit



German Quality Product





**REMS Contact 2000.** Electric soldering unit for soft soldering of copper tubes  $\emptyset \ 6-54 \text{ mm}, \emptyset \ 4-2\%^*$ . 230 V, 50-60 Hz, 2000 W, control voltage 24 V. Soldering pliers with 4 m cable length. Safety transformer, 2 prism electrodes. In a carton.

| ArtNo.      | Din.      |
|-------------|-----------|
| 164011 R220 | 98 310,00 |

Other voltages on request.

### Supply format

**REMS Contact 2000 Super-Pack.** Electric soldering unit for soft soldering of copper tubes Ø 6–54 mm, Ø  $\frac{1}{4}$ –2 $\frac{1}{6}$ °. 230 V or 110 V, 50–60 Hz, 2000 W, control voltage 24 V. Soldering pliers with 4 m cable length, safety transformer, 4 prism electrodes, 2 rod electrodes, 250 g quality soft solder REMS Lot Cu 3, 250 g quality soft solder paste REMS Paste Cu 3, 1 pipe cutter REMS RAS Cu-INOX 3-35, pack of 10 cleaning pads REMS Cu-Vlies. In sturdy steel case.

| ArtNo.     | Din.       |
|------------|------------|
| 164050R220 | 122 500,00 |
|            |            |

#### Accessories

| Description                               | ArtNo.   | Din.     |
|-------------------------------------------|----------|----------|
| Prism electrodes (pack of 2)              | 164111R  | 3 130,00 |
| Prism electrodes with holders (pack of 2) | 164110 R | 5 270,00 |
| Rod electrodes (pack of 2)                | 164115R  | 3 260,00 |
| Steel case with insert                    | 164250R  | 15840,00 |
| REMS soldering material see page 267.     |          |          |



