

# REMS Power-Press ACC

Electro-hydraulic radial press 32 kN  
with automatic retraction

Universal, handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems.

Pipe pressing joints  $\varnothing$  10 – 108 (110) mm  
 $\varnothing$   $\frac{3}{8}$  – 4"

Complete range of REMS pressing tongs/  
pressing rings for all common pressfitting systems,  
see page 198 – 238.

**REMS Power-Press ACC – universal up to  $\varnothing$  110 mm.**  
**Secure crimping in seconds. With automatic circuit**  
**control. Automatic locking of pressing tongs.**

## System advantage

Only **one** type of pressing tongs/pressing rings for all REMS radial presses 32 kN and suitable radial presses of other makes with 32 kN thrust force.

All pressing tongs marked with \* have another connection and also fit the manual radial press REMS Eco-Press. All pressing rings S (PR-2B) marked with \*\* can also be driven with the manual radial press REMS Eco-Press using the adapter tong Z8.

## Pressing tongs/pressing rings for all common systems

Complete assortment of REMS pressing tongs/pressing rings for all common pressfitting systems (page 198 – 238). Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system conformity, safe press jointing. Adapter tongs required for driving the REMS (PR) pressing rings, see page 238.

## Design

Compact, robust, job site-proven. Small in size, slender design, drive unit only 4.7 kg. Works anywhere, free-hand, overhead, in confined areas. Ideal weight distribution for single handed operation. Ergonomically designed housing with recessed grip. Swivelling pressing tongs/adapter tongs seat. Secure seating of pressing tongs by automatic locking. Also suitable for other suitable makes of pressing tongs/pressing rings.

## Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

## Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 32 kN. Powerful electro-hydraulic drive with proven universal motor 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.



German Quality Product



Info

## Supply format

**REMS Power-Press ACC Basic-Pack.** Electro-hydraulic radial press 32 kN with automatic retraction for producing pressing joints  $\varnothing$  10 – 108 (110) mm,  $\varnothing$   $\frac{3}{8}$  – 4". For driving REMS pressing tongs/pressing rings and other suitable makes of pressing tongs/pressing rings. Pressing tongs seat with automatic locking. Electro-hydraulic drive with proven universal motor 230 V or 110 V, 50 – 60 Hz, 450 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Version	Art.-No.	Din.
In sturdy steel case.	577010R220	<b>179 900,00</b>
In L-Boxx system case.	577013R220	<b>185 000,00</b>
Other voltages on request.		



## Accessories

Description	Art.-No.	Din.
<b>REMS Power-Press ACC Drive Unit</b>	577000R220	<b>167 200,00</b>
<b>REMS pressing tongs/pressing rings</b> see page 198 – 238.		
<b>Adapter tongs</b> for REMS pressing rings see page 238.		
<b>REMS cropping tongs</b> for threaded rods see page 241.		
<b>REMS cable shear</b> for electric cable see page 241.		
<b>Steel case</b> with insert	570280R	<b>13 540,00</b>
<b>L-Boxx system case</b> with inserts	571283R	<b>18 010,00</b>

