

REMS cutter wheels

German Quality Products
For REMS pipe cutters and other makes

Specially hardened cutter wheels in approved, tough-hard REMS die steel, ensure a long service life. German Quality Products.

REMS cutter wheels also fit in suitable pipe cutters of other makes, see table with dimensional data.

REMS cutter wheel	Material	Wall thickness	to fit following pipe cutters	Capacity Ø	Art.-No.	Din.
St ½-4", s 8	Steel pipes	s ≤ 8 mm	REMS RAS St ½-2" REMS RAS St 1¼-4"	½-2" 1¼-4"	341614 R	1 910,00
St 1-4", s 12	Steel pipes	s ≤ 12.5 mm	REMS RAS St 1¼-4"	1¼-4"	381622 R	4 380,00
Cu-INOX 3-120, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	REMS RAS Cu-INOX 3-16 REMS RAS Cu-INOX 3-28 REMS RAS Cu-INOX 3-35 REMS RAS Cu-INOX 3-42 REMS RAS Cu-INOX 6-42 REMS RAS Cu-INOX 6-64 REMS RAS Cu-INOX 64-120 REMS RAS Cu 3-35 REMS RAS Cu 3-42	3-16 mm 3-28 mm 3-35 mm 3-42 mm 6-42 mm 6-64 mm 64-120 mm 3-35 mm 3-42 mm	113210 R	1 490,00
Cu-INOX 3-120 S, s 4, on needle bearings	Copper tubes, stainless steel tubes	s ≤ 4 mm	REMS RAS Cu-INOX 3-28 S REMS RAS Cu-INOX 3-35 S REMS RAS Cu-INOX 8-42 S REMS RAS Cu-INOX 8-64 S	3-28 mm 3-35 mm 8-42 mm 8-64 mm	113213 R	2 600,00
Cu-INOX b 3, s 4	Copper tubes, stainless steel tubes	s ≤ 4 mm	See table "Dimensional data for REMS cutter wheels"		113220 R	1 490,00
Cu 3-120, s 3	Copper tubes	s ≤ 3 mm	REMS RAS Cu-INOX 3-16 REMS RAS Cu-INOX 3-25 REMS RAS Cu-INOX 3-28 REMS RAS Cu-INOX 3-35 REMS RAS Cu-INOX 3-42 REMS RAS Cu-INOX 6-42 REMS RAS Cu-INOX 6-64 REMS RAS Cu-INOX 64-120 REMS RAS Cu 3-16 REMS RAS Cu 3-25 REMS RAS Cu 3-28 REMS RAS Cu 3-35 REMS RAS Cu 3-42 REMS RAS Cu 8-42 REMS RAS Cu 8-64	3-16 mm 3-25 mm 3-28 mm 3-35 mm 3-42 mm 6-42 mm 6-64 mm 64-120 mm 3-16 mm 3-25 mm 3-28 mm 3-35 mm 3-42 mm 8-42 mm 8-64 mm	113225 R	1 490,00
P 10-40, s 4,5	Plastic pipes, composite tubes	s ≤ 4,5 mm	REMS RAS P 10-32 T REMS RAS P 10-40 T	10-32 mm 10-40 mm	290023 R	2 400,00
P 10-63, s 7	Plastic pipes, composite tubes	s ≤ 7 mm	REMS RAS P 10-40 REMS RAS P 10-63	10-40 mm 10-63 mm	290016 R	2 400,00
P 50-315, s 11	Plastic pipes, composite tubes	s ≤ 11 mm	REMS RAS P 50-110 REMS RAS P 50-125 REMS RAS P 110-160 REMS RAS P 180-315	50-110 mm 50-125 mm 110-160 mm 180-315 mm	290116 R	2 920,00
P 50-315, s 16	Plastic pipes, composite tubes	s ≤ 16 mm	REMS RAS P 50-110 REMS RAS P 50-125 REMS RAS P 110-160 REMS RAS P 180-315	50-110 mm 50-125 mm 110-160 mm 180-315 mm	290216 R	3 480,00
P 50-315, s 19	Plastic pipes, composite tubes	s ≤ 19 mm	REMS RAS P 50-110 REMS RAS P 50-125 REMS RAS P 110-160 REMS RAS P 180-315	50-110 mm 50-125 mm 110-160 mm 180-315 mm	290316 R	5 610,00
W INOX 10-32/40 S, on needle bearings	Corrugated metal hoses (corrugated pipes) of stainless steel		REMS RAS W INOX 10-32/40 S	DN 10-32 (40)	113461 R	1 460,00

Dimensional data for REMS cutter wheels



REMS cutter wheel	Art.-No.	OD mm	W mm	ID mm
St ½-4", s 8	341614 R	32.30	18.94	9.04
St 1-4", s 12	381622 R	41.30	18.94	9.04
Cu-INOX 3-120, s 4	113210 R	19.70	4.93	5.00
Cu-INOX 3-120 S, s 4	113213 R	19.70	4.93	5.00
Cu-INOX b 3, s 4	113220 R	18.70	3.07	4.80
Cu 3-120, s 3	113225 R	18.70	4.93	5.00
P 10-40, s 4,5	290023 R	20.50	4.93	5.00
P 10-63, s 7	290016 R	25.20	5.97	6.00
P 50-315, s 11	290116 R	35.30	10.95	8.00
P 50-315, s 16	290216 R	45.30	10.95	8.00
P 50-315, s 19	290316 R	51.30	10.95	8.00
W INOX 10-32/40 S	113461 R	26.60	4.93	5.00

German Quality Products

