REMS Ax-Press 30 22 V

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-lon 22V Technology. For battery and corded operation.

Axial compression

Ø 12–32 mm

REMS Ax-Press 30 22V – up to Ø 32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 2.5 Ah battery for approx. 220 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*.

Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system conformity, safe jointing.

Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads. Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

High pressing force for perfect pressing in seconds, e.g. Ø 26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system.Safety tip switch.

Battery or mains operation

Li-lon 22V Technology. Highly resistant Li-lon 21.6V battery with 2.5, 4.4, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-lon 21.6V, 2.5Ah battery for approx. 220 pressings, 4.4Ah for approx. 380 pressings, 5.0Ah for approx. 430 pressings, 9.0Ah for approx. 780 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240V, 90W. Rapid charger 100 – 240V, 290W, for shorter charging times, as accessory. Voltage supply 220–240V/21.6V, 15A output, for mains operation instead of Li-lon battery 21.6 V, as accessory.

Supply format

REMS Ax-Press 30 22V Basic-Pack. Cordless axial press 30 kN for producing compression sleeve joints with crimping sleeve Ø 12–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-lon 21.6 V, 2.5 Ah, rapid charger 220–240V, 50–60Hz, 70W. In sturdy steel case.

€	ArtNo.
2.117,52	573018R220

Accessories

ArtNo.	€
573008R22	1.577,76
571571 R22	258,46
571574R22	372,64
571581R22	310,36
571583R22	414,16
571585R220	175,42
571587R220	414,16
571567 R220	414,16
573282R	110,03
	573008R22 571571R22 571571R22 571574R22 571581R22 571585R22 571587R220 571587R220 571567R220

REMS compression heads

-			
Compression sleeve system	Compression head	ArtNo.	€
Brasstech Raptor/	ME 14 (pack of 2)	573100	107,95
Metalpex/ Raptor 2/	ME 16 (pack of 2)	573102	107,95
MULTItermoSAN	ME 20 (pack of 2)	573106	107,95
	ME 26 (pack of 2)	573108	107,95
	ME 32 (pack of 2)	573110	118,33
General Fittings	ME 14 (pack of 2)	573100	107,95
Serie 5400	ME 16 (pack of 2)	573102	107,95
	ME 20 (pack of 2)	573106	107,95
	ME 26 (pack of 2)	573108	107,95
	ME 32 (pack of 2)	573110	118,33













REMS compression heads

Compression sleeve system	Compression head	ArtNo.	€
Georg Fischer pfci	ME 16 (pack of 2)	573102	107.95
ALUPEX-EXPRESS/	ME 20 (pack of 2)	573106	107,95
Alupex Gas System	ME 26 (pack of 2)	573108	107,95
Logstor	ME 16 (pack of 2)	573102	107,95
	LR 20 (pack of 2)	573430	107,95
	LR 22 (pack of 2)	573432	107,95
	LR 25 (pack of 2)	573434	107,95
	LR 28 (pack of 2)	573436	107,95
	LR 32 (pack of 2)	573438	118,33

Cordless axial press 30 kN