

Powerful, compact electric tool for efficient machining of T-branches of hard and soft tubes for tube installations without fittings.

Hard and soft copper tubes  $\varnothing$  10 – 22 mm  
 $\varnothing$   $\frac{3}{8}$  –  $\frac{7}{8}$ "  
 $s \leq 1.5$  mm

**REMS Hurrican – for making T-branches yourself.**  
**Inexpensive. Also on tubes already installed.**

### System advantage

Only **one** type of extractor tools for REMS Hurrican H, REMS Hurrican and REMS Twist/Hurrican. Simple, inexpensive storage. No confusion possible.

### Cost advantage

No costs for T-branches, storage, procurement. Savings in soldering joints, soldering material and working hours. Higher safety by fewer tube joints.

### Design

Compact, handy, light. Can be used anywhere, free-hand, on pipes already installed. Drill head provides precise drilling without punching with any standard power drill. Drill depth-stop according to the size of T-branch. Tool holder for holding the extractor tools. Limitation of insertion depth to avoid obstruction by using the dimpling pliers. Handy grip wrench for clamping the tool holder onto the pipe.

### Drive

Proven drive unit with hexagon mount. Enormously powerful. Handy, light, only 1.5 kg. Can be used anywhere, free-hand, also on pipes already installed. Robust, maintenance-free gear with safety slipping clutch. Universal motor, 630 W, high-torque forward and reverse at low speed. Stepless, electronic speed control. The speed can be continuously controlled electronically by variable pressure on the safety switch from 0 to 1,000 rpm (accelerator switch).

### Extractor tools

Special design of extractor tools facilitate even and smooth material deformation without burrs and notches. Therefore no secondary treatment required.

### REMS Twist/Hurrican

Space and weight-saving combination set for efficient production of T-branches and for efficient cold-expanding of hard and soft tubes for installations without fittings. Only one drive unit for expanding and extracting tools. Price advantage! See page 311.



German Quality Product



### Supply format

**REMS Hurrican Set.** Electric tube extractor for hard and soft copper tube  $\varnothing$  10 – 22 mm,  $\varnothing$   $\frac{3}{8}$  –  $\frac{7}{8}$ ",  $s \leq .5$  mm. Drive unit with hexagon mount, maintenance-free gear, universal motor 230 V or 110 V, 50 – 60 Hz, 630 W. High torque at low speed, left and right-hand rotation. Safety tip switch. Continuous, electronic speed control from 0 to 1,000 rpm (accelerator switch). Drive holder. Tool holder, drill head, dimpling pliers, lubricant. Extractor tools for pipes in mm or inch. In L-Boxx system case.

| Description                                                                                                                                      | Art.-No.   | €               |
|--------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------------|
| <b>Set 12 + 15 + 18 + 22</b>                                                                                                                     | 151011R220 | <b>1.100,00</b> |
| <b>Set 12 + 14 + 16 + 18 + 22</b>                                                                                                                | 151012R220 | <b>1.170,00</b> |
| <b>Set <math>\frac{3}{8}</math> + <math>\frac{1}{2}</math> + <math>\frac{5}{8}</math> + <math>\frac{3}{4}</math> + <math>\frac{7}{8}</math>"</b> | 151013R220 | <b>1.180,00</b> |

Other voltages on request.

### Accessories

| Description                                      | Tubes $\varnothing$ mm/inch | Art.-No.   | €             |
|--------------------------------------------------|-----------------------------|------------|---------------|
| <b>Extractor tool</b>                            | 10                          | 151105R    | <b>72,40</b>  |
|                                                  | 12                          | 151110R    | <b>72,40</b>  |
|                                                  | 14                          | 151120R    | <b>72,40</b>  |
|                                                  | 15                          | 151125R    | <b>72,40</b>  |
|                                                  | 16                          | 151130R    | <b>72,40</b>  |
|                                                  | 18                          | 151140R    | <b>72,40</b>  |
|                                                  | 20                          | 151145R    | <b>72,40</b>  |
|                                                  | 22                          | 151150R    | <b>72,40</b>  |
|                                                  | $\frac{3}{8}$ "             | 151155R    | <b>76,40</b>  |
|                                                  | $\frac{1}{2}$ "             | 151160R    | <b>74,40</b>  |
|                                                  | $\frac{5}{8}$ "             | 151165R    | <b>74,40</b>  |
|                                                  | $\frac{3}{4}$ "             | 151170R    | <b>74,40</b>  |
|                                                  | $\frac{7}{8}$ "             | 151175R    | <b>74,40</b>  |
| <b>Twist/Hurrican drive unit with stabiliser</b> |                             | 151402R220 | <b>397,00</b> |
| <b>Tool holder</b>                               |                             | 151200R    | <b>91,00</b>  |
| <b>Drill head</b>                                |                             | 151210RMM  | <b>137,00</b> |
| <b>Dimpling pliers</b>                           |                             | 151230R    | <b>43,20</b>  |
| <b>Lubricant (tin)</b>                           |                             | 151240     | <b>10,00</b>  |
| <b>L-Boxx system case with inserts</b>           |                             | 151605R    | <b>149,00</b> |

