Universal, super handy cordless tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-lon 22V Technology. For battery and corded operation.

Pipe pressing joints

Ø 10 – 40 mm Ø 3/8 – 1 1/4"

Complete range of REMS pressing tongs Mini/ pressing rings for all common pressfitting systems, see page 188–223.

REMS Mini-Press S 22 V ACC – universal up to Ø 40 mm. Super light, super small, super handy, ultra fast. Pressing under 4 s. With automatic circuit control. Automatic locking of pressing tongs. Li-Ion 22 V, 2.5 Ah, 54 Wh battery for approx. 390 pressings Viega Profipress DN 15 with one battery charge*.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 188–223). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/ pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS S (PR-2B) pressing rings, see page 223. All pressing rings S (PR-2B) marked with ** can also be driven with the manual radial press REMS Eco-Press using the adapter tong 28.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (Patent EP 1 952 948). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (Patent EP 2 347 862).

Design

Super light, super small, super handy. Drive unit with battery only 2.6 kg. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle $>\!360\,^\circ$. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 22 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

REMS Li-lon 22V Technology, see page 20–25. Highly resistant Li-lon 22V battery with 2.5, 4.4, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-lon 22V, 2.5 Ah, 5.4 Wh batteries for approx. 390 pressings, 4.4 Ah, 95Wh for approx. 685 pressings, 5.0 Ah, 108 Wh for approx. 780 pressings, 9.0 Ah, 194 Wh for approx. 1400 pressings Viega Profipress DN 15 with one battery charge*. Graduated charging status check by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger 100 – 240 V, 90 W, 22 V or 290 W, 22 V, for shorter charging times, as accessory. Voltage supply 220 – 240 V, 22 V, 15 A output, for mains operation instead of Li-lon battery 22 V, as accessory.







German Quality Product





Supply format

REMS Mini-Press S 22V ACC. Cordless radial press 22kN with automatic circuit control for producing pipe pressing joints Ø 10-40 mm, Ø %-1 %. For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 22V, 380 W, obust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. In L-Boxx system case.

Description	Version	ArtNo.	€
Basic-Pack\P	without battery, without rapid charger	578007R22	1.482,00
Basic-Pack	with battery Li-lon 22V, 2.5 Ah, 54Wh, rapid charger 220 – 240 V, 50 – 60 Hz, 70W, 22 V	578016R220	1.875,00

Other voltages on request.



Accessories

Description	ArtNo.	€
Pressing tongs Mini/pressing rings see page 188-223.		
Adapter tongs Mini Z8		
for driving REMS pressing rings S (PR-2B)	574700R	153,00
Pressing tongs Mini Basic E 01 for pressing connection		
material for electric cables, see page 225.	578618	321,00
Cropping tongs Mini for threaded rods see page 226.		
Mini-Press S 22 V ACC drive unit,		
without battery	578003R22	1.342,00
Power-Pack 22 V 2.5 Ah + 2.5 Ah + 90 W, 108 Wh,		
consisting of 2 batteries Li-lon 22 V, 2.5 Ah, 54 Wh,		
rapid charger 100 – 240 V, 50 – 60 Hz, 90 W, 22 V	571590R220	603,00
Battery Li-lon 22V, 2.5 Ah, 54Wh	571571R22	199,00
For other batteries Li-Ion 22 V/Power-Packs 22 V see pa	ge 20-25.	
Rapid charger 100 – 240 V, 50 – 60 Hz, 90 W, 22 V	571585R220	205,00
Rapid charger 100 – 240 V, 50 – 60 Hz, 290 W, 22 V	571587R220	442,00
Voltage supply 220-240 V, 50-60 Hz, 350 W, 22 V, 15 A,		
for mains operation instead of battery Li-lon 22 V.	571567R220	442,00
L-Boxx system case with inserts	578299R	149,00
REMS Lumen 2800 22 V, cordless LED flood light, see page	ge 119	

