Accessories

Description	ArtNo.	€
·		
REMS Simplex 2. Robust, handy drilling stand for core		
drilling up to Ø 202 mm. Description see page 358.	183700R	1.090,00
REMS Titan. Robust, highly stable drilling stand for core		
drilling in steel-reinforced concrete and other materials		
up to Ø 300 mm. For high demands. Description see	102/00D	1 / 50 00
page 358.	183600 R	1.650,00
Titan drilling template for easy setting of the fastening holes. For REMS Titan drilling stand.	183605R	61,50
Carbide masonry drills Ø 15 mm SDS-plus		
for hammer anchors M12	079018	30,10
Hammer anchor M12 (pack of 50), for concrete	079005R50	118,00
Setting iron for hammer anchor M12	182050R	17,20
Carbide masonry drill Ø 20 mm SDS-plus	070010	/7.70
for splaying anchors M12 Splaying anchor M12 (pack of 10), for masonry,	079019	67,70
reusable	079006R10	111,00
Quick clamping set 160 for fastening the drilling stand		
with anchors, consisting of cord threaded bar 160 mm		
with M12 × 52 thread, quick clamping nut, washer.	079010	77,60
Quick clamping set 500 for fastening the drilling stand		
without anchor, consisting of cord threaded bar 500 mm,		
	183607R	70 50
2 quick clamping nuts, 2 washers	183607R	70,50
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate	183607R	70,50
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring	183607 R 183603 R	
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate.		
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%),		
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free,		
2 quick clamping nuts, 2 washers		
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50-60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC	183603R	106,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50-60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling.	183603R 183670R220	106,00 2.040,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer	183603R	106,00 2.040,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid G ½ TDKB, with bores for extracting	183603R 183670R220	106,00 2.040,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide	183603R 183670R220	106,00 2.040,00 139,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid G ½ TDKB, with bores for extracting	183603 R 183670 R220 183604 R	2.040,00 139,00 98,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	183603R 183670R220 183604R 180145R	2.040,00 139,00 98,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns	183603R 183670R220 183604R 180145R	2.040,00 139,00 98,00 20,20
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns Light loosening ring, for light loosening	183603R 183670R220 183604R 180145R 079013 079003	2.040,00 139,00 98,00 20,20
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns Light loosening ring, for light loosening of the diamond core crown	183603R 183670R220 183604R 180145R 079013 079003 180015	2.040,000 139,000 98,000 20,20 40,90
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns Light loosening ring, for light loosening of the diamond core crown Drilling crown extension 200 mm	183603R 183670R220 183604R 180145R 079013 079003 180015 180155R	2.040,00 139,00 98,00 20,20 40,90 22,10 65,30
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid G ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns Light loosening ring, for light loosening of the diamond core crown Drilling crown extension 200 mm Sharpening stone for diamond core drilling crowns	183603R 183670R220 183604R 180145R 079013 079003 180015	70,50 106,00 2.040,00 139,00 98,00 20,20 40,90 22,10 65,30 69,00
2 quick clamping nuts, 2 washers Titan vacuum fastening, consisting of cover plate with nipple for %" screw connection and sealing ring for base plate. Vacuum pump, for vacuum ≤ -900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50 -60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling. Laser drilling centre pointer Drilling start aid 6 ½ TDKB, with bores for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm Carbide masonry drill Ø 8 mm for drilling aid Single open ended wrench size 41 for loosening the universal diamond core drilling crowns Light loosening ring, for light loosening of the diamond core crown Drilling crown extension 200 mm	183603R 183670R220 183604R 180145R 079013 079003 180015 180155R	2.040,00 139,00 98,00 20,20 40,90 22,10 65,30

Dust protection doors, see page 120.

REMS Pull 2 M, dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69, see page 374

